

shall give an authorized representative or special agent of the Department reasonable assistance in the investigation of the incident.

(b) If the Department makes an inquiry to a carrier of hazardous materials in connection with a study of incidents, the carrier shall—

(1) Respond to the inquiry within 30 days after its receipt or within such other time as the inquiry may specify; and

(2) Provide full, true, and correct answers to any questions included in the inquiry.

[Amdt. 171-101, 54 FR 25813, June 19, 1989, as amended at 66 FR 45378, Aug. 28, 2001]

EFFECTIVE DATE NOTE: At 68 FR 67758, Dec. 3, 2003, § 171.21 was revised, effective July 1, 2004. At 69 FR 30119, May 26, 2004, the effective date was delayed until Jan. 1, 2005. For the convenience of the user the revised text follows:

**§ 171.21 Assistance in investigations and special studies.**

(a) A shipper, carrier, package owner, package manufacturer or certifier, repair facility, or person reporting an incident under the provisions of § 171.16 must:

(1) Make all records and information pertaining to the incident available to an authorized representative or special agent of the Department of Transportation upon request; and

(2) Give an authorized representative or special agent of the Department of Transportation reasonable assistance in the investigation of the incident.

(b) If an authorized representative or special agent of the Department of Transportation makes an inquiry of a person required to complete an incident report in connection with a study of incidents, the person shall:

(1) Respond to the inquiry within 30 days after its receipt or within such other time as the inquiry may specify; and

(2) Provide true and complete answers to any questions included in the inquiry.

**PART 172—HAZARDOUS MATERIALS TABLE, SPECIAL PROVISIONS, HAZARDOUS MATERIALS COMMUNICATIONS, EMERGENCY RESPONSE INFORMATION, AND TRAINING REQUIREMENTS**

**Subpart A—General**

- Sec.
- 172.1 Purpose and scope.
- 172.3 Applicability.

**Subpart B—Table of Hazardous Materials and Special Provisions**

- 172.101 Purpose and use of hazardous materials table.
- 172.102 Special provisions.

**Subpart C—Shipping Papers**

- 172.200 Applicability.
- 172.201 Preparation and retention of shipping papers.
- 172.202 Description of hazardous material on shipping papers.
- 172.203 Additional description requirements.
- 172.204 Shipper's certification.
- 172.205 Hazardous waste manifest.

**Subpart D—Marking**

- 172.300 Applicability.
- 172.301 General marking requirements for non-bulk packagings.
- 172.302 General marking requirements for bulk packagings.
- 172.303 Prohibited marking.
- 172.304 Marking requirements.
- 172.306 [Reserved]
- 172.308 Authorized abbreviations.
- 172.310 Class 7 (radioactive) materials.
- 172.312 Liquid hazardous materials in non-bulk packagings.
- 172.313 Poisonous hazardous materials.
- 172.315 Packages containing limited quantities.
- 172.316 Packagings containing materials classed as ORM-D.
- 172.320 Explosive hazardous materials.
- 172.321 Air eligibility mark.
- 172.322 Marine pollutants.
- 172.323 Infectious substances.
- 172.324 Hazardous substances in non-bulk packagings.
- 172.325 Elevated temperature materials.
- 172.326 Portable tanks.
- 172.328 Cargo tanks.
- 172.330 Tank cars and multi-unit tank car tanks.
- 172.331 Bulk packagings other than portable tanks, cargo tanks, tank cars and multi-unit tank car tanks.
- 172.332 Identification number markings.
- 172.334 Identification numbers; prohibited display.
- 172.336 Identification numbers; special provisions.
- 172.338 Replacement of identification numbers.

**Subpart E—Labeling**

- 172.400 General labeling requirements.
- 172.400a Exceptions from labeling.
- 172.401 Prohibited labeling.
- 172.402 Additional labeling requirements.
- 172.403 Class 7 (radioactive) material.
- 172.404 Labels for mixed and consolidated packaging.

## § 172.1

- 172.405 Authorized label modifications.
- 172.406 Placement of labels.
- 172.407 Label specifications.
- 172.411 EXPLOSIVE 1.1, 1.2, 1.3, 1.4, 1.5 and 1.6 labels, and EXPLOSIVE Subsidiary label.
- 172.415 NON-FLAMMABLE GAS label.
- 172.416 POISON GAS label.
- 172.417 FLAMMABLE GAS label.
- 172.419 FLAMMABLE LIQUID label.
- 172.420 FLAMMABLE SOLID label.
- 172.422 SPONTANEOUSLY COMBUSTIBLE label.
- 172.423 DANGEROUS WHEN WET label.
- 172.426 OXIDIZER label.
- 172.427 ORGANIC PEROXIDE label.
- 172.429 POISON INHALATION HAZARD label.
- 172.430 POISON label.
- 172.431 [Reserved]
- 172.432 INFECTIOUS SUBSTANCE label.
- 172.436 RADIOACTIVE WHITE-I label.
- 172.438 RADIOACTIVE YELLOW-II label.
- 172.440 RADIOACTIVE YELLOW-III label.
- 172.441 FISSILE label.
- 172.442 CORROSIVE label.
- 172.444 [Reserved]
- 172.446 CLASS 9 label.
- 172.448 CARGO AIRCRAFT ONLY label.
- 172.450 EMPTY label.

### Subpart F—Placarding

- 172.500 Applicability of placarding requirements.
- 172.502 Prohibited and permissive placarding.
- 172.503 Identification number display on placards.
- 172.504 General placarding requirements.
- 172.505 Placarding for subsidiary hazards.
- 172.506 Providing and affixing placards: Highway.
- 172.507 Special placarding provisions: Highway.
- 172.508 Placarding and affixing placarding: Rail.
- 172.510 Special placarding provisions: Rail.
- 172.512 Freight containers and aircraft unit load devices.
- 172.514 Bulk packagings.
- 172.516 Visibility and display of placards.
- 172.519 General specifications for placards.
- 172.521 DANGEROUS placard.
- 172.522 EXPLOSIVES 1.1, EXPLOSIVES 1.2 and EXPLOSIVES 1.3 placards.
- 172.523 EXPLOSIVES 1.4 placard.
- 172.524 EXPLOSIVES 1.5 placard.
- 172.525 EXPLOSIVES 1.6 placard.
- 172.526 [Reserved]
- 172.527 Background requirements for certain placards.
- 172.528 NON-FLAMMABLE GAS placard.
- 172.530 OXYGEN placard.
- 172.532 FLAMMABLE GAS placard.
- 172.536 [Reserved]
- 172.540 POISON GAS placard.

## 49 CFR Ch. I (10–1–04 Edition)

- 172.542 FLAMMABLE placard.
- 172.544 COMBUSTIBLE placard.
- 172.546 FLAMMABLE SOLID placard.
- 172.547 SPONTANEOUSLY COMBUSTIBLE placard.
- 172.548 DANGEROUS WHEN WET placard.
- 172.550 OXIDIZER placard.
- 172.552 ORGANIC PEROXIDE placard.
- 172.553 [Reserved]
- 172.554 POISON placard.
- 172.555 POISON INHALATION HAZARD placard.
- 172.556 RADIOACTIVE placard.
- 172.558 CORROSIVE placard.
- 172.560 CLASS 9 placard.

### Subpart G—Emergency Response Information

- 172.600 Applicability and general requirements.
- 172.602 Emergency response information.
- 172.604 Emergency response telephone number.
- 172.606 Carrier information contact.

### Subpart H—Training

- 172.700 Purpose and scope.
- 172.701 Federal-State relationship.
- 172.702 Applicability and responsibility for training and testing.
- 172.704 Training requirements.

### Subpart I—Security Plans

- 172.800 Purpose and applicability.
- 172.802 Components of a security plan.
- 172.804 Relationship to other Federal requirements.

APPENDIX A TO PART 172—OFFICE OF HAZARDOUS MATERIALS TRANSPORTATION COLOR TOLERANCE CHARTS AND TABLES  
APPENDIX B TO PART 172—TREFOIL SYMBOL  
APPENDIX C TO PART 172—DIMENSIONAL SPECIFICATIONS FOR RECOMMENDED PLACARD HOLDER

AUTHORITY: 49 U.S.C. 5101–5127; 49 CFR 1.53.

SOURCE: Amdt. 172–29, 41 FR 15996, Apr. 15, 1976, unless otherwise noted.

### Subpart A—General

#### § 172.1 Purpose and scope.

This part lists and classifies those materials which the Department has designated as hazardous materials for purposes of transportation and prescribes the requirements for shipping papers, package marking, labeling, and transport vehicle placarding applicable

to the shipment and transportation of those hazardous materials.

[Amdt. 172-29, 41 FR 15997, Apr. 15, 1976, as amended by 66 FR 45379, Aug. 28, 2001]

### § 172.3 Applicability.

(a) This part applies to—

(1) Each person who offers a hazardous material for transportation, and  
 (2) Each carrier by air, highway, rail, or water who transports a hazardous material.

(b) When a person, other than one of those provided for in paragraph (a) of this section, performs a packaging labeling or marking function required by this part, that person shall perform the function in accordance with this part.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-32, 41 FR 38179, Sept. 9, 1976]

## Subpart B—Table of Hazardous Materials and Special Provisions

### § 172.101 Purpose and use of hazardous materials table.

(a) The Hazardous Materials Table (Table) in this section designates the materials listed therein as hazardous materials for the purpose of transportation of those materials. For each listed material, the Table identifies the hazard class or specifies that the material is forbidden in transportation, and gives the proper shipping name or directs the user to the preferred proper shipping name. In addition, the Table specifies or references requirements in this subchapter pertaining to labeling, packaging, quantity limits aboard aircraft and stowage of hazardous materials aboard vessels.

(b) *Column 1: Symbols.* Column 1 of the Table contains six symbols (“+”, “A”, “D”, “G”, “I” and “W”) as follows:

(1) The plus (+) sign fixes the proper shipping name, hazard class and packing group for that entry without regard to whether the material meets the definition of that class, packing group or any other hazard class definition. When the plus sign is assigned to a proper shipping name in Column (1) of the § 172.101 Table, it means that the material is known to pose a risk to humans. When a plus sign is assigned to mixtures or solutions containing a mate-

rial where the hazard to humans is significantly different from that of the pure material or where no hazard to humans is posed, the material may be described using an alternative shipping name that represents the hazards posed by the material. An appropriate alternate proper shipping name and hazard class may be authorized by the Associate Administrator.

(2) The letter “A” denotes a material that is subject to the requirements of this subchapter only when offered or intended for transportation by aircraft, unless the material is a hazardous substance or a hazardous waste. A shipping description entry preceded by an “A” may be used to describe a material for other modes of transportation provided all applicable requirements for the entry are met.

(3) The letter “D” identifies proper shipping names which are appropriate for describing materials for domestic transportation but may be inappropriate for international transportation under the provisions of international regulations (e.g., IMO, ICAO). An alternate proper shipping name may be selected when either domestic or international transportation is involved.

(4) The letter “G” identifies proper shipping names for which one or more technical names of the hazardous material must be entered in parentheses, in association with the basic description. (See § 172.203(k).)

(5) The letter “I” identifies proper shipping names which are appropriate for describing materials in international transportation. An alternate proper shipping name may be selected when only domestic transportation is involved.

(6) The letter “W” denotes a material that is subject to the requirements of this subchapter only when offered or intended for transportation by vessel, unless the material is a hazardous substance or a hazardous waste. A shipping description entry preceded by a “W” may be used to describe a material for other modes of transportation provided all applicable requirements for the entry are met.

(c) *Column 2: Hazardous materials descriptions and proper shipping names.* Column 2 lists the hazardous materials descriptions and proper shipping names

of materials designated as hazardous materials. Modification of a proper shipping name may otherwise be required or authorized by this section. Proper shipping names are limited to those shown in Roman type (not italics).

(1) Proper shipping names may be used in the singular or plural and in either capital or lower case letters. Words may be alternatively spelled in the same manner as they appear in the ICAO Technical Instructions or the IMDG Code. For example “aluminum” may be spelled “aluminium” and “sulfur” may be spelled “sulphur”. However, the word “inflammable” may not be used in place of the word “flammable”.

(2) Punctuation marks and words in italics are not part of the proper shipping name, but may be used in addition to the proper shipping name. The word “or” in italics indicates that terms in the sequence may be used as the proper shipping name, as appropriate.

(3) The word “poison” or “poisonous” may be used interchangeably with the word “toxic” when only domestic transportation is involved. The abbreviation “n.o.i.” or “n.o.i.b.n.” may be used interchangeably with “n.o.s.”.

(4) Except for hazardous wastes, when qualifying words are used as part of the proper shipping name, their sequence in the package markings and shipping paper description is optional. However, the entry in the Table reflects the preferred sequence.

(5) When one entry references another entry by use of the word “see”, if both names are in Roman type, either name may be used as the proper shipping name (e.g., Ethyl alcohol, *see* Ethanol).

(6) When a proper shipping name includes a concentration range as part of the shipping description, the actual concentration, if it is within the range stated, may be used in place of the concentration range. For example, an aqueous solution of hydrogen peroxide containing 30 percent peroxide may be described as “Hydrogen peroxide, aqueous solution *with not less than 20 percent but not more than 40 percent hydrogen peroxide*” or “Hydrogen peroxide, aqueous solution *with 30 percent hydrogen peroxide*”.

(7) Use of the prefix “mono” is optional in any shipping name, when appropriate. Thus, Iodine monochloride may be used interchangeably with Iodine chloride. In “Glycerol alpha-monochlorohydrin” the term “mono” is considered a prefix to the term “chlorohydrin” and may be deleted.

(8) Use of the word “liquid” or “solid”. The word “liquid” or “solid” may be added to a proper shipping name when a hazardous material specifically listed by name may, due to differing physical states, be a liquid or solid. When the packaging specified in Column 8 is inappropriate for the physical state of the material, the table provided in paragraph (i)(4) of this section should be used to determine the appropriate packaging section.

(9) *Hazardous wastes*. If the word “waste” is not included in the hazardous material description in Column 2 of the Table, the proper shipping name for a hazardous waste (as defined in §171.8 of this subchapter), shall include the word “Waste” preceding the proper shipping name of the material. For example: Waste acetone.

(10) *Mixtures and solutions*. (i) A mixture or solution not identified specifically by name, comprised of a hazardous material identified in the Table by technical name and non-hazardous material, shall be described using the proper shipping name of the hazardous material and the qualifying word “mixture” or “solution”, as appropriate, unless—

(A) Except as provided in §172.101(i)(4) the packaging specified in Column 8 is inappropriate to the physical state of the material;

(B) The shipping description indicates that the proper shipping name applies only to the pure or technically pure hazardous material;

(C) The hazard class, packing group, or subsidiary hazard of the mixture or solution is different from that specified for the entry;

(D) There is a significant change in the measures to be taken in emergencies;

(E) The material is identified by special provision in Column 7 of the §172.101 Table as a material poisonous by inhalation; however, it no longer

meets the definition of poisonous by inhalation or it falls within a different hazard zone than that specified in the special provision; or

(F) The material can be appropriately described by a shipping name that describes its intended application, such as “Coating solution”, “Extracts, flavoring” or “Compound, cleaning liquid”.

(ii) If one or more of the conditions specified in paragraph (c)(10)(i) of this section is satisfied, then a proper shipping name shall be selected as prescribed in paragraph (c)(12)(ii) of this section.

(iii) A mixture or solution not identified in the Table specifically by name, comprised of two or more hazardous materials in the same hazard class, shall be described using an appropriate shipping description (e.g., “Flammable liquid, n.o.s.”). The name that most appropriately describes the material shall be used; e.g., an alcohol not listed by its technical name in the Table shall be described as “Alcohol, n.o.s.” rather than “Flammable liquid, n.o.s.”. Some mixtures may be more appropriately described according to their application, such as “Coating solution” or “Extracts, flavoring liquid” rather than by an n.o.s. entry. Under the provisions of subparts C and D of this part, the technical names of at least two components most predominately contributing to the hazards of the mixture or solution may be required in association with the proper shipping name.

(11) Except for a material subject to or prohibited by §§173.21, 173.54, 173.56(d), 173.56(e), 173.224(c) or 173.225(c) of this subchapter, a material that is considered to be a hazardous waste or a sample of a material for which the hazard class is uncertain and must be determined by testing may be assigned a tentative proper shipping name, hazard class, identification number and packing group, if applicable, based on the shipper’s tentative determination according to:

(i) Defining criteria in this subchapter;

(ii) The hazard precedence prescribed in §173.2a of this subchapter;

(iii) The shippers knowledge of the material;

(iv) In addition to paragraphs (c)(11)(i) through (iii) of this section, for a sample of a material, other than a waste, the following must be met:

(A) Except when the word “Sample” already appears in the proper shipping name, the word “Sample” must appear as part of the proper shipping name or in association with the basic description on the shipping paper.

(B) When the proper shipping description for a sample is assigned a “G” in Column (1) of the §172.101 Table, and the primary constituent(s) for which the tentative classification is based are not known, the provisions requiring a technical name for the constituent(s) do not apply; and

(C) A sample must be transported in a combination packaging which conforms to the requirements of this subchapter that are applicable to the tentative packing group assigned, and may not exceed a net mass of 2.5 kg. (5.5 pounds) per package.

NOTE TO PARAGRAPH (c)(11): For the transportation of self-reactive, organic peroxide and explosive samples, see §§173.224(c)(3), 173.225(c)(2) and 173.56(d) of this subchapter, respectively.

(12) Except when the proper shipping name in the Table is preceded by a plus (+)—

(i) If it is specifically determined that a material meets the definition of a hazard class, packing group or hazard zone, other than the class, packing group or hazard zone shown in association with the proper shipping name, or does not meet the defining criteria for a subsidiary hazard shown in Column 6 of the Table, the material shall be described by an appropriate proper shipping name listed in association with the correct hazard class, packing group, hazard zone, or subsidiary hazard for the material.

(ii) *Generic or n.o.s. descriptions.* If an appropriate technical name is not shown in the Table, selection of a proper shipping name shall be made from the generic or n.o.s. descriptions corresponding to the specific hazard class, packing group, hazard zone, or subsidiary hazard, if any, for the material. The name that most appropriately describes the material shall be used; e.g., an alcohol not listed by its technical name in the Table shall be described as

“Alcohol, n.o.s.” rather than “Flammable liquid, n.o.s.”. Some mixtures may be more appropriately described according to their application, such as “Coating solution” or “Extracts, flavoring, liquid”, rather than by an n.o.s. entry, such as “Flammable liquid, n.o.s.” It should be noted, however, that an n.o.s. description as a proper shipping name may not provide sufficient information for shipping papers and package markings. Under the provisions of subparts C and D of this part, the technical name of one or more constituents which makes the product a hazardous material may be required in association with the proper shipping name.

(iii) *Multiple hazard materials.* If a material meets the definition of more than one hazard class, and is not identified in the Table specifically by name (e.g., acetyl chloride), the hazard class of the material shall be determined by using the precedence specified in § 173.2a of this subchapter, and an appropriate shipping description (e.g., “Flammable liquid, corrosive n.o.s.”) shall be selected as described in paragraph (c)(12)(ii) of this section.

(iv) If it is specifically determined that a material is not a forbidden material and does not meet the definition of any hazard class, the material is not a hazardous material.

(13) *Self-reactive materials and organic peroxides.* A generic proper shipping name for a self-reactive material or an organic peroxide, as listed in Column 2 of the Table, must be selected based on the material’s technical name and concentration, in accordance with the provisions of §§ 173.224 or 173.225 of this subchapter, respectively.

(14) A proper shipping name that describes all isomers of a material may be used to identify any isomer of that material if the isomer meets criteria for the same hazard class or division, subsidiary risk(s) and packing group, unless the isomer is specifically identified in the Table.

(15) Unless a hydrate is specifically listed in the Table, a proper shipping name for the equivalent anhydrous substance may be used, if the hydrate meets the same hazard class or division, subsidiary risk(s) and packing group.

(16) Unless it is already included in the proper shipping name in the § 172.101 Table, the qualifying words “liquid” or “solid” may be added in association with the proper shipping name when a hazardous material specifically listed by name in the § 172.101 Table may, due to the differing physical states of the various isomers of the material, be either a liquid or a solid (for example “Dinitrotoluenes, liquid” and “Dinitrotoluenes, solid”). Use of the words “liquid” or “solid” is subject to the limitations specified for the use of the words “mixture” or “solution” in paragraph (c)(10) of this section. The qualifying word “molten” may be added in association with the proper shipping name when a hazardous material, which is a solid in accordance with the definition in § 171.8 of this subchapter, is offered for transportation in the molten state (for example, “Alkylphenols, solid, n.o.s., molten”).

(d) *Column 3: Hazard class or Division.* Column 3 contains a designation of the hazard class or division corresponding to each proper shipping name, or the word “Forbidden”.

(1) A material for which the entry in this column is “Forbidden” may not be offered for transportation or transported. This prohibition does not apply if the material is diluted, stabilized or incorporated in a device and it is classed in accordance with the definitions of hazardous materials contained in part 173 of this subchapter.

(2) When a reevaluation of test data or new data indicates a need to modify the “Forbidden” designation or the hazard class or packing group specified for a material specifically identified in the Table, this data should be submitted to the Associate Administrator.

(3) A basic description of each hazard class and the section reference for class definitions appear in § 173.2 of this subchapter.

(4) Each reference to a Class 3 material is modified to read “Combustible liquid” when that material is reclassified in accordance with § 173.150 (e) or (f) of this subchapter or has a flash point above 60.5 °C (141 °F) but below 93 °C (200 °F).

(e) *Column 4: Identification number.* Column 4 lists the identification number assigned to each proper shipping

name. Those preceded by the letters "UN" are associated with proper shipping names considered appropriate for international transportation as well as domestic transportation. Those preceded by the letters "NA" are associated with proper shipping names not recognized for international transportation, except to and from Canada. Identification numbers in the "NA9000" series are associated with proper shipping names not appropriately covered by international hazardous materials (dangerous goods) transportation standards, or not appropriately addressed by international transportation standards for emergency response information purposes, except for transportation between the United States and Canada.

(f) *Column 5: Packing group.* Column 5 specifies one or more packing groups assigned to a material corresponding to the proper shipping name and hazard class for that material. Class 2, Class 7, Division 6.2 (other than regulated medical wastes), and ORM-D materials, do not have packing groups. Packing Groups I, II and III indicate the degree of danger presented by the material is either great, medium or minor, respectively. If more than one packing group is indicated for an entry, the packing group for the hazardous material is determined using the criteria for assignment of packing groups specified in subpart D of part 173. When a reevaluation of test data or new data indicates a need to modify the specified packing group(s), the data should be submitted to the Associate Administrator. Each reference in this column to a material which is a hazardous waste or a hazardous substance, and whose proper shipping name is preceded in Column 1 of the Table by the letter "A" or "W", is modified to read "III" on those occasions when the material is offered for transportation or transported by a mode in which its transportation is not otherwise subject to requirements of this subchapter.

(g) *Column 6: Labels.* Column 6 specifies codes which represent the hazard warning labels required for a package filled with a material conforming to the associated hazard class and proper shipping name, unless the package is otherwise excepted from labeling by a

provision in subpart E of this part, or part 173 of this subchapter. The first code is indicative of the primary hazard of the material. Additional label codes are indicative of subsidiary hazards. Provisions in §172.402 may require that a label other than that specified in Column 6 be affixed to the package in addition to that specified in Column 6. No label is required for a material classed as a combustible liquid or for a Class 3 material that is reclassified as a combustible liquid. For "Empty" label requirements, see §173.428 of this subchapter. The codes contained in Column 6 are defined according to the following table:

LABEL SUBSTITUTION TABLE

Label code	Label name
1	Explosive
1.1 <sup>1</sup>	Explosive 1.1 <sup>1</sup>
1.2 <sup>1</sup>	Explosive 1.2 <sup>1</sup>
1.3 <sup>1</sup>	Explosive 1.3 <sup>1</sup>
1.4 <sup>1</sup>	Explosive 1.4 <sup>1</sup>
1.5 <sup>1</sup>	Explosive 1.5 <sup>1</sup>
1.6 <sup>1</sup>	Explosive 1.6 <sup>1</sup>
2.1	Flammable Gas
2.2	Non-Flammable Gas
2.3	Poison Gas
3	Flammable Liquid
4.1	Flammable Solid
4.2	Spontaneously Combustible
4.3	Dangerous When Wet
5.1	Oxidizer
5.2	Organic Peroxide
6.1 (inhalation hazard, Zone A or B).	Poison Inhalation Hazard
6.1 (other than inhalation hazard, Zone A or B) <sup>2</sup> .	Poison
6.2	Infectious substance
7	Radioactive
8	Corrosive
9	Class 9

<sup>1</sup> Refers to the appropriate compatibility group letter.

<sup>2</sup> The packing group for a material is indicated in column 5 of the table.

(h) *Column 7: Special provisions.* Column 7 specifies codes for special provisions applicable to hazardous materials. When Column 7 refers to a special provision for a hazardous material, the meaning and requirements of that special provision are as set forth in §172.102 of this subpart.

(i) *Column 8: Packaging authorizations.* Columns 8A, 8B and 8C specify the applicable sections for exceptions, non-bulk packaging requirements and bulk packaging requirements, respectively, in part 173 of this subchapter. Columns 8A, 8B and 8C are completed in a manner which indicates that "§173." precedes the designated numerical entry.

§ 172.101

For example, the entry “202” in Column 8B associated with the proper shipping name “Gasoline” indicates that for this material conformance to non-bulk packaging requirements prescribed in § 173.202 of this subchapter is required. When packaging requirements are specified, they are in addition to the standard requirements for all packagings prescribed in § 173.24 of this subchapter and any other applicable requirements in subparts A and B of part 173 of this subchapter.

(1) Exceptions. Column 8A contains exceptions from some of the requirements of this subchapter. The referenced exceptions are in addition to those specified in subpart A of part 173 and elsewhere in this subchapter. A “None” in this column means no packaging exceptions are authorized, except as may be provided by special provisions in Column 7.

(2) Non-bulk packaging. Column 8B references the section in part 173 of this subchapter which prescribes packaging requirements for non-bulk packagings. A “None” in this column means non-bulk packagings are not authorized, except as may be provided by special provisions in Column 7. Each reference in this column to a material which is a hazardous waste or a hazardous substance, and whose proper shipping name is preceded in Column 1 of the Table by the letter “A” or “W”, is modified to include “§ 173.203” or “§ 173.213”, as appropriate for liquids and solids, respectively, on those occasions when the material is offered for transportation or transported by a mode in which its transportation is not otherwise subject to the requirements of this subchapter.

(3) Bulk packaging. Column 8C specifies the section in part 173 of this subchapter which prescribes packaging requirements for bulk packagings, subject to the limitations, requirements and additional authorizations of Column 7. A “None” in this column means bulk packagings are not authorized, except as may be provided by special provisions in Column 7. Additional authorizations and limitations for use of IM portable tanks are set forth in Column 7. For each reference in this column to a material which is a hazardous waste or a hazardous substance, and whose

proper shipping name is preceded in Column 1 of the Table by the letter “A” or “W” and which is offered for transportation or transported by a mode in which its transportation is not otherwise subject to the requirements of this subchapter:

(i) The column reference is § 173.240 or § 173.241, as appropriate.

(ii) For a solid material, the exception provided in Special provision B54 is applicable.

(iii) For a Class 9 material which meets the definition of an elevated temperature material, the column reference is § 173.247.

(4) For a hazardous material which is specifically named in the Table and whose packaging sections specify packagings not applicable to the form of the material (e.g., packaging specified is for solid material and the material is being offered for transportation in a liquid form) the following table should be used to determine the appropriate packaging section:

Packaging section reference for solid materials	Corresponding packaging section for liquid materials
§ 173.187 .....	§ 173.181
§ 173.211 .....	§ 173.201
§ 173.212 .....	§ 173.202
§ 173.213 .....	§ 173.203
§ 173.240 .....	§ 173.241
§ 173.242 .....	§ 173.243

(j) *Column 9: Quantity limitations.* Columns 9A and 9B specify the maximum quantities that may be offered for transportation in one package by passenger-carrying aircraft or passenger-carrying rail car (Column 9A) or by cargo aircraft only (Column 9B), subject to the following:

(1) “Forbidden” means the material may not be offered for transportation or transported in the applicable mode of transport.

(2) The quantity limitation is “net” except where otherwise specified, such as for “Consumer commodity” which specifies “30 kg gross.”

(3) When articles or devices are specifically listed by name, the net quantity limitation applies to the entire article or device (less packaging and packaging materials) rather than only to its hazardous components.

(4) A package offered or intended for transportation by aircraft and which is



filled with a material forbidden on passenger-carrying aircraft but permitted on cargo aircraft only, or which exceeds the maximum net quantity authorized on passenger-carrying aircraft, shall be labelled with the CARGO AIRCRAFT ONLY label specified in § 172.448 of this part.

(5) The total net quantity of hazardous material for an outer non-bulk packaging that contains more than one hazardous material may not exceed the lowest permitted maximum net quantity per package as shown in Column 9A or 9B, as appropriate. If one material is a liquid and one is a solid, the maximum net quantity must be calculated in kilograms. See § 173.24a(c)(1)(iv).

(k) *Column 10: Vessel stowage requirements.* Column 10A [Vessel stowage] specifies the authorized stowage locations on board cargo and passenger vessels. Column 10B [Other provisions] specifies codes for stowage requirements for specific hazardous materials. The meaning of each code in Column 10B is set forth in § 176.84 of this subchapter. Section 176.63 of this subchapter sets forth the physical requirements for each of the authorized locations listed in Column 10A. (For bulk transportation by vessel, see 46 CFR parts 30 to 40, 70, 98, 148, 151, 153 and 154.) The authorized stowage locations specified in Column 10A are defined as follows:

(1) Stowage category “A” means the material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel.

(2) Stowage category “B” means—

(i) The material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and

(ii) “On deck only” on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

(3) Stowage category “C” means the material must be stowed “on deck only” on a cargo vessel and on a passenger vessel.

(4) Stowage category “D” means the material must be stowed “on deck only”

on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

(5) Stowage category “E” means the material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

(6) Stowage category “01” means the material may be stowed “on deck” or “under deck” on a cargo vessel (up to 12 passengers) and on a passenger vessel.

(7) Stowage category “02” means the material may be stowed “on deck” or “under deck” on a cargo vessel (up to 12 passengers) and “on deck” in closed cargo transport units or “under deck” in closed cargo transport units on a passenger vessel.

(8) Stowage category “03” means the material may be stowed “on deck” or “under deck” on a cargo vessel (up to 12 passengers) and “on deck” in closed cargo transport units on a passenger vessel.

(9) Stowage category “04” means the material may be stowed “on deck” or “under deck” on a cargo vessel (up to 12 passengers) but the material is prohibited on a passenger vessel.

(10) Stowage category “05” means the material may be stowed “on deck” in closed cargo transport units or “under deck” on a cargo vessel (up to 12 passengers) and on a passenger vessel.

(11) Stowage category “06” means the material may be stowed “on deck” in closed cargo transport units or “under deck” on a cargo vessel (up to 12 passengers) and “on deck” in closed cargo transport units or “under deck” in closed cargo transport units on a passenger vessel.

(12) Stowage category “07” means the material may be stowed “on deck” in closed cargo transport units or “under deck” on a cargo vessel (up to 12 passengers) and “on deck” only in closed

§ 172.101

49 CFR Ch. I (10–1–04 Edition)

cargo transport units on a passenger vessel.

(13) Stowage category “08” means the material may be stowed “on deck” in closed cargo transport units or “under deck” on a cargo vessel (up to 12 passengers) but the material is prohibited on a passenger vessel.

(14) Stowage category “09” means the material may be stowed “on deck only” in closed cargo transport units or “under deck” in closed cargo transport units on a cargo vessel (up to 12 passengers) and on a passenger vessel.

(15) Stowage category “10” means the material may be stowed “on deck” in closed cargo transport units or “under deck” in closed cargo transport units on a cargo vessel (up to 12 passengers) and “on deck” only in closed cargo transport units on a passenger vessel.

(16) Stowage category “11” means the material may be stowed “on deck” in closed cargo transport units or “under deck” in magazine stowage type “c” on a cargo vessel (up to 12 passengers) and “on deck” only in closed cargo transport units on a passenger vessel.

(17) Stowage category “12” means the material may be stowed “on deck” in closed cargo transport units or “under deck” in magazine stowage type “c” on a cargo vessel (up to 12 passengers) but the material is prohibited on a passenger vessel.

(18) Stowage category “13” means the material may be stowed “on deck” in closed cargo transport units or “under deck” in magazine stowage type “A” on a cargo vessel (up to 12 passengers) and “on deck” only in closed cargo transport units on a passenger vessel.

(19) Stowage category “14” means the material may be stowed “on deck” in closed cargo transport units on a cargo vessel (up to 12 passengers) but the material is prohibited on a passenger vessel.

(20) Stowage category “15” means the material may be stowed “on deck” in closed cargo transport units or “under deck” in closed cargo transport units on a cargo vessel (up to 12 passengers) but the material is prohibited on a passenger vessel.

(1) *Changes to the Table.* (1) Unless specifically stated otherwise in a rule document published in the FEDERAL REGISTER amending the Table—

(i) Such a change does not apply to the shipment of any package filled prior to the effective date of the amendment; and

(ii) Stocks of preprinted shipping papers and package markings may be continued in use, in the manner previously authorized, until depleted or for a one-year period, subsequent to the effective date of the amendment, whichever is less.

(2) Except as otherwise provided in this section, any alteration of a shipping description or associated entry which is listed in the §172.101 Table must receive prior written approval from the Associate Administrator.

(3) The proper shipping name of a hazardous material changed in the May 6, 1997 final rule, in effect on October 1, 1997, only by the addition or omission of the word “compressed,” “inhibited,” “liquefied” or “solution” may continue to be used to comply with package marking requirements, until January 1, 2003.

§ 172.101 HAZARDOUS MATERIALS TABLE

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)		(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)
A	Accelerene, see p-Nitrosodimethylaniline.											
	Accumulators, electric, see Batteries, wet etc.											
	Accumulators, pressurized, pneumatic or hydraulic (containing non-flammable gas)											
	Acetal											
	Acetaldehyde	3	UN1088	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E
		3	UN1089	I	3	A3, B16, T11, TP2, TP7	None	201	243	Forbidden	30 L	E
	Acetaldehyde ammonia	9	UN1841	III	9	IB8, IP6	155	204	240	200 kg	200 kg	A
	Acetaldehyde oxime	3	UN2332	III	3	B1, IB3, T4, TP1	150	203	242	60 L	220 L	A
	Acetic acid, glacial or Acetic acid solution, with more than 80 percent acid, by mass.	8	UN2789	II	8, 3	A3, A6, A7, A10, B2, IB2, T7, TP2	154	202	243	1 L	30 L	A
	Acetic acid solution, not less than 50 percent but not more than 80 percent acid, by mass.	8	UN2790	II	8	A3, A6, A7, A10, B2, IB2, T7, TP2	154	202	242	1 L	30 L	A
	Acetic acid solution, with more than 10 percent and less than 50 percent acid, by mass.	8	UN2790	III	8	IB3, T4, TP1	154	203	242	5 L	60 L	A
	Acetic anhydride	8	UN1715	II	8, 3	A3, A6, A7, A10, B2, IB2, T7, TP2	154	202	243	1 L	30 L	A
	Acetone	3	UN1090	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B
	Acetone cyanohydrin, stabilized	6.1	UN1541	I	6.1	2, A3, B9, B14, B32, B76, B77, N34, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D
	Acetone oils	3	UN1091	II	3	IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B
Acetonitrile	3	UN1648	II	3	IB2, T7, TP2	150	202	242	5L	60 L	B	
Acetyl acetone peroxide with more than 9 percent by mass active oxygen.	Forbidden											40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Acetyl benzoyl peroxide, solid, or with more than 40 percent in solution.	Forbidden											
	Acetyl bromide	8	UN1716	II	8	B2, IB2, T8, TP2, TP12	154	202	242	1 L	30 L	C	40
	Acetyl chloride	3	UN1717	II	3, 8	A3, A6, A7, IB1, N34, T8, TP2, TP12	None	202	243	1 L	5 L	B	40
	Acetyl cyclohexanesulfonyl peroxide, with more than 82 percent wetted with less than 12 percent water.	Forbidden											
	Acetyl iodide	8	UN1898	II	8	B2, IB2, T7, TP2, TP13	154	202	242	1 L	30 L	C	40
	Acetyl methyl carbinol	3	UN2621	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Acetyl peroxide, solid, or with more than 25 percent in solution.	Forbidden											
	Acetylene, dissolved	2.1	UN1001		2.1		None	303	None	Forbidden	15 kg	D	25, 40, 57
	Acetylene (liquefied)	Forbidden											
	Acetylene silver nitrate	Forbidden											
	Acetylene tetrabromide, see Tetrabromoethane.	Forbidden											
	Acid butyl phosphate, see Butyl acid phosphate.												
	Acid, sludge, see Sludge acid	6.1	UN2713	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Acridine	3	UN2607	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	40
	Acrolein dimer, stabilized	6.1	UN1092	I	6.1, 3	1, B9, B14, B30, B42, B72, B77, T22, TP2, TP7, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D	40
	Acrolein, stabilized												
	Acrylamide	6.1	UN2074	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	12
	Acrylic acid, stabilized	8	UN2218	II	8, 3	B2, IB2, T7, TP2	154	202	243	1 L	30 L	C	25, 40
	Acrylonitrile, stabilized	3	UN1093	I	3, 6.1	B9, T14, TP2, TP13	None	201	243	Forbidden	30 L	E	40

Research and Special Programs Admin., DOT

§ 172.101

Actuating cartridge, explosive, see Cartridges, power device.																							
Adhesives, containing a flammable liquid.	3	UN1133	I	3	B42, T11, TP1, TP8, TP27	150	201	243	1 L	30 L	B												
Adiponitrile	6.1	UN2205	III	6.1	149, B52, IB2, T4, TP1, TP8	150	173	242	5 L	60 L	B												
	2.2	UN1950		2.2, 8	B1, B52, IB3, T2, TP1	150	173	242	60 L	220 L	A												
Aerosols, corrosive, Packing Group II or III, (each not exceeding 1 L capacity).					IB3, T3, TP1	153	203	241	60 L	220 L	A												
Aerosols, flammable, (each not exceeding 1 L capacity).	2.1	UN1950		2.1	153, A34	306	None	None	75 kg	150 kg	A												
Aerosols, flammable, n.o.s. (engine starting fluid) (each not exceeding 1 L capacity).	2.1	UN1950		2.1	153, N82	306	304	None	Forbidden	150 kg	A												
Aerosols, non-flammable, (each not exceeding 1 L capacity).	2.2	UN1950		2.2	153	306	None	None	75 kg	150 kg	A												
Aerosols, poison, each not exceeding 1 L capacity.	2.2	UN1950		2.2	153	306	None	None	Forbidden	Forbidden	A												
Air-bag inflators, or Air bag modules, or Seat-belt pretensioners.	9	UN3268	III	9	160	166	166	166	25 kg	100 kg	A												
Air, compressed	2.2	UN1002		2.2	78	306	302	302	75 kg	150 kg	A												
Air, refrigerated liquid, (cryogenic liquid).	2.2	UN1003		2.2, 5.1.	T75, TP5, TP22	320	316	318, 319.	Forbidden	150 kg	D												
Air, refrigerated liquid, (cryogenic liquid) non-pressurized.	2.2	UN1003		2.2, 5.1.	T75, TP5, TP22	320	316	318, 319.	Forbidden	Forbidden	D												
Aircraft engines (including turbines), see Engines, internal combustion.																							
Aircraft evacuation slides, see Life saving appliances etc.																							
Aircraft hydraulic power unit fuel tank (containing a mixture of anhydrous hydrazine and monomethyl hydrazine) (M86 fuel).	3	UN3165	I	3, 6.1, 8.	None	None	172	None	Forbidden	42 L	E												
Aircraft survival kits, see Life saving appliances etc.																							
Alcoholates solution, n.o.s., in alcohol.	3	UN3274	II	3, 8	IB2	None	202	243	1 L	5 L	B												
Alcoholic beverages	3	UN3065	II	3	24, B1, IB2, T4, TP1	150	202	242	5 L	60 L	A												
			III	3	24, B1, IB3, N11, T2, TP1	150	203	242	60 L	220 L	A												
Alcohols, n.o.s.	3	UN1987	I	3	T11, TP1, TP8, TP27	None	201	243	1 L	30 L	E												

G

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym- bols	(2) Hazardous materials descrip- tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§ 173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
G	Alcohols, flammable, toxic, n.o.s.	3	UN1986	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	E	40
	Aldehydes, n.o.s.	3	UN1989	III	3, 6.1	B1, IB3, T7, TP1, TP28	None	203	242	60 L	A	.....	.....
	Aldehydes, flammable, toxic, n.o.s.	3	UN1988	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	E	40
G	Aldol	6.1	UN2839	III	3, 6.1	B1, IB3, T7, TP1, TP28	None	203	242	60 L	A	.....	.....
	Alkali metal alcoholates, self-heating, corrosive, n.o.s.	4.2	UN3206	II	6.1, 4.2, 8	IB2, T7, TP2, 64, IB5, IP2	None	202	243	5 L	60 L	A	12
	Alkali metal alloys, liquid, n.o.s.	4.3	UN1421	III	4.2, 8	64, IB8, IP3	None	213	242	25 kg	100 kg	B	.....
	Alkali metal amalgam, liquid	4.3	UN1389	I	4.3	A2, A3, B48, N34	None	201	244	Forbidden	1 L	D	.....
	Alkali metal amalgam, solid	4.3	UN1389	I	4.3	A2, A3, N34	None	201	244	Forbidden	1 L	D	40
	Alkali metal amides	4.3	UN1390	II	4.3	IB4, IP1, N40	None	211	242	Forbidden	15 kg	D	.....
G	Alkali metal dispersions, or Alkali earth metal dispersions, Alkaline corrosive liquids, n.o.s. see Cautic alkali liquids, n.o.s.	4.3	UN1391	I	4.3	A6, A7, A8, A19, A20, IB7, IP2, A2, A3	None	201	244	Forbidden	1 L	D	.....
	Alkaline earth metal alcoholates, n.o.s.	4.2	UN3205	II	4.2	65, IB6, IP2	None	212	241	15 kg	50 kg	B	.....
	Alkaline earth metal alcoholates, n.o.s.	4.2	UN3205	III	4.2	65, IB8, IP3	None	213	241	25 kg	100 kg	B	.....

Alkaline earth metal alloys, n.o.s.	4.3	UN1393	II	4.3	A19, IB7, IP2	151	212	241	15 kg	50 kg	E	
Alkaline earth metal amalgams ..	4.3	UN1392	I	4.3	A19, IB4, IP1, NS4, N40	None	211	242	Forbidden	15 kg	D	
Alkaloids, liquid, n.o.s., or Alkaloid salts, liquid, n.o.s..	6.1	UN3140	I	6.1	A4, T14, TP2, TP27	None	201	243	1 L	30 L	A	
			II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L	A	
			III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	220 L	A	
Alkaloids, solid, n.o.s. or Alkaloid salts, solid, n.o.s. poisonous.	6.1	UN1544	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	
			II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
			III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
Alkyl sulfonic acids, liquid or Aryl sulfonic acids, liquid with more than 5 percent free sulfuric acid.	8	UN2584	II	8	B2, IB2, T8, TP2, TP12, TP13	154	202	242	1 L	30 L	B	
Alkyl sulfonic acids, liquid or Aryl sulfonic acids, liquid with not more than 5 percent free sulfuric acid.	8	UN2586	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	B	
Alkyl sulfonic acids, solid or Aryl sulfonic acids, solid, with more than 5 percent free sulfuric acid.	8	UN2583	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	
Alkyl sulfonic acids, solid or Aryl sulfonic acids, solid with not more than 5 percent free sulfuric acid.	8	UN2585	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	
Alkylphenols, liquid, n.o.s. (including C2-C12 homologues).	8	UN3145	I	8	T14, TP2	None	201	243	0.5 L	2.5 L	B	
			II	8	IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	
			III	8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	
Alkylphenols, solid, n.o.s. (including C2-C12 homologues).	8	UN2430	I	8	IB7, IP1, T10, TP2, TP28	None	211	242	1 kg	25 kg	B	
			II	8	IB8, IP2, IP4, T3, TP2	154	212	240	15 kg	50 kg	B	
			III	8	IB8, IP3, T3, TP1	154	213	240	25 kg	100 kg	A	
Alkylsulfuric acids	8	UN2571	II	8	B2, IB2, T8, TP2, TP12, TP13, TP28	154	202	242	1 L	30 L	C	14
Allethrin, see Pesticides, liquid, toxic, n.o.s..												
Allyl acetate	3	UN2333	II	3, 6.1	IB2, T7, TP1, TP13	None	202	243	1 L	60 L	E	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Allyl alcohol .....	6.1	UN1098	I	6.1, 3	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	40
	Allyl bromide .....	3	UN1099	I	3, 6.1	T14, TP2, TP13	None ...	201 .....	243 .....	Forbidden	30 L	B	40
	Allyl chloride .....	3	UN1100	I	3, 6.1	T14, TP2, TP13	None ...	201 .....	243 .....	Forbidden	30 L	E	40
	<i>Allyl chloroacetate, see Allyl chloroformate.</i>												
	Allyl chloroformate .....	6.1	UN1722	I	6.1, 3, 8	2, A3, B9, B14, B32, B74, N41, T20, TP2, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	40
	Allyl ethyl ether .....	3	UN2335	II	3, 6.1	IB2, T7, TP1, TP13	None ...	202 .....	243 .....	1 L	60 L	E	40
	Allyl formate .....	3	UN2336	I	3, 6.1	T14, TP2, TP13	None ...	201 .....	243 .....	Forbidden	30 L	E	40
	Allyl glycidyl ether .....	3	UN2219	III	3	B1, IB3, T2, TP1	None ...	203 .....	242 .....	60 L	220 L	A	40
	Allyl iodide .....	3	UN1723	II	3, 8	A3, A6, IB1, NG4, T7, TP2, TP13	None ...	202 .....	243 .....	1 L	5 L	B	40
	Allyl isothiocyanate, stabilized ...	6.1	UN1545	II	6.1, 3	A3, A7, IB2, T7, TP2	None ...	202 .....	243 .....	Forbidden	60 L	D	40
	Allylamine .....	6.1	UN2334	I	6.1, 3	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	40
	Allyltrichlorosilane, stabilized .....	8	UN1724	II	8, 3	A7, B2, B6, IB2, NG4, T7, TP2, TP13	None ...	202 .....	243 .....	Forbidden	30 L	C	40
	Aluminum alkyl halides .....	4.2	UN3052	I	4.2, 4.3	B9, B11, T21, TP2, TP7	None ...	181 .....	244 .....	Forbidden	Forbidden	D	40
	Aluminum alkyl hydrides .....	4.2	UN3076	I	4.2, 4.3	B9, B11, T21, TP2, TP7	None ...	181 .....	244 .....	Forbidden	Forbidden	D	40
	Aluminum alkyls .....	4.2	UN3051	I	4.2, 4.3	B9, B11, T21, TP2, TP7	None ...	181 .....	244 .....	Forbidden	Forbidden	D	40
	Aluminum borohydride or Alu- minum borohydride in devices.	4.2	UN2870	I	4.2, 4.3	B11	None ...	181 .....	244 .....	Forbidden	Forbidden	D	40
	Aluminum bromide, anhydrous ...	8	UN1725	II	8	IB8, IP2, IP4	154 .....	212 .....	240 .....	15 kg	50 kg	A	40
	Aluminum bromide, solution .....	8	UN2580	III	8	IB3, T4, TP1	154 .....	203 .....	241 .....	5 L	60 L	A	40



Aluminum carbide .....	4.3	UN1394	II	4.3	A20, IB7, IP2, N41	151	212	242	15 kg	50 kg	A	.....
Aluminum chloride, anhydrous ..	8	UN1726	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	40
Aluminum chloride, solution .....	8	UN2581	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	.....
Aluminum dross, wet or hot .....	Forbidden											.....
Aluminum ferrosilicon powder .....	4.3	UN1395	II	4.3, 6.1	A19, IB5, IP2	151	212	242	15 kg	50 kg	A	40, 85, 103
.....			III	4.3, 6.1	A19, A20, IB4	151	213	241	25 kg	100 kg	A	40, 85, 103
Aluminum hydride .....	4.3	UN2463	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	.....
Aluminum, molten .....	9	NA9260	III	9	IB3, T1, TP3	None	None	247	Forbidden	Forbidden	D	.....
Aluminum nitrate .....	5.1	UN1438	III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
Aluminum phosphate solution, see Corrosive liquids, etc.												.....
Aluminum phosphide .....	4.3	UN1397	I	4.3, 6.1	A8, A19, N40	None	211	242	Forbidden	15 kg	E	40, 85
Aluminum phosphide pesticides	6.1	UN3048	I	6.1	A8, IB7, IP1	None	211	242	Forbidden	15 kg	E	40, 85
Aluminum powder, coated .....	4.1	UN1309	II	4.1	IB8, IP2, IP4	151	212	240	15 kg	50 kg	A	13, 39, 101
.....			III	4.1	IB8, IP3	151	213	240	25 kg	100 kg	A	13, 39, 101
Aluminum powder, uncoated .....	4.3	UN1396	II	4.3	A19, A20, IB7, IP2	151	212	242	15 kg	50 kg	A	39
.....			III	4.3	A19, A20, IB8, IP4	151	213	241	25 kg	100 kg	A	39
Aluminum resinates .....	4.1	UN2715	III	4.1	IB6	151	213	240	25 kg	100 kg	A	.....
Aluminum silicon powder, uncoated.	4.3	UN1398	III	4.3	A1, A19, IB8, IP4	151	213	241	25 kg	100 kg	A	40, 85, 103
Aluminum smelting by-products or Aluminum remelting by-products.	4.3	UN3170	II	4.3	128, B115, IB7, IP2	None	212	242	15 kg	50 kg	B	85, 103
.....			III	4.3	128, B115, IB8, IP4	None	213	241	25 kg	100 kg	B	85, 103
Amatols, see Explosives, blasting, type B.												.....
Amines, flammable, corrosive, n.o.s. or Polyamines, flammable, corrosive, n.o.s.	3	UN2733	I	3, 8	T14, TP1, TP27	None	201	243	0.5 L	2.5 L	D	40
.....			II	3, 8	IB2, T11, TP1, TP27	None	202	243	1 L	5 L	B	40
.....			III	3, 8	B1, IB3, T7, TP1, TP28	150	203	242	5 L	60 L	A	40
Amines, liquid, corrosive, flammable, n.o.s. or Polyamines, liquid, corrosive, flammable, n.o.s.	8	UN2734	I	8, 3	A3, A6, N34, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	A	.....
.....			II	8, 3	IB2, T11, TP2, TP27	None	202	243	1 L	30 L	A	.....

D

G

G

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
G	Amines, liquid, corrosive, n.o.s., or Polyamines, liquid, corrosive, n.o.s.	8	UN2735	I	8	A3, A6, B10, N34, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	A	
							154	202	242	1 L	30 L	A	
							154	203	241	5 L	60 L	A	
G	Amines, solid, corrosive, n.o.s., or Polyamines, solid, corrosive n.o.s.	8	UN3259	I	8	IB7, IP1	None	211	242	1 kg	25 kg	A	
							154	212	240	15 kg	50 kg	A	
							154	213	240	25 kg	100 kg	A	
+	2-Amino-4-chlorophenol	6.1	UN2673	III	8	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
							153	203	241	60 L	220 L	A	
							None	211	None	1 kg	15 kg	E	28, 36
+	2-Amino-5-diethylaminopentane	6.1	UN2946	III	6.1	IB3, T4, TP1	None	203	241	5 L	60 L	A	
							153	203	241	60 L	220 L	A	
							None	211	None	1 kg	15 kg	E	28, 36
+	2-Amino-4,6-Dinitrophenol, wetted with not less than 20 percent water by mass.	6.1	UN3317	I	4.1	23, A8, A19, A20, N41	None	211	242	1 kg	25 kg	A	
							154	203	241	5 L	60 L	A	
							154	203	241	5 L	60 L	A	12
+	N-Aminoethylpiperazine	6.1	UN2512	III	6.1	IB8, IP3, T4, TP1	None	213	240	100 kg	200 kg	A	
							153	213	240	100 kg	200 kg	A	
							None	211	None	1 kg	15 kg	E	28, 36
I	Aminopropyl/diethanolamine, see Amines, etc.	6.1	UN2671	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	B	12, 40
							None	212	242	25 kg	100 kg	B	12, 40
							None	212	242	25 kg	100 kg	B	12, 40
I	Aminopyridines (o-, m-, p-) .....	2.3	UN1005	.....	2.3, 8	4, T50	None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
D	Ammonia, anhydrous .....	2.2	UN1005	.....	2.2	13, T50	None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
D	Ammonia solution, relative density less than 0.880 at 15 degrees C in water, with more than 50 percent ammonia.	2.2	UN3318	.....	2.2	13, T50	None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
I	Ammonia solution, relative density less than 0.880 at 15 degrees C in water, with more than 50 percent ammonia.	2.3	UN3318	.....	2.3, 8	4, T50	None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57
							None	304	314, 315	Forbidden	25 kg	D	40, 57

UN Number	Class	Division	Subclass	Proper Shipping Name	Quantity	Special Provisions	Exemption Code	Other
8 UN2672	8	2.2	.....	Ammonia solutions, relative density between 0.880 and 0.957 at 15 degrees C in water, with more than 10 percent but not more than 35 percent Ammonia.	IB3, IP8, T7, TP1	154	203	241
2.2 UN2073	2.2	2.2	.....	Ammonia solutions, relative density less than 0.880 at 15 degrees C in water, with more than 35 percent but not more than 50 percent ammonia.	.....	306	304	314, 315.
6.1 UN1546	6.1	6.1	.....	Ammonium azide	IB8, IP2, IP4	None	212	242
Forbidden	.....	.....	.....	Ammonium bifluoride, solid, see Ammonium hydrogen difluoride, solid.	.....	.....	.....	.....
.....	.....	.....	.....	Ammonium bifluoride, solid, see Ammonium hydrogen difluoride, solution.	.....	.....	.....	.....
Forbidden	.....	.....	.....	Ammonium bromate	.....	.....	.....	.....
Forbidden	.....	.....	.....	Ammonium chlorate	.....	.....	.....	.....
5.1 UN1439	5.1	5.1	.....	Ammonium dichromate	IB8, IP2, IP4	152	212	242
6.1 UN1843	6.1	6.1	.....	Ammonium dinitro-o-cresolate	IB8, IP2, IP4, T7, TP2	None	212	242
6.1 UN2505	6.1	6.1	.....	Ammonium fluoride	IB8, IP3	153	213	240
6.1 UN2854	6.1	6.1	.....	Ammonium fluorosulfate	IB8, IP3	153	213	240
Forbidden	.....	.....	.....	Ammonium fulminate	.....	.....	.....	.....
8 UN2506	8	8	.....	Ammonium hydrogen sulfate	IB8, IP2, IP4	154	212	240
8 UN1727	8	8	.....	Ammonium hydrogendifluoride, solid.	IB8, IP2, IP4, N34	154	212	240
8 UN2817	8	8, 6.1	.....	Ammonium hydrogendifluoride, solution.	IB2, N34, T8, TP2, TP12, TP13	None	202	243
.....	.....	.....	.....	.....	IB3, T4, TP1, TP12, TP13	154	203	241
.....	.....	.....	.....	Ammonium hydrosulfide, solution, see Ammonium sulfide solution.	.....	.....	.....	.....
.....	.....	.....	.....	Ammonium hydroxide, see Ammonia solutions, etc.	.....	.....	.....	.....
6.1 UN2859	6.1	6.1	.....	Ammonium metavanadate	IB8, IP2, IP4	None	212	242
5.1 UN2067	5.1	5.1	.....	Ammonium nitrate based fertilizer.	52, 150, IB8, IP3	152	213	240
9 UN2071	9	9	.....	Ammonium nitrate based fertilizer.	132, IB8	155	213	240
5.1 UN3375	5.1	5.1	.....	Ammonium nitrate emulsion or Ammonium nitrate suspension or Ammonium nitrate gel, intermediate for blasting explosives.	52, 147	None	214	214

D

AW

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	PG	Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions	Non- bulk	Bulk	Passenger aircraft/rail	Cargo air- craft only	Loca- tion	Other
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8A)	(8B)	(8C)	(9A)	(9B)	(10A)	(10B)
D	Ammonium nitrate-fuel oil mix- ture containing only prilled ammonium nitrate and fuel oil.	1.5D	NA0331	II	1.5D ..		None ..	62 .....	None ..	Forbidden	Forbidden	10	19E
	Ammonium nitrate, liquid (hot concentrated solution).	5.1	UN2426	.....	5.1 .....	B5, T7	None ..	None ..	243 .....	Forbidden	Forbidden	D	59, 60
	Ammonium nitrate, with more than 0.2 percent combustible substances, including any or- ganic substance calculated as carbon, to the exclusion of any other added substance.	1.1D	UN0222	II	1.1D ..		None ..	62 .....	None ..	Forbidden	Forbidden	10	19E
	Ammonium nitrate, with not more than 0.2% total combus- tible material, including any organic substance, calculated as carbon to the exclusion of any other added substance.	5.1	UN1942	III	5.1 .....	A1, A29, IB8, IP3	152 .....	213 .....	240 .....	25 kg	100 kg	A	48, 59, 60, 116
	Ammonium nitrite .....	Forbidden		II	1.1D ..		None ..	62 .....	None ..	Forbidden	Forbidden	10	19E
	Ammonium perchlorate .....	1.1D	UN0402	II	5.1 .....	107	None ..	212 .....	242 .....	Forbidden	Forbidden	E	58, 69, 106
	Ammonium perchlorate .....	5.1	UN1442	II	5.1 .....	107, A9, IB6, IP2	152 .....	212 .....	242 .....	5 kg	25 kg		
	Ammonium permanganate .....	Forbidden		III	5.1 .....		None ..	213 .....	240 .....	25 kg	100 kg	A	
	Ammonium persulfate .....	5.1	UN1444	III	5.1 .....	A1, A29, IB8, IP3	152 .....	62 .....	None ..	Forbidden	Forbidden	10	5E
	Ammonium picrate, dry or wetted with less than 10 per- cent water, by mass.	1.1D	UN0004	II	1.1D ..		None ..	62 .....	None ..	Forbidden	Forbidden	10	19E
	Ammonium picrate, wetted with not less than 10 percent water, by mass.	4.1	UN1310	I	4.1 .....	23, A2, N41	None ..	211 .....	None ..	0.5 kg	0.5 kg	D	28, 36
	Ammonium polysulfide, solution	8	UN2818	II	8, 6.1	IB2, T7, TP2, TP13	None ..	202 .....	243 .....	1 L	30 L	B	12, 26, 40
	Ammonium polyvanadate .....	.....		III	8, 6.1	IB3, T4, TP1, TP13	154 .....	203 .....	241 .....	5 L	60 L	B	12, 26, 40
	Ammonium silicofluoride, see Ammonium fluorosilicate.	6.1	UN2861	II	6.1 .....	IB8, IP2, IP4	None ..	212 .....	242 .....	25 kg	100 kg	A	
	Ammonium sulfide solution .....	8	UN2683	II	8, 6.1, 3.	IB1, T7, TP2, TP13	None ..	202 .....	243 .....	1 L	30 L	B	12, 22, 26, 100

Ammunition, blank, <i>see</i> Cartridges for weapons, blank											.....			.....	
Ammunition, illuminating with or without burster, <i>expelling charge or propelling charge</i> .	UN0171	1.2G ..	II	1.2G ..	62 .....	None ...	Forbidden	Forbidden	03	Forbidden	03	.....		.....	
Ammunition, illuminating with or without burster, <i>expelling charge or propelling charge</i> .	UN0254	1.3G ..	II	1.3G ..	62 .....	None ...	Forbidden	Forbidden	03	Forbidden	03	.....		.....	
Ammunition, illuminating with or without burster, <i>expelling charge or propelling charge</i> .	UN0297	1.4G ..	II	1.4G ..	62 .....	None ...	Forbidden	Forbidden	02	75 kg	02	.....		.....	
Ammunition, incendiary liquid or gel, with burster, <i>expelling charge or propelling charge</i> .	UN0247	1.3J ...	II	1.3J ...	62 .....	None ...	Forbidden	Forbidden	04	Forbidden	04	.....		23E	
Ammunition, incendiary (water-activated contrivances) with burster, <i>expelling charge or propelling charge</i> , <i>see</i> Contrivances, water-activated, etc...															
Ammunition, incendiary, white phosphorus, with burster, <i>expelling charge or propelling charge</i> .	UN0243	1.2H ..	II	1.2H ..	62 .....	None ...	Forbidden	Forbidden	08	Forbidden	08	.....		8E, 14E, 15E, 17E	
Ammunition, incendiary, white phosphorus, with burster, <i>expelling charge or propelling charge</i> .	UN0244	1.3H ..	II	1.3H ..	62 .....	None ...	Forbidden	Forbidden	08	Forbidden	08	.....		8E, 14E, 15E, 17E	
Ammunition, incendiary with or without burster, <i>expelling charge, or propelling charge</i> .	UN0009	1.2G ..	II	1.2G ..	62 .....	None ...	Forbidden	Forbidden	03	Forbidden	03	.....			
Ammunition, incendiary with or without burster, <i>expelling charge, or propelling charge</i> .	UN0010	1.3G ..	II	1.3G ..	62 .....	None ...	Forbidden	Forbidden	03	Forbidden	03	.....			
Ammunition, incendiary with or without burster, <i>expelling charge, or propelling charge</i> .	UN0300	1.4G ..	II	1.4G ..	62 .....	None ...	Forbidden	Forbidden	02	75 kg	02	.....			
Ammunition, practice .....	UN0362	1.4G ..	II	1.4G ..	62 .....	None ...	Forbidden	Forbidden	02	75 kg	02	.....			
Ammunition, practice .....	UN0488	1.3G ..	II	1.3G ..	62 .....	None ...	Forbidden	Forbidden	03	Forbidden	03	.....			
Ammunition, proof .....	UN0363	1.4G ..	II	1.4G ..	62 .....	None ...	Forbidden	Forbidden	02	75 kg	02	.....			
Ammunition, rocket, <i>see</i> Warheads, rocket etc															
Ammunition, SA (small arms), <i>see</i> Cartridges for weapons, etc.															

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
(1)	<i>Ammunition, smoke (water-acti-vated contrivances), white phosphorus, with burster, ex-pelling charge or propelling charge, see Contrivances, water-activated, etc. (UN 0248).</i> <i>Ammunition, smoke (water-acti-vated contrivances), without white phosphorus or phosphides, with burster, ex-pelling charge or propelling charge, see Contrivances, water-activated, etc. (UN 0249).</i> <i>Ammunition smoke, white phos-phorus with burster expelling charge, or propelling charge.</i>	1.2H	UN0245	II	1.2H ..		.....	.....	.....	.....	.....	.....	.....
	<i>Ammunition, smoke, white phos-phorus with burster, expelling charge, or propelling charge.</i>	1.3H	UN0246	II	1.3H ..		.....	62	.....	None	Forbidden	Forbidden	8E, 14E, 15E, 17E
	<i>Ammunition, smoke with or with-out burster, expelling charge or propelling charge.</i>	1.2G	UN0015	II	1.2G ..		.....	62	.....	None	Forbidden	Forbidden	8E, 14E, 15E, 17E
	<i>Ammunition, smoke with or with-out burster, expelling charge or propelling charge.</i>	1.3G	UN0016	II	1.3G ..		.....	62	.....	None	Forbidden	Forbidden	8E, 14E, 15E, 17E
	<i>Ammunition, smoke with or with burster, expelling charge or propelling charge.</i>	1.4G	UN0303	II	1.4G ..		.....	62	.....	None	Forbidden	75 kg	20E, 7E, 8E, 14E, 15E, 17E
	<i>Ammunition, sporting, see Car-tridges for weapons, etc. (UN 0012; UN 0328; UN 0339).</i> <i>Ammunition, tear-producing, non-explosive, without burster or expelling charge, non-fuzed.</i>	6.1	UN2017	II	6.1, 8		None	212	.....	None	Forbidden	50 kg	13, 40

UN Number	Proper Shipping Name	Class	Division	Subdivision	Quantity	Special Provisions	Other	Notes
UN0018	Ammunition, tear-producing with burster, expelling charge or propelling charge.	1.2G	II	1.2G, 8	62	None	Forbidden	8E, 17E, 20E
UN0019	Ammunition, tear-producing with burster, expelling charge or propelling charge.	1.3G	II	1.3G, 8	62	None	Forbidden	8E, 17E, 20E
UN0301	Ammunition, tear-producing with burster, expelling charge or propelling charge.	1.4G	II	1.4G, 8	62	None	Forbidden	7E, 8E, 14E, 15E, 17E
UN2016	Ammunition, toxic, non-explosive, without burster or expelling charge, non-fuzed.	6.1	II	6.1	212	None	Forbidden	13, 40
UN0020	Ammunition, toxic (water-activated contrivances), with burster, expelling charge or propelling charge. see Contrivances, water-activated, etc.	1.2K	II	1.2K, 6.1	62	None	Forbidden	8E, 14E, 15E, 17E
UN0021	Ammunition, toxic with burster, expelling charge, or propelling charge.	1.3K	II	1.3K, 6.1	62	None	Forbidden	8E, 14E, 15E, 17E
UN1104	Amyl acetates	3	III	3	150	B1, IB3, T2, TP1	60 L	
UN2819	Amyl acid phosphate	8	III	8	154	IB3, T4, TP1	5 L	
UN2650	Amyl butyrates	3	III	3	203	B1, IB3, T2, TP1	60 L	
UN1107	Amyl chlorides	3	III	3	202	B2, T4, TP1	5 L	
UN1109	Amyl formates	3	III	3	202	B1, IB3, T2, TP1	60 L	
UN1111	Amyl mercaptans	3	III	3	202	A3, IB2, T4, TP1	5 L	95, 102
UN1110	n-Amyl methyl ketone	3	III	3	203	B1, IB3, T2, TP1	60 L	
UN1112	Amyl nitrate	3	III	3	203	B1, IB3, T2, TP1	60 L	40
UN1113	Amyl nitrites	3	III	3	202	IB2, T4, TP1	5 L	40
UN1106	Amylamines	3	III	3, 8	202	B2, T7, TP1	1 L	
UN1728	Amyltrichlorosilane	8	III	3, 8	203	B1, IB3, T4, TP1	60 L	
			II	8	202	A7, B2, B6, IB2, N84, T7, TP2, TP13	30 L	40
	Anhydrous ammonia, see Ammonia, anhydrous.							
	Anhydrous hydrofluoric acid, see Hydrogen fluoride, anhydrous.							
UN1547	Aniline hydrochloride	6.1	II	6.1	202	IB2, T7, TP2	5 L	40
UN1548	Aniline oil, see Aniline	6.1	III	6.1	153	IB8, IP3	100 kg	
UN2431	Anisidines	6.1	III	6.1	203	IB3, T4, TP1	60 L	
UN2222	Anisole	3	III	3	203	B1, IB3, T2, TP1	60 L	
UN1729	Anisoyl chloride	8	II	8	202	B2, IB2, T7, TP2	1 L	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
	<i>Anti-freeze, liquid, see Flammable liquids, n.o.s.</i>												
	<i>Antimonous chloride, see Antimony trichloride.</i>												
	Antimony compounds, inorganic, liquid, n.o.s.	6.1	UN3141	III	6.1	35, IB3, T7, TP1, TP28	153	203	241	60 L	220 L	A	
	Antimony compounds, inorganic, solid, n.o.s.	6.1	UN1549	III	6.1	35, IB8, IP3	153	213	240	100 kg	200 kg	A	
	Antimony lactate	6.1	UN1550	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Antimony pentachloride, liquid	8	UN1730	II	8	B2, IB2, T7, TP2	None	202	242	1 L	30 L	C	40
	Antimony pentachloride, solutions.	8	UN1731	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	C	40
	Antimony pentafluoride			III	8	IB3, T4, TP1	154	203	241	5 L	60 L	C	40
			UN1732	II	8, 6.1	A3, A6, A7, A10, IB2, N3, T7, TP2	None	202	243	Forbidden	30 L	D	40
	Antimony potassium tartrate	6.1	UN1551	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Antimony powder	6.1	UN2871	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	<i>Antimony sulfide and a chlorate, mixtures of.</i>	Forbidden											
	<i>Antimony sulfide, solid, see Antimony compounds, inorganic, n.o.s.</i>												
	Antimony trichloride, liquid	8	UN1733	II	8	B2, IB2	154	202	242	1 L	30 L	C	40
	Antimony trichloride, solid	8	UN1733	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	40
	<i>Aqua ammonia, see Ammonia solution, etc.</i>												
	Argon, compressed	2.2	UN1006		2.2		306	302	314, 315	75 kg	150 kg	A	
	Argon, refrigerated liquid ( <i>cryogenic liquid</i> )	2.2	UN1951		2.2	T75, TP5	320	316	318	50 kg	500 kg	B	
	Arsenic	6.1	UN1558	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Arsenic acid, liquid	6.1	UN1553	I	6.1	T20, TP2, TP7, TP13	None	201	243	1 L	30 L	B	46
	Arsenic acid, solid	6.1	UN1554	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Arsenic bromide	6.1	UN1555	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	12, 40
	<i>Arsenic chloride, see Arsenic trichloride.</i>												



Research and Special Programs Admin., DOT

§ 172.101

	6.1	UN1556	I	6.1	T14, TP2, TP9, TP13, TP27	None	201	243	1 L	30 L	B	40
Arsenic compounds, liquid, n.o.s. inorganic, including arsenates, n.o.s.; arsenites, n.o.s.; arsenic sulfides, n.o.s.; and organic compounds of arsenic, n.o.s.												
Arsenic compounds, solid, n.o.s. inorganic, including arsenates, n.o.s.; arsenites, n.o.s.; arsenic sulfides, n.o.s.; and organic compounds of arsenic, n.o.s.	6.1	UN1557	I	6.1	IB2, T11, TP2, TP13, TP27, IB3, T7, TP2, TP28, IB7, IP1	None	202	243	5 L	60 L	B	40
Arsenic pentoxide			III	6.1		153	203	241	60 L	220 L	B	40
Arsenic sulfide and a chlorate, mixtures of			I	6.1		None	211	242	5 kg	50 kg	A	
Arsenic trichloride	6.1	UN1560	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	B	40
Arsenic trioxide	6.1	UN1561	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
Arsenic, white, solid, see Arsenic trioxide.			II	6.1	IB8, IP2, IP4	None	212	242	100 kg	100 kg	A	
Arsenic dust	6.1	UN1562	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
Arsenical pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2760	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
Arsenical pesticides, liquid, toxic	6.1	UN2994	II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
			I	6.1	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
			II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
			III	6.1	IB3, T7, TP2, TP28	153	203	241	60 L	220 L	A	40
Arsenical pesticides, liquid, toxic, flammable flash point not less than 23 degrees C.	6.1	UN2993	I	6.1, 3	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
			II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
			III	6.1, 3	B1, IB3, T7, TP2, TP28	153	203	242	60 L	220 L	A	40
Arsenical pesticides, solid, toxic	6.1	UN2759	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
			II	6.1	IB8, IP2, IP4	None	212	242	100 kg	100 kg	A	40
			III	6.1	IB8, IP3	153	213	240	25 kg	200 kg	A	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	<i>Arsenious acid, solid, see Ar- senic trioxide.</i> <i>Arsenious and mercuric iodide solution, see Arsenic com- pounds, liquid, n.o.s.</i> Arsine .....	2.3	UN2188	.....	2.3, 2.1,	1	None ...	192 .....	245 .....	Forbidden	Forbidden	D	40
	Articles, explosive, extremely in- sensitive or Articles, EEI.	1.6N	UN0486	.....	II 1.6N ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.4S	UN0349	.....	II 1.4S ..	101	None ...	62 .....	None ...	25 kg	100 kg	05	.....
G	Articles, explosive, n.o.s. ....	1.4B	UN0350	.....	II 1.4B ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	06	.....
G	Articles, explosive, n.o.s. ....	1.4C	UN0351	.....	II 1.4C ..	101	None ...	62 .....	None ...	Forbidden	75 kg	06	.....
G	Articles, explosive, n.o.s. ....	1.4D	UN0352	.....	II 1.4D ..	101	None ...	62 .....	None ...	Forbidden	75 kg	06	.....
G	Articles, explosive, n.o.s. ....	1.4G	UN0353	.....	II 1.4G ..	101	None ...	62 .....	None ...	Forbidden	75 kg	06	.....
G	Articles, explosive, n.o.s. ....	1.1L	UN0354	.....	II 1.1L ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	8E, 14E, 15E, 17E
G	Articles, explosive, n.o.s. ....	1.2L	UN0355	.....	II 1.2L ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	8E, 14E, 15E, 17E
G	Articles, explosive, n.o.s. ....	1.3L	UN0356	.....	II 1.3L ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	8E, 14E, 15E, 17E
G	Articles, explosive, n.o.s. ....	1.1C	UN0462	.....	II 1.1C ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.1D	UN0463	.....	II 1.1D ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.1E	UN0464	.....	II 1.1E ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.1F	UN0465	.....	II 1.1F ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	.....
G	Articles, explosive, n.o.s. ....	1.2C	UN0466	.....	II 1.2C ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.2D	UN0467	.....	II 1.2D ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.2E	UN0468	.....	II 1.2E ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.2F	UN0469	.....	II 1.2F ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	.....
G	Articles, explosive, n.o.s. ....	1.3C	UN0470	.....	II 1.3C ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.4E	UN0471	.....	II 1.4E ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
G	Articles, explosive, n.o.s. ....	1.4F	UN0472	.....	II 1.4F ..	101	None ...	62 .....	None ...	Forbidden	Forbidden	08	75 kg

Articles, pressurized pneumatic or hydraulic containing non-flammable gas.	Articles, pyrophoric	Articles, pyrotechnic for technical purposes.	Articles, pyrotechnic for technical purposes.	Articles, pyrotechnic for technical purposes.	Articles, pyrotechnic for technical purposes.	Articles, pyrotechnic for technical purposes.	Asbestos	Ascaridole (organic peroxide)	Asphalt, at or above its flash point.	Asphalt, cut back, see Tars, liquid, etc.	Automobile, motorcycle, tractor, other self-propelled vehicle engine, or other mechanical apparatus, see Vehicles or Battery etc.	Aviation regulated liquid, n.o.s.	Aviation regulated solid, n.o.s.	Azauric acid (salt of) (dry)	Azido guanidine picrate (dry)	5-Azido-1-hydroxy tetrazole	Azido hydroxy tetrazole (mercury and silver salts).	3-Azido-1,2-Propylene glycol dinitrate.	Azidodithiocarbonic acid	Azidoethyl nitrate	1-Aziridinylphosphine oxide-(tris), see Tris-(1-aziridinyl) phosphine oxide, solution.	Azodicarbonamide	Azotetrazole (dry)	Barium	Barium alloys, pyrophoric
2.2	1.2L	1.1G	1.2G	1.3G	1.4G	1.4S	9	Forbidden	3			9	9	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	4.1	Forbidden	4.3	4.2
UN3164	UN0380	UN0428	UN0429	UN0430	UN0431	UN0432	NA2212		NA1999			UN3334	UN3335									UN3242	UN1400	UN1854	
2.2	1.2L	1.1G	1.2G	1.3G	1.4G	1.4S	9	Forbidden	3			9	9	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	4.1	Forbidden	4.3	4.2
.....	II	II	II	II	II	II	III	.....	III	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	II	II	I	
306	None	None	None	None	None	None	None	155	150			155	155									212	151	181	
302, 304.	62	62	62	62	62	62	216	203	247			204	204									240	241	None	
None	None	None	None	None	None	None	240	247	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	240	241	None	
No limit	Forbidden	Forbidden	Forbidden	Forbidden	Forbidden	25 kg	200 kg	.....	Forbidden	.....	.....	No limit	No limit	.....	.....	.....	.....	.....	.....	.....	.....	Forbidden	15 kg	Forbidden	
No limit	Forbidden	Forbidden	Forbidden	Forbidden	75 kg	100 kg	200 kg	.....	Forbidden	.....	.....	No limit	No limit	.....	.....	.....	.....	.....	.....	.....	.....	Forbidden	50 kg	Forbidden	
A	08	07	07	07	06	05	A	.....	D	.....	.....	A	A	.....	.....	.....	.....	.....	.....	.....	.....	D	E	D	
.....	8E, 14E, 15E, 17E	.....	.....	.....	.....	.....	34, 40	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	12, 61, 74	.....	.....	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
	Barium azide, dry or wetted with less than 50 percent water, by mass.	1.1A	UN0224	II	1.1A, 6.1.	111, 117	None	62	None	Forbidden	Forbidden	12	
	Barium azide, wetted with not less than 50 percent water, by mass.	4.1	UN1571	I	4.1, 6.1.	162, A2	None	182	None	Forbidden	0.5 kg	D	28
	Barium bromate	5.1	UN2719	II	5.1, 6.1.	IB8, IP2, IP4	None	212	242	5 kg	25 kg	A	56, 58, 106
	Barium chlorate	5.1	UN1445	II	5.1, 6.1.	A9, IB6, IP2, N34, T4, TP1	None	212	242	5 kg	25 kg	A	56, 58, 106
	Barium compounds, n.o.s.	6.1	UN1564	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Barium cyanide	6.1	UN1565	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Barium hypochlorite with more than 22 percent available chlorine.	5.1	UN2741	II	5.1, 6.1.	IB7, IP1, N74, N75	None	211	242	5 kg	50 kg	A	26, 40
	Barium nitrate	5.1	UN1446	II	5.1, 6.1.	A7, A9, IB8, IP2, IP4, N34	152	212	None	5 kg	25 kg	B	56, 58, 106
	Barium oxide	6.1	UN1884	III	6.1	IB8, IP2, IP4	None	212	242	5 kg	25 kg	A	
	Barium perchlorate	5.1	UN1447	II	5.1, 6.1.	IB8, IP3	153	213	240	100 kg	200 kg	A	56, 58, 106
	Barium permanganate	5.1	UN1448	II	5.1, 6.1.	IB6, IP2, T4, TP1	None	212	242	5 kg	25 kg	A	56, 58, 106
	Barium peroxide	5.1	UN1449	II	5.1, 6.1.	IB6, IP2	None	212	242	5 kg	25 kg	A	56, 58, 106, 107, 13, 75, 106
	Barium selenate, see Selenates or Selenites.												
	Barium selenite, see Selenates or Selenites.												
	Batteries, containing sodium	4.3	UN3292	II	4.3		189	189	189	Forbidden	No limit	A	
	Batteries, dry, containing potassium hydroxide solid, electric storage.	8	UN3028	III	8		None	213	None	25 kg gross	230 kg gross	A	
	Batteries, wet, filled with acid, electric storage.	8	UN2794	III	8		159	159	159	30 kg gross	No limit	A	

UN Number	Proper Shipping Name	Class	Division	Sub-division	Section	Sub-section	Special Provisions	Quantity	Limit	Other
8 UN2800	Batteries, wet, non-spillable, electric storage.	III	8	.....	.....	.....	.....	159	No Limit	A
8 UN2795	Batteries, dry, not subject to the requirements of this subchapter.	III	8	.....	.....	.....	130	.....	.....	.....
8 UN2796	Batteries, wet, filled with alkali, electric storage.	II	8	.....	.....	.....	A3, A7, B2, B15, IB2, N6, N34, T8, TP2, TP12	159, 154, 202	30 kg gross, 1 L	A, B
8 UN2797	Battery fluid, acid	II	8	.....	.....	.....	B2, IB2, N6, T7, TP2, TP28	154, 202	1 L	A
9 UN3171	Battery fluid, alkali	.....	9	.....	.....	.....	134	220	No limit	.....
9 UN1990	Battery, lithium type, see Lithium batteries etc.	III	9	.....	.....	.....	.....	203	.....	A
3 UN1114	Battery-powered vehicle or Battery, wet, filled with acid or alkali with vehicle or mechanical equipment containing an internal combustion engine, see Vehicle, etc. or Engines, internal combustion, etc.	II	3	.....	.....	.....	IB3, T2, TP1, IB2, T4, TP1	202, 242	100 L, 5 L	A, B
Forbidden	Benzaldehyde	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene diazonium chloride (dry)	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene diazonium nitrate (dry)	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene phosphorus dichloride, see Phenyl phosphorus dichloride.	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene phosphorus trichloride, see Phenyl phosphorus trichloride.	.....	.....	.....	.....	.....	.....	.....	.....	.....
8 UN2225	Benzene sulfonyl chloride	III	8	.....	.....	.....	IB3, T4, TP1	203	5 L	A
6.1 UN1885	Benzene triozonide	II	6.1	.....	.....	.....	IB8, IP2, IP4	212	25 kg	A
6.1 UN2224	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	6.1	.....	.....	.....	.....	242	.....	.....
6.1 UN2587	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	6.1	.....	.....	.....	.....	242	.....	.....
8 UN2226	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	8	.....	.....	.....	.....	202	.....	.....
3 UN2338	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	3	.....	.....	.....	.....	202	.....	.....
Forbidden	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	.....	.....	.....	.....	.....	.....	.....	.....	.....
Forbidden	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	.....	.....	.....	.....	.....	.....	.....	.....	.....
8 UN1736	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	8	.....	.....	.....	B2, IB2, T8, TP2, TP12, TP13	202	1 L	C
6.1 UN1737	Benzene thiocarbonyl chloride, see Phenyl phosphorus thiocarbonyl chloride.	II	6.1, 8	.....	.....	.....	A3, A7, IB2, N33, N34, T8, TP2, TP12, TP13	202	1 L	D

+

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Benzyl chloride .....	6.1	UN1738	II	6.1, 8	A3, A7, B70, IB2, N33, N42, T8, TP2, TP12, TP13	None ...	202	243	30 L	D	13, 40	
	Benzyl chloride <i>unstabilized</i> .....	6.1	UN1738	II	6.1, 8	A3, A7, B8, B11, IB2, N33, N34, N43, T8, TP2, TP12, TP13	None ...	202	243	30 L	D	13, 40	
	Benzyl chloroformate .....	8	UN1739	I	8	A3, A6, B4, N41, T10, TP2, TP12, TP13	None ...	201	243	2.5 L	D	40	
	Benzyl iodide .....	6.1	UN2653	II	6.1	IB2, T7, TP2	None ...	202	243	60 L	B	12, 40	
	Benzylidimethylamine .....	8	UN2619	II	8, 3	IB2, T7, TP2	None ...	202	243	30 L	A	40, 48	
	Benzylidene chloride .....	6.1	UN1866	II	6.1	IB2, T7, TP2	None ...	202	243	60 L	D	40	
	Beryllium compounds, n.o.s. ....	6.1	UN1566	III	6.1	IB8, IP2, IP4	None ...	212	242	25 kg	A	.....	
	Beryllium nitrate .....	5.1	UN2464	II	5.1, 6.1	IB8, IP3	153	213	240	200 kg	A	.....	
	Beryllium, powder .....	6.1	UN1567	II	6.1, 4.1	IB8, IP2, IP4	None ...	212	242	50 kg	A	.....	
	Bicyclo [2.2.1] hepta-2,5-diene, stabilized or 2,5-Norbornadiene, stabilized.	3	UN2251	II	3	IB2, T7, TP2	150	202	242	60 L	D	.....	
	<i>Biphenyl triozonide</i> .....	Forbidden	UN2782	I	3, 6.1	T14, TP2, TP13, TP27	None ...	201	243	.....	E	.....	
	Bipyridium pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3								30 L			
	Bipyridium pesticides, liquid, toxic.	6.1	UN3016	II	3, 6.1	IB2, T11, TP2, TP13, TP27	None ...	202	243	60 L	B	40	
	.....			I	6.1	T14, TP2, TP13, TP27	None ...	201	243	30 L	B	40	
	.....			II	6.1	IB2, T11, TP2, TP13, TP27	None ...	202	243	60 L	B	40	
	.....			III	6.1	IB3, T7, TP2, TP28	153	203	241	220 L	A	40	
	Bipyridium pesticides, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN3015	I	6.1, 3	T14, TP2, TP13, TP27	None ...	201	243	30 L	B	21, 40	
	.....			II	6.1, 3	IB2, T11, TP2, TP13, TP27	None ...	202	243	60 L	B	21, 40	

Ethydium pesticides, solid, toxic.		UN2781	6.1	III	6.1, 3	B1, IB3, T7, TP2, TP28 IB7, IP1	None	203	242	60 L	220 L	A	21, 40
Bis (Aminoaropyl) piperazine, see Corrosive liquid, n.o.s.				I	6.1	IB8, IP2, IP4 IB8, IP3	None	211	242	5 kg	50 kg	A	40
Bisulfate, aqueous solution	8	UN2837	8	II	8	A7, B2, IB2, N34, T7, TP2 A7, IB3, N34, T4, TP1	154	202	242	1 L	30 L	A	40
Bisulfites, aqueous solutions, n.o.s.	8	UN2693	8	III	8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
Black powder, compressed or Gunpowder, compressed or Black powder, in pellets or Gunpowder, in pellets.	1.1D	UN0028	1.1D	II	1.1D		None	62	None	Forbidden	Forbidden	10	26, 40
Black powder or Gunpowder, granular or as a meal.	1.1D	UN0027	1.1D	II	1.1D		None	62	None	Forbidden	Forbidden	10	
Black powder for small arms	4.1	NA0027	4.1	I	4.1	70	None	170	None	Forbidden	Forbidden	E	
Blasting agent, n.o.s., see Explosives, blasting etc.													
Blasting cap assemblies, see Detonator assemblies, non-electric, for blasting.													
Blasting caps, electric, see Detonators, electric for blasting.													
Blasting caps, non-electric, see Detonators, non-electric, for blasting.													
Bleaching powder, see Calcium hypochlorite mixtures, etc.													
Blue asbestos (Crocidolite or Brown asbestos (amosite,rysorite).	9	UN2212	9	II	9	156, IB8, IP2, IP4	155	216	240	Forbidden	Forbidden	A	34, 40
Bombs, photo-flash	1.1F	UN0037	1.1F	II	1.1F			62	None	Forbidden	Forbidden	08	
Bombs, photo-flash	1.1D	UN0038	1.1D	II	1.1D			62	None	Forbidden	Forbidden	03	
Bombs, photo-flash	1.2G	UN0039	1.2G	II	1.2G			62	None	Forbidden	Forbidden	03	
Bombs, photo-flash	1.3G	UN0299	1.3G	II	1.3G			62	None	Forbidden	Forbidden	03	
Bombs, smoke, non-explosive, with corrosive liquid, without initiating device.	8	UN2028	8	II	8		None	160	None	Forbidden	Forbidden	E	40
Bombs, with bursting charge	1.1F	UN0033	1.1F	II	1.1F			62	None	Forbidden	Forbidden	08	
Bombs, with bursting charge	1.1D	UN0034	1.1D	II	1.1D			62	None	Forbidden	Forbidden	03	
Bombs, with bursting charge	1.2D	UN0035	1.2D	II	1.2D			62	None	Forbidden	Forbidden	03	
Bombs, with bursting charge	1.2F	UN0291	1.2F	II	1.2F			62	None	Forbidden	Forbidden	08	
Bombs with flammable liquid, with bursting charge.	1.1J	UN0399	1.1J	II	1.1J			62	None	Forbidden	Forbidden	04	23E

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Bombs with flammable liquid, with bursting charge.	1.2J	UN0400	II	1.2J				62	None	Forbidden	04	23E
	Boosters with detonator	1.1B	UN0225	II	1.1B			None	62	None	Forbidden	11	
	Boosters with detonator	1.2B	UN0268	II	1.2B			None	62	None	Forbidden	07	
	Boosters, without detonator	1.1D	UN0042	II	1.1D			None	62	None	Forbidden	07	
	Boosters, without detonator	1.2D	UN0283	II	1.2D			None	62	None	Forbidden	07	
	Borate and chlorate mixtures, see Chlorate and borate mixtures.												
	Borneol	4.1	UN1312	III	4.1	A1, IB8, IP3		None	213	240	100 kg	A	
+	Boron tribromide	8	UN2692	I	8, 6.1	2, A3, A7, B9, B14, B52, B74, N34, T20, TP2, TP12, TP13, TP38, TP45		None	227	244	Forbidden	C	12
	Boron trichloride	2.3	UN1741		2.3, 8	3, B9, B14		None	304	314	Forbidden	D	25, 40
	Boron trifluoride	2.3	UN1008		2.3	2, B9, B14		None	302	314, 315	Forbidden	D	40
	Boron trifluoride acetic acid complex.	8	UN1742	II	8	B2, B6, IB2, T8, TP2, TP12		154	202	242	1 L	A	
	Boron trifluoride diethyl etherate	8	UN2604	I	8, 3	A19, T10, TP2		None	201	243	0.5 L	D	40
	Boron trifluoride dihydrate	8	UN2851	II	8	IB8, IP2, IP4, T7, TP2		154	212	240	15 kg	B	12, 40,
	Boron trifluoride dimethyl etherate.	4.3	UN2965	I	4.3, 8, 3	A19, T10, TP2, TP7		None	201	243	Forbidden	D	21, 28, 40, 49, 100
	Boron trifluoride propionic acid complex.	8	UN1743	II	8	B2, IB2, T8, TP2, TP12		154	202	242	1 L	A	
	Box toe gum, see Nitrocellulose etc.												
	Bromates, inorganic, aqueous solution, n.o.s.	5.1	UN3213	II	5.1	IB2, T4, TP1		152	202	242	1 L	B	56, 58, 106
	Bromates, inorganic, n.o.s.	5.1	UN1450	II	5.1	IB8, IP2, IP4		152	212	242	5 kg	A	56, 58, 106
	Bromine azide	Forbidden											



+	Bromine or Bromine solutions	8	UN1744	I	8, 6.1	1, A3, A6, B9, B64, B85, N34, N43, T22, TP2, TP10, TP12, TP13	None	226	249	Forbiddn	Forbiddn	12, 40, 66, 74, 89, 90
	Bromine chloride	2.3	UN2901		2.3, 8, 5.1	2, B9, B14	None	304	314, 315	Forbiddn	Forbiddn	40, 89, 25, 40, 66, 90
+	Bromine pentafluoride	5.1	UN1745	I	5.1, 6.1, 8	1, B9, B14, B30, B72, T22, TP2, TP12, TP13, TP38, TP44	None	228	244	Forbiddn	Forbiddn	25, 40, 66, 90
+	Bromine trifluoride	5.1	UN1746	I	5.1, 6.1, 8	2, B9, B14, B32, B74, T22, TP2, TP12, TP13, TP38, TP45	None	228	244	Forbiddn	Forbiddn	25, 40, 66, 90
	4-Bromo-1,2-dinitrobenzene	Forbiddn										
	4-Bromo-1,2-dinitrobenzene (unstable at 59 degrees C.)	Forbiddn										
	1-Bromo-3-chloropropane	6.1	UN2688	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L A	
	1-Bromo-3-methylbutane	3	UN2341	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L A	
	1-Bromo-3-nitrobenzene (unstable at 56 degrees C.)	Forbiddn										
	2-Bromo-2-nitropropane-1,3-diol	4.1	UN3241	III	4.1	46, IB8, IP3	151	213	None	25 kg	50 kg C	12, 25, 40
	Bromoacetic acid, solid	8	UN1938	II	8	A7, IB8, IP2, IP4, N34, T7	154	212	240	15 kg	50 kg A	
	Bromoacetic acid, solution	8	UN1938	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L A	40
+	Bromoacetone	6.1	UN1569	II	6.1, 3	2, T20, TP2, TP13	None	193	245	Forbiddn	Forbiddn	40
	Bromoacetyl bromide	8	UN2513	II	8	B2, IB2, T8, TP2, TP12	154	202	242	1 L	30 L C	40
	Bromobenzene	3	UN2514	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L A	
	Bromobenzyl cyanides, liquid	6.1	UN1694	I	6.1	T14, TP2, TP13	None	201	243	Forbiddn	30 L D	12, 40
	Bromobenzyl cyanides, solid	6.1	UN1694	I	6.1	T14, TP2, TP13	None	211	242	Forbiddn	50 kg D	12, 40
	1-Bromobutane	3	UN1126	II	3	IB2, T4, TP1	150	202	242	5L	60 L B	40
	2-Bromobutane	3	UN2339	III	3	B1, IB2, T4, TP1	150	202	242	5L	60 L B	40
	Bromochloromethane	6.1	UN1887	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L A	
	2-Bromoethyl ether	3	UN2340	III	3	IB2, T4, TP1	150	202	242	5L	60 L B	40
	Bromoforn	6.1	UN2515	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L A	12, 40
	Bromomethylpropanes	3	UN2342	III	3	IB2, T4, TP1	150	202	242	5L	60 L B	
	2-Bromopentane	3	UN2343	III	3	IB2, T4, TP1	150	202	242	5L	60 L B	40
	Bromopropanes	3	UN2344	III	3	IB2, T4, TP1	150	202	242	60 L	220 L A	40
	3-Bromopropyne	3	UN2345	III	3	IB3, T2, TP1	150	203	242	60 L	220 L A	40
	Bromosilane	Forbiddn										
	Bromobutene-alpha, see Benzyl bromide.											
	Bromotrifluoroethylene	2.1	UN2419		2.1		None	304	314, 315	Forbiddn	150 kg B	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Bromotrifluoromethane or Refrig- erant gas, R 13B1..	2.2	UN1009		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Brucine	6.1	UN1570	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	
	Burstlers, explosive	1.1D	UN0043	II	1.1D		None	62	None	Forbidden	Forbidden	07	
	Butadienes, stabilized	2.1	UN1010		2.1	T50	306	304	314, 315.	Forbidden	150 kg	B	40
	Butane see also Petroleum gases, liquefied.	2.1	UN1011		2.1	19, T50	306	304	314, 315.	Forbidden	150 kg	E	40
	<i>Butane, butane mixtures and mixtures having similar prop- erties in cartridges each not exceeding 500 grams, see Receptacles, etc.</i>												
	Butanediol	3	UN2346	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Butanols	Forbidden	UN1120	II	3	IB2, T4, TP1, TP29	150	202	242	5 L	60 L	B	
	<i>tert-Butoxycarbonyl azide</i>	Forbidden		III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Butyl acetates	3	UN1123	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Butyl acid phosphate	8	UN1718	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Butyl acrylates, stabilized	3	UN2348	III	3	IB3, T4, TP1	154	203	241	5 L	60 L	A	
	Butyl alcohols, see Butanols			III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Butyl benzenes	3	UN2709	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	<i>n-Butyl bromide, see 1- Bromobutane.</i>												
	<i>n-Butyl chloride, see Chlorobutanes.</i>												
D	sec-Butyl chloroformate	6.1	NA2742	I	6.1, 3, 8.	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	1 L	30 L	A	12, 13, 22, 25, 40, 48, 100
	<i>n-Butyl chloroformate</i>	6.1	UN2743	I	6.1, 8, 3.	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	A	12, 13, 21, 25, 40, 100
	<i>Butyl ethers, see Dibutyl ethers</i>												

Butyl ethyl ether, see Ethyl butyl ether.																											
n-Butyl formate	3	UN1128	II	3		IB2, T4, TP1	150	202	242		5 L	60 L	B														
tert-Butyl hydroperoxide, with more than 90 percent with water.	Forbidden																										
tert-Butyl hypochlorite	4.2	UN3255	I	4.2, 8		IB2, T7, TP2	None	211	243		Forbidden	Forbidden	D														
N-n-Butyl imidazole	6.1	UN2690	II	6.1		1, A7, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None	202	243		5 L	60 L	A														
tert-Butyl isocyanate	6.1	UN2484	I	6.1, 3		B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	226	244		Forbidden	Forbidden	D													40	
n-Butyl isocyanate	6.1	UN2485	I	6.1, 3		2, A7, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244		Forbidden	Forbidden	D													40	
Butyl mercaptans	3	UN2347	II	3		A3, IB2, T4, TP1	150	202	242		5 L	60 L	D													26, 95	
n-Butyl methacrylate, stabilized	3	UN2227	III	3		B1, IB3, T2, TP1	150	203	242		60 L	220 L	A														
Butyl methyl ether	3	UN2350	II	3		IB2, T4, TP1	150	202	242		5 L	60 L	B														
Butyl nitriles	3	UN2351	I	3		T11, TP1, TP8, TP27	150	201	243		1 L	30 L	E													40	
tert-Butyl peroxyacetate, with more than 76 percent in solution.	Forbidden																										
n-Butyl peroxydicarbonate, with more than 52 percent in solution.	Forbidden																										
tert-Butyl peroxyisobutyrate, with more than 77 percent in solution.	Forbidden																										
Butyl phosphoric acid, see Butyl acid phosphates.																											
Butyl propionates	3	UN1914	III	3		B1, IB3, T2, TP1	150	203	242		60 L	220 L	A														
5-tert-Butyl-2,4,6-trinitro-m-xylene or Musk xylene.	4.1	UN2956	III	4.1		159	None	223	None		Forbidden	Forbidden	D													12, 25, 48, 127	
Butyl vinyl ether, stabilized	3	UN2352	II	3		IB2, T4, TP1	150	202	242		5 L	60 L	B													40	
n-Butylamine	3	UN1125	II	3, 8		IB2, T7, TP1	None	202	242		1 L	5 L	B													40	
N-Butylaniline	6.1	UN2738	II	6.1		IB2, T7, TP2	None	202	243		5 L	60 L	A														
tert-Butylcyclohexylchloroformate	6.1	UN2747	III	6.1		IB3, T4, TP1	153	203	241		60 L	220 L	A													12, 13, 25	
Butylene see also Petroleum gases, liquefied.	2.1	UN1012		2.1		19, T50	306	304	314, 315.		Forbidden	150 kg	E													40	
1,2-Butylene oxide, stabilized	3	UN3022	II	3		IB2, T4, TP1	150	202	242		5 L	60 L	B													49	
Butyltoluenes	6.1	UN2667	III	6.1		IB3, T4, TP1	153	203	241		60 L	220 L	A														
Butyltrichlorosilane	8	UN1747	II	8, 3		A7, B2, B6, B2, NS4, T7, TP2, TP13	None	202	243		Forbidden	30 L	C													40	
1,4-Butynediol	6.1	UN2716	III	6.1		A1, IB8, IP3	None	213	240		100 kg	200 kg	A														61, 70

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§ 173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Butyraldehyde	3	UN1129	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Butyraldoxime	3	UN2840	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Butyric acid	8	UN2820	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	12
	Butyric anhydride	8	UN2739	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	
	Butyronitrile	3	UN2411	II	3, 6.1	IB2, T7, TP1	None	202	243	1 L	60 L	E	40
	Butyl chloride	3	UN2353	II	3, 8	IB2, T8, TP2, TP12, TP13	None	202	243	1 L	5 L	C	40
	Cacodylic acid	6.1	UN1572	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	E	26
	Cadmium compounds	6.1	UN2570	II	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	
				II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
				III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Caesium hydroxide	8	UN2682	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	
	Caesium hydroxide solution	8	UN2681	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	A	
				III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	
	Calcium	4.3	UN1401	II	4.3	IB7, IP2	151	212	241	15 kg	50 kg	E	
	Calcium arsenate	6.1	UN1573	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Calcium arsenate and calcium arsenite, mixtures, solid	6.1	UN1574	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Calcium bisulfite solution, see Bisulfites, aqueous solutions, n.o.s.												
	Calcium carbide	4.3	UN1402	I	4.3	A1, A8, B55, B59, IB4, IP1, N34	None	211	242	Forbidden	15 kg	B	
				II	4.3	A1, A8, B55, B59, IB7, IP2, N34	151	212	241	15 kg	50 kg	B	
	Calcium chlorate	5.1	UN1452	II	5.1	IB8, IP2, IP4, N34	152	212	242	5 kg	25 kg	A	56, 58, 106
	Calcium chlorate aqueous solution.	5.1	UN2429	II	5.1	A2, IB2, N41, T4, TP1	152	202	242	1 L	5 L	B	56, 58, 106
				III	5.1	A2, IB2, N41, T4, TP1	152	203	241	2.5 L	30 L	B	56, 58, 106
	Calcium chlorite	5.1	UN1453	II	5.1	A9, IB8, IP2, IP4, N34	152	212	242	5 kg	25 kg	A	56, 58, 106
	Calcium cyanamide with more than 0.1 percent of calcium carbide.	4.3	UN1403	III	4.3	A1, A19, IB8, IP4	151	213	241	25 kg	100 kg	A	

Calcium cyanide .....	6.1	UN1575	I	6.1	IB7, IP1, N79, N80	None	211	242	5 kg	50 kg	A	26, 40
Calcium dithionite or Calcium hydrosulfite .....	4.2	UN1923	II	4.2	A19, A20, IB6, IP2	None	212	241	15 kg	50 kg	E	13
Calcium hydride .....	4.3	UN1404	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	.....
Calcium hydrosulfite, see Calcium dithionite .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Calcium hypochlorite, dry or Calcium hypochlorite mixtures dry with more than 39 percent available chlorine (8.8 percent available oxygen) .....	5.1	UN1748	II	5.1	A7, A9, IB8, IP2, IP4, N34, W9	152	212	None	5 kg	25 kg	D	4, 5, 25, 48, 56, 58, 69
Calcium hypochlorite, hydrated or Calcium hypochlorite, hydrated mixtures, with not less than 5.5 percent but not more than 16 percent water .....	5.1	UN2880	II	5.1	IB8, IP2, IP4, W9	152	212	240	5 kg	25 kg	D	4, 5, 25, 48, 56, 58, 69
Calcium hypochlorite mixtures, dry, with more than 10 percent but not more than 39 percent available chlorine .....	5.1	UN2208	III	5.1	A1, A29, IB8, IP3, N34, W9	152	213	240	25 kg	100 kg	D	4, 5, 25, 48, 56, 58, 69
Calcium manganese silicon .....	4.3	UN2844	III	4.3	A1, A19, IB8, IP2, IP4	151	213	241	25 kg	100 kg	A	85, 103
Calcium nitrate .....	5.1	UN1454	III	5.1	34, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
Calcium oxide .....	8	UN1910	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	.....
Calcium perchlorate .....	5.1	UN1455	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	56, 58, 106
Calcium permanganate .....	5.1	UN1456	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	D	56, 58, 69, 106, 107
Calcium peroxide .....	5.1	UN1457	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	13, 75, 106
Calcium phosphide .....	4.3	UN1360	I	4.3, 6.1	A8, A19, N40	None	211	242	Forbidden	15 kg	E	40, 85
Calcium, pyrophoric or Calcium alloys, pyrophoric .....	4.2	UN1855	I	4.2	.....	None	187	None	Forbidden	Forbidden	D	.....
Calcium resinate .....	4.1	UN1313	III	4.1	A1, A19, IB6	None	213	240	25 kg	100 kg	A	.....
Calcium resinate, fused .....	4.1	UN1314	III	4.1	A1, A19, IB4	None	213	240	25 kg	100 kg	A	.....
Calcium selenate, see Selenates or Selenites .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Calcium silicide .....	4.3	UN1405	II	4.3	A19, IB7, IP2	151	212	241	15 kg	50 kg	B	85, 103
Camphor oil .....	3	UN1130	III	4.3	A1, A19, IB8, IP4	151	213	241	25 kg	100 kg	B	85, 103
Camphor, synthetic .....	4.1	UN2717	III	4.1	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Carbon primers, see Primers, tubular .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Caproic acid .....	8	UN2829	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	.....
Caps, blasting, see Detonators, etc. ....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

A

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
I	Carbamate pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2758	I	3, 6.1	T14, TP2, TP13, TP27	None ...	201	243	Forbidden	30 L	B	40
							None ...	202	243	1 L	60 L	B	40
I	Carbamate pesticides, liquid, toxic.	6.1	UN2992	I	6.1	T14, TP2, TP13, TP27	None ...	201	243	1 L	30 L	B	40
							None ...	202	243	5 L	60 L	B	40
I	Carbamate pesticides, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN2991	I	6.1, 3	T14, TP2, TP13, TP28	None ...	201	243	1 L	30 L	B	40
							None ...	202	243	5 L	60 L	B	40
I	Carbamate pesticides, solid, toxic.	6.1	UN2757	I	6.1	B1, IB3, T7, TP2, TP28	None ...	203	242	60 L	220 L	A	40
							None ...	211	242	5 kg	50 kg	A	40
I	Carbolic acid, see Phenol, solid or Phenol, molten.	4.2	UN1362	III	4.2	IB8, IP2, IP4	None ...	212	242	25 kg	100 kg	A	40
							None ...	213	240	100 kg	200 kg	A	40
I	Carbon, animal or vegetable ori- gin.	4.2	UN1361	II	4.2	IB8, IP3	None ...	213	241	Forbidden	Forbidden	A	12
							None ...	213	241	Forbidden	Forbidden	A	12
I	Carbon dioxide	2.2	UN1013	.....	2.2	.....	306	302, 304.	75 kg	150 kg	A	.....	
							306	302, 304, 314, 315.	75 kg	150 kg	A	.....	
I	Carbon dioxide and nitrous oxide mixtures.	2.2	UN1015	.....	2.2	.....	306	None	75 kg	150 kg	A	.....	
							306	304, 314, 315.	75 kg	150 kg	A	.....	
I	Carbon dioxide and oxygen mix- tures, compressed.	2.2	UN1014	.....	2.2,	5.1.	306	304	75 kg	150 kg	A	.....	
							306	304	75 kg	150 kg	A	.....	

Carbon dioxide, refrigerated liquid.	2.2	UN2187	.....	2.2	.....	TP5	306	304	314, 315	50 kg	500 kg	B	.....
Carbon dioxide, solid or Dry ice	9	UN1845	III	None	217	B16, T14, TP2, TP7, TP13	217	217	240	200 kg	200 kg	C	40
Carbon disulfide	3	UN1131	I	3, 6.1	None	4	None	201	243	Forbidden	Forbidden	D	18, 40, 115
Carbon monoxide, compressed	2.3	UN1016	.....	2.3, 2.1.	None	6	None	302	314, 315	25 kg	25 kg	D	40
Carbon monoxide and hydrogen mixture, compressed.	2.3	UN2600	.....	2.3, 2.1.	None	4, T75, TP5	None	302	302	Forbidden	Forbidden	D	40
Carbon monoxide, refrigerated liquid ( <i>cyrogenic liquid</i> ).	2.3	NA9202	.....	2.3, 2.1.	None	2	None	316	318	Forbidden	Forbidden	D	.....
Carbon tetrabromide	6.1	UN2516	III	6.1	153	IB8, IP3	153	213	240	100 kg	200 kg	A	25
Carbon tetrachloride	6.1	UN1846	II	6.1	None	IB2, N36, T7, TP2	None	202	243	5 L	60 L	A	40
Carbonyl chloride, see Phosgene.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Carbonyl fluoride	2.3	UN2417	.....	2.3, 8	None	3, B14	None	302	None	Forbidden	Forbidden	D	40
Carbonyl sulfide	2.3	UN2204	.....	2.3, 2.1.	None	2	None	304	314, 315	Forbidden	Forbidden	D	40
Cartridge cases, empty primed, see Cases, cartridge, empty, with primer.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Cartridges, actuating, for aircraft ejector seat catapult, fire extinguisher, canopy removal or apparatus, see Cartridges, power devices.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Cartridges, explosive, see Charges, demolition.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Cartridges, flash	1.1G	UN0049	II	1.1G	None	62	None	62	None	Forbidden	Forbidden	07	.....
Cartridges, flash	1.3G	UN0050	II	1.3G	None	62	None	62	None	75 kg	75 kg	07	.....
Cartridges for weapons, blank	1.1C	UN0326	II	1.1C	None	62	None	62	None	Forbidden	Forbidden	07	.....
Cartridges for weapons, blank	1.2C	UN0413	II	1.2C	None	62	None	62	None	Forbidden	Forbidden	07	.....
Cartridges for weapons, blank or Cartridges, small arms, blank.	1.4S	UN0014	II	None	63	63	63	62	None	25 kg	100 kg	05	.....
Cartridges for weapons, blank or Cartridges, small arms, blank.	1.3C	UN0327	II	1.3C	None	62	None	62	None	Forbidden	Forbidden	07	.....
Cartridges for weapons, blank or Cartridges, small arms, blank.	1.4C	UN0338	II	1.4C	None	62	None	62	None	75 kg	75 kg	06	.....
Cartridges for weapons, blank or Cartridges, small arms, blank.	1.2C	UN0328	II	1.2C	None	62	None	62	None	Forbidden	Forbidden	03	.....
Cartridges for weapons, inert projectile.	1.4S	UN0012	II	None	63	63	63	62	None	25 kg	100 kg	05	.....
Cartridges for weapons, inert projectile or Cartridges, small arms.	1.4C	UN0339	II	1.4C	None	62	None	62	None	Forbidden	Forbidden	06	.....
Cartridges for weapons, inert projectile or Cartridges, small arms.	1.3C	UN0417	II	1.3C	None	62	None	62	None	Forbidden	Forbidden	06	.....

A W

D

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
(1)	Cartridges for weapons, with bursting charge.	1.1F	UN0005	II	1.1F		None	62	None	Forbidden	Forbidden	08	
	Cartridges for weapons, with bursting charge.	1.1E	UN0006	II	1.1E		None	62	None	Forbidden	Forbidden	03	
	Cartridges for weapons, with bursting charge.	1.2F	UN0007	II	1.2F		None	62	None	Forbidden	Forbidden	08	
	Cartridges for weapons, with bursting charge.	1.2E	UN0321	II	1.2E		None	62	None	Forbidden	Forbidden	03	
	Cartridges for weapons, with bursting charge.	1.4F	UN0348	II	1.4F		None	62	None	Forbidden	Forbidden	08	
	Cartridges for weapons, with bursting charge.	1.4E	UN0412	II	1.4E		None	62	None	Forbidden	75 kg	02	
	Cartridges, oil well	1.3C	UN0277	II	1.3C		None	62	None	Forbidden	Forbidden	07	
	Cartridges, oil well	1.4C	UN0278	II	1.4C		None	62	None	Forbidden	75 kg	06	
	Cartridges, power device	1.3C	UN0275	II	1.3C		None	62	None	Forbidden	75 kg	07	
	Cartridges, power device	1.4C	UN0276	II	1.4C	110	None	62	None	Forbidden	75 kg	06	
	Cartridges, power device	1.4S	UN0323	II	1.4S	110	63	62	None	25 kg	100 kg	05	
	Cartridges, power device	1.2C	UN0381	II	1.2C		None	62	None	Forbidden	Forbidden	07	
	Cartridges power devices (used to project fastening devices).	ORM-D				None	63	None	None	30 kg gross	30 kg gross	A	
	D	Cartridges, safety, blank, see Cartridges for weapons, blank (UN 0014).											
Cartridges, safety, see Cartridges for weapons, other than blank or Cartridges, power device (UN 0323).													
Cartridges, signal		1.3G	UN0054	II	1.3G		None	62	None	Forbidden	75 kg	07	
Cartridges, signal		1.4G	UN0312	II	1.4G		None	62	None	Forbidden	75 kg	06	
Cartridges, signal		1.4S	UN0405	II	1.4S		None	62	None	25 kg	100 kg	05	
Cartridges, small arms		ORM-D					63	None	None	30 kg gross	30 kg gross	A	
Cartridges, sporting, see Cartridges for weapons, other than blank.													
Cartridges, starter, jet engine, see Cartridges, power device.													
Cases, cartridge, empty with primer.		1.4S	UN0055	II	1.4S	50	None	62	None	25 kg	100 kg	05	



A W	Cases, cartridges, empty with primer.	1.4C UN0379	II	1.4C ..	50	None ...	62 .....	None ...	Forbidden	75 kg	06	.....
	Cases, combustible, empty, without primer.	1.4C UN0446	II	1.4C ..		None ...	62 .....	None ...	Forbidden	75 kg	06	.....
	Cases, combustible, empty, without primer.	1.3C UN0447	II	1.3C ..		None ...	62 .....	None ...	Forbidden	Forbidden	07	.....
	Casinghead gasoline see Gasoline.											
	Castor beans or Castor meal or Castor pomace or Castor flake.	9 UN2969	II	None	IB8, IP2, IP4	155 .....	204 .....	240 .....	No limit	No limit	E	34, 40
G	Caustic alkali liquids, n.o.s. ....	8 UN1719	II	8 .....	B2, IB2, T11, TP2, TP27	154 .....	202 .....	242 .....	1 L	30 L	A	.....
	Caustic potash, see Potassium hydroxide etc.		III	8 .....	IB3, T7, TP1, TP28	154 .....	203 .....	241 .....	5 L	60 L	A	.....
	Caustic soda, (etc.) see Sodium hydroxide etc.											
	Cells, containing sodium .....	4.3 UN3292	II	4.3 .....		189 .....	189 .....	189 .....	25 kg gross	No limit	A	.....
	Celluloid, in block, rods, rolls, sheets, tubes, etc., except scrap.	4.1 UN2000	III	4.1 .....		None .....	213 .....	240 .....	25 kg	100 kg	A	.....
	Celluloid, scrap .....	4.2 UN2002	III	4.2 .....	IB8, IP3	None .....	213 .....	241 .....	Forbidden	Forbidden	D	.....
	Cement, see Adhesives containing flammable liquid.											
	Cerium, slabs, ingots, or rods ....	4.1 UN1333	II	4.1 .....	IB8, IP2, IP4, N34	None .....	212 .....	240 .....	15 kg	50 kg	A	74, 91
	Cerium, turnings or gritty powder	4.3 UN3078	II	4.3 .....	A1, IB7, IP2	151 .....	212 .....	242 .....	15 kg	50 kg	E	.....
	Cesium or Caesium .....	4.3 UN1407	I	4.3 .....	A19, IB1, IP1, N34, N40	None .....	211 .....	242 .....	Forbidden	15 kg	D	.....
	Cesium nitrate or Caesium nitrate.	5.1 UN1451	III	5.1 .....	A1, A29, IB8, IP3	152 .....	213 .....	240 .....	25 kg	100 kg	A	.....
D	Charcoal briquettes, shell, screenings, wood, etc. ....	4.2 NA1361	III	4.2 .....	IB8	151 .....	213 .....	240 .....	25 kg	100 kg	A	12
	Charges, bursting, plastics bonded.	1.1D UN0457	II	1.1D ..		None .....	62 .....	None ...	Forbidden	Forbidden	07	.....
	Charges, bursting, plastics bonded.	1.2D UN0458	II	1.2D ..		None .....	62 .....	None ...	Forbidden	Forbidden	07	.....
	Charges, bursting, plastics bonded.	1.4D UN0459	II	1.4D ..		None .....	62 .....	None ...	Forbidden	75 kg	06	.....
	Charges, bursting, plastics bonded.	1.4S UN0460	II	1.4S ...		None .....	62 .....	None ...	25 kg	100 kg	05	.....
	Charges, demolition .....	1.1D UN0048	II	1.1D ..		None .....	62 .....	None ...	Forbidden	Forbidden	03	.....
	Charges, depth .....	1.1D UN0056	II	1.1D ..		None .....	62 .....	None ...	Forbidden	Forbidden	03	.....
	Charges, expelling, explosive, for fire extinguishers, see Cartridges, power device.											
	Charges, explosive, commercial without detonator.	1.1D UN0442	II	1.1D ..		None .....	62 .....	None ...	Forbidden	Forbidden	07	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
D	Charges, explosive, commercial without detonator.	1.2D	UN0443	II	1.2D ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, explosive, commercial without detonator.	1.4D	UN0444	II	1.4D ..		None ...	62	None ...	Forbidden	75 kg	06	.....
	Charges, explosive, commercial without detonator.	1.4S	UN0445	II	1.4S ...		None ...	62	None ...	25 kg	100 kg	05	.....
	Charges, propelling	1.1C	UN0271	II	1.1C ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, propelling	1.3C	UN0272	II	1.3C ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, propelling	1.2C	UN0415	II	1.2C ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, propelling	1.4C	UN0491	II	1.4C ..		None ...	62	None ...	Forbidden	75 kg	06	.....
	Charges, propelling, for cannon	1.3C	UN0242	II	1.3C ..		None ...	62	None ...	Forbidden	Forbidden	10	.....
	Charges, propelling, for cannon	1.1C	UN0279	II	1.1C ..		None ...	62	None ...	Forbidden	Forbidden	10	.....
	Charges, shaped, flexible, linear	1.2C	UN0414	II	1.2C ..		None ...	62	None ...	Forbidden	Forbidden	10	.....
	Charges, shaped, flexible, linear	1.4D	UN0237	II	1.4D ..	101	None ...	62	None ...	Forbidden	75 kg	06	.....
	Charges, shaped, flexible, linear	1.1D	UN0288	II	1.1D ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, shaped, without deto-nator.	1.1D	UN0059	II	1.1D ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, shaped, without deto-nator.	1.2D	UN0439	II	1.2D ..		None ...	62	None ...	Forbidden	Forbidden	07	.....
	Charges, shaped, without deto-nator.	1.4D	UN0440	II	1.4D ..		None ...	62	None ...	Forbidden	75 kg	06	.....
	Charges, shaped, without deto-nator.	1.4S	UN0441	II	1.4S ...		None ...	62	None ...	25 kg	100 kg	05	.....
	Charges, supplementary explo-sive.	1.1D	UN0060	II	1.1D ..		None ...	62	None ...	Forbidden	Forbidden	10	.....
	Chemical kit	8	NA1760	II	8	.....	154	161	None ...	1 L	30 L	B	40
	Chemical kits	9	UN3316	II	9	.....	15	161	None ...	10 kg	10 kg	A	40
	Chloral anhydrous, stabilized	6.1	UN2075	II	6.1	.....	IB2, T7, TP2	202	243	5 L	60 L	D	56, 58, 106
Chlorate and borate mixtures	5.1	UN1458	II	5.1	.....	A9, IB8, IP2, IP4, N34	152	240	5 kg	25 kg	A	56, 58, 106	
						A9, IB8, IP3, N34	152	240	25 kg	100 kg	A	56, 58, 106	
Chlorate and magnesium chlo-ride mixtures.	5.1	UN1459	II	5.1	.....	A9, IB8, IP2, IP4, N34, T4, TP1	152	240	5 kg	25 kg	A	56, 58, 106	
						A9, IB8, IP3, N34, T4, TP1	152	240	25 kg	100 kg	A	56, 58, 106	
Chlorate of potash, see Potas-sium chlorate.													
Chlorate of soda, see Sodium chlorate.													

Chlorates, inorganic, aqueous solution, n.o.s.	5.1	UN3210	II	5.1	IB2, T4, TP1	152	202	242	1 L	5 L	B	56, 58, 106
Chlorates, inorganic, n.o.s.	5.1	UN1461	II	5.1	A9, IB6, IP2, N34	152	212	242	5 kg	25 kg	A	56, 58, 106
Chloric acid aqueous solution, with not more than 10 percent chloric acid.	5.1	UN2626	II	5.1	IB2	None	229	None	Forbidden	Forbidden	D	56, 58, 106
Chloride of phosphorus, see chloric acid.												
Phosphorus trichloride.												
Chloride of sulfur, see Sulfur chloride.												
Chlorinated lime, see Calcium hypochlorite mixtures, etc.												
Chlorine	2.3	UN1017		2.3, 8	2, B9, B14, T50, TP19	None	304	314, 315	Forbidden	Forbidden	D	40, 51, 55, 62, 68, 89, 90
Chlorine azide	Forbidden											
Chlorine dioxide, hydrate, frozen	5.1	NA9191	II	5.1, 6.1		None	229	None	Forbidden	Forbidden	E	
Chlorine dioxide (not hydrate)	Forbidden											
Chlorine pentafluoride	2.3	UN2548		2.3, 5.1, 8	1, B7, B9, B14	None	304	314	Forbidden	Forbidden	D	40, 89, 90
Chlorine trifluoride	2.3	UN1749		2.3, 5.1, 8	2, B7, B9, B14	None	304	314	Forbidden	Forbidden	D	40, 89, 90
Chlorite solution	8	UN1908	II	8	A3, A6, A7, B2, IB2, N34, T7, TP2, TP24	154	202	242	1 L	30 L	B	26
Chlorites, inorganic, n.o.s.												
1-Chloro-1,1-difluoroethane or Refrigerant gas R 142b.	5.1	UN1462	II	5.1	A3, A6, A7, B2, IB3, N34, T4, TP2, TP24	154	203	241	5 L	60 L	B	26
3-Chloro-4-methylphenyl isocyanate.	2.1	UN2517		2.1	A7, IB6, IP2, N34	152	212	242	5 kg	25 kg	A	56, 58, 106
1-Chloro-1,2,2,2-tetrafluoroethane or Refrigerant gas R 124.	6.1	UN2236	II	6.1	T50	None	202	243	Forbidden	150 kg	B	40
4-Chloro-o-toluidine hydrochloride.	2.2	UN1021		2.2	IB2	None	202	243	5 L	60 L	B	40
1-Chloro-2,2,2-trifluoroethane or Refrigerant gas R 133a.	6.1	UN1579	III	6.1	T50	306	304	314, 315	75 kg	150 kg	A	
Chloroacetic acid, molten	2.2	UN1983		2.2	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	
Chloroacetic acid, solid	6.1	UN3250	II	6.1, 8	T50	306	304	314, 315	75 kg	150 kg	A	
	6.1	UN1751	II	6.1, 8	IB1, T7, TP3, TP28	None	202	243	Forbidden	Forbidden	C	40
	6.1	UN1751	II	6.1, 8	A3, A7, IB8, IP4, N34	None	212	242	15 kg	50 kg	A	40

D

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8A)	(8B)	(8C)	(9A)	(9B)	(10A)	(10B)
	Chloroacetic acid, solution .....	6.1	UN1750	II	6.1, 8	A7, IB2, N34, T7, TP2	None ...	202 .....	243 .....	1 L	30 L	C	40
	Chloroacetone, stabilized .....	6.1	UN1695	I	6.1, 3, 8	2, B9, B14, B32, B74, N12, N32, N34, T20, TP2, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	21, 40, 100
+	<i>Chloroacetone (unstabilized)</i> .....	Forbidden	UN2668	II	6.1, 3	2, B9, B14, B32, B74, IB99, T20, TP2, TP38, TP45	.....	.....	.....	.....	.....	A	.....
	Chloroacetone (CN), liquid	6.1	UN1697	II	6.1	A3, IB2, N12, N32, N33, T11, TP2, TP13, TP27	None ...	202 .....	243 .....	Forbidden	60 L	D	12, 40
	Chloroacetophenone (CN), solid	6.1	UN1697	II	6.1	A3, IB8, IP2, IP4, N12, N32, N33, N34, T7, TP2, TP13	None ...	212 .....	None ...	Forbidden	100 kg	D	12, 40
	Chloroacetyl chloride .....	6.1	UN1752	I	6.1, 8	2, A3, A6, A7, B3, B8, B9, B14, B32, B74, B77, N34, N43, T20, TP2, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	40
	Chloroanilines, liquid .....	6.1	UN2019	II	6.1	IB2, T7, TP2	None ...	202 .....	243 .....	5 L	60 L	A	.....
	Chloroanilines, solid .....	6.1	UN2018	II	6.1	IB8, IP2, IP4, T7, TP2	None ...	212 .....	242 .....	25 kg	100 kg	A	.....
	Chloroanisidines .....	6.1	UN2233	III	6.1	IB8, IP3	153 .....	213 .....	240 .....	100 kg	200 kg	A	.....
	Chlorobenzene .....	3	UN1134	III	3	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	.....
	Chlorobenzol, see Chloro- benzene.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Chlorobenzotrifluorides .....	3	UN2234	III	3	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	40
	Chlorobenzyl chlorides .....	6.1	UN2235	III	6.1	IB3, T4, TP1	153 .....	203 .....	241 .....	60 L	220 L	A	.....
	Chlorobutanes .....	3	UN1127	III	3	IB2, T4, TP1	150 .....	202 .....	242 .....	5 L	60 L	B	.....
	Chlorocresols, liquid .....	6.1	UN2669	II	6.1	IB2, T7, TP2	None ...	202 .....	243 .....	5 L	60 L	A	12
	Chlorocresols, solid .....	6.1	UN2669	II	6.1	IB8, IP2, IP3, T7	None ...	212 .....	242 .....	25 kg	100 kg	A	12
	Chlorodifluorobromomethane or Refrigerant gas R 12B1.	2.2	UN1974	.....	2.2	T50	306 .....	304 .....	314, 315	75 kg	150 kg	A	.....

	Chlorodifluoromethane and chloropentafluoroethane mixture or Refrigerant gas R 502 with fixed boiling point, with approximately 49 percent chlorodifluoromethane.	2.2	UN1973	.....	2.2	T50	306	304	314, 315.	75 kg	150 kg	A	.....
+	Chlorodinitrobenzenes, liquid	6.1	UN1577	II	6.1	T50	306	304	314, 315.	75 kg	150 kg	A	.....
+	Chlorodinitrobenzenes, solid	6.1	UN1577	II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L	B	91
	2-Chloroethanal	6.1	UN2232	I	6.1	IB8, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	91
	Chloroform	6.1	UN1888	III	6.1	B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
G	Chloroformates, toxic, corrosive, flammable, n.o.s.	6.1	UN2742	II	6.1, 8, 3.	IB3, N36, T7, TP2	153	203	241	60 L	220 L	A	40
G	Chloroformates, toxic, corrosive, n.o.s.	6.1	UN3277	II	6.1, 8	5, IB1, T7, TP2	None	202	243	1 L	30 L	A	12, 13, 21, 25, 40, 100
	Chloromethyl chloroformate	6.1	UN2745	II	6.1, 8	IB2, T8, TP2, TP13, TP28	None	202	243	1 L	30 L	A	12, 13, 25, 40
	Chloromethyl ethyl ether	3	UN2354	II	3, 6.1	IB2, T7, TP1, TP13	None	202	243	1 L	60 L	E	12, 13, 21, 25, 40, 100
+	Chloronitroanilines	6.1	UN2237	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	.....
+	Chloronitrobenzene, ortho, liquid	6.1	UN1578	II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	A	.....
	Chloronitrobenzenes meta or para, solid	6.1	UN1578	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	.....
	Chloronitrobenzenes, liquid	6.1	UN2433	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	.....
	Chloronitrobenzenes, solid	6.1	UN2433	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	.....
	Chloropentafluoroethane or Refrigerant gas R 115.	2.2	UN1020	.....	2.2	150	306	304	314, 315.	75 kg	150 kg	A	.....
	Chlorophenolates, liquid or Phenolates, liquid.	8	UN2904	III	8	IB3	154	203	241	5 L	60 L	A	.....
	Chlorophenolates, solid or Phenolates, solid.	8	UN2905	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	.....
	Chlorophenols, liquid	6.1	UN2021	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	.....
	Chlorophenols, solid	6.1	UN2020	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	.....
	Chlorophenyltrichlorosilane	8	UN1753	II	8	A7, B2, B6, IB2, N34, T7, TP2	None	202	242	Forbidden	30 L	C	40
+	Chloropicrin	6.1	UN1580	I	6.1	2, B7, B9, B14, B32, B46, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Chloropicrin and methyl bromide mixtures.	2.3	UN1581	.....	2.3	2, B9, B14, T50	None	193	314, 315.	Forbidden	Forbidden	D	25, 40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Chloropicrin and methyl chloride mixtures. <i>Chloropicrin mixture, flammable (pressure not exceeding 14.7 psia at 115 degrees F flash point, below 100 degrees F) see Toxic liquids, flammable, etc.</i>	2.3	UN1582		2.3	2, T50	None	193	245	Forbidden	Forbidden	D	25, 40
	Chloropicrin mixtures, n.o.s.	6.1	UN1583	I	6.1	5	None	201	243	Forbidden	Forbidden	C	40
				III	6.1	IB2	None	202	243	Forbidden	Forbidden	C	40
				III	6.1	IB3	153	203	241	Forbidden	Forbidden	C	40
D	Chloroacetaldehyde	6.1	NA9263	I	6.1, 8	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	B	40
	Chloroacetic acid, solid	8	UN2507	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	
	Chloroacetic acid, liquid	3	UN1991	I	3, 6.1	B57, T14, TP2, TP13	None	201	243	Forbidden	30 L	D	40
	<i>Chloroacetic acid, uninhibited</i>	Forbidden											
	1-Chloropropane	3	UN1278	II	3	IB2, N34, T7, TP2	None	202	242	Forbidden	Forbidden	E	
	2-Chloropropane	3	UN2356	I	3	N36, T11, TP2, TP13	150	201	243	1 L	30 L	E	
	3-Chloropropanol-1	6.1	UN2849	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	2-Chloropropane	3	UN2456	I	3	A3, N36, T11, TP2	150	201	243	1 L	30 L	E	
	2-Chloropropionic acid	8	UN2511	III	8	IB3, T4, TP2	154	203	241	5 L	60 L	A	8
	2-Chloropyridine	6.1	UN2822	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40
	Chlorosilanes, corrosive, flammable, n.o.s.	8	UN2986	II	8, 3	IB2, T11, TP2, TP27	None	202	243	1 L	30 L	C	40
	Chlorosilanes, corrosive, n.o.s.	8	UN2987	II	8	B2, IB2, T14, TP2, TP27	154	202	242	1 L	30 L	C	40
	Chlorosilanes, flammable, corrosive, n.o.s.	3	UN2985	II	3, 8	IB1, T11, TP2, TP13, TP27	None	201	243	1 L	5 L	B	40
	Chlorosilanes, toxic, corrosive, n.o.s.	6.1	UN3361	II	6.1, 8	IB1, T11, TP2, TP13	None	202	243	1 L	30 L	C	40
	Chlorosilanes, toxic, corrosive, flammable, n.o.s.	6.1	UN3362	II	6.1, 3, 8	IB1, T11, TP2, TP13	None	202	243	1 L	30 L	C	40, 125

UN Number	Proper Shipping Name	Class	Division	Subdivision	Quantity	Special Provisions	Other	Notes
4.3 UN2988	Chlorosilanes, water-reactive, flammable, corrosive, n.o.s.	I	4.3, 3, 8	A2, T10, TP2, TP7, TP13	None	201	244	1 L 21, 28, 40, 49, 100, 40
8 UN1754	Chlorosulfonic acid (with or without sulfur trioxide)	I	8, 6.1	2, A3, A6, A10, B9, B10, B14, B32, B74, T20, TP2, TP12, TP38, TP45	None	227	244	Forbidden C
3 UN2238	Chlorobutenes	III	3	B1, IB3, T2, TP1, TP28	150	203	242	220 L A
6.1 UN2239	Chlorotoluidines liquid	III	6.1	IB3, T7, TP1	153	203	241	220 L A
6.1 UN2239	Chlorotoluidines solid	III	6.1	IB8, IP3, T4, TP1	153	213	240	200 kg A
2.2 UN2399	Chlorotrifluoromethane and trifluoromethane azeotropic mixture or Refrigerant gas R 503 with approximately 60 percent chlorotrifluoromethane		2.2		306	304	314, 315	150 kg A 75 kg A
2.2 UN1022	Chlorotrifluoromethane or Refrigerant gas R 13		2.2		306	304	314, 315	150 kg A
8 UN1755	Chromic acid solution	II	8	B2, IB2, T8, TP2, TP12	154	202	242	30 L C 40
		III	8	IB3, T4, TP1, TP12	154	203	241	60 L C 40
	Chromic anhydride, see Chromium trioxide, anhydrous							
8 UN1756	Chromic fluoride, solid	II	8	IB8, IP2, IP4	154	212	240	50 kg A 26
8 UN1757	Chromic fluoride, solution	III	8	B2, IB2, T7, TP2	154	202	242	30 L A 1 L
		III	8	IB3, T4, TP1	154	203	241	60 L A 5 L
5.1 UN2720	Chromium nitrate	III	5.1	A1, A29, IB8, IP3	152	213	240	100 kg A 25 kg C
8 UN1758	Chromium oxychloride	I	8	A3, A6, A7, B10, N34, T10, TP2, TP12	None	201	243	2.5 L C 40, 66, 74, 89, 90
5.1 UN1463	Chromium trioxide, anhydrous	II	5.1, 8	IB8, IP4	None	212	242	25 kg A
8 UN2240	Chromosulfuric acid	I	8	A3, A6, A7, B4, B6, N34, T10, TP2, TP12, TP13	None	201	243	2.5 L B 40, 66, 74, 89, 90
	Chromyl chloride, see Chromium oxychloride							
	Cigar and cigarette lighters, charged with fuel, see Lighters or Lighter refills containing flammable gas							
	Coal briquettes, hot							
Forbidden 2.3 UN1023	Coal gas, compressed		2.3		None	302	314, 315	25 kg D 40
3 UN1136	Coal tar distillates, flammable	II	3	IB2, T4, TP1	150	202	242	60 L B
		III	3	B1, IB3, T4, TP1, TP29	150	203	242	220 L A

+

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Coal tar dye, corrosive, liquid, n.o.s., see Dyes, liquid or solid, n.o.s., or Dye intermediates, liquid or solid, corrosive, n.o.s.												
	Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining).	3	UN1139	I	3	T11, TP1, TP8, TP27	150	201	243	1 L	30 L	E	
				II	3	149, IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B	
	Cobalt naphthenates, powder	4.1	UN2001	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Cobalt resinates, precipitated	4.1	UN1318	III	4.1	A19, IB8, IP3	151	213	240	25 kg	100 kg	A	
	Coke, hot	Forbidden		III	4.1	A1, A19, IB6	151	213	240	25 kg	100 kg	A	
D G	Collodion, see Nitrocellulose etc												
	Combustible liquid, n.o.s.	Combustible liquid	NA1993	III	None	IB3, T1, T4, TP1	150	203	241	60 L	220 L	A	
G	Components, explosive train, n.o.s.	1.2B	UN0382	II	1.2B	101	None	62	None	Forbidden	Forbidden	11	
G	Components, explosive train, n.o.s.	1.4B	UN0383	II	1.4B	101	None	62	None	Forbidden	75 kg	06	
G	Components, explosive train, n.o.s.	1.4S	UN0384	II	1.4S	101	None	62	None	25 kg	100 kg	05	
G	Components, explosive train, n.o.s.	1.1B	UN0461	II	1.1B	101	None	62	None	Forbidden	Forbidden	11	
D G	Compounds, cleaning liquid	8	NA1760	I	8	A7, B10, T14, TP2, TP9, TP27	None	201	243	0.5 L	2.5 L	B	40
				II	8	B2, IB2, N37, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III	8	IB3, N37, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
D G	Compounds, cleaning liquid	3	NA1993	I	3	T11, TP1, TP9	150	201	243	1 L	30 L	E	
				II	3	IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B	



Research and Special Programs Admin., DOT

§ 172.101

D G	Compounds, tree killing, liquid or Compounds, weed killing, liq- uid.	8	NA1760	I	8	B1, B52, IB3, T4, TP1, TP29 A7, B10, T14, TP2, TP9, TP27	None	201	243	0.5 L	2.5 L B	40
D G	Compounds, tree killing, liquid or Compounds, weed killing, liq- uid.	3	NA1993	II	8	B2, IB2, N37, T11, TP2, TP27 IB3, N37, T7, TP1, TP28 T11, TP1, TP9	154	202	242	1 L	30 L B	40
D G	Compounds, tree killing, liquid or Compounds, weed killing, liq- uid.	6.1	NA2810	III	8	B1, B52, IB3, T4, TP1, TP29 T14, TP2, TP13, TP27	154	203	241	5 L	60 L A	40
D G	Compounds, tree killing, liquid or Compounds, weed killing, liq- uid.	6.1	NA2810	I	3	T11, TP1, TP9	150	201	243	1 L	30 L E	40
G	Compressed gas, flammable, n.o.s.	2.1	UN1954	II	3	IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L B	40
G	Compressed gas, n.o.s.	2.2	UN1956	III	3	B1, B52, IB3, T4, TP1, TP29	150	203	242	60 L	220 L A	40
G	Compressed gas, oxidizing, n.o.s.	2.2	UN3156	I	6.1	T14, TP2, TP13, TP27	None	201	243	1 L	30 L B	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone A.	2.3	UN3304	II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L B	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone B.	2.3	UN3304	III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	220 L A	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone C.	2.3	UN3304		2.1		306	302	314, 315.	Forbidden	150 kg D	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone D.	2.3	UN3304		2.2		306	302	314, 315.	75 kg	150 kg A	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone A.	2.3	UN3304		2.2		307	305	314, 315.	75 kg	150 kg D	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone B.	2.3	UN3304		2.3		306	302	314, 315.	Forbidden	Forbidden D	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone C.	2.3	UN3304		2.3, 8		None	192	245	Forbidden	Forbidden D	40
GI	Compressed gas, toxic, corro- sive, n.o.s. Inhalation Hazard Zone D.	2.3	UN3304		2.3, 8		None	302	314, 315.	Forbidden	Forbidden D	40
GI	Compressed gas, toxic, flamm- able, corrosive, n.o.s. Inha- lation Hazard Zone A.	2.3	UN3305		2.3, 2.1, 8.		None	192	245	Forbidden	Forbidden D	17, 40
GI	Compressed gas, toxic, flamm- able, corrosive, n.o.s. Inha- lation Hazard Zone B.	2.3	UN3305		2.3, 2.1, 8.		None	302	314, 315.	Forbidden	Forbidden D	17, 40
GI	Compressed gas, toxic, flamm- able, corrosive, n.o.s. Inha- lation Hazard Zone C.	2.3	UN3305		2.3, 2.1, 8.		None	302	314, 315.	Forbidden	Forbidden D	17, 40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym- bols	(2) Hazardous materials descrip- tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
G I	Compressed gas, toxic, flam- mable, corrosive, n.o.s. <i>Inha- lation Hazard Zone D.</i>	2.3	UN3305	.....	2.3, 2.1, 8.	4	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	17, 40	
G	Compressed gas, toxic, flam- mable, n.o.s. <i>Inhalation haz- ard Zone A.</i>	2.3	UN1953	.....	2.3, 2.1.	1	None ... 192	245	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, flam- mable, n.o.s. <i>Inhalation haz- ard Zone B.</i>	2.3	UN1953	.....	2.3, 2.1.	2, B9, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, flam- mable, n.o.s. <i>Inhalation Haz- ard Zone C.</i>	2.3	UN1953	.....	2.3, 2.1.	3, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, flam- mable, n.o.s. <i>Inhalation Haz- ard Zone D.</i>	2.3	UN1953	.....	2.3, 2.1.	4	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, n.o.s. <i>In- halation Hazard Zone A.</i>	2.3	UN1955	.....	2.3	1	None ... 192	245	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, n.o.s. <i>In- halation Hazard Zone B.</i>	2.3	UN1955	.....	2.3	2, B9, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40	
G	Compressed gas, toxic, n.o.s. <i>In- halation Hazard Zone C.</i>	2.3	UN1955	.....	2.3	3, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40	
G I	Compressed gas, toxic, oxidiz- ing, corrosive, n.o.s. <i>In- halation Hazard Zone A.</i>	2.3	UN3306	.....	2.3, 5.1, 8.	1	None ... 192	244	Forbidden	Forbidden	D	40, 89, 90	
G I	Compressed gas, toxic, oxidi- zing, corrosive, n.o.s. <i>Inhala- tion Hazard Zone B.</i>	2.3	UN3306	.....	2.3, 5.1, 8.	2, B9, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40, 89, 90	
G I	Compressed gas, toxic, oxidi- zing, corrosive, n.o.s. <i>Inhala- tion Hazard Zone C.</i>	2.3	UN3306	.....	2.3, 5.1, 8.	3, B14	None ... 302, 305.	314, 315.	Forbidden	Forbidden	D	40, 89, 90	
G	Compressed gas, toxic, oxidi- zing, n.o.s. <i>Inhalation Haz- ard Zone A.</i>	2.3	UN3303	.....	2.3, 5.1.	1	None ... 192	245	Forbidden	Forbidden	D	40	

G	Compressed gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone B.	2.3	UN3303	.....	2.3, 5.1.	2, B9, B14	None	302, 305.	314, 315.	Forbidden	Forbidden	D	40
G	Compressed gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone C.	2.3	UN3303	.....	2.3, 5.1.	3, B14	None	302, 305.	314, 315.	Forbidden	Forbidden	D	40
G	Compressed gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone D.	2.3	UN3303	.....	2.3, 5.1.	4	None	302, 305.	314, 315.	Forbidden	Forbidden	D	40
D	Consumer commodity	ORM-D		.....	None		156, 306.	156, 306.	None	30 kg gross	30 kg gross	A	.....
	Contrivances, water-activated, with burster, expelling charge or propelling charge.	1.2L	UN0248	II	1.2L	101	None	62	None	Forbidden	Forbidden	08	8E, 14E, 15E, 17E
	Contrivances, water-activated, with burster, expelling charge or propelling charge.	1.3L	UN0249	II	1.3L	101	None	62	None	Forbidden	Forbidden	08	8E, 14E, 15E, 17E
	Copper acetoarsenite	6.1	UN1585	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	Copper acetylacrylate	Forbidden		.....	.....		.....	.....	.....	.....	.....		.....
	Copper amine azide	6.1	UN1586	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	Copper arsenite	3	UN2776	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
	Copper based pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	Copper based pesticides, liquid, toxic.	6.1	UN3010	I	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	Copper based pesticides, liquid, toxic, flammable flash point not less than 23 degrees C.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	Copper based pesticides, solid, toxic.	6.1	UN2775	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....		.....
	Copper chlorate	5.1	UN2721	II	5.1	A1, IB8, IP2, IP4	152	212	242	5 kg	25 kg	A	56, 58, 106
	Copper chloride	8	UN2802	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	.....
	Copper cyanide	6.1	UN1587	II	6.1	IB8, IP2, IP4	None	204	242	25 kg	100 kg	A	26

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
A W	Copper selenate, see Selenates or Selenites.												
	Copper selenite, see Selenates or Selenites.												
	Copper tetramine nitrate	Forbidden 4.2	UN1363	III	4.2	IB8, IP3, IP6	None	213	241	Forbidden	Forbidden	A	13, 19, 48, 119
	Copa												
	Cord, detonating, flexible	1.1D	UN0065	II	1.1D	102	63(a)	62	None	None	Forbidden	07	
	Cord, detonating, flexible	1.4D	UN0289	II	1.4D		None	62	None	None	Forbidden	75 kg	06
	Cord, detonating or Fuse deto-nating metal clad	1.2D	UN0102	II	1.2D		None	62	None	None	Forbidden	07	
	Cord, detonating or Fuse, deto-nating metal clad	1.1D	UN0290	II	1.1D		None	62	None	None	Forbidden	07	
	Cord, detonating, mild effect or Fuse, detonating, mild effect metal clad	1.4D	UN0104	II	1.4D		None	62	None	None	Forbidden	75 kg	06
	Cord, igniter	1.4G	UN0066	II	1.4G		None	62	None	None	Forbidden	75 kg	06
G	Cordeau detonant fuse, see Cord, detonating, etc; Cord, detonating, flexible.												
	Cordite, see Powder, smokeless												
	Corrosive liquid, acidic, inor-ganic, n.o.s.		UN3264	I	8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II	8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III	8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
				I	8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II	8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III	8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
				I	8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II	8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
G	Corrosive liquid, basic, inor-ganic, n.o.s.		UN3266	I	8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II	8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III	8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
				I	8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40

Research and Special Programs Admin., DOT

§ 172.101

G	Corrosive liquid, basic, organic, n.o.s.	8	UN3267	I 8	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II 8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III 8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
G	Corrosive liquid, self-heating, n.o.s.	8	UN3301	I 8, 4.2	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	D	
				II 8, 4.2	B2, IB1	154	202	242	1 L	30 L	D	
				I 8, 3	B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	C	25, 40
G	Corrosive liquids, flammable, n.o.s.			II 8, 3	B2, IB2, T11, TP2, TP27	None	202	243	1 L	30 L	C	25, 40
G	Corrosive liquids, n.o.s.	8	UN1760	I 8	A7, B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
				II 8	B2, IB2, T11, TP2, TP27	154	202	242	1 L	30 L	B	40
				III 8	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	A	40
G	Corrosive liquids, oxidizing, n.o.s.	8	UN3093	I 8, 5.1	None	None	201	243	Forbidden	2.5 L	C	89
				II 8, 5.1	IB2	None	202	243	1 L	30 L	C	89
				I 8, 6.1	A7, B10, T14, TP2, TP27	None	201	243	0.5 L	2.5 L	B	40
G	Corrosive liquids, toxic, n.o.s.	8	UN2922	II 8, 6.1	B3, IB2, T7, TP2	None	202	243	1 L	30 L	B	40
				III 8, 6.1	IB3, T7, TP1, TP28	154	203	241	5 L	60 L	B	40
G	Corrosive liquids, water-reactive, n.o.s.	8	UN3094	I 8, 4.3	None	None	201	243	Forbidden	1 L	E	
				II 8, 4.3	IB7, IP1	None	202	243	1 L	5 L	E	
				I 8	None	None	211	242	1 kg	25 kg	B	
G	Corrosive solid, acidic, inorganic, n.o.s.	8	UN3260	II 8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	B	
				III 8	IB8, IP3	154	213	240	25 kg	100 kg	A	
				I 8	IB7, IP1	None	211	242	1 kg	25 kg	B	
G	Corrosive solid, acidic, organic, n.o.s.	8	UN3261	II 8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	B	
				III 8	IB8, IP3	154	213	240	25 kg	100 kg	A	
				I 8	IB7, IP1	None	211	242	1 kg	25 kg	B	
G	Corrosive solid, basic, inorganic, n.o.s.	8	UN3262	II 8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	B	
				III 8	IB8, IP3	154	213	240	25 kg	100 kg	A	
				I 8	IB7, IP1	None	211	242	1 kg	25 kg	B	
G	Corrosive solid, basic, organic, n.o.s.	8	UN3263	II 8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	B	
				III 8	IB8, IP3	154	213	240	25 kg	100 kg	A	
				I 8, 4.1	IB6	None	211	242	1 kg	25 kg	B	12, 25
G	Corrosive solids, flammable, n.o.s.	8	UN2921	II 8, 4.1	IB8, IP2, IP4	None	212	242	15 kg	50 kg	B	12, 25
				I 8	IB7, IP1	None	211	242	1 kg	25 kg	B	
G	Corrosive solids, n.o.s.	8	UN1759	I 8	None	None	211	242	1 kg	25 kg	B	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
					II 8	128, IB8, IP2, IP4	212	240	15 kg	50 kg	A		
G	Corrosive solids, oxidizing, n.o.s.	8	UN3084		III 8	128, IB8, IP3	213	240	25 kg	100 kg	A		
G	Corrosive solids, self-heating, n.o.s.	8	UN3095		II 8, 5.1	IB6, IP2	211	242	1 kg	25 kg	C		
G	Corrosive solids, toxic, n.o.s.	8	UN2923		II 8, 4.2	IB6, IP2	212	243	1 kg	25 kg	C		
G	Corrosive solids, water-reactive, n.o.s.	8	UN3096		II 8, 4.2	IB6, IP2	212	242	15 kg	50 kg	C		
D W	Cotton	9	NA1365		I 8, 6.1	IB7	211	242	1 kg	25 kg	B	40	
A W	Cotton waste, oily	4.2	UN1364		II 8, 6.1	IB8, IP2, IP4	212	240	15 kg	50 kg	B	40	
A I	Cotton, wet	4.2	UN1365		III 8, 6.1	IB8, IP3	154	213	240	100 kg	B	40, 95	
W	Coumarin derivative pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN3024		I 8, 4.3	IB4, IP1	211	243	1 kg	25 kg	D		
					II 8, 4.3	IB6, IP2	212	242	15 kg	50 kg	D		
					9	137, IB8, IP2, IP4, W41	None	None	No limit	No limit	A		
					III 4.2	IB8, IP6	213	241	Forbidden	Forbidden	A	54	
					III 4.2	IB8, IP6	204	241	Forbidden	Forbidden	A		
					I 3, 6.1	T14, TP2, TP13, TP27	201	243	Forbidden	Forbidden	B	40	
					II 3, 6.1	IB2, T11, TP2, TP13, TP27	202	243	1 L	60 L	B	40	
					I 6.1	T14, TP2, TP13, TP27	201	243	1 L	30 L	B	40	
					II 6.1	IB2, T11, TP2, TP27	202	243	5 L	60 L	B	40	
					III 6.1	IB3, T7, TP1, TP28	203	241	60 L	220 L	A	40	
					I 6.1, 3	T14, TP2, TP13, TP27	201	243	1 L	30 L	B	40	
					II 6.1, 3	IB2, T11, TP2, TP13, TP27	202	243	5 L	60 L	B	40	
					III 6.1, 3	B1, IB3, T7, TP1, TP28	203	242	60 L	220 L	A	40	

Coumarin derivative pesticides, solid, toxic	6.1	UN3027	I	6.1	IB7, IP1, T14, TP2, TP27	None	211	242	5 kg	50 kg	A	40
			II	6.1	IB8, IP2, IP4, T11, IP2, TP27	None	212	242	25 kg	100 kg	A	40
			III	6.1	IB8, IP3, T7, TP1, TP28	153	213	240	100 kg	200 kg	A	40
Cresols, liquid	6.1	UN2076	II	6.1, 8	IB8, IP2, IP4, T7, TP2	None	202	243	1 L	30 L	B	
Cresols, solid	6.1	UN2076	II	6.1, 8	IB8, IP2, IP4, T7, TP2	None	202	243	1 L	30 L	B	
Cresylic acid	6.1	UN2022	II	6.1, 8	IB2, T7, TP2, TP13	None	202	243	1 L	30 L	B	
Crotonaldehyde, stabilized	6.1	UN1143	I	6.1, 3	2, B9, B14, B32, B74, B77, T20, TP2, TP13	None	227	244	Forbidden	Forbidden	B	40
Crotonic acid liquid	8	UN2823	III	8	TP38, TP45	154	203	241	5 L	60 L	A	12
Crotonic acid, solid	8	UN2823	III	8	IB3, T4, TP1	154	203	241	25 kg	100 kg	A	12
Crotonylene	3	UN1144	I	3	IB8, IP3	154	201	243	1 L	30 L	E	
Cupriethylenediamine solution	8	UN1761	II	8, 6.1	T11, TP2	150	201	243	1 L	30 L	A	
			III	8, 6.1	IB2, T7, TP2	None	202	243	1 L	30 L	A	95
			III	8, 6.1	IB3, T7, TP1, TP28	154	203	242	5 L	60 L	A	
Cutters, cable, explosive	1.4S	UN0070	II	1.4S		None	62	None	25 kg	100 kg	05	
Cyanide or cyanide mixtures, dry, see Cyanides, inorganic, solid, n.o.s.												
Cyanide solutions, n.o.s.	6.1	UN1935	I	6.1	B37, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40, 52
			II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	A	40, 52
			III	6.1	IB3, T7, TP2, TP13, TP28	153	203	241	60 L	220 L	A	40, 52
Cyanides, inorganic, solid, n.o.s.	6.1	UN1588	I	6.1	IB7, IP1, N74, N75	None	211	242	5 kg	50 kg	A	52
			II	6.1	IB8, IP2, IP4, N74, N75	None	212	242	25 kg	100 kg	A	52
			III	6.1	IB8, IP3, N74, N75	153	213	240	100 kg	200 kg	A	52
Cyanogen	2.3	UN1026		2.3		None	304	245	Forbidden	Forbidden	D	40
				2.1		None	211	242	1 kg	15 kg	D	40
Cyanogen bromide	6.1	UN1889	I	6.1, 8	A6, A8	None	192	245	Forbidden	Forbidden	D	40
Cyanogen chloride, stabilized	2.3	UN1589		2.3, 8		None	192	245	15 kg	50 kg	A	12, 40
Cyanuric chloride	8	UN2670	II	8	IB8, IP2, IP4	None	212	240	Forbidden	Forbidden	D	40
Cyanuric triazide	Forbidden					None	304	314	Forbidden	Forbidden	B	40
Cyclobutane	2.1	UN2601		2.1		306	304	314	Forbidden	150 kg	B	
				2.1		None	202	315	1 L	30 L	A	12, 13, 21, 25, 40, 100
Cyclobutyl chloroformate	6.1	UN2744	II	6.1, 8, 3	IB1, T7, TP2, TP13	None	202	243	1 L	30 L	A	
1,5,9-Cyclododecatriene	6.1	UN2518	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Cycloheptane .....	3	UN2241	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	40
	Cycloheptatriene .....	3	UN2603	II	3, 6.1	IB2, T7, TP1, TP13	None	202	243	1 L	60 L	E	40
	Cycloheptene .....	3	UN2242	II	3	B1, IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
	Cyclohexane .....	3	UN1145	III	3	B1, IB3, T2, TP1	150	202	242	5 L	60 L	E	.....
	Cyclohexanone .....	3	UN1915	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	Cyclohexene .....	3	UN2256	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E	.....
	Cyclohexenyldichlorosilane .....	8	UN1762	II	8	A7, B2, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	Cyclohexyl acetate .....	3	UN2243	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	Cyclohexyl isocyanate .....	6.1	UN2488	I	6.1, 3	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Cyclohexyl mercaptan .....	3	UN3054	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	40, 95
	Cyclohexylamine .....	8	UN2357	II	8, 3	IB2, T7, TP2	None	202	243	1 L	30 L	A	40
	Cyclohexyltrichlorosilane .....	8	UN1763	II	8	A7, B2, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	Cyclonite and cyclotetramethylenetetranitramine mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Cyclonite and HMX mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Cyclonite and octogen mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Cyclonite, see Cyclotrimethylenetrinitramine, etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Cyclooctadiene phosphines, see 9-Phosphabicyclononanes.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....



Cyclooctadienes .....	3	UN2520	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Cyclooctatetraene .....	3	UN2358	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Cyclopentane .....	3	UN1146	II	3	IB2, T7, TP1	150	202	242	5 L	60 L	E	.....
Cyclopentane, methyl, see Methylcyclopentane .....												
Cyclopentanol .....	3	UN2244	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Cyclopentanone .....	3	UN2245	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Cyclopentene .....	3	UN2246	II	3	IB2, T7, TP2	150	202	242	5 L	60 L	E	40
Cyclopropane .....	2.1	UN1027	.....	2.1	T50	306	304	314, 315.	Forbidden	150 kg	E	40
Cyclotetramethylene (dry tetranitramine or unpigmented) (HMX) .....	Forbidden											
Cyclotetramethylenetetranitramine, desensitized or Octogen, desensitized or HMX, desensitized .....	1.1D	UN0484	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Cyclotetramethylenetetranitramine, wettered or HMX, wettered or Octogen, wettered with not less than 15 percent water, by mass .....	1.1D	UN0226	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Cyclotrimethylenetrinitramine and cyclotetramethylenetetranitramine mixtures, wettered or desensitized see RDX and HMX mixtures, wettered or desensitized etc. ....												
Cyclotrimethylenetrinitramine and octogen, mixtures, wettered or desensitized see RDX and HMX mixtures, wettered or desensitized etc. ....												
Cyclotrimethylenetrinitramine and HMX mixtures, wettered or desensitized see RDX and HMX mixtures, wettered or desensitized etc. ....	1.1D	UN0483	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Cyclotrimethylenetrinitramine, desensitized or Cyclonite, desensitized or Hexogen, desensitized or RDX, desensitized .....	1.1D	UN0072	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Cyclotrimethylenetrinitramine, wettered or Cyclonite, wettered or Hexogen, wettered or RDX, wettered with not less than 15 percent water by mass .....												
Cymenes .....	3	UN2046	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
	Dangerous Goods in Machinery or Dangerous Goods in Appa- ratus.	9	UN3363			136	None ...	222	None ...	None ...	No limit	A	
	Decaborane	4.1	UN1868	II	4.1.	A19, A20, IB6, IP2	None ...	212	None ...	None ...	Forbidden	50 kg	A
	Decahydronaphthalene	3	UN1147	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	n-Decane	3	UN2247	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Deflagrating metal salts of aro- matic nitroderivatives, n.o.s.	1.3C	UN0132	II	1.3C		None ...	62	None ...	None ...	Forbidden	10	5E
	Delay electric igniter, see Ignit- ers.												
	Depth charges, see Charges, depth.												
	Detonating relays, see Deto- nators, etc.												
	Detonator assemblies, non-elec- tric for blasting.	1.1B	UN0360	II	1.1B		None ...	62	None ...	None ...	Forbidden	11	
	Detonator assemblies, non-elec- tric, for blasting.	1.4B	UN0361	II	1.4B	103	63(f), 63(g)	62	None ...	None ...	Forbidden	75 kg	06
	Detonator, assemblies, non- electric for blasting.	1.4S	UN0500	II	1.4S		63(f), 63(g)	62	None ...	None ...	25 kg	100 kg	05
	Detonators, electric, for blasting	1.1B	UN0030	II	1.1B		63(f), 63(g)	62	None ...	None ...	Forbidden	11	
	Detonators, electric, for blasting	1.4B	UN0255	II	1.4B	103	63(f), 63(g)	62	None ...	None ...	Forbidden	75 kg	06
	Detonators, electric for blasting	1.4S	UN0456	II	1.4S		63(f), 63(g)	62	None ...	None ...	25 kg	100 kg	05
	Detonators for ammunition	1.1B	UN0073	II	1.1B		None ...	62	None ...	None ...	Forbidden	11	
	Detonators for ammunition	1.2B	UN0364	II	1.2B		None ...	62	None ...	None ...	Forbidden	11	
	Detonators for ammunition	1.4B	UN0365	II	1.4B	103	None ...	62	None ...	None ...	Forbidden	75 kg	06
	Detonators for ammunition	1.4S	UN0366	II	1.4S		None ...	62	None ...	None ...	25 kg	100 kg	05
	Detonators, non-electric, for blasting.	1.1B	UN0029	II	1.1B		None ...	62	None ...	None ...	Forbidden	11	
	Detonators, non-electric, for blasting.	1.4B	UN0267	II	1.4B	103	63(f), 63(g)	62	None ...	None ...	Forbidden	75 kg	06
	Detonators, non-electric, for blasting.	1.4S	UN0455	II	1.4S		63(f), 63(g)	62	None ...	None ...	25 kg	100 kg	05
	Deuterium, compressed	2.1	UN1957		2.1		306	302	None ...	None ...	Forbidden	150 kg	E

UN3150	2.1	306	304	None	Forbidden	150 kg	B	40
Devices, small, hydrocarbon gas powered or Hydrocarbon gas refills for small devices with release device.								
UN2841 D-n-amylamine D-n-butyl peroxydicarbonate, with more than 52 percent in solution.	3 Forbidden	150	203	242	60 L	220 L	A	
UN2248 Di-n-butylamine 2,2-Di-(tert-butylperoxy) butane, with more than 55 percent in solution. Di-(tert-butylperoxy) phthalate, with more than 55 percent in solution. 2,2-Di-(4,4-d-tert-butylperoxycyclohexyl) propane, with more than 42 percent with inert solid. Di-2,4-dichlorobenzoyl peroxide, with more than 75 percent with water. 1,2-Di-(dimethylamino)ethane Di-2-ethylhexyl phosphoric acid, see Diisooctyl acid phosphate. Di-(1-hydroxytetrazole) (dry) Di-(1-naphthoyl) peroxide a,a'-Di-(nitroxy) methyl ether Di-(beta-nitroxyethyl) ammonium nitrate.	8 Forbidden	None	202	243	1 L	30 L	A	
UN2372 Diacetone alcohol peroxides, with more than 57 percent in solution with more than 9 percent hydrogen peroxide, less than 26 percent diacetone alcohol and less than 9 percent water; total active oxygen content more than 9 percent by mass.	3 Forbidden	150	202	242	5 L	60 L	B	
UN1148 Diacetone alcohol peroxides, with more than 57 percent in solution with more than 9 percent hydrogen peroxide, less than 26 percent diacetone alcohol and less than 9 percent water; total active oxygen content more than 9 percent by mass. Diacetyl, see Butanedione Diacetyl peroxide, solid, or with more than 25 percent in solution. Diagnostic specimen Diethylamine Diethyl ether	3 Forbidden	150	203	242	5 L 60 L	60 L 220 L	B A	
UN2359 Diethylamine	6.2 3	134 None	199 202	None 243	4 L or 4kg 1 L	4L or 4 kg 5 L	A B	40 21, 40, 100 40
UN2360 Diethyl ether	3	None	202	243	1 L	60 L	E	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
D	4,4'-Diaminodiphenyl methane ...	6.1	UN2651	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	
	<i>p</i> -Diazobenzene	Forbidden											
	1,2-Diazidobethane	Forbidden											
	1,1'-Diazaminonaphthalene	Forbidden											
	Diazoaminotetrazole (dry)	Forbidden											
	Diazodinitrophenol (dry)	Forbidden											
	Diazodinitrophenol, wetted with not less than 40 percent water or mixture of alcohol and water, by mass.	1.1A	UN0074	II	1.1A	111, 117	None	62	None	Forbidden	Forbidden	12	
	Diazodiphenylmethane	Forbidden											
	Diazonium nitrites (dry)	Forbidden											
	Diazonium perchlorates (dry)	Forbidden											
1,3-Diazopropane	Forbidden												
Dibenzyl peroxycarbonate, with more than 87 percent with water.	Forbidden												
Dibenzylchlorosilane	8	UN2434	II	8	B2, IB2, T7, TP2, TP13	154	202	242	1 L	30 L	C	40	
Diborane	2.3	UN1911	2.3	2.1	1	None	302	None	Forbidden	Forbidden	D	40, 57	
Diborane mixtures	2.1	NA1911		2.1	5	None	302	245	None	Forbidden	Forbidden	D	40, 57
Dibromoacetylene	Forbidden												
1,2-Dibromobutan-3-one	6.1	UN2648	II	6.1	IB2	None	202	243	243	5 L	60 L	B	40
Dibromochloropropane	6.1	UN2872	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A		
Dibromodifluoromethane, F12B2	9	UN1941	III	None	T11, TP2	155	203	241	100 L	220 L	A	25	
1,2-Dibromoethane, see Ethylene dibromide.													
Dibromomethane	6.1	UN2664	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A		
Dibutyl ethers	3	UN1149	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A		
Dibutylaminoethanol	6.1	UN2873	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A		
<i>N,N</i> -Dichloroazodicarbonamide (salts of) (dry).	Forbidden												
1,1-Dichloro-1-nitroethane	6.1	UN2650	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	12, 40	
3,5-Dichloro-2,4,6-trifluoropyridine.	6.1	NA9264	I	6.1	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	A		
Dichloroacetic acid	8	UN1784	II	8	A3, A6, A7, B2, IB2, N34, T8, TP2, TP12	154	202	242	1 L	30 L	A		

UN Number	Classification	Label	Quantity	Special Provisions	Other	Weight	Volume	Temperature
1,3-Dichloroacetone	6.1	UN2649	II	6.1	IB8, IP2, IP4	100 kg	30 L	12, 40
Dichloroacetyl chloride	8	UN1765	II	8	A3, A6, A7, B2, B6, IB2, N34, T7, TP2	30 L		40
Dichloroacetylene	Forbidden							
Dichloroanilines, liquid	6.1	UN1590	II	6.1	IB2, T7, TP2	60 L		40
Dichloroanilines, solid	6.1	UN1590	II	6.1	IB8, IP2, IP4, T7, TP2	100 kg		40
o-Dichlorobenzene	6.1	UN1591	III	6.1	IB3, T4, TP1	220 L		
2,2'-Dichlorodimethyl ether	6.1	UN1916	II	6.1, 3	IB2, N33, N34, T7, TP2	60 L		
Dichlorodifluoromethane and difluoroethane azetropic mixture or Refrigerant gas R 500 with approximately 74 percent dichlorodifluoromethane.	2.2	UN2602		2.2	T50	150 kg		
Dichlorodifluoromethane or Refrigerant gas R 12.	2.2	UN1028		2.2	T50	150 kg		
Dichlorodimethyl ether, symmetrical.	6.1	UN2249	I	6.1, 3		Forbidden		40
1,1-Dichloroethane	3	UN2362	II	3	IB2, T4, TP1	60 L		40
1,2-Dichloroethane, see Ethylene dichloride.								
Dichloroethyl sulfide	Forbidden							
1,2-Dichloroethylene	3	UN1150	II	3	IB2, T7, TP2	60 L		
Dichlorodifluoromethane or Refrigerant gas R21.	2.2	UN1029		2.2	T50	150 kg		
Dichloroisocyanuric acid, dry, or Dichloroisocyanuric acid salts.	5.1	UN2465	II	5.1	28, IB8, IP4	25 kg		13
Dichloroisopropyl ether	6.1	UN2490	II	6.1	IB2, T7, TP2	60 L		
Dichloromethane	6.1	UN1593	III	6.1	IB3, N36, T7, TP2	220 L		
Dichloropentanes	3	UN1152	III	3	B1, IB3, T2, TP1	220 L		
Dichlorophenyl isocyanates	6.1	UN2250	II	6.1	IB8, IP2, IP4, T7, TP2	100 kg		25, 40, 48
Dichlorophenyltrichlorosilane	8	UN1766	II	8	A7, B2, B6, IB2, N34, T7, TP2, TP13	30 L		40
1,2-Dichloropropane	3	UN1279	II	3	IB2, N36, T4, TP1	60 L		
1,3-Dichloropropanol-2	6.1	UN2750	II	6.1	IB2, T7, TP2	60 L		12, 40
Dichloropropane and propylene dichloride mixture, see 1,2-Dichloropropane.								
Dichloropropenes	3	UN2047	II	3	IB2, T4, TP1	60 L		
Dichlorosilane	2.3	UN2189	III	2.3, 2.1, 8.	B1, IB3, T2, TP1, 2, B9, B14	220 L		17, 40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
D	1,2-Dichloro-1,1,2,2-tetrafluoroethane or Refrigerant gas R 114.	2.2	UN1958		2.2	150	306	304	314, 315.	75 kg	150 kg	A	
	<i>Dichlorovinylchloroarsine</i>	Forbidden											
	<i>Dicycloheptadiene, see Bicyclo [2,2,1] hepta-2,5-diene, stabilized.</i>												
	Dicyclohexylamine	8	UN2565	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	
	Dicyclohexylammonium nitrite	4.1	UN2687	III	4.1	IB8, IP3	151	213	240	25 kg	100 kg	A	48
	Dicyclopentadiene	3	UN2048	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Didymium nitrate	5.1	UN1465	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	
	Diesel fuel	3	NA1983	III	None	144, B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A	
	Diesel fuel	3	UN 1202	III	3	144, B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	<i>Diethanol nitrosamine dinitrate (dry).</i>	Forbidden											
+	Diethoxymethane	3	UN2373	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E	
	3,3-Diethoxypropene	3	UN2374	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Diethyl carbonate	3	UN2366	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	<i>Diethyl cellosolve, see Ethylene glycol diethyl ether.</i>												
	Diethyl ether or Ethyl ether	3	UN1155	I	3	T11, TP2	150	201	243	1 L	30 L	E	40
	Diethyl ketone	3	UN1156	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	<i>Diethyl peroxydicarbonate, with more than 27 percent in solution.</i>	Forbidden											
	Diethyl sulfate	6.1	UN1594	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	C	
	Diethyl sulfide	3	UN2375	II	3	IB2, T7, TP1, TP13	None	202	243	5 L	60 L	E	
	Diethylamine	3	UN1154	II	3, 8	IB2, N34, T7, TP1	None	202	243	1 L	5 L	E	40
+	2-Diethylaminoethanol	8	UN2686	II	8, 3	B2, IB2, T7, TP2	None	202	243	1 L	30 L	A	
	3-Diethylamino-propylamine	3	UN2684	III	3, 8	B1, IB3, T4, TP1	150	203	242	5 L	60 L	A	
	N,N-Diethylamine	6.1	UN2432	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	Diethylbenzene	3	UN2049	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Diethylchlorosilane	8	UN1767	II	8, 3	A7, B6, IB2, N34, T7, TP2, TP13	None	202	243	Forbidden	30 L	C	40
<i>Diethylene glycol dinitrate</i>	Forbidden												

Diethyleneglycol dinitrate, desensitized with not less than 25 percent non-volatile water-insoluble pigments, by mass.	1.1D	UN0075	II	1.1D	None	62	None	Forbiddn	Forbiddn	13	21E
Diethylenetriamine	8	UN2079	II	8	154	202	242	1 L	30 L	A	40
N,N-Diethylethylenediamine	8	UN2685	II	8, 3	None	202	243	1 L	30 L	A	
Diethylaluminum bromide	Forbiddn										
Diethylthiophos-phonyl chloride	8	UN2751	II	8	None	212	240	15 kg	50 kg	D	12, 40
Diethylzinc	4.2	UN1366	I	4.2, 4.3	None	181	244	Forbiddn	Forbiddn	D	18
<i>Difluorochloroethanes, see 1-chloro-1,1-difluoroethanes.</i>											
1,1-Difluoroethane or Refrigerant gas R 152a	2.1	UN1030		2.1	306	304	314, 315	Forbiddn	150 kg	B	40
1,1-Difluoroethylene or Refrigerant gas R 1132a	2.1	UN1959		2.1	306	304	None	Forbiddn	150 kg	E	40
Difluoromethane or Refrigerant gas R 32	2.1	UN3252		2.1	306	302	314, 315	Forbiddn	150 kg	D	40
Difluorophosphoric acid, anhydrous.	8	UN1768	II	8	None	202	242	1 L	30 L	A	40
2,3-Dihydropran	3	UN2376	II	3	150	202	242	5 L	60 L	B	
1,8-Dihydroxy-2,4,5,7-tetraaminoanthraquinone (chrysamminic acid).	Forbiddn										
Diacetamide	Forbiddn										
Diisobutyl ketone	3	UN1157	III	3	150	203	242	60 L	220 L	A	
Diisobutylamine	3	UN2361	III	3, 8	150	203	242	5 L	60 L	A	
Diisobutylene, isomeric compounds.	3	UN2050	II	3	150	202	242	5 L	60 L	B	
Diisooctyl acid phosphate	8	UN1902	III	8	154	203	241	5 L	60 L	A	
Diisopropyl ether	3	UN1159	II	3	150	202	242	5 L	60 L	E	40
Diisopropylamine	3	UN1158	II	3, 8	None	202	243	1 L	5 L	B	
Diisopropylbenzene hydroperoxide, with more than 72 percent in solution.	Forbiddn										
Diketene, stabilized	6.1	UN2521	I	6.1, 3	None	227	244	Forbiddn	Forbiddn	D	40, 49
1,2-Dimethoxyethane	3	UN252	II	3	150	202	242	5 L	60 L	B	
1,1-Dimethoxyethane	3	UN2377	II	3	150	202	242	5 L	60 L	B	
Dimethyl carbonate	3	UN1161	II	3	150	202	242	5 L	60 L	B	
Dimethyl chloroacphosphate, see Dimethyl thiophosphoryl chloride.											
2,5-Dimethyl-2,5-dihydroperoxy hexane, with more than 82 percent with water.	Forbiddn										

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Dimethyl disulfide .....	3	UN2381	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	40
	Dimethyl ether .....		UN1033										
	Dimethyl-N-propylamine .....	3	UN2266	II	3, 8	IB2, T7, TP2, TP13	None	202	243	1 L	5 L	B	40
	Dimethyl sulfate .....	6.1	UN1595	I	6.1, 8	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Dimethyl sulfide .....	3	UN1164	II	3	IB1, T7, TP2	None	202	242	5 L	60 L	E	40
	Dimethyl thiophosphoryl chloride .....	6.1	UN2267	II	6.1, 8	IB2, T7, TP2	None	202	243	1 L	30 L	B	25
	Dimethylamine, anhydrous .....	2.1	UN1032	.....	2.1	T50	None	304	314, 315.	Forbidden	150 kg	D	40
	Dimethylamine solution .....	3	UN1160	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	.....
	2-Dimethylaminoacetone .....	3	UN2378	II	3, 6.1	IB2, T7, TP1	None	202	243	1 L	60 L	A	26, 40
	2-Dimethylaminoethanol .....	8	UN2051	II	8, 3	B2, IB2, T7, TP2	154	202	243	1 L	30 L	A	.....
	2-Dimethylaminoethyl acrylate .....	6.1	UN3302	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	D	25
	2-Dimethylaminoethyl methacrylate .....	6.1	UN2522	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	B	40
	N,N-Dimethylaniline .....	6.1	UN2253	II	6.1	IB1, T7, TP2	None	202	243	5 L	60 L	A	.....
2,3-Dimethylbutane .....	3	UN2457	II	3	IB2, T7, TP1	150	202	242	5 L	60 L	E	.....	
1,3-Dimethylbutylamine .....	3	UN2379	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	.....	
Dimethylcarbamoyl chloride .....	8	UN2262	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	A	40	
Dimethylcyclohexanes .....	3	UN2263	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....	
N,N-Dimethylcyclohexylamine .....	8	UN2264	II	8, 3	B2, IB2, T7, TP2	154	202	243	1 L	30 L	A	40	
Dimethylchlorosilane .....	3	UN1162	II	3, 8	B77, IB2, T7, TP2, TP13	None	202	243	Forbidden	Forbidden	B	40	
Dimethyldiethoxysilane .....	3	UN2380	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....	
Dimethyldioxanes .....	3	UN2707	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....	
N,N-Dimethylformamide .....	.....	.....	.....	.....	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....	
N,N-Dimethylformamide .....	.....	.....	.....	.....	B1, IB3, T2, TP2	150	203	242	60 L	220 L	A	.....	
Dimethylhexane dihydroperoxide (dty) .....	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	
Dimethylhydrazine, symmetrical .....	6.1	UN2382	I	6.1, 3	2, A7, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40	



Dimethylhydrazine, unsymmetrical.	6.1	UN1163	I	6.1, 3, 8.	2, B7, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	21, 38, 40, 100
2,2-Dimethylpropane	2.1	UN2044		2.1		306	304	314, 315.	Forbidden	150 kg	E	40
Dimethylzinc	4.2	UN1370	I	4.2, 4.3	B11, B16, T21, TP2, TP7	None	181	244	Forbidden	Forbidden	D	18
Dinitro-o-cresol, solid	6.1	UN1598	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	
Dinitro-o-cresol, solution	6.1	UN1598	II	6.1	IB2, IP2, IP4, T7, TP2	None	202	243	5 L	60 L	A	
1,3-Dinitro-5,5-dimethylhydantoin.	Forbidden											
Dinitro-7,8-dimethylglycoluril (dry).	Forbidden											
1,3-Dinitro-4,5-dinitrosobenzene	Forbidden											
1,4-Dinitro-1,1,4,4-tetramethylolbutanetetranitrate (dry).	Forbidden											
2,4-Dinitro-1,3,5-trimethylbenzene.	6.1	UN1596	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	91
Dinitroanilines	6.1	UN1597	II	6.1	11, IB2, T7, TP2	None	202	243	5 L	60 L	A	91
Dinitrobenzenes, liquid	6.1	UN1597	II	6.1	11, IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	91
Dinitrobenzenes, solid	6.1	UN1597	II	6.1								
Dinitrochlorobenzene, see Chlorodinitrobenzene.	Forbidden											
1,2-Dinitroethane	Forbidden											
1,1-Dinitroethane (dry)	2.3	UN1067		2.3, 5.1, 8.	1, B7, B14, B45, B46, B61, B66, B67, B77, T50, TP21	None	336	314	Forbidden	Forbidden	D	40, 89, 90
Dinitrogen tetroxide	2.3											
Dinitroglucuril or Dingu	1.1D	UN0489	II	1.1D		None	62	None	Forbidden	Forbidden	10	
Dinitromethane	Forbidden											
Dinitrophenol, dry or wetted with less than 15 percent water, by mass.	1.1D	UN0076	II	1.1D, 6.1.		None	62	None	Forbidden	Forbidden	10	5E
Dinitrophenol solutions	6.1	UN1599	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	36
Dinitrophenol, wetted with not less than 15 percent water, by mass.	4.1	UN1320	I	4.1, 6.1.	IB3, T4, TP1 23, A8, A19, A20, N41	None	203	241	60 L	220 L	A	36
Dinitrophenolates, alkali metals, dry or wetted with less than 15 percent water, by mass.	1.3C	UN0077	II	1.3C, 6.1.		None	62	None	1 kg	1 kg	E	28, 36
Dinitrophenolates, wetted with not less than 15 percent water, by mass.	4.1	UN1321	I	4.1, 6.1.	23, A8, A19, A20, N41	None	211	None	1 kg	15 kg	E	28, 36

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
(1)	Dinitropropylene glycol .....	Forbidden 1.1D	UN0078	II	1.1D ..		None	62	None	Forbidden	Forbidden	10	5E
	Dinitrosorcinol, dry or wetted with less than 15 percent water, by mass. (heavy metal salts of) (dry).	Forbidden											
	2,4-Dinitrosorcinol (heavy metal salts of) (dry).	Forbidden											
	4,6-Dinitrosorcinol (heavy metal salts of) (dry).	Forbidden											
	Dinitrosorcinol, wetted with not less than 15 percent water, by mass.	4.1	UN1322	I	4.1 .....	23, A8, A19, A20, N41	None	211	None	1 kg	15 kg	E	28, 36
	3,5-Dinitrosalicylic acid (lead salt) (dry).	Forbidden											
	Dinitrosobenzene .....	1.3C	UN0406	II	1.3C ..		None	62	None	Forbidden	Forbidden	10	
	Dinitrosobenzylamine and salts of (dry).	Forbidden											
	2,2-Dinitrosilbene .....	Forbidden											
	Dinitrotoluenes, liquid .....	6.1	UN2038	II	6.1 .....	IB2, T7, TP2	None	202	243	5 L	60 L	A	
	Dinitrotoluenes, molten .....	6.1	UN1600	II	6.1 .....	T7, TP3	None	202	243	Forbidden	Forbidden	C	
	Dinitrotoluenes, solid .....	6.1	UN2038	II	6.1 .....	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	
	1,9-Dinitroxy pentamethylene-2,4,6,8-tetramine (dry).	Forbidden											
	Dioxane .....	3	UN1165	II	3 .....	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Dioxolane .....	3	UN1166	II	3 .....	IB2, T4, TP1	150	202	242	5 L	60 L	B	40
	Dipentene .....	3	UN2052	III	3 .....	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Diphenylamine chloroarsine .....	6.1	UN1698	I	6.1 .....	A8, B14, B32, N33, N34, T14, TP2, TP13, TP27	None	201	None	Forbidden	Forbidden	D	40
	Diphenylchloroarsine, liquid .....	6.1	UN1699	I	6.1 .....	A8, B14, B32, IB7, IP1, N33, N34	None	201	243	Forbidden	30 L	D	40
	Diphenylchloroarsine, solid .....	6.1	UN1699	I	6.1 .....		None	211	242	Forbidden	15 kg	D	40
	Diphenyldichlorosilane .....	8	UN1769	II	8 .....	A7, B2, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	Diphenylmethyl bromide .....	8	UN1770	II	8 .....	IB8, IP2, IP4	154	212	240	15 kg	50 kg	D	40

	1.1D	UN0401	II	1.1D ..		None ...	62 .....	None ...	Forbidden	Forbidden	10	.....
Dipicryl sulfide, dry or wetted with less than 10 percent water, by mass.	4.1	UN2852	I	4.1 .....	A2, N41	None ...	211 .....	None ...	Forbidden	0.5 kg	D	28
Dipicryl sulfide, wetted with not less than 10 percent water, by mass.	Forbidden											
Dipicrylamine, see Hexanitrodiphenylamine.												
Dipropionyl peroxide, with more than 26 percent in solution.	3	UN2384	II	3 .....	IB2, T4, TP1	150 .....	202 .....	242 .....	5 L	60 L	B	
Dipropyl ether	3	UN2710	III	3 .....	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	
Dipropyl ketone	3	UN2383	II	3, 8 .....	IB2, T7, TP1	None .....	202 .....	243 .....	1 L	5 L	B	
Dipropylamine	8	UN1903	I	8 .....	A7, B10, T14, TP2, TP27	None .....	201 .....	243 .....	0.5 L	2.5 L	B	
Disinfectant, liquid, corrosive, n.o.s.	8	UN1903	II	8 .....	B2, IB2, T7, TP2	154 .....	202 .....	242 .....	1 L	30 L	B	
Disinfectants, liquid, corrosive n.o.s.												
Disinfectants, liquid, toxic, n.o.s.	6.1	UN3142	III	8 .....	IB3, T4, TP1	154 .....	203 .....	241 .....	5 L	60 L	A	
.....			I	6.1 .....	A4, T14, TP2, TP27	None .....	201 .....	243 .....	1 L	30 L	A	40
.....			II	6.1 .....	IB2, T11, TP2, TP27	None .....	202 .....	243 .....	5 L	60 L	A	40
.....			III	6.1 .....	IB3, T7, TP1, TP28	153 .....	203 .....	241 .....	60 L	220 L	A	40
Disinfectants, solid, toxic, n.o.s.	6.1	UN1601	II	6.1 .....	IB8, IP2, IP4	None .....	212 .....	242 .....	25 kg	100 kg	A	40
Disodium trioxosulfate	8	UN3253	III	6.1 .....	IB8, IP3	153 .....	213 .....	240 .....	100 kg	200 kg	A	40
Dispersant gases, n.o.s. see Refrigerant gases, n.o.s.			III	8 .....	IB8, IP3	154 .....	213 .....	240 .....	25 kg	100 kg	A	
Divinyl ether, stabilized	3	UN1167	I	3 .....	T11, TP2	None .....	201 .....	243 .....	1 L	30 L	E	40
Dodecyltrichlorosilane	8	UN1771	II	8 .....	A7, B2, B6, IB2, NG4, T7, TP2, TP13	None .....	202 .....	242 .....	Forbidden	30 L	C	40
Dry ice, see Carbon dioxide, solid.												
Dyes, liquid, corrosive, n.o.s. or Dye intermediates, liquid, corrosive, n.o.s.	8	UN2801	I	8 .....	11, B10, T14, TP2, TP27	None .....	201 .....	243 .....	0.5 L	2.5 L	A	
.....			II	8 .....	11, B2, IB2, T11, TP2, TP27	154 .....	202 .....	242 .....	1 L	30 L	A	
.....			III	8 .....	11, IB3, T7, TP1, TP28	154 .....	203 .....	241 .....	5 L	60 L	A	
Dyes, liquid, toxic, n.o.s. or Dye intermediates, liquid, toxic, n.o.s.	6.1	UN1602	II	6.1 .....	IB2	None .....	202 .....	243 .....	5 L	60 L	A	
.....			III	6.1 .....	IB3	153 .....	203 .....	241 .....	60 L	220 L	A	
Dyes, solid, corrosive, n.o.s. or Dye intermediates, solid, corrosive, n.o.s.	8	UN3147	I	8 .....	IB7, IP1	None .....	211 .....	242 .....	1 kg	25 kg	A	
.....			II	8 .....	IB8, IP2, IP4	154 .....	212 .....	240 .....	15 kg	50 kg	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§ 173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
G	Dyes, solid, toxic, n.o.s. or Dye intermediates, solid, toxic, n.o.s.	6.1	UN3143	III 1	8 6.1	IB8, IP3 A5, IB7, IP1, T14, TP2, TP27	154 None	213 211	240 242	25 kg 5 kg	100 kg 50 kg	A A	
	Dynamite, see Explosive, blasting, Type A.												
	Electrolyte (acid or alkali) for batteries, see Battery fluid, acid or Battery fluid, alkali.												
	Elevated temperature liquid, flammable, n.o.s., with flash point above 37.8 C, at or above its flash point.												
	Elevated temperature liquid, n.o.s., at or above 100 C and below its flash point (including molten metals, molten salts, etc.)												
	Elevated temperature solid, n.o.s., at or above 240 C, see § 173.247(h)(4).												
	Engines, internal combustion, flammable gas powered.												
	Engines, internal combustion, flammable liquid powered.												
	Environmentally hazardous substances, liquid, n.o.s.												
	Environmentally hazardous substances, solid, n.o.s.												
+	Epibromohydrin	6.1	UN2558	I	6.1, 3	T14, TP2, TP13	None	201	243	Forbidden	Forbidden	D	40
	Epichlorohydrin	6.1	UN2023	II	6.1, 3	IB2, T7, TP2, TP13	None	202	243	5 L	60 L A	A	40
G	1,2-Epoxy-3-ethoxypropane	3	UN2752	III 3	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Esters, n.o.s.	3	UN3272	III 3	3	IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B	
						B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A	



§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age											
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other										
+	Ethyl hydroperoxide .....	Forbidden	UN2385	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....										
	Ethyl isobutyrate .....		UN2481											None	226	244	Forbidden	D	40				
D	Ethyl isocyanate .....	Forbidden	UN1192	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....										
	Ethyl lactate .....		UN2363											None	201	243	Forbidden	E	95, 102				
	Ethyl mercaptan .....		UN2277											150	202	242	5 L	60 L	B	.....			
	Ethyl methacrylate, stabilized .....		UN1039											None	201	314, 315	Forbidden	B	40	.....			
	Ethyl methyl ether .....		UN1193											150	202	242	5 L	60 L	B	.....			
	Ethyl methyl ketone or Methyl ethyl ketone .....		UN1194											None	201	None	Forbidden	E	40, 105	.....			
	Ethyl nitrite solutions .....		UN2524											150	203	242	60 L	220 L	A	.....			
	Ethyl orthoformate .....		UN2525											153	203	241	60 L	220 L	A	.....			
	Ethyl oxalate .....		NA2927											None	227	244	Forbidden	D	40	.....			
	Ethyl perchlorate .....		Forbidden											6.1	NA2927	I	6.1, 8	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	D
Ethyl phosphonothioic dichloride, anhydrous .....																							
D	Ethyl phosphonous dichloride, anhydrous pyrophoric liquid .....	6.1	NA2845	I	6.1, 4.2	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	D	40											
D	Ethyl phosphorodichloridate .....	6.1	NA2927	I	6.1, 8	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	D	40											
D	Ethyl propionate .....	Forbidden	UN1195	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....										
	Ethyl propyl ether .....		UN2615											150	202	242	5 L	60 L	E	.....			
	Ethyl silicate, see Tetraethyl silicate .....		.....											.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Ethylacetylene, stabilized .....		UN2452											None	304	314, 315	Forbidden	B	40	.....			
D	Ethylamine .....	2.1	UN1036	.....	2.1	B77, T50	None	321	314, 315	Forbidden	D	40											

	3	UN2270	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	40
Ethylamine, aqueous solution with not less than 50 percent but not more than 70 percent ethylamine.												
N-Ethylaniline	6.1	UN2272	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
2-Ethylaniline	6.1	UN2273	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
Ethylbenzene	3	UN1175	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
N-Ethylbenzyloluidines liquid	6.1	UN2753	III	6.1	IB3, T7, TP1	153	203	241	60 L	220 L	A	
N-Ethylbenzyloluidines solid	6.1	UN2753	III	6.1	IB8, IP3, T7, TP1	153	213	240	100 kg	200 kg	A	
2-Ethylbutanol	3	UN2275	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
2-Ethylbutyl acetate	3	UN1177	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
2-Ethylbutyraldehyde	3	UN1178	II	3	B1, IB2, T4, TP1	150	202	242	5 L	60 L	B	
Ethylchloroarsine	6.1	UN1892	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
Ethylchlorosilane	4.3	UN1183	I	4.3, 8, 3	A2, A3, A7, N34, T10, TP2, TP7, TP13	None	201	244	Forbidden	1 L	D	21, 28, 40, 49, 100
Ethylene	2.1	UN1962		2.1		306	304	302	Forbidden	150 kg	E	40
Ethylene, acetylene and propylene in mixture, refrigerated liquid with at least 71.5 percent ethylene with not more than 22.5 percent acetylene and not more than 6 percent propylene.	2.1	UN3138		2.1	T75, TP5	None	304	314, 315	Forbidden	Forbidden	D	40
Ethylene chlorohydrin	6.1	UN1135	I	6.1, 3	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
Ethylene diamine diperchlorate	Forbidden											
Ethylene dibromide	6.1	UN1605	I	6.1	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
Ethylene dibromide and methyl bromide liquid mixtures, see Methyl bromide and ethylene dibromide, liquid mixtures.												
Ethylene dichloride	3	UN1184	II	3, 6.1	IB2, T7, TP1	None	202	243	1 L	60 L	B	40
Ethylene glycol diethyl ether	3	UN1153	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	A	
Ethylene glycol diethyl ether	3	UN1153	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
Ethylene glycol dinitrate	Forbidden											
Ethylene glycol monoethyl ether acetate.	3	UN1171	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
Ethylene glycol monoethyl ether ether.	3	UN1172	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
Ethylene glycol monomethyl ether.	3	UN1188	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Ethylene glycol monomethyl ether acetate.	3	UN1189	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Ethylene oxide and carbon dioxide mixture with more than 87 percent ethylene oxide.	2.3	UN3300		2.3, 2.1.	4	None	304	314, 315.	Forbidden	Forbidden	D	40
	Ethylene oxide and carbon dioxide mixtures with more than 9 percent but not more than 87 percent ethylene oxide.	2.1	UN1041		2.1	T50	306	304	314, 315.	Forbidden	25 kg	B	40
	Ethylene oxide and carbon dioxide mixtures with not more than 9 percent ethylene oxide.	2.2	UN1952		2.2		306	304	314, 315.	75 kg	150 kg	A	
	Ethylene oxide and chlorotetrafluoroethane mixture with not more than 8.8 percent ethylene oxide.	2.2	UN3297		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Ethylene oxide and dichlorodifluoromethane mixture, with not more than 12.5 percent ethylene oxide.	2.2	UN3070		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Ethylene oxide and pentafluoroethane mixture with not more than 7.9 percent ethylene oxide.	2.2	UN3298		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Ethylene oxide and propylene oxide mixtures, with not more than 30 percent ethylene oxide.	3	UN2983	I	3, 6.1	5, A11, N4, N34, T14, TP2, TP7, TP13	None	201	243	Forbidden	30 L	E	40
	Ethylene oxide and tetrafluoroethane mixture with not more than 5.6 percent ethylene oxide.	2.2	UN3299		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Ethylene oxide or Ethylene oxide with nitrogen up to a total pressure of 1MPa (10 bar) at 50 degrees C.	2.3	UN1040		2.3, 2.1.	4, T50, TP20	None	323	323	Forbidden	25 kg	D	40
	Ethylene, refrigerated liquid (cryogenic liquid).	2.1	UN1038		2.1	T75, TP5	None	316	318, 319.	Forbidden	Forbidden	D	40
	Ethylenediamine	8	UN1604	II	8, 3	IB2, T7, TP2	154	202	243	1 L	30 L	A	40



UN1185	6.1	UN1185	I	6.1, 3	1, B9, B14, B30, B72, B77, N25, N32, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D	40
Ethyleneimine, stabilized												
Ethylhexaldehyde, see Octyl aldehydes etc.												
2-Ethylhexyl chloroformate	6.1	UN2748	II	6.1, 8	IB2, T7, TP2, TP13	None	202	243	1 L	30 L	A	12, 13, 21, 25, 40, 100, 40
2-Ethylhexylamine	3	UN2276	III	3, 8	B1, IB3, T4, TP1	150	203	242	5 L	60 L	A	
Ethylphenyldichlorosilane	8	UN2435	II	8	A7, B2, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	
1-Ethylpiperidine	3	UN2386	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	
N-Ethyltrouidines	6.1	UN2754	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	
Ethyltrichlorosilane	3	UN1196	II	3, 8	A7, IB1, N34, T7, TP2, TP13	None	202	243	1 L	5 L	B	40
Etiologic agent, see Infectious substances etc.												
Explosive articles, see Articles, explosive, n.o.s. etc.												
Explosive, blasting, type A	1.1D	UN0081	II	1.1D		None	62	None	Forbidden	Forbidden	10	21E
Explosive, blasting, type B	1.1D	UN0082	II	1.1D		None	62	None	Forbidden	Forbidden	10	
Explosive, blasting, type B or Agent blasting, Type B.	1.5D	UN0331	II	1.5D	105, 106	None	62	None	Forbidden	Forbidden	10	
Explosive, blasting, type C	1.1D	UN0083	II	1.1D	123	None	62	None	Forbidden	Forbidden	10	22E
Explosive, blasting, type D	1.1D	UN0084	II	1.1D		None	62	None	Forbidden	Forbidden	10	
Explosive, blasting, type E	1.1D	UN0241	II	1.1D		None	62	None	Forbidden	Forbidden	10	19E
Explosive, blasting, type E or Agent blasting, Type E.	1.5D	UN0332	II	1.5D	105, 106	None	62	None	Forbidden	Forbidden	10	
Explosive, forbidden. See §173.54	Forbidden											
Explosive substances, see Substances, explosive, n.o.s. etc.												
Explosives, slurry, see Explosive, blasting, type E.												
Explosives, water gels, see Explosive, blasting, type E.												
Extracts, aromatic, liquid	3	UN1169	II	3	149, IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B	
Extracts, flavoring, liquid	3	UN1197	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
Fabric with animal or vegetable oil, see Fibers or fabrics, etc.												
Ferric arsenate	6.1	UN1606	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
Ferric arsenite	6.1	UN1607	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
Ferric chloride, anhydrous	8	UN1773	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
(1)	Ferric chloride, solution .....	8	UN2582	III	8	B15, IB3, T4, TP1	154	203	241	5 L	60 L	A	.....
	Ferric nitrate .....	5.1	UN1466	III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
	Ferrocenium .....	4.1	UN1323	II	4.1	59, A19, IB8, IP2, IP4	151	212	240	15 kg	50 kg	A	.....
	Ferrosilicon, with 30 percent or more but less than 50 percent silicon .....	4.3	UN1408	III	4.3, 6.1.	A1, A19, IB8, IP4	151	213	240	25 kg	100 kg	A	13, 40, 85, 103
D	Ferrous arsenate .....	6.1	UN1608	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
D	Ferrous chloride, solid .....	8	NA1759	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	.....
	Ferrous chloride, solution .....	8	NA1760	II	8	B3, IB2, T11, TP2, TP7	154	202	242	1 L	30 L	B	40
	Ferrous metal borings or Ferrous metal shavings or Ferrous metal turnings or Ferrous metal cuttings in a form liable to self-heating .....	4.2	UN2793	III	4.2	A1, A19, IB8, IP3, IP6	None	213	241	25 kg	100 kg	A	.....
	Fertilizer ammoniating solution with free ammonia .....	2.2	UN1043	.....	2.2	.....	306	304	314, 315.	Forbidden	150 kg	E	40
A, I, W	Fibers, animal or Fibers, vegetable burnt, wet or damp .....	4.2	UN1372	III	4.2	.....	151	213	240	Forbidden	Forbidden	A	.....
A W	Fibers or Fabrics, animal or vegetable or Synthetic, n.o.s. with animal or vegetable oil .....	4.2	UN1373	III	4.2	137, IB8, IP3	None	213	241	Forbidden	Forbidden	A	.....
	Fibers or Fabrics impregnated with weakly nitrated nitrocellulose, n.o.s. .....	4.1	UN1353	III	4.1	A1, IB8, IP3	None	213	240	25 kg	100 kg	D	.....
I, W	Fibers, vegetable, dry .....	4.1	UN3360	III	4.1	137	151	213	240	No limit	No limit	A	.....
	Films, nitrocellulose base, from which gelatine has been removed; film scrap, see Celluloid scrap .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Films, nitrocellulose base, gelatine coated (except scrap) .....	4.1	UN1324	III	4.1	.....	None	183	None	25 kg	100 kg	D	91
	Fire extinguisher charges, corrosive liquid .....	8	UN1774	II	8	N41	154	202	None	1 L	30 L	A	.....
	Fire extinguisher charges, explosive, see Cartridges, power device .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

Fire extinguishers containing compressed or liquefied gas.	2.2	UN1044	.....	2.2	18, 110	309	309	None	75 kg	150 kg	A	.....
Firelighters, solid with flammable liquid.	4.1	UN2623	III	4.1	A1, A19	None	213	None	25 kg	100 kg	A	.....
Fireworks	1.1G	UN0333	II	1.1G	108	None	62	None	Forbidden	Forbidden	07	.....
Fireworks	1.2G	UN0334	II	1.2G	108	None	62	None	Forbidden	Forbidden	07	.....
Fireworks	1.3G	UN0335	II	1.3G	108	None	62	None	Forbidden	Forbidden	07	.....
Fireworks	1.4G	UN0336	II	1.4G	108	None	62	None	Forbidden	75 kg	06	.....
Fireworks	1.4S	UN0337	II	1.4S	108	None	62	None	25 kg	100 kg	05	.....
First-aid kits	9	UN3316	.....	9	15	161	161	None	10 kg	10 kg	A	88, 122, 128
Fish meal, stabilized or Fish scrap, stabilized.	9	UN2216	III	.....	155, IB8	155	218	218	No limit	No limit	B	88, 122, 128
Fish meal, unstabilized or Fish scrap, unstabilized.	4.2	UN1374	II	4.2	155, A1, A19, IB8, IP2	None	212	241	15 kg	50 kg	B	88, 122, 128
Fissile radioactive materials, see Radioactive material, fissile, n.o.s.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Flammable compressed gas, see Compressed or Liquefied gas, flammable, etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Flammable compressed gas (small receptacles not fitted with a dispersion device, not refillable), see Receptacles, etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Flammable gas in lighters, see Lighters or lighter refills, cigaretters, containing flammable gas.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Flammable liquid, toxic, corrosive, n.o.s.	3	UN3286	I	3, 6.1, 8	T14, TP2, TP13, IB2, T11, TP2, TP13, TP27, T14, TP2	None	201	243	Forbidden	2.5 L	E	21, 40, 100
Flammable liquids, corrosive, n.o.s.	3	UN2924	II	3, 6.1, 8	IB2, T11, TP2, TP13, TP27, T14, TP2	None	202	243	1 L	5 L	B	21, 40, 100
.....	.....	.....	I	3, 8	IB2, T11, TP2, TP27	None	201	243	0.5 L	2.5 L	E	40
.....	.....	.....	II	3, 8	IB2, T11, TP2, TP27	None	202	243	1 L	5 L	B	40
.....	.....	.....	III	3, 8	B1, IB3, T7, TP1, TP28	150	203	242	5 L	60 L	A	40
Flammable liquids, n.o.s.	3	UN1993	I	3	T11, TP1, TP27, IB2, T7, TP1, TP8, TP28	150	201	243	1 L	30 L	E	.....
.....	.....	.....	II	3	B1, B52, IB3, T4, TP1, TP29	150	202	242	5 L	60 L	B	.....
.....	.....	.....	III	3	T14, TP2, TP13, TP27	150	203	242	60 L	220 L	A	.....
Flammable liquids, toxic, n.o.s.	3	UN1992	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	E	40
.....	.....	.....	II	3, 6.1	IB2, T7, TP2, TP13	None	202	243	1 L	60 L	B	40

W

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
G	Flammable solid, corrosive, inor- ganic, n.o.s.	4.1	UN3180	III	3, 6.1	B1, IB3, T7, TP1, TP28	150	203	242	60 L	220 L	A	40
G	Flammable solid, inorganic, n.o.s.	4.1	UN3178	III	4.1, 8	A1, IB6, IP2	151	212	242	15 kg	50 kg	D	40
G	Flammable solid, organic, mol- ten, n.o.s.	4.1	UN3176	III	4.1, 8	A1, IB8, IP3	151	213	242	25 kg	100 kg	D	40
G	Flammable solid, oxidizing, n.o.s.	4.1	UN3097	III	4.1	IB1, T3, TP3, TP26	151	212	240	Forbiddn	Forbiddn	C	40
G	Flammable solid, toxic, inor- ganic, n.o.s.	4.1	UN3179	III	4.1, 6.1	IB1, T1, TP3, TP26	151	213	240	Forbiddn	Forbiddn	C	40
G	Flammable solids, corrosive, or- ganic, n.o.s.	4.1	UN2925	III	4.1, 8	131	None	214	214	Forbiddn	Forbiddn	E	40
G	Flammable solids, organic, n.o.s.	4.1	UN1325	III	4.1	131	None	214	214	Forbiddn	Forbiddn	D	40
G	Flammable solids, toxic, organic, n.o.s.	4.1	UN2926	III	4.1, 6.1	A1, IB6, IP2	151	212	242	15 kg	50 kg	B	40
G	Flares, aerial	1.3G	UN0093	III	6.1	A1, IB6	151	213	242	25 kg	100 kg	B	40
G	Flares, aerial	1.4G	UN0403	II	1.3G ..		None	62	None	Forbiddn	75 kg	07	06
G	Flares, aerial	1.4S	UN0404	II	1.4G ..		None	62	None	Forbiddn	75 kg	06	05
G	Flares, aerial	1.1G	UN0420	II	1.4S ..		None	62	None	Forbiddn	100 kg	07	07
G	Flares, aerial	1.2G	UN0421	II	1.1G ..		None	62	None	Forbiddn	Forbiddn	07	07
G	Flares, <i>airplane, see</i> Flares, aer- ial.	1.2G		II	1.2G ..		None	62	None	Forbiddn	Forbiddn	07	07

Flares, signal, see Cartridges, signal.													
Flares, surface	1.3G ..	II	UN0092	None ..	62 ..	None ..	Forbidden	75 kg	07				
Flares, surface	1.1G ..	II	UN0418	None ..	62 ..	None ..	Forbidden	Forbidden	07				
Flares, surface	1.2G ..	II	UN0419	None ..	62 ..	None ..	Forbidden	Forbidden	07				
Flares, water-activated, see Contrivances, water-activated, etc.													
Flash powder	1.1G ..	II	UN0094	None ..	62 ..	None ..	Forbidden	Forbidden	15				
Flash powder	1.3G ..	II	UN0305	None ..	62 ..	None ..	Forbidden	Forbidden	15				
Flue dusts, poisonous, see Arsenical dust.													
Fluoric acid, see Hydrofluoric acid, etc.													
Fluorine, compressed	2.3	.....	UN1045	None ..	302 ..	None ..	Forbidden	Forbidden	D		40, 89, 90		
Fluoroacetic acid	6.1	I	UN2642	None ..	211 ..	242 ..	1 kg	15 kg	E				
Fluoroanilines	6.1	III	UN2941	IB7, IP1	203 ..	241 ..	60 L	220 L	A				
Fluorobenzene	3	II	UN2387	IB3, T4, TP1	150 ..	202 ..	5 L	60 L	B				
Fluoroboric acid	8	II	UN1775	IB2, T4, TP1	202 ..	242 ..	1 L	30 L	A				
				A6, A7, B2, B15, 154, IB2, N3, N34, T7, TP2									
Fluorophosphoric acid anhydrous.	8	II	UN1776	A6, A7, B2, IB2, N3, N34, T8, TP2, TP12	202 ..	242 ..	1 L	30 L	A				
Fluorosilicates, n.o.s.	6.1	III	UN2856	IB8, IP3	213 ..	240 ..	100 kg	200 kg	A		26		
Fluosilicic acid	8	II	UN1778	A6, A7, B2, B15, IB2, N3, N34, T8, TP2, TP12	202 ..	242 ..	1 L	30 L	A				
Fluosulfonic acid	8	I	UN1777	A3, A6, A7, A10, B6, B10, N3, T10, TP2, TP12	201 ..	243 ..	0.5 L	2.5 L	D		40		
Fluorotoluenes	3	II	UN2388	IB2, T4, TP1	202 ..	242 ..	5 L	60 L	B		40		
Forbidden materials. See § 173.21.	Forbidden												
Formaldehyde, solutions, flammable.	3	III	UN1198	B1, IB3, T4, TP1	203 ..	242 ..	5 L	60 L	A		40		
Formaldehyde, solutions, with not less than 25 percent formaldehyde.	8	III	UN2209	IB3, T4, TP1	203 ..	241 ..	5 L	60 L	A				
Formalin, see Formaldehyde, solutions.													
Formic acid	8	II	UN1779	B2, B28, IB2, T7, TP2	202 ..	242 ..	1 L	30 L	A		40		
Fracturing devices, explosive, without detonators for oil wells.	1.1D	II	UN0099	None ..	62 ..	None ..	Forbidden	Forbidden	07				
Fuel, aviation, turbine engine	3	I	UN1863	144, T11, TP1, TP8	201 ..	243 ..	1 L	30 L	E				

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
D	Fuel Oil (No. 1, 2, 4, 5, or 6) .....	3	NA 1993		3	144, IB2, T4, TP1, TP8	202	242	60 L	5 L	B		
	<i>Fuel system components (in- cluding fuel control units (FCU), carburetors, fuel lines, fuel pumps) see Dangerous Goods in Apparatus or Dan- gerous Goods in Machinery.</i>					144, B1, IB3, T2, TP1	203	242	220 L	60 L	A		
	<i>Fulminate or mercury (dry) .....</i>					144, B1, IB3, T4, TP1, TP29	203	242	220 L	60 L	A		
	<i>Fulminate of mercury, wet, see Mercury fulminate, etc.</i>												
	<i>Fulminating gold .....</i>	Forbidden											
	<i>Fulminating mercury .....</i>	Forbidden											
	<i>Fulminating platinum .....</i>	Forbidden											
	<i>Fulminating silver .....</i>	Forbidden											
	<i>Fulminic acid .....</i>	Forbidden											
	<i>Fumaryl chloride .....</i>	Forbidden											
	<i>Fumigated lading, see §§172.302(g), 173.9 and 176.76(h).</i>	8	UN1780	II	8	B2, IB2, T7, TP2	202	242	30 L	1 L	C	8, 40	
	<i>Fumigated transport vehicle or freight container see 173.9.</i>												
	<i>Furadehydres .....</i>	6.1	UN1199	II	6.1, 3	IB2, T7, TP2	202	243	60 L	5 L	A		
	<i>Furan .....</i>	3	UN2389	I	3	T12, TP2, TP13	201	243	30 L	1 L	E	40	
	<i>Furfuryl alcohol .....</i>	6.1	UN2874	III	6.1	IB3, T4, TP1	203	241	220 L	60 L	A	26, 74	
	<i>Furfurylamine .....</i>	3	UN2526	III	3, 8	B1, IB3, T4, TP1	203	242	60 L	5 L	A	40	
	<i>Fuse, detonating, metal clad, see Cord, detonating, metal clad.</i>												
	<i>Fuse, detonating, mild effect, metal clad, see Cord, deto- nating, mild effect, metal clad.</i>												
	<i>Fuse, igniter tubular metal clad</i>	1.4G	UN0103	II	1.4G		62	None	75 kg	Forbidden	06		
	<i>Fuse, non-detonating, instan- taneous or quickmatch.</i>	1.3G	UN0101	II	1.3G		62	None	Forbidden	Forbidden	07		

D	Fuse, safety	1.4S	UN0105	II	1.4S	None	62	None	25 kg	100 kg	05	
	Fuse (railway or highway)	4.1	NA1325	II	4.1	None	184	None	15 kg	50 kg	B	
	Fusel oil	3	UN1201	III	3	150	202	242	5 L	60 L	B	
	Fuses, tracer, see Tracers for ammunition					150	203	242	60 L	220 L	A	
	Fuses, combination, percussion and time, see Fuses, detonating (UN0257, UN0367); Fuses, igniting (UN0317, UN0368)											
	Fuses, detonating	1.1B	UN0106	II	1.1B	None	62	None	Forbidden	Forbidden	11	
	Fuses, detonating	1.2B	UN0107	II	1.2B	None	62	None	Forbidden	Forbidden	11	
	Fuses, detonating	1.4B	UN0257	II	1.4B	116	62	None	Forbidden	Forbidden	06	
	Fuses, detonating	1.4S	UN0367	II	1.4S	116	62	None	25 kg	100 kg	05	
	Fuses, detonating, with protective features	1.1D	UN0408	II	1.1D	None	62	None	Forbidden	Forbidden	07	
	Fuses, detonating, with protective features	1.2D	UN0409	II	1.2D	None	62	None	Forbidden	Forbidden	07	
	Fuses, detonating, with protective features	1.4D	UN0410	II	1.4D	None	62	None	Forbidden	75 kg	06	
	Fuses, igniting	1.3G	UN0316	II	1.3G	None	62	None	Forbidden	Forbidden	07	
	Fuses, igniting	1.4G	UN0317	II	1.4G	None	62	None	Forbidden	75 kg	06	
	Fuses, igniting	1.4S	UN0368	II	1.4S	None	62	None	25 kg	100 kg	05	
	Galactan trinitrate	Forbidden										
	Gallium	8	UN2803	III	8	None	162	240	20 kg	20 kg	B	48
	Gas cartridges, (flammable) without a release device, non-refillable	2.1	UN2037		2.1	306	304	None	1 kg	15 kg	B	40
	Gas generator assemblies (air-craft), containing a non-flammable non-toxic gas and a propellant cartridge	2.2			2.2	None	335	None	75 kg	150 kg	A	
D	Gas identification set	2.3	NA9035	III	2.3	None	194	None	Forbidden	Forbidden	D	
	Gas oil	3	UN1202		3	144, B1, IB3, T2, TP1	203	242	60 L	220 L	A	
G	Gas, refrigerated liquid, flammable, n.o.s. (cryogenic liquid)	2.1	UN3312		2.1	T75, TP5	316	318	Forbidden	Forbidden	D	40
G	Gas, refrigerated liquid, n.o.s. (cryogenic liquid)	2.2	UN3158		2.2	T75, TP5	316	318	50 kg	500 kg	D	
G	Gas, refrigerated liquid, oxidizing, n.o.s. (cryogenic liquid)	2.2	UN3311		2.2,	T75, TP5	316	318	Forbidden	Forbidden	D	
	Gas sample, non-pressurized, flammable, n.o.s., not refrigerated liquid	2.1	UN3167		2.1	306	302	None	1 L	5 L	D	
	Gas sample, nonpressurized, toxic, flammable, n.o.s., not refrigerated liquid	2.3	UN3168		2.3,	6	302	None	Forbidden	1 L	D	
					2.1.							

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Gas sample, nonpressurized, toxic, n.o.s., not refrigerated liquid.	2.3	UN3169		2.3	6	306	302, 304	None	Forbidden	1 L	D	
D	Gasohol gasoline mixed with ethyl alcohol, with not more than 20 percent alcohol.	3	NA1203	II	3	144	150	202	242	5 L	60 L	E	
	Gasoline	3	UN1203	II	3	139, B33, B1, T8	150	202	242	5 L	60 L	E	
	Gasoline, casinghead, see Gasoline.												
	Gelatine, blasting, see Explosive, blasting, type A.												
	Gelatine dynamites, see Explosive, blasting, type A.												
	Germane	2.3	UN2192		2.3, 2.1	2	None	302	245	Forbidden	Forbidden	D	40
	Glycerol-1,3-dinitrate	Forbidden											
	Glycerol gluconate trinitrate	Forbidden											
	Glycerol lactate trinitrate	Forbidden											
	Glycerol alpha-monochlorohydrin	6.1	UN2699	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	Glyceryl trinitrate, see Nitroglycerin, etc.												
	Glycidaldehyde	3	UN2622	II	3, 6.1	IB2, T7, TP1	150	202	243	1 L	60 L	A	40
	Grenades, hand or rifle, with bursting charge.	1.1D	UN0284	II	1.1D			62	None	Forbidden	Forbidden	07	
	Grenades, hand or rifle, with bursting charge.	1.2D	UN0285	II	1.2D			62	None	Forbidden	Forbidden	07	
	Grenades, hand or rifle, with bursting charge.	1.1F	UN0292	II	1.1F			62	None	Forbidden	Forbidden	08	
	Grenades, hand or rifle, with bursting charge.	1.2F	UN0293	II	1.2F			62	None	Forbidden	Forbidden	08	
	Grenades, illuminating, see Ammunition, illuminating, etc.												
	Grenades, practice, hand or rifle	1.4S	UN0110	II	1.4S			62	None	25 kg	100 kg	05	
	Grenades, practice, hand or rifle	1.3G	UN0318	II	1.3G			62	None	Forbidden	Forbidden	07	
	Grenades, practice, hand or rifle	1.2G	UN0372	II	1.2G			62	None	Forbidden	Forbidden	07	
	Grenades, practice hand or rifle	1.4G	UN0462	II	1.4G			62	None	Forbidden	Forbidden	06	
	Grenades, smoke, see Ammunition, smoke, etc.												
	Guandine nitrate	5.1	UN1467	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	73



Guanyl nitrosaminoquanylidene hydrazine (dry).	Forbidden	UN0113	II	1.1A ...	111, 117	None ...	62	None ...	Forbidden	Forbidden	12	.....
Guanyl nitrosaminoquanylidene hydrazine, wetted with not less than 30 percent water, by mass.	Forbidden											.....
Guanyl nitrosaminoquanyltetrazene (dry).	1.1A	UN0114	II	1.1A ...	111, 117	None ...	62	None ...	Forbidden	Forbidden	12	.....
Guanyl nitrosaminoquanyltetrazene, wetted or Tetrazene, wetted with not less than 30 percent water or mixture of alcohol and water, by mass.												.....
Gunpowder, compressed or Gunpowder in pellets, see Black powder (UN 0028).												.....
Gunpowder, granular or as a meal, see Black powder (UN 0027).												.....
Hafnium powder, dry	4.2	UN2545	I II	4.2 4.2	A19, A20, IB6, IP2, N34	None ... None ...	211 212	242 241	Forbidden 15 kg	Forbidden 50 kg	D D	.....
Hafnium powder, wetted with not less than 25 percent water (a visible excess of water must be present) (a) mechanically produced, particle size less than 53 microns; (b) chemically produced, particle size less than 840 microns.	4.1	UN1326	III II	4.2 4.1	IB8, IP3 A6, A19, A20, IB6, IP2, N34	None ... None ...	213 212	241 241	25 kg 15 kg	100 kg 50 kg	D E	.....
Hand signal device, see Signal devices, hand.												.....
Hazardous substances, liquid or solid, n.o.s., see Environmentally hazardous substances, etc.												.....
Hazardous waste, liquid, n.o.s. ...	9	NA3082	III	9	IB3, T2, TP1	155	203	241	No limit	No limit	A	.....
Hazardous waste, solid, n.o.s. ...	9	NA3077	III	9	B54, IB8, IP2	155	213	240	No limit	No limit	A	.....
Heating oil, light	3	UN1202	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Helium, compressed	2.2	UN1046		2.2		306	302	302, 314.	75 kg	150 kg	A	85
Helium-oxygen mixture, see Rare gases and oxygen mixtures.												.....
Helium, refrigerated liquid (cryogenic liquid).	2.2	UN1963		2.2	T75, TP5	320	316	318	50 kg	500 kg	B	.....

D G  
D G

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Heptafluoropropane or Refrigerant gas R 227.	2.2	UN2296		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	n-Heptaldehyde	3	UN3056	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Heptanes	3	UN1206	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	n-Heptene	3	UN2278	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Hexachloroacetone	6.1	UN2661	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	B	12, 40
	Hexachlorobenzene	6.1	UN2729	III	6.1	IB3, T4, IB3	153	203	241	60 L	220 L	A	
	Hexachlorobutadiene	6.1	UN2279	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	Hexachlorocyclopentadiene	6.1	UN2646	I	6.1	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Hexachlorophene	6.1	UN2875	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Hexadecyltrichlorosilane	8	UN1781	II	8	A7, B2, B6, IB2, N34, T7, TP2	None	202	242	Forbidden	30 L	C	40
	Hexadienes	3	UN2458	II	3	IB2, T4, TP1	None	202	242	5 L	60 L	B	
	Hexaethyl tetraphosphate and compressed gas mixtures.	2.3	UN1612		2.3	3	None	334	None	Forbidden	Forbidden	D	40
	Hexaethyl tetraphosphate, liquid	6.1	UN1611	II	6.1	IB2, IP2, IP4, N76	None	202	243	5 L	60 L	E	40
	Hexaethyl tetraphosphate, solid	6.1	UN1611	II	6.1	IB8, IP2, IP4, N76	None	212	242	25 kg	100 kg	E	40
	Hexafluoroacetone	2.3	UN2420		2.3, 8	2, B9, B14	None	304	314, 315.	Forbidden	Forbidden	D	40
	Hexafluoroacetone hydrate	6.1	UN2552	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	B	40
	Hexafluoroethane, or Refrigerant gas R116.	2.2	UN2193		2.2		306	304	314, 315.	75 kg	150 A	A	
	Hexafluorophosphoric acid	8	UN1782	II	8	A6, A7, B2, IB2, N3, N34, T8, TP2, TP12	None	202	242	1 L	30 L	A	
	Hexafluoropropylene compressed or Refrigerant gas R 1216.	2.2	UN1858		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
	Hexaldehyde	3	UN1207	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Hexamethylene diisocyanate	6.1	UN2281	II	6.1	IB2, T7, TP2, TP13	None	202	243	5 L	60 L	C	13, 40
	Hexamethylene triperoxide diamine (dry).	Forbidden											
	Hexamethylenediamine, solid	8	UN2280	III	8	IB8, IP3, T4, TP1	154	213	240	25 kg	100 kg	A	12

Hexamethylenediamine solution	8	UN1783	II	8	IB2, T7, TP2	None	202	242	1 L	30 L	A	.....
Hexamethylenimine	3	UN2493	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	.....
Hexamethylenetetramine	4.1	UN1328	III	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	.....
Hexamethyl benzene	Forbidden		III	4.1	A1, IB8, IP3	151	213	240	25 kg	100 kg	A	.....
Hexanitrate	3	UN1208	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E	.....
Hexanes	Forbidden											.....
2,2',4,4',6,6'-dihydroxyazobenzene (dry)	Forbidden											.....
Hexanitrooxy benzene	Forbidden											.....
N,N'-(hexanitrodiphenyl) ethylene ditramine (dry)	Forbidden											.....
Hexanitrodiphenyl urea	Forbidden											.....
2,2',3',4',4',6'-Hexanitrodiphenylamine	1.1D	UN0079	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Hexanitrodiphenylamine or Dicycylamine or Hexyl	Forbidden											.....
2,3',4',4',6,6'-Hexanitrodiphenylether	Forbidden											.....
Hexanitroethane	Forbidden											.....
Hexanitroxanilide	Forbidden											.....
Hexanitrosilbene	1.1D	UN0392	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Hexanoic acid, see Corrosive liquids, n.o.s.												.....
Hexanols	3	UN2282	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
1-Hexene	3	UN2370	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E	.....
Hexogen												.....
cyclotetramethylenetetranitramine mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.												.....
Hexogen and HMX mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.												.....
Hexogen and octogen mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.												.....
Hexogen, see Cyclotrimethylenetrinitramine, etc.												.....
Hexolite, or Hexolol dry or wetted with less than 15 percent water, by mass.	1.1D	UN0118	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Hexolonal	1.1D	UN0393	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Hexyl, see Hexanitrodiphenylamine.												.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
(1)	Hexyltrichlorosilane .....	8	UN1784	II	8	A7, B2, B6, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	<i>High explosives, see individual explosives entries.</i>												
	HM-X, <i>see</i> Cyclooctamethylene trinitramine, <i>etc.</i>												
	Hydrazine, anhydrous .....	8	UN2029	I	8, 3, 6.1	A3, A6, A7, A10, B7, B16, B53	None	201	243	Forbidden	2.5 L	D	40, 125
	Hydrazine aqueous solution with more than 37% hydrazine, by mass.	8	UN2030	I	8, 6.1	151, B16, B53, T10, TP2, TP13	None	201	243	Forbidden	2.5 L	D	40
	Hydrazine, aqueous solution with not more than 37 percent hydrazine, by mass.	6.1	UN3293	III	6.1	B16, B53, IB2, T7, TP2, TP13	None	202	243	Forbidden	30 L	D	40
	Hydrazine azide .....	Forbidden				B16, B53, IB3, T4, TP1	154	203	241	5 L	60 L	D	40
	Hydrazine chlorate .....	Forbidden				IB3, T4, TP1	153	203	241	60 L	220 L	A	
	Hydrazine dicarbonic acid diazide.	Forbidden											
	Hydrazine perchlorate .....	Forbidden											
	Hydrazine selenate .....	Forbidden											
	Hydroic acid, anhydrous, <i>see</i> Hydrogen iodide, anhydrous.												
	Hydroic acid .....	8	UN1787	II	8	A3, A6, B2, IB2, N41, T7, TP2	154	202	242	1 L	30 L	C	
	Hydrobromic acid, anhydrous, <i>see</i> Hydrogen bromide, anhydrous.					IB3, T4, TP1	154	203	241	5 L	60 L	C	8
	Hydrobromic acid, with more than 49 percent hydrobromic acid.	8	UN1788	II	8	B2, B15, IB2, N41, T7, TP2	154	202	242	Forbidden	Forbidden	C	
	.....					IB3, T4, TP1	154	203	241	Forbidden	Forbidden	C	8

Hydrobromic acid, with not more than 49 percent hydrobromic acid.	8	UN1788	II	8	A3, A6, B2, B15, IB2, N41, T7, TP2	154	202	242	1 L	30 L	C	
Hydrocarbon gas mixture, compressed, n.o.s.	2.1	UN1964	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	C	8
Hydrocarbon gas mixture, liquefied, n.o.s.	2.1	UN1965		2.1		306	302	314, 315	Forbidden	150 kg	E	40
Hydrocarbons, liquid, n.o.s.	3	UN3295		2.1	T50	306	304	314, 315	Forbidden	150 kg	E	40
Hydrochloric acid, anhydrous, see Hydrogen chloride, anhydrous.			I	3	144, T11, TP1, TP8, TP28	150	201	243	1 L	30 L	E	
Hydrochloric acid			II	3	144, IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B	
			III	3	144, B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A	
Hydrochloric acid	8	UN1789	II	8	A3, A6, B3, B15, IB2, N41, T8, TP2, TP12	154	202	242	1 L	30 L	C	
			III	8	IB3, T4, TP1, TP12	154	203	241	5 L	60 L	C	8
Hydrocyanic acid, anhydrous, see Hydrogen cyanide etc.			I	6.1	2, B61, B65, B77, B82, T20, TP2, TP13	None	195	244	Forbidden	Forbidden	D	40
Hydrocyanic acid, aqueous solutions or Hydrogen cyanide, aqueous solutions with not more than 20 percent hydrogen cyanide.	6.1	UN1613										
Hydrocyanic acid, aqueous solutions with less than 5 percent hydrogen cyanide.	6.1	NA1613	II	6.1	IB1, T14, TP2, TP13, TP27	None	195	243	Forbidden	5 L	D	40
Hydrocyanic acid, liquefied, see Hydrogen cyanide, etc.												
Hydrocyanic acid (prussic), unstabilized.	Forbidden											
Hydrofluoric acid and Sulfuric acid mixtures.	8	UN1786	I	8, 6.1	A6, A7, B15, B23, N5, N34, T10, TP2, TP12, TP13	None	201	243	Forbidden	2.5 L	D	40
Hydrofluoric acid, anhydrous, see Hydrogen fluoride, anhydrous.												
Hydrofluoric acid, with more than 60 percent strength.	8	UN1790	I	8, 6.1	A6, A7, B4, B15, B23, N5, N34, T10, TP2, TP12, TP13	None	201	243	0.5 L	2.5 L	D	12, 40
			II	8, 6.1	A6, A7, B15, IB2, N5, N34, T8, TP2, TP12	None	202	243	1 L	30 L	D	12, 40

D

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
(1)	<i>Hydrofluoroboric acid, see Fluoroboric acid.</i> <i>Hydrofluorosilicic acid, see Fluorosilicic acid.</i> Hydrogen and Methane mix- tures, compressed.	2.1	UN2034		2.1		306	302	302, 314, 315.	Forbidden	150 kg	E	40
	Hydrogen bromide, anhydrous ...	2.3	UN1048		2.3, 8	3, B14	None	304	314, 315.	Forbidden	25 kg	D	40
	Hydrogen chloride, anhydrous ...	2.3	UN1050		2.3, 8	3	None	304	None	Forbidden	Forbidden	D	40
	Hydrogen chloride, refrigerated liquid.	2.3	UN2186		2.3, 8	3, B6	None	None	314, 315.	Forbidden	Forbidden	B	40
	Hydrogen, compressed	2.1	UN1049		2.1		306	302	302, 314.	Forbidden	150 kg	E	40, 57
	Hydrogen cyanide, solution in al- cohol with not more than 45 percent hydrogen cyanide.	6.1	UN3294	I	6.1, 3	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Hydrogen cyanide, stabilized with less than 3 percent water.	6.1	UN1051	I	6.1, 3	1, B35, B61, B65, B77, B82	None	195	244	Forbidden	Forbidden	D	40
	Hydrogen cyanide, stabilized, with less than 3 percent water and absorbed in a porous inert material.	6.1	UN1614	I	6.1	5	None	195	None	Forbidden	Forbidden	D	25, 40
	Hydrogen fluoride, anhydrous ...	8	UN1052	I	8, 6.1	3, B7, B46, B71, B77, T10, TP2	None	163	243	Forbidden	Forbidden	D	40
	Hydrogen iodide, anhydrous	2.3	UN2197		2.3	3, B14	None	304	314, 315.	Forbidden	Forbidden	D	40
	<i>Hydrogen iodide solution, see Hydroiodic acid, solution.</i> Hydrogen peroxide and peroxy- acetic acid mixtures, stabilized with acids, water and not more than 5 percent peroxy- acetic acid.	5.1	UN3149	II	5.1, 8	145, A2, A3, A6, B53, IB2, IP5, T7, TP2, TP6, TP24	None	202	243	1 L	5 L	D	25, 66, 75, 106

Hydrogen peroxide, aqueous solutions with more than 40 percent but not more than 60 percent hydrogen peroxide (stabilized as necessary).	5.1	UN2014	II	5.1, 8	12, A3, A6, B53, B80, B81, B85, IB2, IP5, T7, TP2, TP6, TP24, TP37	None	202	243	Forbidden	Forbidden	D	25, 66, 75, 106
Hydrogen peroxide, aqueous solutions with not less than 20 percent but not more than 40 percent hydrogen peroxide (stabilized as necessary).	5.1	UN2014	II	5.1, 8	A2, A3, A6, B53, IB2, IP5, T7, TP2, TP6, TP24, TP37	None	202	243	1 L	5 L	D	25, 66, 75, 106
Hydrogen peroxide, aqueous solutions, with not less than 8 percent but less than 20 percent hydrogen peroxide, (stabilized as necessary).	5.1	UN2984	III	5.1	A1, IB2, IP5, T4, TP1, TP6, TP24, TP37	152	203	241	2.5 L	30 L	B	25, 75, 106
Hydrogen peroxide stabilized or Hydrogen peroxide aqueous solutions, stabilized with more than 60 percent hydrogen peroxide.	5.1	UN2015	I	5.1, 8	12, A3, A6, B53, B80, B81, B85, T10, TP2, TP6, TP24, TP37	None	201	243	Forbidden	Forbidden	D	25, 66, 75, 106
Hydrogen, refrigerated liquid (cryogenic liquid).	2.1	UN1966		2.1	T75, TP5	None	316	318, 319	Forbidden	Forbidden	D	40
Hydrogen selenide, anhydrous ..	2.3	UN2202		2.3, 2.1.	1	None	192	245	Forbidden	Forbidden	D	40
Hydrogen sulfate, see Sulfuric acid.												
Hydrogen sulfide ..	2.3	UN1053		2.3	2, B9, B14	None	304	314, 315	Forbidden	Forbidden	D	40
Hydrogen difluorides, n.o.s. solid	8	UN1740	II	8	IB5, IP2, IP4, N3, N34	None	212	240	15 kg	50 kg	A	25, 26, 40
			III	8	IB8, IP3, N3, N34	154	213	240	25 kg	100 kg	A	25, 26, 40
Hydrogen difluorides, n.o.s. solutions.	8	UN1740	II	8	IB2, N3, N34	None	202	242	1 L	30 L	A	25, 26, 40
			III	8	IB3, IP3, N3, N34	154	203	241	5 L	60 L	A	25, 26, 40
Hydroquinone ..	6.1	UN2662	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	
Hydrochloric acid, see Fluorosilicic acid.												
Hydroxyl amine iodide ..	Forbidden											
Hydroxylamine sulfate ..	8	UN2865	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	
Hypochlorite solutions ..	8	UN1791	II	8	A7, B2, B15, IB2, IP5, N34, T7, TP2, TP24	154	202	242	1 L	30 L	B	26
			III	8	IB3, N34, T4, TP2, TP24	154	203	241	5 L	60 L	B	26

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
(1)	Hypochlorites, inorganic, n.o.s. . .	5.1	UN3212	II	5.1	IB8, IP2, IP4	152	212	240	5 kg	25 kg	D	48, 56, 58, 69, 106, 116, 118
	<i>Hyponitrous acid</i> . . . . .	Forbidden											
	<i>Igniter fuse, metal clad, see Fuse, igniter, tubular, metal clad.</i>												
	Igniters . . . . .	1.1G	UN0121	II	1.1G		None	62	None	Forbidden	Forbidden	07	
	Igniters . . . . .	1.2G	UN0314	III	1.2G		None	62	None	Forbidden	Forbidden	07	
	Igniters . . . . .	1.3G	UN0315	II	1.3G		None	62	None	Forbidden	Forbidden	07	
	Igniters . . . . .	1.4G	UN0325	II	1.4G		None	62	None	Forbidden	Forbidden	06	
	Igniters . . . . .	1.4S	UN0454	II	1.4S		None	62	None	Forbidden	Forbidden	05	
	3,3'-Innodiopropylamine . . . . .	8	UN2269	III	8	IB3, T4, TP2	154	203	241	25 kg	100 kg	A	
G	Infectious substances, affecting animals <i>only</i> .	6.2	UN2900		6.2	A81, A82	134	196	None	50 mL or 50 g	4 L or 4 kg	B	40
G	Infectious substances, affecting humans.	6.2	UN2814		6.2	A81, A82	134	196	None	50 mL or 50 g	4 L or 4 kg	B	40
	<i>Inflamable, see Flammable</i> . . . . .												
	<i>Initiating explosives (dry)</i> . . . . .	Forbidden											
	<i>Inositol hexanitrate (dry)</i> . . . . .	Forbidden											
G	Insecticide gases, n.o.s. . . . .	2.2	UN1968		2.2		306	304	314, 315	75 kg	150 kg	A	
G	Insecticide gases, flammable, n.o.s..	2.1	UN3354		2.1	T50	306	304	314, 315	Forbidden	150 kg	D	40
G	Insecticide gases, toxic, flammable, n.o.s. <i>Inhalation hazard Zone A.</i>	2.3	UN3355		2.3, 2.1.	1	None	192	245	Forbidden	Forbidden	D	40
G	Insecticide gases, toxic, flammable, n.o.s. <i>Inhalation hazard Zone B.</i>	2.3	UN3355		2.3, 2.1.	2, B9, B14	None	302, 305.	314, 315.	Forbidden	Forbidden	D	40
G	Insecticide gases, toxic, flammable, n.o.s. <i>Inhalation hazard Zone C.</i>	2.3	UN3355		2.3, 2.1.	3, B14	None	302, 305.	314, 315.	Forbidden	Forbidden	D	
G	Insecticide gases, toxic, flammable, n.o.s. <i>Inhalation hazard Zone D.</i>	2.3	UN3355		2.3, 2.1.	4	None	302, 305.	314, 315.	Forbidden	Forbidden	D	



	UN1967	2.3	.....	2.3	.....	3	None	.....	193, 334.	245	.....	Forbidden	Forbidden	D	40
G	Insecticide gases, toxic, n.o.s. ....	2.3	.....	2.3	.....	3	None	.....	193, 334.	245	.....	Forbidden	Forbidden	D	40
	<i>Inulin trinitrate (dry)</i> .....	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Iodine azide (dry)</i> .....	8	II	8	.....	B6, IB8, IP2, IP4, N41, T7, TP2	None	.....	212	240	.....	Forbidden	50 kg	D	40, 66, 74, 89, 90
	<i>Iodine monochloride</i> .....	8	II	8	.....	.....	None	.....	212	240	.....	Forbidden	50 kg	D	40, 66, 74, 89, 90
	<i>Iodine pentafluoride</i> .....	5.1	I	5.1, 6.1, 8.	.....	.....	None	.....	205	243	.....	Forbidden	Forbidden	D	25, 40, 66, 90
	2-Isobutane .....	3	II	3	.....	IB2, T4, TP1	150	.....	202	242	.....	60 L	60 L	B	.....
	Iodomethylpropanes .....	3	II	3	.....	IB2, T4, TP1	150	.....	202	242	.....	60 L	60 L	B	.....
	Iodopropanes .....	3	III	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	220 L	220 L	A	.....
	<i>Iodoxy compounds (dry)</i> .....	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Iridium nitratopentamine iridium nitrate.</i>	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Iron chloride, see Ferric chloride</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Iron oxide, spent, or Iron sponge, spent obtained from coal gas purification.</i>	4.2	III	4.2	.....	B18, IB8, IP3	None	.....	213	240	.....	Forbidden	Forbidden	E	.....
	<i>Iron penta carbonyl</i> .....	6.1	I	6.1, 3	.....	1, B9, B14, B30, B72, B77, T22, TP2, TP13, TP38, TP44	None	.....	226	244	.....	Forbidden	Forbidden	D	40
	<i>Iron sesquichloride, see Ferric chloride.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Irritating material, see Tear gas substances, etc.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Isobutane <i>see also</i> Petroleum gases, liquefied.	2.1	.....	2.1	.....	19, T50	306	.....	304	314, 315.	.....	Forbidden	150 kg	E	40
	Isobutanol or Isobutyl alcohol	3	III	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	60 L	220 L	A	.....
	Isobutyl acetate	3	II	3	.....	IB2, T4, TP1	150	.....	202	242	.....	60 L	60 L	B	.....
	Isobutyl acrylate, stabilized	3	III	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	220 L	220 L	A	.....
	Isobutyl alcohol, <i>see</i> Isobutanol	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Isobutyl aldehyde, <i>see</i> Isobutyraldehyde.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
D	Isobutyl chloroformate	6.1	I	6.1, 3, 8.	.....	2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	.....	227	244	.....	1 L	30 L	A	12, 13, 22, 25, 40, 48, 100
	Isobutyl formate	3	II	3	.....	IB2, T4, TP1	150	.....	202	242	.....	5 L	60 L	B	.....
	Isobutyl isobutyrate	3	III	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	60 L	220 L	A	.....
	Isobutyl isocyanate	3	I	3, 6.1	.....	1, B9, B14, B30, B72, T22, TP2, TP13, TP27	None	.....	226	244	.....	Forbidden	Forbidden	D	40
	Isobutyl methacrylate, stabilized	3	III	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	60 L	220 L	A	.....
	Isobutyl propionate	3	II	3	.....	B1, IB3, T2, TP1	150	.....	203	242	.....	60 L	220 L	B	.....
	Isobutylamine	3	II	3, 8	.....	IB2, T7, TP1	None	.....	202	243	.....	5 L	5 L	B	40
	Isobutylene <i>see also</i> Petroleum gases, liquefied.	2.1	.....	2.1	.....	19, T50	306	.....	304	314, 315.	.....	Forbidden	150 kg	E	40



Isopropenylbenzene .....	3	UN2303	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	.....
Isopropyl acetate .....	3	UN1220	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	.....
Isopropyl acid phosphate .....	8	UN1793	III	8	IB8, IP3, T4, TP1	154	213	240	25 kg	100 kg	.....
Isopropyl alcohol, see Isopropanol.											40
Isopropyl butyrate .....	3	UN2405	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	.....
Isopropyl chloroacetate .....	3	UN2947	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	.....
Isopropyl chloroformate .....	6.1	UN2407	I	6.1, 3, 8,	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP44	None	227	244	Forbidden	Forbidden	B
Isopropyl 2-chloropropionate .....	3	UN2934	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A
Isopropyl isobutyrate .....	3	UN2406	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B
Isopropyl isocyanate .....	3	UN2483	I	3, 6.1	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D
Isopropyl mercaptan, see Propanethiols.											.....
Isopropyl nitrate .....	3	UN1222	II	3	IB2, IP7	150	202	None	5 L	60 L	D
Isopropyl phosphoric acid, see Isopropyl acid phosphate.											.....
Isopropyl propionate .....	3	UN2409	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B
Isopropylamine .....	3	UN1221	I	3, 8	T11, TP2	None	201	243	0.5 L	2.5 L	E
Isopropylbenzene .....	3	UN1918	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A
Isopropylcumyl hydroperoxide, with more than 72 percent in solution.	Forbidden										.....
Isosorbide dinitrate mixture with not less than 60 percent lac- tose, mannose, starch or cal- cium hydrogen phosphate.	4.1	UN2907	II	4.1	IB6, IP2, N85	None	212	None	15 kg	50 kg	E
Isothiocyanic acid .....	Forbidden										.....
Jet fuel, see Fuel aviation, tur- bine engine.											.....
Jet perforating guns, charged oil well, with detonator.	1.1D	NA0124	II	1.1D	55, 56	None	62	None	Forbidden	Forbidden	07
Jet perforating guns, charged oil well, with detonator.	1.4D	NA0494	II	1.4D	55, 56	None	62	None	Forbidden	Forbidden	06
Jet perforating guns, charged oil well, without detonator.	1.1D	UN0124	II	1.1D	55	None	62	None	Forbidden	Forbidden	07
Jet perforating guns, charged, oil well, without detonator.	1.4D	UN0494	II	1.4D	55, 114	None	62	None	Forbidden	300 kg	06
Jet perforators, see Charges, shaped, etc.											.....
Jet tappers, without detonator, see Charges, shaped, etc.											.....
Jet thrust igniters, for rocket mo- tors or Jato, see Igniters.											.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Jet thrust unit (Jatb), see Rocket motors.												
	Kerosene	3	UN1223	III	3	144, B1, IB3, T2, TP2	150	203	242	60 L	220 L	A	
G	Ketones, liquid, n.o.s.	3	UN1224	I	3	T11, TP1, TP8, TP27	None	201	243	1 L	30 L	E	
				II	3	IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B	
				III	3	B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A	
	Krypton, compressed	2.2	UN1056		2.2	T75, TP5	306	302	None	75 kg	150 kg	A	
	Krypton, refrigerated liquid (cryogenic liquid).	2.2	UN1970		2.2		320	None	None	50 kg	500 kg	B	
	Lacquer base or lacquer chips, nitrocellulose, dry, see Nitro-cellulose, etc. (UN 2557).												
	Lacquer base or lacquer chips, plastic, wet with alcohol or solvent, see Nitrocellulose (UN2059, UN2555, UN2556, UN2557) or Paint etc.(UN1263).												
	Lead acetate	6.1	UN1616	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Lead arsenates	6.1	UN1617	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Lead arsenites	6.1	UN1618	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Lead azide (dry)	Forbidden								Forbidden	Forbidden	12	
	Lead azide, wetted with not less than 20 percent water or mixture of alcohol and water, by mass.	1.1A	UN0129	II	1.1A	111, 117	None	62	None	Forbidden	Forbidden		
	Lead compounds, soluble, n.o.s.	6.1	UN2291	III	6.1	138, IB8, IP3	153	213	240	100 kg	200 kg	A	
	Lead cyanide	6.1	UN1620	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	26
	Lead dioxide	5.1	UN1872	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	
	Lead dross, see Lead sulfate, with more than 3 percent free acid.												
	Lead nitrate	5.1	UN1469	II	5.1, 6.1.	IB8, IP2, IP4	None	212	242	5 kg	25 kg	A	
	Lead nitrosarcinate (dry)	Forbidden											

Lead perchlorate, solid	5.1	UN1470	II	5.1, 6.1.	IB8, IP2, T4, TP1	None	212	242	5 kg	25 kg	A	56, 58, 106
Lead perchlorate, solution	5.1	UN1470	II	5.1, 6.1.	IB1, T4, TP1	None	202	243	1 L	5 L	A	56, 58, 106
Lead peroxide, see Lead dioxide												
Lead phosphite, dibasic	4.1	UN2989	II	4.1	IB8, IP2, IP4	None	212	240	5 kg	25 kg	B	34
Lead picrate (dry)	Forbidden		III	4.1	IB8, IP3	151	213	240	15 kg	50 kg	B	34
Lead stannate (dry)	Forbidden											
Lead stannate, wetted or Lead trinitrosorcinat, wetted with not less than 20 percent water or mixture of alcohol and water, by mass.	1.1A	UN0130	II	1.1A	111, 117	None	62	None	Forbidden	Forbidden	12	
Lead sulfate with more than 3 percent free acid.	8	UN1794	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	
Lead trinitrosorcinat, see Lead stannate, etc.												
Life-saving appliances, not self inflating containing dangerous goods as equipment.	9	UN3072		None	143	None	219	None	No limit	No limit	A	
Life-saving appliances, self inflating.	9	UN2990		None		None	219	None	No limit	No limit	A	
Lighter replacement cartridges containing liquefied petroleum gases (and similar devices, each not exceeding 65 grams), see Lighters or lighter refills etc. containing flammable gas.												
Lighters, fuse	1.4S	UN0131	II	1.4S	N10	None	62	None	25 kg	100 kg	05	40
Lighters or lighter refills containing flammable gas.	2.1	UN1057		2.1		None	21, 308	None	1 kg	15 kg	B	
Lime, unslaked, see Calcium oxide.												
Liquefied gas, flammable, n.o.s.	2.1	UN3161		2.1	T50	306	304	314, 315.	Forbidden	150 kg	D	40
Liquefied gas, n.o.s.	2.2	UN3163		2.2	T50	306	304	314, 315.	75 kg	150 kg	A	
Liquefied gas, oxidizing, n.o.s.	2.2	UN3157		2.2, 5.1.		306	304	314, 315.	75 kg	150 kg	D	
Liquefied gas, toxic, corrosive, n.o.s. Inhalation Hazard Zone A.	2.3	UN3308		2.3, 8	1	None	192	245	Forbidden	Forbidden	D	40
Liquefied gas, toxic, corrosive, n.o.s. Inhalation Hazard Zone B.	2.3	UN3308		2.3, 8	2, B9, B14	None	304	314, 315.	Forbidden	Forbidden	D	40
Liquefied gas, toxic, corrosive, n.o.s. Inhalation Hazard Zone C.	2.3	UN3308		2.3, 8	3, B14	None	304	314, 315.	Forbidden	Forbidden	D	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
G I	Liquefied gas, toxic, corrosive, n.o.s. <i>Inhalation Hazard Zone D.</i>	2.3	UN3308	.....	2.3, 8	4	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G I	Liquefied gas, toxic, flammable, corrosive, n.o.s. <i>Inhalation Hazard Zone A.</i>	2.3	UN3309	.....	2.3, 8, 2.1,	1	None ...	192 .....	245 .....	Forbidden	Forbidden	D	17, 40
G I	Liquefied gas, toxic, flammable, corrosive, n.o.s. <i>Inhalation Hazard Zone B.</i>	2.3	UN3309	.....	2.3, 8, 2.1,	2, B9, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	17, 40
G I	Liquefied gas, toxic, flammable, corrosive, n.o.s. <i>Inhalation Hazard Zone C.</i>	2.3	UN3309	.....	2.3, 8, 2.1,	3, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	17, 40
G I	Liquefied gas, toxic, flammable, corrosive, n.o.s. <i>Inhalation Hazard Zone D.</i>	2.3	UN3309	.....	2.3, 8, 2.1,	4	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	17, 40
G	Liquefied gas, toxic, flammable, n.o.s. <i>Inhalation Hazard Zone A.</i>	2.3	UN3160	.....	2.3, 2.1.	1	None ...	192 .....	245 .....	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, flammable, n.o.s. <i>Inhalation Hazard Zone B.</i>	2.3	UN3160	.....	2.3, 2.1.	2, B9, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, flammable, n.o.s. <i>Inhalation Hazard Zone C.</i>	2.3	UN3160	.....	2.3, 2.1.	3, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, flammable, n.o.s. <i>Inhalation Hazard Zone D.</i>	2.3	UN3160	.....	2.3, 2.1.	4	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, n.o.s. <i>Inhalation Hazard Zone A.</i>	2.3	UN3162	.....	2.3 .....	1	None ...	192 .....	245 .....	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, n.o.s. <i>Inhalation Hazard Zone B.</i>	2.3	UN3162	.....	2.3 .....	2, B9, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, n.o.s. <i>Inhalation Hazard Zone C.</i>	2.3	UN3162	.....	2.3 .....	3, B14	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, n.o.s. <i>Inhalation Hazard Zone D.</i>	2.3	UN3162	.....	2.3 .....	4	None ...	304 .....	314, 315.	Forbidden	Forbidden	D	40
G I	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. <i>Inhalation Hazard Zone A.</i>	2.3	UN3310	.....	2.3, 5.1, 8.	1	None ...	192 .....	245 .....	Forbidden	Forbidden	D	40, 89, 90

GI	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. Inhalation Hazard Zone B.	2.3	UN3310	.....	2.3, 5.1, 8.	2, B9, B14	None	304	314, 315.	Forbidden	Forbidden	D	40, 89, 90
GI	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. Inhalation Hazard Zone C.	2.3	UN3310	.....	2.3, 5.1, 8.	3, B14	None	304	314, 315.	Forbidden	Forbidden	D	40, 89, 90
GI	Liquefied gas, toxic, oxidizing, corrosive, n.o.s. Inhalation Hazard Zone D.	2.3	UN3310	.....	2.3, 5.1, 8.	4	None	304	314, 315.	Forbidden	Forbidden	D	40, 89, 90
G	Liquefied gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone A.	2.3	UN3307	.....	2.3, 5.1.	1	None	192	245	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone B.	2.3	UN3307	.....	2.3, 5.1.	2, B9, B14	None	304	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone C.	2.3	UN3307	.....	2.3, 5.1.	3, B14	None	304	314, 315.	Forbidden	Forbidden	D	40
G	Liquefied gas, toxic, oxidizing, n.o.s. Inhalation Hazard Zone D.	2.3	UN3307	.....	2.3, 5.1.	4	None	304	314, 315.	Forbidden	Forbidden	D	40
	Liquefied gases, non-flammable charged with nitrogen, carbon dioxide or air.	2.2	UN1058	.....	2.2		306	304	None	75 kg	150 kg	A	.....
	Liquefied hydrocarbon gas, see Hydrocarbon gas mixture, liquefied, n.o.s.												
	Liquefied natural gas, see Methane, etc. (UN 1972).												
	Liquefied petroleum gas see Petroleum gases, liquefied.												
	Lithium	4.3	UN1415	I	4.3	A7, A19, IB1, IP1, N45	None	211	244	Forbidden	15 kg	E	.....
	Lithium acetylide ethylene-diamine complex, see Water reactive solid etc.												
	Lithium alkyls	4.2	UN2445	I	4.2, 4.3.	B11, T21, TP2, TP7	None	181	244	Forbidden	Forbidden	D	.....
	Lithium aluminum hydride	4.3	UN1410	I	4.3	A19	None	211	242	Forbidden	15 kg	E	.....
	Lithium aluminum hydride, ethereal.	4.3	UN1411	I	4.3, 3	A2, A3, A11, N34	None	201	244	Forbidden	1 L	D	40
	Lithium batteries, contained in equipment.	9	UN3091	II	9	29, A54, A55	185	185	None	5 kg	35kg	A	.....
	Lithium batteries packed with equipment.	9	UN3091	II	9	29, A54, A55	185	185	None	5 kg gross	35 kg gross	A	.....
	Lithium battery	9	UN3090	II	9	29, A54, A55	185	185	None	5 kg gross	35 kg gross	A	.....
	Lithium borohydride	4.3	UN1413	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	.....
	Lithium ferrosilicon	4.3	UN2830	II	4.3	A19, IB7, IP2	151	212	241	Forbidden	15 kg	E	40, 85, 103
	Lithium hydride	4.3	UN1414	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
(1)	Lithium hydride, fused solid .....	4.3	UN2805	II	4.3	A8, A19, A20, IB4	151	212	241	15 kg	50 kg	E	.....
	Lithium hydroxide .....	8	UN2680	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	.....
	Lithium hydroxide, solution .....	8	UN2679	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	A	.....
	Lithium hypochlorite, dry with more than 39% available chlorine (6.8% available oxygen) or Lithium hypochlorite mix-tures, dry with more than 39% available chlorine (6.8% avail-able oxygen).	5.1	UN1471	III	8	IB3, T4, TP2	154	203	241	5 L	60 L	A	96
	<i>Lithium in cartridges, see Lith-ium.</i>	.....	.....	.....	5.1	A9, IB8, IP2, IP4, N34	152	212	240	5 kg	25 kg	A	48, 56, 58, 69, 106, 116
	Lithium nitrate .....	5.1	UN2722	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
	Lithium nitride .....	4.3	UN2806	I	4.3	A19, IB4, IP1, N40	None	211	242	Forbidden	15 kg	E	.....
	Lithium peroxide .....	5.1	UN1472	II	5.1	A9, IB6, IP2, N34	152	212	None	5 kg	25 kg	A	13, 75, 106
	Lithium silicon .....	4.3	UN1417	II	4.3	A19, A20, IB7, IP2	151	212	241	15 kg	50 kg	A	85, 103
	LNG, see Methane etc. (UN 1972).	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	London purple .....	6.1	UN1621	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	LPG, see Petroleum gases, liq-uedified.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Lye, see Sodium hydroxide, so-lutions.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Magnesium alkyls .....	4.2	UN3053	I	4.2,	B11, T21, TP2, TP7	None	181	244	Forbidden	Forbidden	D	18
	Magnesium aluminum phosphide.	4.3	UN1419	I	4.3,	A19, N34, N40	None	211	242	Forbidden	15 kg	E	40, 85
	Magnesium arsenate .....	6.1	UN1622	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	Magnesium bisulfite solution, see Bisulfites, aqueous solu-tions, n.o.s.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Magnesium bromate .....	5.1	UN1473	II	5.1	A1, IB8, IP4	152	212	242	5 kg	25 kg	A	56, 58, 106



Magnesium chlorate .....	5.1	UN2723	II	5.1	IB8, IP2, IP4	152	212	242	5 kg	25 kg	A	56, 58, 106
Magnesium diamide .....	4.2	UN2004	II	4.2	A8, A19, A20, IB6	None	212	241	15 kg	50 kg	C	.....
Magnesium diphenyl .....	4.2	UN2005	I	4.2	.....	None	187	244	Forbidden	.....	C	.....
Magnesium dross, wet or hot .....	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Magnesium fluorosilicate .....	6.1	UN2853	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	26
Magnesium granules, coated, particle size not less than 149 microns.	4.3	UN2950	III	4.3	A1, A19, IB8, IP4	151	213	240	25 kg	100 kg	A	.....
Magnesium hydride .....	4.3	UN2010	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	.....
Magnesium or Magnesium alloys with more than 50 percent magnesium in pellets, turnings or ribbons.	4.1	UN1869	III	4.1	A1, IB8, IP3	151	213	240	25 kg	100 kg	A	39
Magnesium nitrate .....	5.1	UN1474	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
Magnesium perchlorate .....	5.1	UN1475	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	56, 58, 106
Magnesium peroxide .....	5.1	UN1476	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	13, 75, 106
Magnesium phosphide .....	4.3	UN2011	I	4.3, 6.1	A19, N40	None	211	None	Forbidden	15 kg	E	106, 40, 85
Magnesium, powder or Magnesium alloys, powder.	4.3	UN1418	I	4.3, 4.2	A19, B56	None	211	244	Forbidden	15 kg	A	39
.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Magnesium scrap, see Magnesium, etc. (UN 1869).	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Magnesium silicide .....	4.3	UN2624	II	4.3	A19, A20, IB7, IP2	151	212	241	15 kg	50 kg	B	85, 103
Magnetized material, see § 173.21	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Maleic anhydride .....	8	UN2215	III	8	IB8, IP3, T4, TP1	154	213	240	25 kg	100 kg	A	.....
Malononitrile .....	6.1	UN2647	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	12
Mancozeb (manganese ethylenebisdithiocarbamate complex with zinc) see Maneb.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Maneb or Maneb preparations with not less than 60 percent maneb.	4.2	UN2210	III	4.2, 4.3	57, A1, A19, IB6	None	213	242	25 kg	100 kg	A	34
Maneb stabilized or Maneb preparations, stabilized against self-heating.	4.3	UN2968	III	4.3	54, A1, A19, IB8, IP4	151	213	242	25 kg	100 kg	B	34
Manganese nitrate .....	5.1	UN2724	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
Mannitan tetranitrate .....	4.1	UN1330	III	4.1	A1, IB6	151	213	240	25 kg	100 kg	A	.....
Mannitol hexanitrate (dry) .....	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....





§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
A	Mercury bromides .....	6.1	UN1634	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	Mercury compounds, liquid, n.o.s. ....	6.1	UN2024	I	6.1		None	201	243	1 L	30 L	B	40
	.....												
	Mercury compounds, solid, n.o.s. ....	6.1	UN2025	II	6.1	IB3	None	202	243	5 L	60 L	B	40
	.....												
	Mercury compounds, solid, n.o.s. ....	6.1		III	6.1	IB3	None	203	241	60 L	220 L	B	40
	.....												
	Mercury compounds, solid, n.o.s. ....	6.1		I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	.....
	.....												
	Mercury contained in manufac- tured articles.		8	UN2809	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A
Mercury cyanide .....				III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	.....
.....					8		None	164	None	No limit	No limit	B	40, 97
Mercury fulminate, wetted with water, or mixture of alcohol and water, by mass.		6.1	UN1636	II	6.1	IB8, IP2, IP4, N74, N75	None	212	242	25 kg	100 kg	A	26
Mercury fulminate, wetted with water, or mixture of alcohol and water, by mass.		1.1A	UN0135	II	1.1A	111, 117	None	62	None	Forbidden	Forbidden	12	.....
Mercury gluconate .....		6.1	UN1637	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury iodide, solid .....		6.1	UN1638	II	6.1	IB2, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury iodide aqueous basic ammonobasic (iodide of Millon's base).		Forbidden											
Mercury iodide, solution .....		6.1	UN1638	II	6.1	IB8, IP2, IP4	None	202	243	5 L	60 L	A	.....
Mercury nitride .....		Forbidden											
Mercury nucleate .....		6.1	UN1639	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury oleate .....		6.1	UN1640	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury oxide .....		6.1	UN1641	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury oxycyanide .....		Forbidden											
Mercury oxycyanide, desensitized.		6.1	UN1642	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	26, 91
Mercury potassium iodide .....		6.1	UN1643	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury salicylate .....		6.1	UN1644	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury sulfates .....		6.1	UN1645	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mercury thiocyanate .....		6.1	UN1646	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Mesityl oxide .....		3	UN1229	III	3	B1, IB3, T2, TP1	None	203	242	60 L	220 L	A	.....
Metal alkyl halides, water-reactive n.o.s. or Metal aryl halides, water-reactive, n.o.s. ....		4.2	UN3049	I	4.2, 4.3.	B9, B11, T21, TP2, TP7	None	181	244	Forbidden	Forbidden	D	.....

Metal alkyl hydrides, water-reactive, n.o.s. or Metal aryl hydrides, water-reactive, n.o.s.	4.2	UN3050	I	4.2, 4.3	B9, B11, T21, TP2, TP7	None	181	244	Forbidden	D	Forbidden	40
Metal alkyls, water-reactive, n.o.s. or Metal aryls, water-reactive n.o.s.	4.2	UN2003	I	4.2, 4.3	B11, T21, TP2, TP7	None	181	244	Forbidden	D	Forbidden	40
Metal carbonyls, n.o.s.	6.1	UN3281	I	6.1	5, T14, TP2, TP13, TP27	None	201	243	1 L	B	30 L	40
			II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	B	60 L	40
			III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	A	220 L	40
Metal catalyst, dry	4.2	UN2881	I	4.2	N34	None	187	None	Forbidden	C	Forbidden	
			II	4.2	IB6, IP2, N34	None	187	242	Forbidden	C	50 kg	
			III	4.2	IB8, IP3, N34	None	187	241	100 kg	C	100 kg	
Metal catalyst, wetted with a visible excess of liquid	4.2	UN1378	II	4.2	A2, A8, IB1, N34	None	212	None	Forbidden	C	50 kg	
Metal hydrides, flammable, n.o.s.	4.1	UN3182	II	4.1	A1, IB4	151	212	240	15 kg	E	50 kg	
Metal hydrides, water reactive, n.o.s.	4.3	UN1409	III	4.1	A1, IB4	151	213	240	100 kg	E	100 kg	
			I	4.3	A19, N34, N40	None	211	242	Forbidden	D	15 kg	
			II	4.3	A19, IB4, N34, N40	151	212	242	15 kg	D	50 kg	
Metal powder, self-heating, n.o.s.	4.2	UN3189	II	4.2	IB6, IP2	None	212	241	15 kg	C	50 kg	
Metal powders, flammable, n.o.s.	4.1	UN3089	III	4.2	IB8, IP3	None	213	241	25 kg	C	100 kg	
			II	4.1	IB8, IP2, IP4	151	212	240	15 kg	B	50 kg	
Metal salts of methyl nitramine (dry)	Forbidden		III	4.1	IB6	151	213	240	25 kg	B	100 kg	
Metal salts of organic compounds, flammable, n.o.s.	4.1	UN3181	II	4.1	A1, IB8, IP2, IP4	151	212	240	15 kg	B	50 kg	40
Met aldehyde	4.1	UN1332	III	4.1	A1, IB8, IP3	151	213	240	25 kg	B	100 kg	40
Metallic substance, water-reactive, n.o.s.	4.3	UN3208	I	4.3	A1, IB8, IP3, IB4	None	211	242	25 kg	A	100 kg	40
			II	4.3	IB7, IP2	151	212	242	15 kg	E	50 kg	40
			III	4.3	IB8, IP4	151	213	241	100 kg	E	100 kg	40
Metallic substance, water-reactive, self-heating, n.o.s.	4.3	UN3209	I	4.3, 4.2	IB5, IP2	None	211	242	Forbidden	E	15 kg	40
			II	4.3	IB5, IP2	None	212	242	15 kg	E	50 kg	40
			III	4.3	IB8, IP4	None	213	242	25 kg	E	100 kg	40
Methacrylaldehyde, stabilized	3	UN2396	II	3, 6.1	45, IB2, T7, TP1, TP13	None	202	243	1 L	E	60 L	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Methacrylic Acid, stabilized .....	8	UN2531	II	8 .....	IB3, T4, TP1, TP18, TP 30	154 .....	202 .....	242 .....	1 L	30 L	C	40
+	Methacrylonitrile, stabilized .....	3	UN3079	I	3, 6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP13, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	12, 40, 48
	Methyl alcohol .....	3	UN2614	III	3 .....	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	.....
	Methane and hydrogen, mix- tures, see Hydrogen and methane, mixtures, etc.												
	Methane, compressed or Natural gas, compressed (with high methane content).	2.1	UN1971	.....	2.1 .....		306 .....	302 .....	302 .....	Forbidden	150 kg	E	40
	Methane, refrigerated liquid (cryogenic liquid) or Natural gas, refrigerated liquid (cryogenic liquid), with high meth- ane content.	2.1	UN1972	.....	2.1 .....	T75, TP5	None ...	None ...	318 .....	Forbidden	Forbidden	D	40
	Methanesulfonyl chloride .....	6.1	UN3246	I	6.1, 8	2, B9, B14, B32, B74, T20, TP2, TP12, TP13, TP38, TP45	None ...	227 .....	244 .....	Forbidden	Forbidden	D	40
+ I	Methanol .....	3	UN1230	II	3, 6.1	IB2, T7, TP2	150 .....	202 .....	242 .....	1 L	60 L	B	40
D	Methanol .....	3	UN1230	II	3 .....	IB2, T7, TP2	150 .....	202 .....	242 .....	1 L	60 L	B	40
	Methazoic acid .....	Forbidden											
	4-Methoxy-4-methylpentan-2- one.	3	UN2993	III	3 .....	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	.....
+	1-Methoxy-2-propanol .....	3	UN3092	III	3 .....	B1, IB3, T2, TP1	150 .....	203 .....	242 .....	60 L	220 L	A	.....
	Methoxymethyl isocyanate .....	3	UN2605	I	3, 6.1	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None ...	226 .....	244 .....	Forbidden	Forbidden	D	40
	Methyl acetate .....	3	UN1231	II	3 .....	IB2, T4, TP1	150 .....	202 .....	242 .....	5 L	60 L	B	.....
	Methyl acetylene and propa- diene mixtures, stabilized.	2.1	UN1060	.....	2.1 .....	T50	306 .....	304 .....	314 .....	Forbidden	150 kg	B	40
	Methyl acrylate, stabilized .....	3	UN1919	II	3 .....	IB2, T4, TP1, TP13	150 .....	202 .....	242 .....	5 L	60 L	B	.....
	Methyl alcohol, see Methanol .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

Methyl allyl chloride .....	3	UN2554	II	3	IB2, T4, TP1, TP13	150	202	242	5 L	60 L	E	.....
Methyl amyl ketone, see Amyl methyl ketone.												.....
Methyl bromide .....	2.3	UN1062		2.3	3, B14, T50, T53	None	193	314, 315.	Forbidden	Forbidden	D	40
Methyl bromide and chloropicrin mixtures with more than 2 percent chloropicrin, see Chloropicrin and methyl bromide mixtures.												.....
Methyl bromide and chloropicrin mixtures with not more than 2 percent chloropicrin, see percent chloropicrin.												.....
Methyl bromide and ethylene dibromide mixtures, liquid.	6.1	UN1647	I	6.1	2, B9, B14, B32, B74, N65, T20, TP2, TP13, TP38, TP44	None	227	244	Forbidden	Forbidden	C	40
Methyl bromoacetate .....	6.1	UN2643	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	D	40
2-Methylbutanal .....	3	UN3371	II	3	IB2, T4, TP1	150	202	242	5 L	30 L	B	.....
2-Methyl-1-butene .....	3	UN2459	I	3	T11, TP2	None	201	243	1 L	30 L	E	.....
2-Methyl-2-butene .....	3	UN2460	II	3	IB2, T7, TP1	None	202	242	5 L	60 L	E	.....
3-Methyl-1-butene .....	3	UN2561	I	3	T11, TP2	None	201	243	1 L	30 L	E	.....
Methyl tert-butyl ether .....	3	UN2398	II	3	IB2, T7, TP1	150	202	242	5 L	60 L	E	.....
Methyl butyrate .....	3	UN1237	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Methyl chloride, or Refrigerant gas R 40.	2.1	UN1063	.....	2.1	T50	306	304	314, 315.	5 kg	100 kg	D	40
Methyl chloride and chloropicrin mixtures, see Chloropicrin and methyl chloride mixtures.												.....
Methyl chloride and methylene chloride mixtures.	2.1	UN1912	.....	2.1	T50	306	304	314, 315.	Forbidden	150 kg	D	40
Methyl chloroacetate .....	6.1	UN2295	I	6.1, 3	T14, TP2, TP13	None	201	243	1 L	30 L	D	.....
Methyl chloroformate, see Methyl chloroformate.												.....
Methyl chloroform, see 1,1,1-Trichloroethane.												.....
Methyl chloroformate .....	6.1	UN1238	I	6.1, 3, 8.	1, B9, B14, B30, B72, N34, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D	21, 40, 100
Methyl chloromethyl ether .....	6.1	UN1239	I	6.1, 3	1, B9, B14, B30, B72, T22, TP2, TP38, TP44	None	226	244	Forbidden	Forbidden	D	40
Methyl 2-chloropropionate .....	3	UN2933	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Methyl dichloroacetate .....	6.1	UN2299	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	.....
Methyl ethyl ether, see Ethyl methyl ether.												.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
(1)	Methyl ethyl ketone, <i>see</i> Ethyl methyl ketone. <i>Methyl ethyl ketone peroxide, in solution with more than 9 per- cent by mass active oxygen.</i> 2-Methyl-5-ethylpyridine ..... Methyl fluoride, or Refrigerant gas R 41. Methyl formate ..... 2-Methyl-2-neptanethiol .....	Forbidden  6.1 2.1 3 6.1	UN2300 UN2454 UN1243 UN3023	III ..... I I	6.1 ..... 3 6.1, 3	IB3, T4, TP1  T11, TP2 2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45 2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45 B1, IB3, T2, TP1 IB2, T4, TP1	153 306 150 None	203 304 201 227	241 314, 315. 243 244	60 L Forbidden 1 L Forbidden	220 L 150 kg 30 L Forbidden	A E E D	..... ..... 40 ..... 40, 102
	Methyl iodide .....	6.1	UN2644	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	A	12, 40
	Methyl isobutyl carbinol .....	3	UN2053	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	Methyl isobutyl ketone <i>Methyl isobutyl ketone peroxide, in solution with more than 9 percent by mass active oxy- gen.</i> Methyl isocyanate .....	Forbidden  6.1	UN1245 UN2480	II I	3 6.1, 3	IB2, T4, TP1 1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44 IB2, T4, TP1	150 None	202 226	242 244	5 L Forbidden	60 L Forbidden	B D	..... 26, 40
	Methyl isopropenyl ketone, sta- bilized. Methyl isothiocyanate .....	3 6.1	UN1246 UN2477	II I	3 6.1, 3	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45 IB2, T4, TP1	150 None	202 227	242 244	5 L Forbidden	60 L Forbidden	B A	..... .....
	Methyl isovalerate .....	3	UN2400	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
	Methyl magnesium bromide, in ethyl ether. Methyl mercaptan .....	4.3 2.3	UN1928 UN1064	I .....	4, 3, 3 2, 3, 2, 1.	3, B7, B9, B14, T50	None None	201 304	243 314, 315.	Forbidden Forbidden	1 L 25 kg	D D	..... 40



Methyl mercaptopropionaldehyde, see 4-Thiopentanal.																							40	
Methyl methacrylate monomer, stabilized.	3	UN1247	II	3	IB2, T4, TP1	150	202	242	5 L	60 L														
Methyl nitramine (dry)	Forbidden																							
Methyl nitrate	Forbidden																							
Methyl nitrite	Forbidden																							
Methyl norbornene dicarboxylic anhydride, see Corrosive liquids, n.o.s.																								
Methyl orthosilicate	6.1	UN2606	I	6.1, 3	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	E												40	
Methyl phosphonic dichloride	6.1	NA9206	I	6.1, 8	2, A3, B9, B14, B32, B74, N34, N43, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	C													
Methyl phosphonothioic dichloride, anhydrous, see Corrosive liquid, n.o.s.																								
Methyl phosphonous dichloride, pyrophoric liquid.	6.1	NA2845	I	6.1, 4.2	2, B9, B14, B16, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D													18
Methyl picric acid (heavy metal salts of)	Forbidden																							
Methyl propionate	3	UN1248	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B													
Methyl propyl ether	3	UN2612	II	3	IB2, T7, TP2	150	202	242	5 L	60 L	E													40
Methyl propyl ketone	3	UN1249	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B													
Methyl sulfite, see Dimethyl sulfide.																								
Methyl sulfide, see Dimethyl sulfide.																								
Methyl trichloroacetate	6.1	UN2533	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A													
Methyl trimethylol methane trinitrate.	Forbidden																							
Methyl vinyl ketone, stabilized	6.1	UN1251	I	6.1, 3, 8,	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	B													40
Methylal	3	UN1234	II	3	IB2, T7, TP2	None	202	242	5 L	60 L	E													
Methylamine, anhydrous	2.1	UN1061		2.1	150	306	304	314	Forbidden	150 kg	B													40
Methylamine, aqueous solution								315																
Methylamine dinitramine and dry salts thereof.	3	UN1235	II	3, 8	B1, IB2, T7, TP1	150	202	243	1 L	5 L	E													41
	Forbidden																							

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
D	Methylamine nitroform	Forbidden											
	Methylamine perchlorate (dry)	3	UN1233	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Methylamyl acetate	6.1	UN2294	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	N-Methylamine	6.1	UN2937	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	alpha-Methylbenzyl alcohol	3	UN2397	III	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	3-Methylbutan-2-one	3	UN2945	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	40
	N-Methylbutylamine	3	UN2945	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	40
	Methylchlorosilane	2.3	UN2534		2.3, 8	2, A2, A3, A7, B9, B14, N34	None	226	314, 315	Forbidden	Forbidden	D	17, 40
	Methylcyclohexane	3	UN2296	II	3	B1, IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Methylcyclohexanol, flammable	3	UN2617	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Methylcyclohexanone	3	UN2297	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Methylcyclopentane	3	UN2298	III	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Methylchloroarsine	6.1	NA1556	I	6.1	2, T20, TP4, TP12, TP13, TP38, TP45	None	192	None	Forbidden	Forbidden	D	40
Methylchlorosilane	4.3	UN1242	I	4.3, 8, 3	A2, A3, A7, B6, B77, N34, T10, TP2, TP7, TP13	None	201	243	Forbidden	1 L	D	21, 28, 40, 49, 100	
Methylene chloride, see Dichloromethane.													
Methylene glycol dinitrate	Forbidden												
2-Methylfuran	3	UN2301	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E		
a-Methylglucoside tetranitrate	Forbidden												
a-Methylglycerol trinitrate	Forbidden												
5-Methylhexan-2-one	3	UN2302	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A		
Methylhydrazine	6.1	UN1244	I	6.1, 3, 8	1, B7, B9, B14, B30, B72, B77, N34, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D	21, 40, 49, 100	
4-Methylmorpholine or n-methylmorpholine.	3	UN2535	II	3, 8	B6, IB2, T7, TP1	None	202	243	1 L	5 L	B	40	
Methylpentadienes	3	UN2461	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E		
2-Methylpentan-2-ol	3	UN2560	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A		
Methylpentanes, see Hexanes													
Methylphenylchlorosilane	8	UN2437	II	8	IB2, T7, TP2, TP13	154	202	242	1 L	30 L	C	40	
1-Methylpiperidine	3	UN2399	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B		

Methyltetrahydrofuran .....	3	UN2536	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Methyltrichlorosilane .....	3	UN1250	I	3, 8	A7, B6, B7, N84, T11, TP2, B1, IB2, T4, TP1	None	201	243	Forbidden	2.5 L	B	.....
alpha-Methylvaleraldehyde .....	3	UN2367	II	3	B1, IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Mine rescue equipment containing carbon dioxide, see Carbon dioxide.												
Mines with bursting charge .....	1.1F	UN0136	II	1.1F			62	None	Forbidden	Forbidden	08	.....
Mines with bursting charge .....	1.1D	UN0137	II	1.1D			62	None	Forbidden	Forbidden	03	.....
Mines with bursting charge .....	1.2D	UN0138	II	1.2D			62	None	Forbidden	Forbidden	03	.....
Mixed acid, see Nitric acid, mixtures etc.	1.2F	UN0294	II	1.2F			62	None	Forbidden	Forbidden	08	.....
Mobility aids, see Battery powered equipment or Battery powered vehicle.												
Model rocket motor .....	1.4C	NA0276	II	1.4C	51	None	62	None	Forbidden	75 kg	06	.....
Model rocket motor .....	1.4S	NA0323	II	1.4S	51	None	62	None	25 kg	100 kg	05	.....
Molybdenum pentachloride .....	8	UN2508	III	8	IB8, IP3, T4, TP1	154	213	240	25 kg	100 kg	C	.....
Monochloroacetone (unstabilized).	Forbidden											.....
Monochloroethylene, see Vinyl chloride, stabilized.												
Monoethanolamine, see Ethanolamine, solutions.												
Monoethylamine, see Ethylamine.												
Morpholine .....	8	UN2054	I	8, 3	T10, TP2	None	201	243	.5 L	2.5 L	A	.....
Morpholine, aqueous, mixture, see Corrosive liquids, n.o.s.												
Motor fuel anti-knock compounds see Motor fuel anti-knock mixtures.												
Motor fuel anti-knock mixtures ...	6.1	UN1649	I	6.1	14, 151, B9, B90, T14, TP2, TP13	None	201	244	Forbidden	30 L	D	25, 40
Motor spirit, see Gasoline												
Muriatic acid, see Hydrochloric acid.												
Musk xylene, see 5-tert-Butyl-2,4,6-trinitro-m-xylene.												
Naphtha see Petroleum distillates n.o.s.												
Naphthalene, crude or Naphthalene, refined.	4.1	UN1334	III	4.1	A1, IB8, IP3	151	213	240	25 kg	100 kg	A	.....
Naphthalene diazonide	Forbidden											
beta-Naphthylamine .....	6.1	UN1650	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	.....
alpha-Naphthylamine .....	6.1	UN2077	III	6.1	IB8, IP3, T3, TP1	153	213	240	100 kg	200 kg	A	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel slow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Naphthalene, molten	4.1	UN2304	III	4.1	A1, IB1, T1, TP3	151	213	241	Forbidden	Forbidden	C	
	Naphthylamineperchlorate	Forbidden											
	Naphthylthiourea	6.1	UN1651	II	6.1	IB8, IP2, IP4	None	212	242	100 kg	100 kg	A	
	Naphthylurea	6.1	UN1652	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Natural gases (with high meth-ane content), see Methane, etc. (UN 1971, UN 1972).												
	Neohexane, see Hexanes												
	Neon, compressed	2.2	UN1065		2.2	T75, TP5	306	302	302	75 kg	150 kg	A	
	Neon, refrigerated liquid (cryo-genic liquid).	2.2	UN1913		2.2		320	316	None	50 kg	500 kg	B	
	New explosive or explosive de-vice, see §§ 173.51 and 173.56												
	Nickel carbonyl	6.1	UN1259	I	6.1, 3	1	None	198	None	Forbidden	Forbidden	D	18, 40
	Nickel cyanide	6.1	UN1653	II	6.1	IB8, IP2, IP4, N74, N75	None	212	242	25 kg	100 kg	A	26
	Nickel nitrate	5.1	UN2725	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	
	Nickel nitrite	5.1	UN2726	III	5.1	A1, IB8, IP3	152	213	240	25 kg	100 kg	A	56, 58
	Nickel picrate	Forbidden											
	Nicotine	6.1	UN1654	II	6.1	IB2	None	202	243	60 L	60 L	A	
	Nicotine compounds, liquid, n.o.s. or Nicotine prepara-tions, liquid, n.o.s.	6.1	UN3144	I	6.1	A4	None	201	243	1 L	30 L	B	40
	Nicotine compounds, solid, n.o.s. or Nicotine prepara-tions, solid, n.o.s.												
	Nicotine hydrochloride or Nico-tine hydrochloride solution.												
	Nicotine salicylate	6.1	UN1657	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Nicotine sulfate, solid	6.1	UN1658	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Nicotine sulfate, solution	6.1	UN1658	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	
	Nicotine tartrate	6.1	UN1659	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Nitrated paper (unstable)	Forbidden											

Nitrates, inorganic, aqueous solution, n.o.s.	5.1	UN3218	II	5.1	58, IB2, T4, TP1	152	202	242	1 L	5 L	B	46
Nitrates, inorganic, n.o.s.	5.1	UN1477	III	5.1	58, IB2, T4, TP1 IB8, IP2, IP4	152	203	241	2.5 L	30 L	B	46
Nitrates of diazonium compounds.	Forbidden		III	5.1	IB8, IP3	152	212	240	5 kg	25 kg	A	46
Nitrating acid mixtures, spent with more than 50 percent nitric acid.	8	UN1826	I	8, 5.1	T10, TP2, TP12, TP13	None	158	243	Forbidden	2.5 L	D	40, 66
Nitrating acid mixtures spent with not more than 50 percent nitric acid.	8	UN1826	II	8	B2, IB2, T8, TP2	None	158	242	Forbidden	30 L	D	40
Nitrating acid mixtures with more than 50 percent nitric acid.	8	UN1796	I	8, 5.1	T10, TP2, TP12, TP13	None	158	243	Forbidden	2.5 L	D	40, 66
Nitrating acid mixtures with not more than 50 percent nitric acid.	8	UN1796	II	8	B2, IB2, T8, TP2, TP12, TP13	None	158	242	Forbidden	30 L	D	40
Nitric acid other than red fuming, with more than 70 percent nitric acid.	8	UN2031	I	8, 5.1	B47, B53, T10, TP2, TP12, TP13	None	158	243	Forbidden	2.5 L	D	44, 66, 89, 90, 110, 111
Nitric acid other than red fuming, with not more than 70 percent nitric acid.	8	UN2031	II	8	B2, B47, B53, IB2, T8, TP2, TP12	None	158	242	Forbidden	30 L	D	44, 66, 89, 90, 110, 111
Nitric acid, red fuming	8	UN2032	I	8, 5.1, 6.1	2, B9, B32, B74, T20, TP2, TP12, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40, 66, 74, 89, 90
Nitric oxide, compressed	2.3	UN1660		2.3, 5.1, 8	1, B37, B46, B50, B60, B77	None	337	None	Forbidden	Forbidden	D	40, 89, 90
Nitric oxide and dinitrogen tetroxide mixtures or Nitric oxide and nitrogen dioxide mixtures.	2.3	UN1975		2.3, 5.1, 8	1, B7, B9, B14, B45, B46, B61, B66, B67, B77	None	337	None	Forbidden	Forbidden	D	40, 89, 90
Nitrites, flammable, toxic, n.o.s.	3	UN3273	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	E	40, 52
Nitrites, toxic, flammable, n.o.s.	6.1	UN3275	II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40, 52
Nitrites, toxic, n.o.s.	6.1	UN3276	I	6.1, 3	5, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
Nitrites, toxic, n.o.s.	6.1	UN3276	II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
Nitrites, toxic, n.o.s.	6.1	UN3276	I	6.1	5, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	
Nitrites, toxic, n.o.s.	6.1	UN3276	II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L	B	
Nitrites, toxic, n.o.s.	6.1	UN3276	III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	220 L	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
(1)	Nitrites, inorganic, aqueous solu-tion, n.o.s.	5.1	UN3219	II	5.1	IB1, T4, TP1	152	202	242	1 L	5 L	B	46, 56, 58
	Nitrites, inorganic, n.o.s.	5.1	UN2627	III	5.1	IB2, T4, TP1	152	203	241	2.5 L	30 L	B	46, 56, 58
	3-Nitro-4-chlorobenzotrifluoride	6.1	UN2307	II	5.1	33, IB8, IP4	152	212	None	5 kg	25 kg	A	46, 56, 58
	6-Nitro-4-diazotoluene-3-sulfonic acid (dry)	Forbidden		II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40
	Nitro isobutane triol trinitrate	Forbidden											
	N-Nitro-N-methylglycolamide ni-trate	Forbidden											
	2-Nitro-2-methylpropanol nitrate	Forbidden											
	Nitro urea	1.1D	UN0147	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	N-Nitroaniline	Forbidden		II	6.1		None	212	242	25 kg	100 kg	A	
	Nitroanilines (o-, m-, p-)	6.1	UN1661	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	
	Nitroanisole	6.1	UN2730	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	
	Nitrobenzene	6.1	UN1662	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40
	m-Nitrobenzene diazonium per-chlorate	Forbidden											
	Nitrobenzenesulfonic acid	8	UN2305	II	8	IB2	154	202	242	1 L	30 L	A	
	Nitrobenzol, see Nitrobenzene												
	5-Nitrobenzotriazol	1.1D	UN0385	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Nitrobenzotrifluorides	6.1	UN2306	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40
	Nitrobenzenes liquid	6.1	UN2732	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	
	Nitrobenzenes solid	6.1	UN2732	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	
	Nitrocellulose, dry or wetted with less than 25 percent water (or alcohol), by mass	1.1D	UN0340	II	1.1D		None	62	None	Forbidden	Forbidden	13	27E
	Nitrocellulose membrane filters, with not more than 12.6% ni-trogen, by dry mass	4.1	UN3270	II	4.1	43, A1	151	212	240	1 kg	15 kg	D	
	Nitrocellulose, plasticized with not less than 18 percent plas-ticizing substance, by mass	1.3C	UN0343	II	1.3C		None	62	None	Forbidden	Forbidden	10	

	3	UN2059	II 3	IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B	
Nitrocellulose, solution, flammable with not more than 12.6 percent nitrogen, by mass, and not more than 55 percent nitrocellulose.											
Nitrocellulose, unmodified or plasticized with less than 18 percent plasticizing substance, by mass.	1.1D	UN0341	III 3 II 1.1D	B1, IB3, T2, TP1	150 None	203 62	242 None	60 L Forbidden	220 L Forbidden	A 13	27E
Nitrocellulose, wetted with not less than 25 percent alcohol, by mass.	1.3C	UN0342	II 1.3C		None	62	None	Forbidden	Forbidden	10	
Nitrocellulose with alcohol with not less than 25 percent alcohol by mass, and with not more than 12.6 percent nitrogen, by dry mass.	4.1	UN2556	II 4.1		151	212	None	1 kg	15 kg	D	28
Nitrocellulose, with not more than 12.6 percent nitrogen, by dry mass, or Nitrocellulose mixture with pigment or Nitrocellulose mixture with plasticizer or Nitrocellulose mixture with pigment and plasticizer.	4.1	UN2557	II 4.1	44	151	212	None	1 kg	15 kg	D	28
Nitrocellulose with water with not less than 25 percent water, by mass.	4.1	UN2555	II 4.1		151	212	None	15 kg	50 kg	E	28
Nitrochlorobenzene, see Chloronitrobenzenes etc.											
Nitrocresols	6.1	UN2446	III 6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
Nitroethane	3	UN2842	III 3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
Nitroethyl nitrate	Forbidden										
Nitroethylene polymer	Forbidden										
Nitrogen, compressed	2.2	UN1066	2.2		306	302	314 315	75 kg	150 kg	A	
Nitrogen dioxide, see Dinitrogen tetroxide.											
Nitrogen fertilizer solution, see Fertilizer ammoniating solution etc.											
Nitrogen, mixtures with rare gases, see Rare gases and nitrogen mixtures.											
Nitrogen peroxide, see Dinitrogen tetroxide.											
Nitrogen, refrigerated liquid cryogenic liquid.	2.2	UN1977	2.2	T75, TP5	320	316	318	50 kg	500 kg	D	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions (8A)	Non- bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air- craft only (9B)	Loca- tion (10A)	Other (10B)
(1)	Nitrogen tetroxide and nitric oxide mixtures, see Nitric oxide and nitrogen tetroxide mixtures. Nitrogen tetroxide, see Dinitrogen tetroxide. Nitrogen trichloride Nitrogen trifluoride	Forbidden 2.2	UN2451		2.2, 5.1.		None	302	None	75 kg	150 kg	D	40
	Nitrogen triiodide Nitrogen triiodide monoamine Nitrogen trioxide	Forbidden 2.3	UN2421		2.3, 5.1.	1	None	336	245	Forbidden	Forbidden	D	40, 89, 90
	Nitroglycerin, desensitized with not less than 40 percent non-volatile water insoluble phlegmatizer, by mass. Nitroglycerin, liquid, not desensitized.	1.1D	UN0143	II	1.1D, 6.1.	125	None	62	None	Forbidden	Forbidden	13	21E
	Nitroglycerin mixture, desensitized, liquid, flammable, n.o.s. with not more than 30 percent nitroglycerin, by mass. Nitroglycerin mixture, desensitized, liquid, n.o.s. with not more than 30% nitroglycerin, by mass.	Forbidden 3	UN3343		3	129	None	214	None	Forbidden	Forbidden	D	
	Nitroglycerin mixture, desensitized, solid, n.o.s. with more than 2 percent but not more than 10 percent nitroglycerin, by mass.	3	UN3357	II	3	142	None	202	243	5 L	60 L	E	
	Nitroglycerin mixture, desensitized, solid, n.o.s. with more than 2 percent but not more than 10 percent nitroglycerin, by mass.	4.1	UN3319	II	4.1	118	None	None	None	Forbidden	0.5 kg	E	
	Nitroglycerin, solution in alcohol, with more than 1 percent but not more than 5 percent nitroglycerin.	3	UN3084	II	3	N8	None	202	None	Forbidden	5 L	E	



UN number	UN description	1.1D	II	1.1D ..	None ...	62 .....	None ...	Forbiddn	Forbiddn	10	21E
1.1D UN0144	Nitroglycerin, solution in alcohol, with more than 1 percent but not more than 10 percent nitroglycerin.		II	1.1D ..	None ...	62 .....	None ...	Forbiddn	Forbiddn	10	21E
3 UN1204	Nitroglycerin solution in alcohol with not more than 1 percent nitroglycerin.		II	3 .....	None ...	202 .....	None ...	5 L	60 L	B	.....
Forbiddn UN0282	Nitroguanidine nitrate	1.1D	II	1.1D ..	None ...	62 .....	None ...	Forbiddn	Forbiddn	10	.....
4.1 UN1336	Nitroguanidine or Picrite, dry or wetted with less than 20 percent water, by mass.		I	4.1 .....	None ...	211 .....	None ...	1 kg	15 kg	E	28
Forbiddn UN1798	1-Nitrohydantoin	8	I	8 .....	None ...	201 .....	243 .....	Forbiddn	2.5 L	D	40, 66, 74, 89, 90
Forbiddn	Nitrohydrochloric acid										
Forbiddn	Nitromannite (dry)										
Forbiddn	Nitromannite, wetted, see Mannitol hexanitrate, etc.										
3 UN1261	Nitromethane		II	3 .....	150 .....	202 .....	None ...	Forbiddn	60 L	A	.....
Forbiddn	Nitromuratic acid, see Nitrohydrochloric acid.										
4.1 UN2538	Nitronaphthalene		III	4.1 .....	151 .....	213 .....	240 .....	25 kg	100 kg	A	.....
6.1 UN1663	Nitrophenols (o-; m-; p-)		III	6.1 .....	153 .....	213 .....	240 .....	100 kg	200 kg	A	.....
Forbiddn	m-Nitrophenyldinitro methane										
4.1 UN3376	4-Nitrophenylhydrazine, with not less than 30% water, by mass.		I	4.1 .....	None ...	211 .....	None ...	Forbiddn	Forbiddn	E	36
3 UN2608	Nitropropanes		III	3 .....	150 .....	203 .....	242 .....	60 L	220 L	A	.....
4.2 UN1369	p-Nitrosodimethylaniline		II	4.2 .....	None ...	212 .....	241 .....	15 kg	50 kg	D	34
1.1D UN0146	Nitrostarch, dry or wetted with less than 20 percent water, by mass.		II	1.1D ..	None ...	62 .....	None ...	Forbiddn	Forbiddn	10	.....
4.1 UN1337	Nitrostarch, wetted with not less than 20 percent water, by mass.		I	4.1 .....	None ...	211 .....	None ...	1 kg	15 kg	D	28
Forbiddn	Nitrosugars (dry)										
2.3 UN1069	Nitrosyl chloride			2.3, 8	None ...	304 .....	314 .....	Forbiddn	Forbiddn	D	40
8 UN2308	Nitrosylsulfuric acid		II	8 .....	154 .....	202 .....	315, 242 .....	1 L	30 L	D	40, 66, 74, 89, 90
6.1 UN1664	Nitrotoluenes, liquid o-, m-, p-, ..		II	6.1 .....	None ...	202 .....	243 .....	5 L	60 L	A	.....
6.1 UN1664	Nitrotoluenes, solid m-, or p-		II	6.1 .....	None ...	212 .....	242 .....	25 kg	100 kg	A	.....
6.1 UN2660	Nitrotoluidines (mono)		III	6.1 .....	153 .....	213 .....	240 .....	100 kg	200 kg	A	.....
1.1D UN0490	Nitrotriazolone or NTO		II	1.1D ..	None ...	62 .....	None ...	Forbiddn	Forbiddn	10	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§ 173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Nitrous oxide and carbon dioxide mixtures, see Carbon dioxide and nitrous oxide mixtures.												
	Nitrous oxide	2.2	UN1070		2.2, 5.1.		306	304	314, 315.	75 kg	150 kg	A	40
	Nitrous oxide, refrigerated liquid	2.2	UN2201		2.2, 5.1.	B6, T75, TP5, TP22	None	304	314, 315.	Forbidden	Forbidden	B	40
	Nitroxylene, (o-, m-, p-)	6.1	UN1665	II	6.1	IB2, IP2, IP4, T7, TP2	None	202	243	5 L	60 L	A	
	Nitroxyl, see Nitroxylene												
	Nonanes	3	UN1920	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Non-flammable gas, n.o.s., see Compressed gas, etc. or Liquefied gas, etc.												
	Nonliquefied gases, see Compressed gases, etc.												
	Nonliquefied hydrocarbon gas, see Hydrocarbon gas mixture, compressed, n.o.s.												
	Nonyltrichlorosilane	8	UN1799	II	8	A7, B2, B6, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	Nordhausen acid, see Sulfuric acid, fuming etc.												
	2,5-Norbornadiene, stabilized, see Bicyclo 2.2.1 hepta-2,5-diene, stabilized.												
	Octadecyltrichlorosilane	8	UN1800	II	8	A7, B2, B6, IB2, N34, T7, TP2, TP13	None	202	242	Forbidden	30 L	C	40
	Octadiene	3	UN2309	II	3	B1, IB2, T4, TP1	150	202	242	5 L	60 L	B	
	1,7-Octadecyne-1,8-dimethoxy-9-octadecynoic acid.	Forbidden											
	Octafluorobut-2-ene or Refrigerant gas R 1318.	2.2	UN2422		2.2		None	304	314, 315.	75 kg	150 kg	A	
	Octafluorocyclobutane, or Refrigerant gas RC 318.	2.2	UN1976		2.2	T50	None	304	314, 315.	75 kg	150 kg	A	

UN number	Proper shipping name	Class	Division	Subdivision	Label	Quantity	Special provisions	Other	Additional	Notes
UN2424	Octafluoropropane or Refrigerant gas R 218.	2.2		T50	None	304	314, 315.	150 kg	A	
UN1262	Octanes, etc. see Cyclohexane, etc. Cyclotetramethylene tetranitramine, etc. Octolite or Octol, dry or wetted with less than 15 percent water, by mass.	3		IB2, T4, TP1	150	202	242	60 L	B	
UN0266		1.1D			None	62	None	Forbidden	10	
UN0496	Octonal	1.1D		B1, IB3, T2, TP1	None	62	None	Forbidden	10	
UN1191	Octyl aldehydes	3		A7, B2, B6, IB2, N84, T7, TP2, TP13	150	203	242	220 L	A	
UN1801	Octyltrichlorosilane	8			None	202	242	30 L	C	40
UN1071	Oil gas, compressed	2.3		6	None	304	314, 315.	25 kg	D	40
	Oilum; see Sulfuric acid, fuming									
	Organic peroxide type A, liquid or solid.	Forbidden								
G	Organic peroxide type B, liquid	5.2		53	152	225	None	Forbidden	D	12, 40
G	Organic peroxide type B, liquid, temperature controlled.	5.2		53	None	225	None	Forbidden	D	2, 40
G	Organic peroxide type B, solid	5.2		53	152	225	None	Forbidden	D	12, 40
G	Organic peroxide type B, solid, temperature controlled.	5.2		53	None	225	None	Forbidden	D	2, 40
G	Organic peroxide type C, liquid	5.2			152	225	None	10 L	D	12, 40
G	Organic peroxide type C, liquid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type C, solid	5.2			152	225	None	10 kg	D	12, 40
G	Organic peroxide type C, solid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type D, liquid	5.2			152	225	None	10 L	D	12, 40
G	Organic peroxide type D, liquid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type D, solid	5.2			152	225	None	10 kg	D	12, 40
G	Organic peroxide type D, solid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type E, liquid	5.2			152	225	None	25 L	D	12, 40
G	Organic peroxide type E, liquid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type E, solid	5.2			152	225	None	25 kg	D	12, 40
G	Organic peroxide type E, solid, temperature controlled.	5.2			None	225	None	Forbidden	D	2, 40
G	Organic peroxide type F, liquid	5.2		IB52, IP5, T23	152	225	225	25 L	D	12, 40
G	Organic peroxide type F, liquid, temperature controlled.	5.2		IB52, T23	None	225	225	Forbidden	D	2, 40
G	Organic peroxide type F, solid	5.2		IB52, T23	152	225	225	25 kg	D	12, 40
G	Organic peroxide type F, solid, temperature controlled.	5.2		IB52, T23	None	225	225	Forbidden	D	2

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
D	Organic phosphate, mixed with compressed gas or Organic phosphate compound, mixed with compressed gas or Or- ganic phosphorus compound, mixed with compressed gas. Organic pigments, self-heating .. Organoarsenic compound, n.o.s.	2.3  4.2 6.1	NA1955  UN3313 UN3280	 II III I	2.3 4.2 6.1	3  IB8, IP4 IB8, IP3 5, IB7, IP1, T14, TP2, TP27 IB8, IP2, IP4, T11, TP2, TP27 IB8, IP3, T7, TP1, TP28 T14, TP2, TP13, TP27	None None None	334 212 213 211	None 241 241 242	None 15 kg 25 kg 5 kg	Forbidden 50 kg 100 kg 50 kg	Forbidden C C B	40
	Organochlorine pesticides liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2762	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
	Organochlorine pesticides, liq- uid, toxic.	6.1	UN2996	II	3, 6.1	IB2, T11, TP2, TP13, TP27 T14, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
	Organochlorine pesticides, liq- uid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN2995	III	6.1	IB2, T11, TP2, TP13, TP27 IB3, T7, TP2, TP28 T14, TP2, TP13, TP27	None	202 203	243 241	5 L 60 L	60 L 220 L	B A	40 40
	Organochlorine, pesticides, solid, toxic.	6.1	UN2761	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
				II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
				III	6.1, 3	B1, IB3, T7, TP2, TP28	153	203	242	60 L	220 L	A	40
				II	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
				III	6.1	IB8, IP2, IP4 IB8, IP3	None	212 153	242 240	25 kg 100 kg	100 kg 200 kg	A A	40 40

G	Organometallic compound or Compound solution or Compound dispersion, water-reactive, flammable, n.o.s.	4.3	UN3207	I	4.3, 3	T13, TP2, TP7	None	201	244	Forbidden	1 L	E	40
				II	4.3, 3	IB1, IP2, T7, TP2, TP7	None	202	243	1 L	5 L	E	40
				III	4.3, 3	IB2, IP4, T7, TP2, TP7	None	203	242	5 L	60 L	E	40
G	Organometallic compound, solid, water-reactive, flammable, n.o.s.	4.3	UN3372	I	4.3, 4.1.	IB4, N40	None	211	242	Forbidden	15 kg	E	40
				II	4.3, 4.1.	IB4	151	212	242	15 kg	50 kg	E	40
				III	4.3, 4.1.	IB6	151	213	241	25 kg	100 kg	E	40
G	Organometallic compound, toxic n.o.s.	6.1	UN3282	I	6.1	IB7, IP1, T14, TP2, TP27	None	211	242	5 kg	50 kg	B	
				II	6.1	IB8, IP2, IP4, T11, TP2, TP27	None	212	242	25 kg	100 kg	B	
				III	6.1	IB8, IP3, T7, TP1, TP28	153	213	240	100 kg	200 kg	A	
				I	6.1, 3	5, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
				I	6.1	5, IB7, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	
				II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L	B	
				III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	220 L	A	
				I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
				II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
				I	6.1	N76, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
				II	6.1	IB2, N76, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
				III	6.1	IB3, N76, T7, TP2, TP28	153	203	241	60 L	220 L	A	40
				I	6.1, 3	N76, T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
				II	6.1, 3	IB2, N76, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
				III	6.1, 3	B1, IB3, N76, T7, TP2, TP28	153	203	242	60 L	220 L	A	40
				I	6.1	IB7, IP1, N77	None	211	242	5 kg	50 kg	A	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Organotin compounds, liquid, n.o.s.	6.1	UN2788	I	6.1	IB8, IP3, N34, T14, TP2, TP13, TP27	None	201	243	1 L	200 kg	30 L	40
	Organotin compounds, solid, n.o.s.	6.1	UN3146	I	6.1	IB3, T7, TP2, TP28	None	203	241	60 L	220 L	A	40
	Organotin pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2787	I	3, 6.1	IB8, IP3, T14, TP2, TP13, TP27	None	201	243	Forbidden	200 kg	30 L	40
	Organotin pesticides, liquid, toxic.	6.1	UN3020	I	6.1	IB2, T11, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
	Organotin pesticides, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN3019	I	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
	Organotin pesticides, solid, toxic	6.1	UN2786	I	6.1	IB7, IP1, TP28	None	211	242	5 kg	50 kg	A	40
	Orthoironilines, see Nitroironilines etc.						153	213	240	100 kg	200 kg	A	40

D G	Osmium tetroxide .....	6.1	UN2471	I	6.1	A8, IB7, IP1, N33, N34	None	211	242	5 kg	50 kg	B	40
D G	Other regulated substances, liquid, n.o.s.	9	NA3082	III	9	IB3, T2, TP1	155	203	241	No limit	No limit	A	.....
D G	Other regulated substances, solid, n.o.s.	9	NA3077	III	9	B54, IB8, IP2	155	213	240	No limit	No limit	A	.....
G	Oxidizing liquid, corrosive, n.o.s.	5.1	UN3098	I	5.1, 8		None	201	244	Forbidden	2.5 L	D	13, 56, 58, 69, 106
	.....			II	5.1, 8	IB1	None	202	243	1 L	5 L	B	34, 56, 58, 69, 106
	.....			III	5.1, 8	IB2	152	203	242	2.5 L	30 L	B	34, 56, 58, 69, 106
G	Oxidizing liquid, n.o.s. ....	5.1	UN3139	I	5.1	127, A2	None	201	243	Forbidden	2.5 L	D	56, 58, 69, 106
	.....			II	5.1	127, A2, IB2	152	202	242	1 L	5 L	B	56, 58, 69, 106
	.....			III	5.1	127, A2, IB2	152	203	241	2.5 L	30 L	B	56, 58, 69, 106
G	Oxidizing liquid, toxic, n.o.s. ....	5.1	UN3099	I	5.1, 6.1		None	201	244	Forbidden	2.5 L	D	56, 58, 69, 106
	.....			II	5.1, 6.1	IB1	None	202	243	1 L	5 L	B	56, 58, 69, 106
	.....			III	5.1, 6.1	IB2	152	203	242	2.5 L	30 L	B	56, 58, 69, 106
G	Oxidizing solid, corrosive, n.o.s.	5.1	UN3085	I	5.1, 8		None	211	242	1 kg	15 kg	D	13, 56, 58, 69, 106
	.....			II	5.1, 8	IB6, IP2	None	212	242	5 kg	25 kg	B	13, 34, 56, 58, 69, 106
	.....			III	5.1, 8	IB8, IP3	152	213	240	25 kg	100 kg	B	13, 34, 56, 58, 69, 106
G	Oxidizing solid, flammable, n.o.s.	5.1	UN3137	I	5.1, 4.1		None	214	214	Forbidden	Forbidden		.....
G	Oxidizing solid, n.o.s. ....	5.1	UN1479	I	5.1	IB6, IP1	None	211	242	1 kg	15 kg	D	56, 58, 69, 106
	.....			II	5.1	IB8, IP2, IP4	152	212	240	5 kg	25 kg	B	56, 58, 69, 106
	.....			III	5.1	IB8, IP3	152	213	240	25 kg	100 kg	B	56, 58, 69, 106
G	Oxidizing solid, self-heating, n.o.s.	5.1	UN3100	II	5.1, 4.2		None	214	214	Forbidden	Forbidden		.....
G	Oxidizing solid, toxic, n.o.s. ....	5.1	UN3087	I	5.1, 6.1		None	211	242	1 kg	15 kg	D	56, 58, 69, 106

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions	Non-bulk	Bulk	Passenger aircraft/rail	Cargo air-craft only	Loca-tion	Other
(1)						(7)	(8A)	(8B)	(8C)	(9A)	(9B)	(10A)	(10B)
				II	5.1, 6.1.	IB6, IP2	None	212	242	5 kg	25 kg	B	56, 58, 69, 95, 106
				III	5.1, 6.1.	IB8, IP3	152	213	240	25 kg	100 kg	B	56, 58, 69, 95, 106
G	Oxidizing solid, water-reactive, n.o.s. Oxygen and carbon dioxide mix-tures, see Carbon dioxide and oxygen mixtures. Oxygen, compressed Oxygen difluoride, compressed	5.1	UN3121		5.1, 4.3.		None	214	214	Forbidden	Forbidden		
					2.2, 5.1.	A52	306	302	314, 315.	75 kg	150 kg	A	
					2.3, 5.1, 8.	1	None	304	None	Forbidden	Forbidden	D	13, 40, 89, 90
				II	5.1	60, A51	None	212	None	Forbidden	25 kg gross	D	56, 58, 69, 106
+	Oxygen generator, chemical (in-cluding when contained in as-sociated equipment, e.g., pas-senger service units (PSUs), portable breathing equipment (PBE), etc). Oxygen generator, chemical, spent. Oxygen, mixtures with rare gases, see Rare gases and oxygen mixtures. Oxygen, refrigerated liquid (cryo-genic liquid). Paint including paint, lacquer, enamel, stain, shellac solu-tions, varnish, polish, liquid filler, and liquid lacquer base.	9	NA3356	III	9	61	None	213	None	Forbidden	Forbidden	A	
					2.2, 5.1.	T75, TP5, TP22	320	316	318	Forbidden	Forbidden	D	
				I	3	T11, TP1, TP8	150	201	243	1 L	30 L	E	
				II	3	149, B52, IB2, T4, TP1, TP8	150	173	242	5 L	60 L	B	
				III	3	B1, B52, IB3, T2, TP1	150	173	242	60 L	220 L	A	
	Paint or Paint related material ...	8	UN3066	II	8	B2, IB2, T7, TP2	154	173	242	1 L	30 L	A	



Paint related material including paint thinning, drying, removing, or reducing compound.	3	UN1263	III	8	B52, IB3, T4, TP1 T11, TP1, TP8	154	173	241	5 L	60 L A	.....
Paper, unsaturated oil treated incompletely dried (including carbon paper).	4.2	UN1379	III	4.2	IB8, IP3	None	213	241	Forbidden	Forbidden A	.....
Paraldehyde	4.1	UN2213	III	4.1	A1, IB8, IP3	151	213	240	25 kg	100 kg A	.....
Paraldehyde	3	UN1264	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L A	.....
Paranitroaniline, see Nitroanilines etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Parathion and compressed gas mixture.	2.3	NA1967	.....	2.3	3	None	334	245	Forbidden	Forbidden E	40
Paris green, solid, see Copper acetoarsenite.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
PCB, see Polychlorinated biphenyls.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Pentaborane	4.2	UN1380	I	4.2, 6.1	1	None	205	245	Forbidden	Forbidden D	.....
Pentachloroethane	6.1	UN1669	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L A	40
Pentachlorophenol	6.1	UN3155	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg A	.....
Pentaerythrite tetranitrate (dry)	Forbidden	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Pentaerythrite tetranitrate mixture, desensitized, solid, n.o.s. with more than 10 percent but not more than 20 percent PETN, by mass.	4.1	UN3344	II	4.1	118, N85	None	214	None	Forbidden	Forbidden E	.....
Pentaerythritol tetranitrate or PETN, with not less than 7 percent wax by mass.	1.1D	UN0411	II	1.1D	.....	None	62	None	Forbidden	Forbidden 10	.....
Pentaerythrite tetranitrate, wetted or Pentaerythritol tetranitrate, wetted, or PETN, wetted with not less than 25 percent water, by mass, or Pentaerythrite tetranitrate, or Pentaerythritol tetranitrate or PETN, desensitized with not less than 15 percent phlegmatizer by mass.	1.1D	UN0150	II	1.1D	121	None	62	None	Forbidden	Forbidden 10	.....
Pentaerythritol tetranitrate, see Pentaerythrite tetranitrate, etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Pentfluoroethane or Refrigerant gas R 125.	2.2	UN3220	.....	2.2	T50	306	304	314, 315.	75 kg	150 kg A	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Pentamethylheptane .....	3	UN2286	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	Pentane-2,4-dione .....	3	UN2310	III	3, 6.1	B1, IB3, T4, TP1	150	203	242	60 L	220 L	A	.....
	Pentanes .....	3	UN1265	I	3	T11, TP2	150	201	243	1 L	30 L	E	.....
	<i>Pentanitroaniline (dry)</i> .....	Forbidden		II	3	IB2, T4, TP1	150	202	242	5 L	60 L	E	.....
	Pentanols .....	3	UN1105	II	3	IB2, T4, TP1, TP29	150	202	242	5 L	60 L	B	.....
	.....	.....	.....	III	3	B1, B3, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	1-Pentene ( <i>n</i> -amylene) .....	3	UN1108	I	3	T11, TP2	150	201	243	1 L	30 L	E	.....
	1-Pentol .....	8	UN2705	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	B	.....
	Pentolite, <i>dry or wetted with less than 15 percent water, by mass.</i> .....	1.1D	UN0151	II	1.1D	None	62	None	None	Forbidden	Forbidden	10	38
	Perchlorates, inorganic, aqueous solution, n.o.s. ....	5.1	UN3211	II	5.1	IB2, T4, TP1	152	202	242	1 L	5 L	B	46, 56, 58
	.....	.....	.....	III	5.1	IB2, T4, TP1	152	202	241	2.5 L	30 L	B	56, 58, 69, 106
	<i>Pepper spray, see Aerosols, etc. or Self-defense spray, non-pressurized.</i> .....	.....	.....	III	5.1	.....	152	203	241	2.5 L	30 L	B	56, 58, 69, 106
	Perchlorates, inorganic, n.o.s. ....	5.1	UN1481	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	46, 56
	.....	Forbidden		III	5.1	IB8, IP3	152	213	240	25 kg	100 kg	A	46, 56
	<i>Perchloric acid, with more than 72 percent acid by mass.</i> .....	5.1	UN1873	I	5.1, 8	A2, A3, N41, T10, TP1, TP12	None	201	243	Forbidden	2.5 L	D	66
	<i>Perchloric acid with more than 50 percent but not more than 72 percent acid, by mass.</i> .....	8	UN1802	II	8, 5.1	IB2, N41, T7, TP2	None	202	243	Forbidden	30 L	C	66
	<i>Perchloric acid with not more than 50 percent acid by mass.</i> .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	<i>Perchloroethylene, see Tetrachloroethylene.</i> .....	6.1	UN1670	I	6.1	2, A3, A7, B9, B14, B32, B74, N34, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Perchloromethyl mercaptan .....	.....	.....	.....	.....	2, B9, B14	None	302	314, 315	Forbidden	Forbidden	D	40
	Perchloryl fluoride .....	2.3	UN3083	.....	2.3, 5.1	.....	None	.....	.....	.....	.....	.....	.....

Material Description	Hazard Class	UN Number	Packing Group	Label Code	Provisions	Quantity	Restrictions	Volume/Weight	Classification	Notes
<i>Percussion caps, see Primers, cap type.</i>										
Perfluoro-2-butene, see Octafluorobut-2-ene.										
Perfluoro(ethyl vinyl ether)	2.1	UN3154		2.1	306	302, 304, 305		150 kg	E	40
Perfluoro(methyl vinyl ether)	2.1	UN3153		2.1	306	302, 304, 305	Forbidden	150 kg	E	40
Perfumery products with flammable solvents.	3	UN1266	II	3	150	202	15 L	60 L	B	
Permanganates, inorganic, aqueous solution, n.o.s.	5.1	UN3214	III	3	150	203	60 L	220 L	A	56, 58, 69, 106, 107
Permanganates, inorganic, n.o.s.	5.1	UN1482	II	5.1	152	212	5 kg	25 kg	D	56, 58, 69, 106, 107
			III	5.1	152	213	25 kg	100 kg	D	56, 58, 69, 106, 107
Peroxides, inorganic, n.o.s.	5.1	UN1483	II	5.1	None	212	5 kg	25 kg	A	13, 75, 106
			III	5.1	152	213	25 kg	100 kg	A	13, 75, 106
Peroxyacetic acid, with more than 43 percent and with more than 6 percent hydrogen peroxide.	Forbidden									
Persulfates, inorganic, aqueous solution, n.o.s.	5.1	UN3216	III	5.1	152	203	2.5 L	30 L	A	
Persulfates, inorganic, n.o.s.	5.1	UN3215	III	5.1	152	213	25 kg	100 kg	A	
Pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN3021	I	3, 6.1	None	201	Forbidden	30 L	B	
			II	3, 6.1	None	202	1 L	60 L	B	
			I	6.1, 3	None	201	1 L	30 L	B	40
Pesticides, liquid, toxic, flammable, n.o.s., flash point not less than 23 degrees C.	6.1	UN2903	II	6.1, 3	None	202	5 L	60 L	B	40
			III	6.1, 3	153	203	60 L	220 L	A	40
			I	6.1	None	201	1 L	30 L	B	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identi- fication Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age		
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other	
G					6.1	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40	
					6.1	IB3, T7, TP2, TP28	153	203	241	60 L	220 L	A	40	
		6.1	UN2588		6.1	IB7	None	211	242	5 kg	50 kg	A	40	
					6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	40	
					6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	40	
D					3	UN1267		201	243	1 L	30 L	E		
					3	144, T11, TP1, TP8	None	201	243	1 L	30 L	E		
					3	144, IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B		
					3	144, B1, IB3, T2, TP1	150	203	242	60 L	220 L	A		
					3	144, T11, TP1, TP8	150	201	243	1 L	30 L	E		
					3	144, IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B		
					3	144, B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A		
					2.1	UN1075	T50	306	314, 315	Forbidden	150 kg	E	40	
					3	NA1270	144, T11, TP1, TP9	None	201	243	1 L	30 L	E	
					3	144, IB2, T7, TP1, TP8, TP28	150	202	242	5 L	60 L	B		
+					3	144, B1, IB3, T4, TP1, TP29	150	203	242	60 L	220 L	A		
					6.1	UN2645	IB8, IP2, IP4	None	212	242	25 kg	100 kg	B	40
					6.1	UN2311	IB3, T4, TP1	153	203	241	60 L	220 L	A	
					6.1	UN2312	B14, T7, TP3	None	202	243	Forbidden	Forbidden	B	40
					6.1	UN1671	IB8, IP2, IP4, N78, T6, TP2	None	212	242	25 kg	100 kg	A	
					6.1	UN2821	IB2, T7, TP2	None	202	243	5 L	60 L	A	
					6.1	UN1803	IB3, T4, TP1	153	203	241	60 L	220 L	A	
					8		B2, IB2, N41, TP2	154	202	242	1 L	30 L	C	14

Phenoxyacetic acid derivative pesticide, liquid, flammable, toxic flash point less than 23 degrees C.	3	UN3346	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbiddn	30 L	B	40
Phenoxyacetic acid derivative pesticide, liquid, toxic.	6.1	UN3348	II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
			I	6.1	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
			II	6.1	IB2, T11, TP2, TP27	153	202	243	5 L	60 L	B	40
			III	6.1	IB3, T7, TP2, TP28	153	203	241	60 L	220 L	A	40
Phenoxyacetic acid derivative pesticide, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN3347	I	6.1, 3	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
			II	6.1, 3	IB2, T11, TP2, TP13, TP27	153	202	243	5 L	60 L	B	40
			III	6.1, 3	IB3, T7, TP2, TP28	153	203	241	60 L	220 L	A	40
Phenoxyacetic acid derivative pesticide, solid, toxic.	6.1	UN3345	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
			II	6.1	IB8, IP2, IP4	153	212	242	25 kg	100 kg	A	40
			III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	40
Phenyl chloroformate	6.1	UN2746	II	6.1, 8	IB2, T7, TP2, TP13	None	202	243	1 L	30 L	A	12, 13, 21, 25, 40, 100
Phenyl isocyanate	6.1	UN2487	I	6.1, 3	2, B9, B14, B32, B74, B77, N33, N34, T20, TP2, TP13, TP38, TP45	None	227	244	Forbiddn	Forbiddn	D	40
Phenyl mercaptan	6.1	UN2337	I	6.1, 3	2, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbiddn	Forbiddn	B	26, 40
Phenyl phosphorus dichloride	8	UN2798	II	8	B2, B15, IB2, T7, TP2	154	202	242	Forbiddn	30 L	B	40
Phenyl phosphorus trichloride	8	UN2799	II	8	B2, B15, IB2, T7, TP2	154	202	242	Forbiddn	30 L	B	40
Phenyl urea pesticides, liquid, toxic.	6.1	UN3002	I	6.1	T14, TP2, TP27	None	201	243	1 L	30 L	B	40
			II	6.1	T7, TP2	None	202	243	5 L	60 L	B	40
			III	6.1	T4, TP1	153	203	241	60 L	220 L	A	40
Phenylacetone, liquid	6.1	UN2470	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	26
Phenylacetyl chloride	8	UN2577	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	C	40
Phenylcarbamine chloride	6.1	UN1672	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP45	None	227	244	Forbiddn	Forbiddn	D	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age		
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other	
+	<i>m</i> -Phenylene diaminedipchlorate (dry).	Forbidden												
	Phenylenediamines ( <i>o</i> -, <i>m</i> -, <i>p</i> -)	6.1	UN1673	III	6.1	IB8, IP3, T7, TP1	153	213	240	100 kg	200 kg	A		
	Phenylhydrazine	6.1	UN2572	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40	
	Phenylmercuric acetate	6.1	UN1674	I	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A		
	Phenylmercuric compounds, n.o.s.	6.1	UN2026	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A		
	.....						None	212	242	25 kg	100 kg	A		
	.....						None	213	240	100 kg	200 kg	A		
	Phenylmercuric hydroxide	6.1	UN1894	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A		
	Phenylmercuric nitrate	6.1	UN1895	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A		
	Phenyltrichlorosilane	8	UN1804	II	8	A7, B6, IB2, N34, T7, TP2	None	202	242	Forbidden	30 L	C	40	
	Phosgene	2.3	UN1076	.....	2.3, 8	1, B7, B46	None	192	314	Forbidden	Forbidden	D	40	
	9-Phosphabicyclonanes or Cyclooctadiene phosphines.	4.2	UN2940	.....	4.2	A19, IB6, IP2	None	212	241	Forbidden	50 kg	A		
	Phosphine	2.3	UN2199	.....	.....	1	None	192	245	Forbidden	Forbidden	D	40	
	Phosphoric acid, liquid	8	UN1805	III	8	2.3, 2.1.	A7, IB3, IP3, N34, T4, TP1	154	203	241	5 L	60 L	A	
	Phosphoric acid, solid	8	UN1805	III	8	.....	IB8, IP3, T3, TP1	154	213	240	25 kg	100 kg	A	
Phosphoric acid triethylenimine, see Tris-(1-aziridinyl)phosphine oxide, solution.	.....													
Phosphoric anhydride, see Phosphorus pentoxide.	.....													
Phosphorus acid	8	UN2834	III	8	.....	IB8, IP3, T3, TP1	154	213	240	25 kg	100 kg	A	48	
Phosphorus, amorphous	4.1	UN1338	III	4.1	.....	A1, A19, B1, B9, B26, IB8, IP3	None	213	243	25 kg	100 kg	A	74	
Phosphorus bromide, see Phosphorus tribromide.	.....													
Phosphorus chloride, see Phosphorus trichloride.	.....													
Phosphorus heptasulfide, free from yellow or white phosphorus.	4.1	UN1339	II	4.1	.....	A20, IB4, N34	None	212	240	15 kg	50 kg	B	74	

Phosphorus oxybromide .....	8	UN1939	II	8	B8, IB8, IP2, IP4, N41, N43, T7, TP2	None	212	240	Forbiddn	50 kg	C	12, 40
Phosphorus oxybromide, molten	8	UN2576	II	8	B2, B8, IB1, N41, N43, T7, TP3, TP13	None	202	242	Forbiddn	Forbiddn	C	40
Phosphorus oxychloride .....	8	UN1810	II	8, 6.1	2, A7, B9, B14, B32, B74, B77, N34, T20, TP2, TP38, TP45	None	227	244	Forbiddn	Forbiddn	C	40
Phosphorus pentabromide .....	8	UN2691	II	8	A7, IB8, IP2, IP4, N34	154	212	240	Forbiddn	50 kg	B	12, 40
Phosphorus pentachloride .....	8	UN1806	II	8	A7, IB8, IP2, IP4, N34	None	212	240	Forbiddn	50 kg	C	40
Phosphorus pentafluoride .....	2.3	UN2198		2.3, 8	2, B9, B14	None	302, 304, 315	314, 315	Forbiddn	Forbiddn	D	40
Phosphorus pentasulfide, free from yellow or white phosphorus.	4.3	UN1340	II	4.3, 4.1	A20, B59, IB4	151	212	242	15 kg	50 kg	B	74
Phosphorus pentoxide .....	8	UN1807	II	8	A7, IB8, IP2, IP4, N34	154	212	240	15 kg	50 kg	A	.....
Phosphorus sesquisulfide, free from yellow or white phosphorus.	4.1	UN1341	II	4.1	A20, IB4, N34	None	212	240	15 kg	50 kg	B	74
Phosphorus tribromide .....	8	UN1808	II	8	A3, A6, A7, B2, B25, IB2, N34, N43, T7, TP2	None	202	242	Forbiddn	30 L	C	40
Phosphorus trichloride .....	6.1	UN1809	I	6.1, 8	2, B9, B14, B15, B32, B74, B77, N34, T20, TP2, TP13, TP38, TP45	None	227	244	Forbiddn	Forbiddn	C	40
Phosphorus trioxide .....	8	UN2578	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	12
Phosphorus trisulfide, free from yellow or white phosphorus.	4.1	UN1343	II	4.1	A20, IB4, N34	None	212	240	15 kg	50 kg	B	74
Phosphorus, white dry or Phosphorus, white, under water or Phosphorus white, in solution or Phosphorus yellow dry or Phosphorus, yellow, under water or Phosphorus, yellow, in solution.	4.2	UN1381	I	4.2, 6.1	B9, B26, N34, T9, TP3, TP31	None	188	243	Forbiddn	Forbiddn	E	
Phosphorus white, molten .....	4.2	UN2447	I	4.2, 6.1	B9, B26, N34, T21, TP3, TP7, TP26	None	188	243	Forbiddn	Forbiddn	D	.....
Phosphorus (white or red) and a chlorate, mixtures of. Phosphoryl chloride, see Phosphorus oxychloride.	Forbiddn											.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
(1)	Phthalic anhydride with more than .05 percent maleic anhy-dride.	8	UN2214	III	8	IB8, IP3, T4, TP3	154	213	240	25 kg	100 kg	A	
	Picolines	3	UN2313	III	3	B1, IB3, T4, TP1	150	203	242	60 L	220 L	A	40
	Picric acid, see Trinitrophenol, etc.												
	Picrite, see Nitroguanidine, etc ..												
	Picryl chloride, see Trinitrochlorobenzene.												
	Pine oil	3	UN1272	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	alpha-Pinene	3	UN2368	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Piperazine	8	UN2579	III	8	IB8, IP3, T4, TP1, TP30	154	213	240	25 kg	100	A	12
	Piperidine	8	UN2401	I	8, 3	T10, TP2	None	201	243	0.5 L	2.5 L	B	
	Pivaloyl chloride see Trimethylacetyl chloride.												
	Plastic molding compound in dough, sheet or extruded rope form evolving flammable vapor.	9	UN3314	III	9	32, IB8, IP6	155	221	221	100 kg	200 kg	A	85, 87
	Plastic solvent, n.o.s., see Flam-mable liquids, n.o.s..												
	Plastics, nitrocellulose-based, self-heating, n.o.s..	4.2	UN2006	III	4.2		None	213	None	Forbidden	Forbidden	C	
	Poisonous gases, n.o.s., see Compressed or liquefied gases, flammable or toxic, n.o.s..												
	Polyalkylamines, n.o.s., see Amines, etc.												
	Polychlorinated biphenyls, liquid	9	UN2315	II	9	9, 81, 140, IB3, T4, TP1	155	202	241	100 L	220 L	A	95
	Polychlorinated biphenyls, solid	9	UN2315	II	9	9, 81, 140, IB7	155	212	240	100 kg	200 kg	A	95
	Polyester resin kit	3	UN3269		3	40	152	225	None	5 kg	5 kg	B	
	Polyhalogenated biphenyls, liq-uid or Polyhalogenated terphenyls liquid.	9	UN3151	II	9	IB3	155	204	241	100 L	220 L	A	95



Polyhalogenated biphenyls, solid or terphenyls, solid.	9	UN3152	II	9	.....	IB8, IP2, IP4	155	204	241	100 kg	200 kg	A	95
Polymeric beads, expandable, evolving flammable vapor.	9	UN2211	III	9	.....	32, IB8, IP6, IP7	155	221	221	100kg	200kg	A	85, 87
Potassium	4.3	UN2257	I	4.3	.....	A19, A20, B27, IB1, IP1, N6, N34, T9, TP3, TP7, TP31	None	211	244	Forbidden	15 kg	D	.....
Potassium arsenate	6.1	UN1677	II	6.1	.....	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Potassium arsenite	6.1	UN1678	II	6.1	.....	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
Potassium bisulfite solution, see Bisulfites, aqueous solutions, n.o.s.	4.3	UN1870	I	4.3	.....	A19, N40	None	211	242	Forbidden	15 kg	E	.....
Potassium borohydride	5.1	UN1484	II	5.1	.....	IB8, IP4	152	212	242	5 kg	25 kg	A	56, 58, 106
Potassium bromate	Forbidden												
Potassium carbonyl	5.1	UN1485	II	5.1	.....	A9, IB8, IP4, N34	152	212	242	5 kg	25 kg	A	56, 58, 106
Potassium chlorate	5.1	UN2427	II	5.1	.....	A2, IB2, T4, TP1	152	202	241	1 L	5 L	B	56, 58, 106
Potassium chlorate, aqueous solution.	.....	.....	III	5.1	.....	A2, IB2, T4, TP1	152	203	241	2.5 L	30 L	B	56, 58, 69, 106
Potassium chlorate mixed with mineral oil, see Explosive, blasting, type C	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Potassium cuprocyanide	6.1	UN1679	II	6.1	.....	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	26
Potassium cyanide	6.1	UN1680	I	6.1	.....	B69, B77, IB7, IP1, N74, N75, T14, TP2, TP13	None	211	242	5 kg	50 kg	B	52
Potassium dichloro isocyanurate or Potassium dichloro-s-triazinetriene, see Dichloroisocyanuric acid or Dichloroisocyanuric acid salts etc.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Potassium dithionite or Potassium hydrosulfite.	4.2	UN1929	II	4.2	.....	A8, A19, A20, IB6, IP2	None	212	241	15 kg	50 kg	E	13
Potassium fluoride	6.1	UN1812	III	6.1	.....	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	26
Potassium fluoracetate	6.1	UN2628	I	6.1	.....	IB7, IP1	None	211	242	5 kg	50 kg	E	.....
Potassium fluorosilicate	6.1	UN2655	III	6.1	.....	IB8, IP3	153	213	240	100 kg	200 kg	A	26
Potassium hydrate, see Potassium hydroxide, solid, see Potassium hydrogen fluoride, see Potassium hydrogen difluoride.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Potassium hydrogen fluoride solution, see Corrosive liquid, n.o.s.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	Potassium hydrogen sulfate .....	8	UN2509	II	8	A7, IB8, IP2, IP4, N34	154	212	240	15 kg	50 kg	A	.....
	Potassium hydrogendifluoride, solid.	8	UN1811	II	8, 6.1	IB8, IP2, IP4, N3, N34, T7, TP2	154	212	240	15 kg	50 kg	A	25, 26, 40
	Potassium hydrogendifluoride, solution.	8	UN1811	II	8, 6.1	IB8, IP2, IP4, N3, N34, T7, TP2	154	202	243	1 L	30 L	A	25, 26, 40
	Potassium hydrosulfite, see Potassium dithionite.												
	Potassium hydroxide, liquid, see Potassium hydroxide solution.												
	Potassium hydroxide, solid .....	8	UN1813	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	.....
	Potassium hydroxide, solution .....	8	UN1814	III	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	A	.....
	Potassium hypochlorite, solution, see Hypochlorite solutions, etc.												
	Potassium, metal alloys .....	4.3	UN1420	I	4.3	A19, A20, B27, IB4, IP1	None	211	244	Forbidden	15 kg	D	.....
	Potassium metal, liquid alloy, see Alkali metal alloys, liquid, n.o.s.												
	Potassium metavanadate .....	6.1	UN2864	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	.....
	Potassium monoxide .....	8	UN2033	III	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	.....
	Potassium nitrate .....	5.1	UN1486	III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	.....
	Potassium nitrate and sodium nitrite mixtures.	5.1	UN1487	II	5.1	B78, IB8, IP4	152	212	240	5 kg	25 kg	A	56, 58
	Potassium nitrite .....	5.1	UN1488	II	5.1	IB8, IP4	152	212	242	5 kg	25 kg	A	56, 58
	Potassium perchlorate, solid .....	5.1	UN1489	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	106
	Potassium perchlorate, solution	5.1	UN1489	II	5.1	IB2, T4, TP1	152	202	242	1 L	5 L	A	56, 58, 106
	Potassium permanganate .....	5.1	UN1490	II	5.1	IB8, IP4	152	212	240	5 kg	25 kg	D	56, 58, 69, 106, 107
	Potassium peroxide .....	5.1	UN1491	I	5.1	A20, IB6, IP1, N34	None	211	None	Forbidden	15 kg	B	13, 75, 106
	Potassium persulfate .....	5.1	UN1492	III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	.....

Potassium phosphide .....	4.3	UN2012	I	4.3, 6.1.	A19, N40	None	211	None	Forbidden	15 kg	E	40, 85
Potassium selenate, see Selenates or Selenites.												
Potassium selenite, see Selenates or Selenites.												
Potassium sodium alloys .....	4.3	UN1422	I	4.3	A19, B27, IB4, IP1, N34, N40, T9, TP3, TP7, TP31	None	211	244	Forbidden	15 kg	D	
Potassium sulfide, anhydrous or Potassium sulfide with less than 30 percent water of crystallization.	4.2	UN1382	II	4.2	A19, A20, B16, IB6, IP2, N34	None	212	241	15 kg	50 kg	A	
Potassium sulfide, hydrated with not less than 30 percent water of crystallization.	8	UN1847	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	26
Potassium superoxide .....	5.1	UN2466	I	5.1	A20, IB6, IP1	None	211	None	Forbidden	15 kg	B	13, 75, 106
Powder cake, wetted or Powder paste, wetted with not less than 17 percent alcohol by mass.	1.1C	UN0433	II	1.1C		None	62	None	Forbidden	Forbidden	10	
Powder cake, wetted or Powder paste, wetted with not less than 25 percent water, by mass.	1.3C	UN0159	II	1.3C		None	62	None	Forbidden	Forbidden	10	
Powder paste, see Powder cake, etc.												
Powder, smokeless .....	1.1C	UN0160	II	1.1C		None	62	None	Forbidden	Forbidden		26E
Powder, smokeless .....	1.3C	UN0161	II	1.3C		None	62	None	Forbidden	Forbidden		26E
Power device, explosive, see Cartridges, power device.												
Primers, cap type .....	1.4S	UN0044	II	None		None	62	None	25 kg	100 kg	05	
Primers, cap type .....	1.1B	UN0377	II	1.1B		None	62	None	Forbidden	Forbidden	11	
Primers, cap type .....	1.4B	UN0378	II	1.4B		None	62	None	Forbidden	75 kg	06	
Primers, small arms, see Primers, cap type.												
Primers, tubular .....	1.3G	UN0319	II	1.3G		None	62	None	Forbidden	Forbidden	07	
Primers, tubular .....	1.4G	UN0320	II	1.4G		None	62	None	Forbidden	75 kg	06	
Printing ink, flammable or Printing ink related material (including printing ink thinning or reducing compound, flammable).	1.4S	UN0376	II	None		None	62	None	25 kg	100 kg	05	
	3	UN1210	I	3	T11, TP1, TP8	150	173	243	1 L	30 L	E	
			II	3	149, IB2, T4, TP1, TP8	150	173	242	5 L	60 L	B	
			III	3	B1, IB3, T2, TP1	150	173	242	60 L	220 L	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age		
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other	
(1)	<i>Projectiles, illuminating, see Am-munition, illuminating, etc.</i> <i>Projectiles, inert with tracer</i> ..... <i>Projectiles, inert, with tracer</i> ..... <i>Projectiles, inert, with tracer</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with burster or expel-ling charge</i> ..... <i>Projectiles, with bursting charge</i> ..... <i>Projectiles, with bursting charge</i> ..... <i>Projectiles, with bursting charge</i> ..... <i>Projectiles, with bursting charge</i> ..... <i>Projectiles, with bursting charge</i> ..... <i>Propadiene, stabilized</i> .....	1.4S	UN0345	II	1.4S ..									
		1.3G	UN0424	II	1.3G ..					25 kg	100 kg	01		
		1.4G	UN0425	II	1.4G ..					Forbidden	Forbidden	03		
		1.2D	UN0346	II	1.2D ..					Forbidden	Forbidden	03		
		1.4D	UN0347	II	1.4D ..					Forbidden	75 kg	02		
		1.2F	UN0426	II	1.2F ..					Forbidden	Forbidden	08		
		1.4F	UN0427	II	1.4F ..					Forbidden	Forbidden	08		
		1.2G	UN0434	II	1.2G ..					Forbidden	Forbidden	03		
		1.4G	UN0435	II	1.4G ..					Forbidden	75 kg	02		
		1.1F	UN0167	II	1.1F ..					Forbidden	Forbidden	08		
		1.1D	UN0168	II	1.1D ..					Forbidden	Forbidden	03		
		1.2D	UN0169	II	1.2D ..					Forbidden	Forbidden	08		
		1.2F	UN0324	II	1.2F ..					Forbidden	Forbidden	03		
		1.4D	UN0344	II	1.4D ..					Forbidden	75 kg	02		
		2.1	UN2200		2.1 ..				None ..	304	Forbidden	150 kg	B	40
			<i>Propadiene mixed with methyl acetylene, see Methyl acetylene and propadiene mixtures, stabilized.</i>											
			<i>Propane see also Petroleum gases, liquefied.</i>	2.1	UN1978		2.1 ..	19, T50		306	Forbidden	150 kg	E	40
			<i>Propanethiols</i> .....	3	UN2402	II	3 .....	IB2, T4, TP1, TP13		150	202	5 L	E	95, 102
			<i>n-Propanol or Propyl alcohol, normal.</i>	3	UN1274	II	3 .....	B1, IB2, T4, TP1		150	202	5 L	B	
			<i>Propellant, liquid</i> .....	1.3C	UN0495	III	3 .....	B1, IB3, T2, TP1		150	203	60 L	A	
			<i>Propellant, liquid</i> .....	1.1C	UN0497	II	1.3C ..	37		None	62	Forbidden	10	
	<i>Propellant, liquid</i> .....	1.1C	UN0498	II	1.1C ..	37		None	62	Forbidden	10			
	<i>Propellant, solid</i> .....	1.3C	UN0499	II	1.1C ..			None	62	Forbidden		26E		
	<i>Propellant, solid</i> .....	1.3C	UN0499	II	1.3C ..			None	62	Forbidden		26E		
	<i>Propellant, solid</i> .....	1.4C	UN0501		1.4C ..			None	62	Forbidden	A	24E		

Propionaldehyde	3	UN1275	II	3	IB2, T7, TP1	150	202	242	5 L	60 L	E	40
Propionic acid	8	UN1848	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	40
Propionic anhydride	8	UN2496	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	40
Propionitrile	3	UN2404	II	3, 6.1	IB2, T7, TP1, TP13	None	202	243	Forbidden	60 L	E	40
Propionyl chloride	3	UN1815	II	3, 8	IB1, T7, TP1	None	202	243	1 L	5 L	B	40
n-Propyl acetate	3	UN1276	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	40
Propyl alcohol, see Propanol												
n-Propyl benzene	3	UN2384	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	40
Propyl chloride see 1-Chloropropane.												
n-Propyl chloroformate	6.1	UN2740	I	6.1, 3, 8	2, A3, A6, A7, B9, B14, B32, B74, B77, N34, T20, TP2, TP13, TP38, TP44	None	227	244	Forbidden	Forbidden	B	21, 40, 100
Propyl formates	3	UN1281	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	40
n-Propyl isocyanate	6.1	UN2482	I	6.1, 3	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	D	40
Propyl mercaptan, see Propanethiols.												
n-Propyl nitrate	3	UN1865	II	3	IB2, IP7	150	202	None	5 L	60 L	D	40
Propylamine	3	UN1277	II	3, 8	IB2, N34, T7, TP1	None	202	243	1 L	5 L	E	40
Propylene see also Petroleum gases, liquefied.	2.1	UN1077		2.1	19, T50	306	304	314, 315	Forbidden	150 kg	E	40
Propylene chlorohydrin	6.1	UN2611	II	6.1, 3	IB2, T7, TP2, TP13	None	202	243	5 L	60 L	A	12, 40, 48
Propylene oxide	3	UN1280	I	3	A3, N34, T11, TP2, TP7	None	201	243	1 L	30 L	E	40
Propylene tetramer	3	UN2850	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	40
1,2-Propylenediamine	8	UN2258	II	8, 3	A3, A6, IB2, N34, T7, TP2	None	202	243	1 L	30 L	A	40
Propyleneimine, stabilized	3	UN1921	I	3, 6.1	A3, N34, T14, TP2, TP13	None	201	243	1 L	30 L	B	40
Propyltrichlorosilane	8	UN1816	II	8, 3	A7, B2, B6, IB2, N34, T7, TP2, TP13	None	202	243	Forbidden	30 L	C	40
Prussic acid, see Hydrogen cyanide.												
Pyrethroid pesticide, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN3350	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
Pyrethroid pesticide, liquid toxic			II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
Pyrethroid pesticide, liquid toxic	6.1	UN3352	I	6.1	T14, TP2, TP13, TP27	None	211	242	1 L	30 L	A	40

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Pyrethroid pesticide, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN3351	I	6.1, 3	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40
	Pyrethroid pesticide, solid, toxic		UN3349	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
	Pyridine		UN1282	III	6.1	IB8, IP2, IP4	153	212	242	25 kg	100 kg	A	40
	Pyridine perchlorate	Forbidden		II	3	IB8, IP3	153	213	240	100 kg	200 kg	A	40
	Pyrophoric liquid, inorganic, n.o.s.	4.2	UN3194	I	4.2	IB2, T4, TP2	None	202	242	5 L	60 L	B	21, 100
	Pyrophoric liquids, organic, n.o.s.	4.2	UN2845	I	4.2	B11, T22, TP2, TP7	None	181	244	Forbidden	Forbidden	D	18
	Pyrophoric metals, n.o.s., or Pyrophoric alloys, n.o.s.	4.2	UN1383	I	4.2	B11	None	187	242	Forbidden	Forbidden	D	
	Pyrophoric organometallic compound, water-reactive, n.o.s.	4.2	UN3203	I	4.2, 4.3	T21, TP2, TP7	None	187	242	Forbidden	Forbidden	D	18
	Pyrophoric solid, inorganic, n.o.s.	4.2	UN3200	I	4.2		None	187	242	Forbidden	Forbidden	D	
	Pyrophoric solids, organic, n.o.s.	4.2	UN2846	I	4.2	B2, IB2, T8, TP2, TP12	None	187	242	Forbidden	Forbidden	D	40
	Pyrosulfonyl chloride	8	UN1817	II	8		154	202	242	1 L	30 L	C	
	Pyroxylin solution or solvent, see Nitrocellulose.												
	Pyrolydine	3	UN1922	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	40
	Quebrachitol pentanitrate	Forbidden											
	Quicklime, see Calcium oxide												
	Quinoline	6.1	UN2656	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	12
	R 12, see Dichlorodifluoromethane.												
	R 12B1, see Chlorodifluorobromomethane.												

<i>R</i> 13, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorotrifluoromethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 13B1, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Bromotrifluoromethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 14, see Tetrafluoromethane ...	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 21, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Dichlorodifluoromethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 22, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorodifluoromethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 114, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Dichlorotetrafluoroethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 115, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chloropentafluoroethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 116, see Hexafluoroethane ...	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 124, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorotetrafluoroethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 133a, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorotrifluoroethane.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 152a, see Difluoroethane ...	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 500, see Dichlorodifluoro-	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
methane and difluoroethane,	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>etc.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 502, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorodifluoromethane and	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
chloropentafluoroethane mix-	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
ture, <i>etc.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
<i>R</i> 503, see	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Chlorotrifluoromethane and	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
trifluoromethane, <i>etc.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, excepted	7	UN2909	.....	.....	.....	None	.....	.....	.....	.....	.....	.....	.....
package—articles manufac-	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
tured from natural uranium or	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
depleted uranium or natural	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
thorium.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, excepted	7	UN2908	.....	.....	.....	Empty	.....	.....	.....	.....	.....	.....	.....
package—empty packaging.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, excepted	7	UN2911	.....	.....	.....	None	.....	.....	.....	.....	.....	.....	.....
package—instruments or arti-	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
cles.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, excepted	7	UN2910	.....	.....	.....	None	.....	.....	.....	.....	.....	.....	.....
package—limited quantity of	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
material.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, low spe-	7	UN2912	.....	.....	.....	7	A56, T5, TP4, W7	.....	.....	.....	.....	.....	.....
cific activity (LSA-I) non fissile	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
or fissile-excepted.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
Radioactive material, low spe-	7	UN3321	.....	.....	.....	7	A56, T5, TP4, W7	.....	.....	.....	.....	.....	.....
cific activity (LSA-II) non	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
fissile or fissile-excepted.	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions	Non-bulk	Bulk	Passenger aircraft/rail	Cargo air-craft only	Loca-tion	Other
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8A)	(8B)	(8C)	(9A)	(9B)	(10A)	(10B)
	Radioactive material, low specific activity (LSA-II) <i>non fissile or fissile excepted.</i>	7	UN3322		7	A56, T5, TP4, W7	421, 422, 428.	427	427			A	95, 129
	Radioactive material, surface contaminated objects (SCO-I or SCO-II) <i>non fissile or fissile excepted.</i>	7	UN2913		7	A56	421, 422, 428.	427	427			A	95
	Radioactive material, transported under special arrangement, <i>non fissile or fissile excepted.</i>	7	UN2919		7	A56, 139						A	95, 105
	Radioactive material, transported under special arrangement, fissile.	7	UN3331		7	A56, 139						A	95, 105
	Radioactive material, Type A package, fissile <i>non-special form.</i>	7	UN3327		7	A56, W7, W8	453	417	417			A	95, 105, 131
	Radioactive material, Type A package <i>non-special form, non fissile or fissile excepted.</i>	7	UN2915		7	A56, W7, W8		415	415			A	95, 130
	Radioactive material, Type A package, special form <i>non fissile or fissile excepted.</i>	7	UN3332		7	A56, W7, W8		415, 476.	415, 476.			A	95
	Radioactive material, Type A package, special form, fissile.	7	UN3333		7	A56, W7, W8	453	417	417			A	95, 105
	Radioactive material, Type B(M) package, fissile.	7	UN3329		7	A56	453	417	417			A	95, 105
	Radioactive material, Type B(M) package <i>non fissile or fissile excepted.</i>	7	UN2917		7	A56		416	416			A	95, 105
	Radioactive material, Type B(U) package, fissile.	7	UN3328		7	A56	453	417	417			A	95, 105
	Radioactive material, Type B(U) package <i>non fissile or fissile excepted.</i>	7	UN2916		7	A56		416	416			A	95, 105
	Radioactive material, uranium hexafluoride <i>non fissile or fissile excepted.</i>	7	UN2978		7, 8		423	420, 427.	420, 427.			A	95, 132



	7	UN2977	7, 8	453	417, 420, 240	417, 420, 240	Forbidden	Forbidden	A	95, 132
Radioactive material, uranium hexafluoride, fissile.		UN2977	7, 8	453	417, 420, 240	417, 420, 240	Forbidden	Forbidden	A	95, 132
Rags, oily	4.2	UN1856	4.2	151	213	213	Forbidden	Forbidden	A	
Railway torpedo, see Signals, railway track, explosive.										
Rare gases and nitrogen mixtures, compressed.	2.2	UN1981	2.2	306	302	302	75 kg	150 kg	A	
Rare gases and oxygen mixtures, compressed.	2.2	UN1980	2.2	306	302	302	75 kg	150 kg	A	
Rare gases mixtures, compressed.	2.2	UN1979	2.2	306	302	302	75 kg	150 kg	A	
RC										
see 318.										
Octafluorocyclobutane.										
RDX										
cyclooctamethylenetetranitramine, wetted or desensitized										
see RDX and HMX mixtures, wetted or desensitized.										
RDX and HMX mixtures, wetted with not less than 15 percent water by mass or RDX and HMX mixtures, desensitized with not less than 10 percent phlegmatizer by mass.	1.1D	UN0391	1.1D	None	62	None	Forbidden	Forbidden	10	
RDX and Octogen mixtures, wetted or desensitized see RDX and HMX mixtures, wetted or desensitized etc.										
RDX and HMX mixtures, wetted or desensitized etc.										
RDX, see Cyclooctamethylene trinitramine, etc.										
Receptacles, small, containing gas (gas cartridges) flammable, without release device, not refillable and not exceeding 1 L capacity.	2.1	UN2037	2.1	306	304	304	1 kg	15 kg	B	40
Receptacles, small, containing gas (gas cartridges) non-flammable, without release device, not refillable and not exceeding 1 L capacity.	2.2	UN2037	2.2	306	304	304	1 kg	15 kg	B	40
Red phosphorus, see Phosphorus, amorphous.										
Refrigerant gas R 404A	2.2	UN3337	2.2	T50	306	304	75 kg	150 kg	A	
Refrigerant gas R 407A	2.2	UN3338	2.2	T50	306	304	75 kg	150 kg	A	
Refrigerant gas R 407B	2.2	UN3339	2.2	T50	306	304	75 kg	150 kg	A	
Refrigerant gas R 407C	2.2	UN3340	2.2	T50	306	304	75 kg	150 kg	A	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
G	Refrigerant gases, n.o.s. ....	2.2	UN1078		2.2	T50	306	304	314, 315	75 kg	150 kg	A	
	Refrigerant gases, n.o.s. or Dis-persant gases, n.o.s..	2.1	NA1954		2.1	T50	306	304	314, 315	Forbidden	150 kg	D	40
	Refrigerating machines, con-taining flammable, non-toxic, liquefied gas.	2.1	UN3358		2.1		306	306	306	Forbidden	Forbidden	C	40
D	Refrigerating machines, con-taining non-flammable, non-toxic, liquefied or compressed gas or ammonia solution (UN2672).	2.2	UN2857		2.2	A53	306, 307	306	306, 307	450 kg	450 kg	A	
	Regulated medical waste .....	6.2	UN3291	II	6.2	A13	134, 197	197	197	No Limit	No Limit	A	40
E	Release devices, explosive .....	1.4S	UN0173	II	1.4S		None	62	None	25 kg	100 kg	05	
	Resin solution, flammable .....	3	UN1866	I	3	B52, T11, TP1, TP8	150	201	243	1 L	30 L	E	
				II	3	149, B52, IB2, T4, TP1, TP8	150	173	242	5 L	60 L	B	
F	Resorcinol .....	6.1	UN2876	III	6.1	B1, B52, IB3, T2, TP1	150	173	242	60 L	220 L	A	
	Rifle grenade, see Grenades, hand or rifle, etc.					IB8, IP3	153	213	240	100 kg	200 kg	A	
	Rifle powder, see Powder, smokeless (UN 0160).												
G	Rivets, explosive .....	1.4S	UN0174	II	1.4S		None	62	None	25 kg	100 kg	05	
	Road asphalt or tar liquid, see Tars, liquid, etc.												
	Rocket motors .....	1.3C	UN0186	II	1.3C	109	None	62	None	Forbidden	220 kg	03	
H	Rocket motors .....	1.1C	UN0280	II	1.1C	109	None	62	None	Forbidden	Forbidden	03	
	Rocket motors .....	1.2C	UN0281	II	1.2C	109	None	62	None	Forbidden	Forbidden	03	
	Rocket motors, liquid fueled .....	1.2J	UN0395	II	1.2J	109	None	62	None	Forbidden	Forbidden	04	23E
I	Rocket motors, liquid fueled .....	1.3J	UN0396	II	1.3J	109	None	62	None	Forbidden	Forbidden	04	23E
	Rocket motors with hypergolic liquids with or without an ex-pelling charge.	1.3L	UN0250	II	1.3L	109	None	62	None	Forbidden	Forbidden	08	8E, 14E, 15E

UN number	UN description	1.2L	109	None	62	None	Forbiddn	Forbiddn	Forbiddn	8E, 14E, 15E
UN0322	Rocket motors with hypergolic liquids with or without an expelling charge.	1.2L	109	None	62	None	Forbiddn	Forbiddn	Forbiddn	8E, 14E, 15E
UN0238	Rockets, line-throwing	1.2G		None	62	None	Forbiddn	Forbiddn	Forbiddn	07
UN0240	Rockets, line-throwing	1.3G		None	62	None	Forbiddn	Forbiddn	Forbiddn	75 kg
UN0453	Rockets, line-throwing	1.4G		None	62	None	Forbiddn	Forbiddn	Forbiddn	75 kg
UN0397	Rockets, liquid fueled with bursting charge.	1.1J		None	62	None	Forbiddn	Forbiddn	Forbiddn	04
UN0398	Rockets, liquid fueled with bursting charge.	1.2J		None	62	None	Forbiddn	Forbiddn	Forbiddn	04
UN0180	Rockets, with bursting charge	1.1F		None	62	None	Forbiddn	Forbiddn	Forbiddn	08
UN0181	Rockets, with bursting charge	1.1E		None	62	None	Forbiddn	Forbiddn	Forbiddn	03
UN0182	Rockets, with bursting charge	1.2E		None	62	None	Forbiddn	Forbiddn	Forbiddn	03
UN0295	Rockets, with bursting charge	1.2F		None	62	None	Forbiddn	Forbiddn	Forbiddn	08
UN0436	Rockets, with expelling charge	1.2C		None	62	None	Forbiddn	Forbiddn	Forbiddn	03
UN0437	Rockets, with expelling charge	1.3C		None	62	None	Forbiddn	Forbiddn	Forbiddn	03
UN0438	Rockets, with expelling charge	1.4C		None	62	None	Forbiddn	Forbiddn	Forbiddn	75 kg
UN0183	Rockets, with inert head	1.3C		None	62	None	Forbiddn	Forbiddn	Forbiddn	03
UN0502	Rockets, with inert head	1.2C		None	62	None	Forbiddn	Forbiddn	Forbiddn	1E, 5E
UN1286	Rosin oil	3	IB2, T4, TP1 IB1, IB3, T2, TP1 IB8, IP2, IP4	150 150 151	202 203 212	242 242 240	Forbiddn Forbiddn Forbiddn	Forbiddn Forbiddn Forbiddn	Forbiddn Forbiddn Forbiddn	220 L 60 L 50 kg
UN1345	Rubber scrap or Rubber shoddy, powdered or granulated, not exceeding 840 microns and rubber content exceeding 45%. Rubber solution	4.1		151	212	240	Forbiddn	Forbiddn	Forbiddn	
UN1287	Rubidium	3	149, IB2, T4, TP1, TP8	150	202	242	Forbiddn	Forbiddn	Forbiddn	60 L
UN1423	Rubidium	4.3	B1, IB3, T2, TP1 22, A7, A19, IB1, IP1, N34, N40, N45	150 None	203 211	242 242	Forbiddn	Forbiddn	Forbiddn	220 L 15 kg
UN2678	Rubidium hydroxide	8	IB8, IP2, IP4, T7, TP2	154	212	240	Forbiddn	Forbiddn	Forbiddn	50 kg
UN2677	Rubidium hydroxide solution	8	B2, IB2, T7, TP2 IB3, T4, TP1	154 154	202 203	242 241	Forbiddn Forbiddn	Forbiddn Forbiddn	Forbiddn Forbiddn	30 L 60 L
UN0190	Safety fuse, see Fuse, safety Samples, explosive, other than initiating explosives. Sand acid, see Fluorosilicic acid Seed cake, containing vegetable oil solvent extractions and expelled seeds, with not more than 10 percent of oil and when the amount of moisture is higher than 11 percent, with not more than 20 percent of oil and moisture combined. Seed cake with more than 1.5 percent oil and not more than 11 percent moisture.		113	None	62	None	Forbiddn	Forbiddn	Forbiddn	14
UN1386	Seed cake, containing vegetable oil solvent extractions and expelled seeds, with not more than 10 percent of oil and when the amount of moisture is higher than 11 percent, with not more than 20 percent of oil and moisture combined. Seed cake with more than 1.5 percent oil and not more than 11 percent moisture.	4.2	IB8, IP3, IP6, N7	None	213	241	Forbiddn	Forbiddn	Forbiddn	13
UN1386	Seed cake with more than 1.5 percent oil and not more than 11 percent moisture.	4.2	IB8, IP3, IP6, N7	None	213	241	Forbiddn	Forbiddn	Forbiddn	13

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
I	Seed cake with not more than 1.5 percent oil and not more than 11 percent moisture.	4.2	UN2217	III	None	IB8, IP3, IP6, N7	None	213	241	Forbidden	Forbidden	A	13
	Selenates or Selenites	6.1	UN2630	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	E	
	Selenic acid	8	UN1905	I	8	IB7, IP1, N34	None	211	242	Forbidden	25 kg	A	
	Selenium compound, n.o.s.	6.1	UN3283	I	6.1	IB7, IP1, T14, TP2, TP27	None	211	242	5 kg	50 kg	B	
				II	6.1	IB8, IP2, IP4, T11, TP2, TP27	None	212	242	25 kg	100 kg	B	
				III	6.1	IB8, IP3, T7, TP1, TP28	153	213	240	100 kg	200 kg	A	
	Selenium disulfide	6.1	UN2657	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Selenium hexafluoride	2.3	UN2194		2.3, 8		None	302	None	Forbidden	Forbidden	D	40
	Selenium nitride	Forbidden					None						
	Selenium oxychloride	8	UN2879	I	8, 6.1	A3, A6, A7, N34, T10, TP2, TP12, TP13	None	201	243	0.5 L	2.5 L	E	40
	Self-defense spray, aerosol, see Aerosols, etc.												
+ A	Self-defense spray, non-pressurized.	9	NA3334	III	9	A37	155	203	None	No limit	No limit	A	
D		4.2	UN3188	II	4.2, 8	IB2	None	202	243	1 L	5 L	C	
G	Self-heating liquid, corrosive, inorganic, n.o.s.	4.2	UN3185	III	4.2, 8	IB2	None	203	241	5 L	60 L	C	
				II	4.2, 8	IB2	None	202	243	1 L	5 L	C	
G	Self-heating liquid, inorganic, n.o.s.	4.2	UN3186	III	4.2, 8	IB2	None	203	241	5 L	60 L	C	
				II	4.2	IB2	None	202	242	1 L	5 L	C	
G	Self-heating liquid, organic, n.o.s.	4.2	UN3183	III	4.2	IB2	None	203	241	5 L	60 L	C	
				II	4.2	IB2	None	202	242	1 L	5 L	C	
G	Self-heating liquid, toxic, inorganic, n.o.s.	4.2	UN3187	III	4.2, 6.1	IB2	None	203	241	5 L	60 L	C	
				II	4.2, 6.1	IB2	None	202	243	1 L	5 L	C	
G	Self-heating liquid, toxic, or-ganic, n.o.s.	4.2	UN3184	III	4.2, 6.1	IB2	None	203	241	5 L	60 L	C	
				II	4.2, 6.1	IB2	None	202	243	1 L	5 L	C	

G	Self-heating solid, corrosive, inorganic, n.o.s.	4.2	UN3192	III	4.2, 6.1	IB2	None	203	241	5 L	60 L	C	.....
G	Self-heating solid, corrosive, organic, n.o.s.	4.2	UN3126	III	4.2, 8	IB5, IP2	None	212	242	15 kg	50 kg	C	.....
G	Self-heating solid, corrosive, organic, n.o.s.	4.2	UN3190	III	4.2, 8	IB8, IP3	None	213	242	25 kg	100 kg	C	.....
G	Self-heating solid, inorganic, n.o.s.	4.2	UN3088	III	4.2	IB6, IP2	None	212	241	25 kg	100 kg	C	.....
G	Self-heating solid, oxidizing, n.o.s.	4.2	UN3127	III	4.2	IB8, IP3	None	213	241	25 kg	100 kg	C	.....
G	Self-heating solid, toxic, inorganic, n.o.s.	4.2	UN3191	III	4.2, 5.1, 6.1	IB5, IP2	None	212	242	15 kg	50 kg	C	.....
G	Self-heating solid, toxic, organic, n.o.s.	4.2	UN3128	III	4.2, 6.1	IB8, IP3	None	213	242	25 kg	100 kg	C	.....
G	Self-propelled vehicle, see Engines or Batteries etc.	4.1	UN3221	II	4.1	53	None	224	None	Forbidden	Forbidden	D	.....
G	Self-reactive liquid type B, temperature controlled.	4.1	UN3231	II	4.1	53	None	224	None	Forbidden	Forbidden	D	61, 2, 61
G	Self-reactive liquid type C, temperature controlled.	4.1	UN3223	II	4.1	None	None	224	None	5 L	10 L	D	61, 2, 61
G	Self-reactive liquid type D, temperature controlled.	4.1	UN3225	II	4.1	None	None	224	None	5 L	10 L	D	61, 2, 61
G	Self-reactive liquid type E, temperature controlled.	4.1	UN3227	II	4.1	None	None	224	None	10 L	25 L	D	61, 2, 61
G	Self-reactive liquid type F, temperature controlled.	4.1	UN3237	II	4.1	T23	None	224	None	10 L	25 L	D	61, 2, 61
G	Self-reactive solid type B, temperature controlled.	4.1	UN3222	II	4.1	53	None	224	None	Forbidden	Forbidden	D	61, 2, 61
G	Self-reactive solid type C, temperature controlled.	4.1	UN3224	II	4.1	53	None	224	None	5 kg	10 kg	D	61, 2, 61
G	Self-reactive solid type D, temperature controlled.	4.1	UN3226	II	4.1	None	None	224	None	5 kg	10 kg	D	61, 2, 61
G	Self-reactive solid type D, temperature controlled.	4.1	UN3236	II	4.1	None	None	224	None	Forbidden	Forbidden	D	61, 2, 61

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
G	Self-reactive solid type E .....	4.1	UN3228	II	4.1		None	224	None	None	25 kg	D	61
G	Self-reactive solid type E, tem-perature controlled.	4.1	UN3238	II	4.1		None	224	None	None	Forbidden	D	2, 61
G	Self-reactive solid type F .....	4.1	UN3230	II	4.1		None	224	None	None	25 kg	D	61
G	Self-reactive solid type F, tem-perature controlled.	4.1	UN3240	II	4.1		None	224	None	None	Forbidden	D	2, 61
	Shale oil .....	3	UN1288	I	3	T11, TP1, TP8, TP27	None	201	243	243	30 L	B	
	.....					IB2, T4, TP1, TP8	150	202	242	242	60 L	B	
	.....					B1, IB3, T2, TP1	150	203	242	242	220 L	A	
	<i>Shaped charges, see Charges, shaped, etc.</i>												
	Signal devices, hand .....	1.4G	UN0191	II	1.4G		None	62	None	None	75 kg	06	
	Signal devices, hand .....	1.4S	UN0373	II	1.4S		None	62	None	None	100 kg	05	
	Signals, distress, ship .....	1.1G	UN0184	II	1.1G		None	62	None	None	Forbidden	07	
	Signals, distress, ship .....	1.3G	UN0195	II	1.3G		None	62	None	None	75 kg	07	
	<i>Signals, highway, see Signal de-vices, hand.</i>												
	Signals, railway track, explosive	1.1G	UN0192	II	1.1G		None	62	None	None	Forbidden	07	
	Signals, railway track, explosive	1.4S	UN0193	II	1.4S		None	62	None	None	100 kg	05	
	Signals, railway track, explosive	1.3G	UN0492	II	1.3G		None	62	None	None	Forbidden	07	
	Signals, railway track, explosive	1.4G	UN0493	II	1.4G		None	62	None	None	75 kg	06	
	<i>Signals, ship distress, water-ac-tivated, see Contrivances, water-activated, etc.</i>												
	Signals, smoke .....	1.1G	UN0196	II	1.1G		None	62	None	None	Forbidden	07	
	Signals, smoke .....	1.4G	UN0197	II	1.4G		None	62	None	None	75 kg	06	
	Signals, smoke .....	1.2G	UN0313	II	1.2G		None	62	None	None	Forbidden	07	
	Signals, smoke .....	1.3G	UN0487	II	1.3G		None	62	None	None	Forbidden	07	
	Silane .....	2.1	UN2203	II	2.1		None	302	None	None	Forbidden	E	40, 57, 104
	<i>Silicofluoric acid, see Fluorosilicic acid.</i>												
	<i>Silicon chloride, see Silicon tet-rachloride.</i>												
	Silicon powder, amorphous .....	4.1	UN1346	III	4.1	A1, IB8, IP3	None	213	240	240	100 kg	A	
	Silicon tetrachloride .....	8	UN1818	II	8	A3, A6, B2, B6, IB2, T7, TP2, TP7	154	202	242	242	30 L	C	40

UN number	Proper shipping name	Class	Division	Subdivision	Special provisions	Quantity	Forbidden	Forbidden	Forbidden	Quantity	Forbidden	Quantity
UN1859	Silicon tetrafluoride	2.3	Forbidden		2, 3, 8	None	302	None	None	2	None	40
UN1683	Silver acetylide (dry)	6.1	Forbidden		6.1	None	212	None	None	IB8, IP2, IP4	25 kg	100 kg
	Silver arsenite	6.1	Forbidden		6.1	None	212	None	None	IB8, IP2, IP4	25 kg	100 kg
	Silver azide (dry)	6.1	Forbidden		6.1	None	212	None	None	IB8, IP2, IP4	25 kg	100 kg
	Silver chlorite (dry)	6.1	Forbidden		6.1	None	212	None	None	IB8, IP2, IP4	25 kg	100 kg
	Silver cyanide	6.1	Forbidden		6.1	None	212	None	None	IB8, IP2, IP4	25 kg	100 kg
	Silver fulminate (dry)	5.1	Forbidden		5.1	152	212	152	None	IB8, IP4	5 kg	25 kg
	Silver nitrate	5.1	Forbidden		5.1	None	212	None	None	IB8, IP4	5 kg	25 kg
	Silver oxalate (dry)	5.1	Forbidden		5.1	None	212	None	None	IB8, IP4	5 kg	25 kg
	Silver picrate (dry)	5.1	Forbidden		5.1	None	212	None	None	IB8, IP4	5 kg	25 kg
	Silver picrate, wetted with not less than 30 percent water, by mass.	4.1	Forbidden		4.1	None	211	None	None	23	Forbidden	28, 36
	Sludge, acid	8	Forbidden		8	None	202	None	None	A3, A7, B2, IB2, N34, T8, TP2, TP12, TP28	30 L	14
	Smokeless powder for small arms (100 pounds or less).	4.1	Forbidden		4.1	None	171	None	None	16	Forbidden	7.3 kg
	Soda lime with more than 4 percent sodium hydroxide.	8	Forbidden		8	154	213	154	240	IB8, IP3	25 kg	100 kg
	Sodium	4.3	Forbidden		4.3	None	211	None	244	A7, A8, A19, A20, B9, B48, B88, IB4, IP1, N34, T9, TP3, TP7, TP31, TP46	15 kg	D
	Sodium aluminate, solid	8	Forbidden		8	154	213	154	240	IB8, IP3	25 kg	100 kg
	Sodium aluminate, solution	8	Forbidden		8	154	202	154	242	B2, IB2, T7, TP2	1 L	30 L
	Sodium aluminum hydride	4.3	Forbidden		4.3	154	203	154	241	IB3, T4, TP1	5 L	60 L
	Sodium ammonium vanadate	6.1	Forbidden		6.1	None	212	None	242	A8, A19, A20, IB1	Forbidden	50 kg
	Sodium arseniate	6.1	Forbidden		6.1	None	212	None	242	IB8, IP2, IP4	25 kg	100 kg
	Sodium arsenate	6.1	Forbidden		6.1	None	212	None	242	IB8, IP2, IP4	25 kg	100 kg
	Sodium arsenite, aqueous solutions.	6.1	Forbidden		6.1	None	202	None	243	IB2, T7, TP2	5 L	60 L
	Sodium arsenite, solid	6.1	Forbidden		6.1	153	203	153	241	IB3, T4, TP2	60 L	220 L
	Sodium azide	6.1	Forbidden		6.1	None	212	None	242	IB8, IP2, IP4	25 kg	100 kg
	Sodium bifluoride, see Sodium hydrogendifluoride.											
	Sodium bisulfite, solution, see Bisulfites, aqueous solutions, n.o.s.											
	Sodium borohydride	4.3	Forbidden		4.3	N40	211	None	242	None	Forbidden	15 kg

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							Excep-tions (8A)	Non-bulk (8B)	Bulk (8C)	Passenger aircraft/rail (9A)	Cargo air-craft only (9B)	Loca-tion (10A)	Other (10B)
(1)	Sodium borohydride and sodium hydroxide solution, with not more than 12 percent sodium borohydride and not more than 40 percent sodium hydroxide by mass.	8	UN3320	II	8	B2, IB2, N34, T7, TP2	154	202	242	1 L	30 L	A	26
	Sodium bromate	5.1	UN1494	III	8	B2, IB3, N34, T4, TP2	154	203	241	5 L	60 L	A	
	Sodium cacodylate	6.1	UN1688	II	5.1	IB8, IP4	152	212	242	5 kg	25 kg	A	56, 58, 106
	Sodium chlorate	5.1	UN1495	II	5.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	26
	Sodium chlorate, aqueous solution.	5.1	UN2428	II	5.1	A9, IB8, IP4, N34, T4, TP1	152	212	240	5 kg	25 kg	A	56, 58, 106
	Sodium chlorate mixed with dinitrotoluene, see Explosive blasting, type C.			III	5.1	A2, IB2, T4, TP1	152	202	241	1 L	5 L	B	56, 58, 106
	Sodium chlorite					A2, IB2, T4, TP1	152	203	241	2.5 L	30 L	B	56, 58, 69, 106
	Sodium chloroacetate	6.1	UN1496	II	5.1	A9, IB8, IP2, IP4, N34, T4, TP1	None	212	242	5 kg	25 kg	A	56, 58, 106
	Sodium cuprocyanide, solid	6.1	UN2316	I	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	
	Sodium cuprocyanide, solution	6.1	UN2317	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	26
	Sodium cyanide	6.1	UN1689	I	6.1	T14, TP2, TP13	None	201	243	1 L	30 L	B	26, 40
	Sodium dichloroisocyanurate or triazetrione, see Dichloroisocyanuric acid etc.					B69, B77, IB7, IP1, N74, N75, T14, TP2, TP13	None	211	242	5 kg	50 kg	B	52
	Sodium dinitro-o-cresolate, dry or wetted with less than 15 percent water, by mass.	1.3C	UN0234	II	1.3C		None	62	None	Forbidden	Forbidden	10	5E
	Sodium dinitro-o-cresolate, wetted, with not less than 10% water by mass.	4.1	UN3369	I	4.1	162, A8, A19, N41, N84	None	211	None	0.5 kg	0.5 kg	E	36



Sodium dinitro-o-cresolate, wetted with not less than 15 percent water, by mass.	4.1	UN1348	I	4.1, 6.1.	23, A8, A19, A20, N41	None	211	None	1 kg	15 kg	E	28, 36
Sodium dithionite or Sodium hydrosulfite.	4.2	UN1384	II	4.2	A19, A20, IB6, IP2	None	212	241	15 kg	50 kg	E	13
Sodium fluoride	6.1	UN1690	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	26
Sodium fluoracetate	6.1	UN2629	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	E	26
Sodium fluosilicate	6.1	UN2674	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	26
Sodium hydrate, see Sodium hydroxide, solid.												
Sodium hydride	4.3	UN1427	I	4.3	A19, N40	None	211	242	Forbidden	15 kg	E	12, 25, 26, 40
Sodium hydrogendifluoride, solid	8	UN2439	II	8	IB8, IP2, IP4, N3, N34	154	212	240	15 kg	50 kg	A	12, 25, 26, 40
Sodium hydrogendifluoride solution.	8	UN2439	II	8	IB8, IP2, IP4, N3, N34	154	202	242	1 L	30 L	A	12, 25, 26, 40
Sodium hydrosulfide, with less than 25 percent water of crystallization.	4.2	UN2318	II	4.2	A7, A19, A20, IB6, IP2	None	212	241	15 kg	50 kg	A	26
Sodium hydrosulfide, see Sodium dithionite.												
Sodium hydroxide, solid	8	UN1823	II	8	A7, IB8, IP2, IP4, T7, TP2	154	212	240	15 kg	50 kg	A	26
Sodium hydroxide solution	8	UN1824	II	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	
					B2, IB2, N34, T7, TP2	154	202	242	1 L	30 L	A	
					IB3, N34, T4, TP1	154	203	241	5 L	60 L	A	
Sodium hypochlorite, solution, see Hypochlorite solutions etc.												
Sodium metal, liquid alloy, see Alkali metal alloys, liquid, n.o.s.												
Sodium methylate	4.2	UN1431	II	4.2, 8	A19, IB5, IP2	None	212	242	15 kg	50 kg	B	
Sodium methylate solutions in alcohol.	3	UN1289	II	3, 8	IB2, T7, TP1, TP8	None	202	243	1 L	5 L	B	
Sodium monoxide	8	UN1825	III	3, 8	B1, IB3, T4, TP1	150	203	242	5 L	60 L	A	
Sodium nitrate	5.1	UN1498	III	8	IB8, IP2, IP4	154	212	240	15 kg	50 kg	A	
Sodium nitrate and potassium nitrate mixtures.	5.1	UN1499	III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	
Sodium nitrite	5.1	UN1500	III	5.1, 6.1.	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	56, 58
Sodium pentachlorophenate	6.1	UN2567	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	56, 58
Sodium perchlorate	5.1	UN1502	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	A	56, 58, 106
Sodium permanganate	5.1	UN1503	II	5.1	IB6, IP2	152	212	242	5 kg	25 kg	D	56, 58, 69, 106, 107

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
(1)	Sodium peroxide .....	5.1	UN1504	I	5.1 .....	A20, IB6, IP1, N34	None ...	211 .....	None ...	Forbidden	15 kg	B	13, 75, 106
	Sodium peroxoborate, anhy-drous.	5.1	UN3247	II	5.1 .....	IB8, IP4	152 .....	212 .....	240 .....	5 kg	25 kg	A	13, 25, 106
	Sodium persulfate .....	5.1	UN1505	III	5.1 .....	A1, IB8, IP3	152 .....	213 .....	240 .....	25 kg	100 kg	A	40, 85
	Sodium phosphide .....	4.3	UN1492	I	4.3, 6.1.	A19, N40	None ...	211 .....	None ...	Forbidden	15 kg	E	40, 85
	Sodium picramate, dry or wetted with less than 20 percent water, by mass.	1.3C	UN0235	II	1.3C ..		None ...	62 .....	None ...	Forbidden	Forbidden	10	5E
	Sodium picramate, wetted with not less than 20 percent water, by mass.	4.1	UN1349	I	4.1 .....	23, A8, A19, N41	None ...	211 .....	None ...	Forbidden	15 kg	E	28, 36
	Sodium picryl peroxide .....	Forbidden											
	Sodium potassium alloys, see Potassium sodium alloys.												
	Sodium selenate, see Selenates or Selenites.												
	Sodium sulfide, anhydrous or Sodium sulfide with less than 30 percent water of crys-tallization.	4.2	UN1385	II	4.2 .....	A19, A20, IB6, IP2, N34	None ...	212 .....	241 .....	15 kg	50 kg	A	
Sodium sulfide, hydrated with not less than 30 percent water.	8	UN1849	II	8 .....	IB8, IP2, IP4, T7, TP2	154 .....	212 .....	240 .....	15 kg	50 kg	A	26	
Sodium superoxide .....	5.1	UN2547	I	5.1 .....	A20, IB6, IP1, N34	None ...	211 .....	None ...	Forbidden	15 kg	E	13, 75, 106	
Sodium tetranitride .....	Forbidden												
Solids containing corrosive liq-uid, n.o.s..	8	UN3244	II	8 .....	49, IB5	154 .....	212 .....	240 .....	15 kg	50 kg	B	40	
Solids containing flammable liq-uid, n.o.s..	4.1	UN3175	II	4.1 .....	47, IB6, IP2	151 .....	212 .....	240 .....	15 kg	50 kg	B		
Solids containing toxic liquid, n.o.s..	6.1	UN3243	II	6.1 .....	48, IB2	None ...	212 .....	240 .....	25 kg	100 kg	B	40	
Sounding devices, explosive .....	1.2F	UN0204	II	1.2F ..		None ...	62 .....	None ...	Forbidden	Forbidden	08		
Sounding devices, explosive .....	1.1F	UN0296	II	1.1F ..		None ...	62 .....	None ...	Forbidden	Forbidden	08		
Sounding devices, explosive .....	1.1D	UN0374	II	1.1D ..		None ...	62 .....	None ...	Forbidden	Forbidden	07		
Sounding devices, explosive .....	1.2D	UN0375	II	1.2D ..		None ...	62 .....	None ...	Forbidden	Forbidden	07		
Spirits of salt, see Hydrochloric acid.													



§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifi- cation Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age		
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other	
D I	Substituted nitrophenol pes- ticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2780	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40	
	Substituted nitrophenol pes- ticides, liquid, toxic.	6.1	UN3014	II	3, 6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40	
	Substituted nitrophenol pes- ticides, liquid, toxic.	6.1	UN3014	I	6.1	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40	
	Substituted nitrophenol pes- ticides, liquid, toxic.	6.1	UN3014	II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40	
	Substituted nitrophenol pes- ticides, liquid, toxic, flammable flash point not less than 23 degrees C.	6.1	UN3013	III	6.1	IB3, T7, TP2, TP28	153	203	241	60 L	220 L	A	40	
	Substituted nitrophenol pes- ticides, liquid, toxic.	6.1	UN3013	I	6.1, 3	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	B	40	
	Substituted nitrophenol pes- ticides, solid, toxic.	6.1	UN2779	II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40	
	Substituted nitrophenol pes- ticides, solid, toxic.	6.1	UN2779	III	6.1, 3	B1, IB3, T7, TP2, TP28	153	203	242	60 L	220 L	A	40	
	Sucrose octanilate (dry)	Forbidden	6.1	UN2779	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
	Sulfamic acid	8	UN2967	II	6.1	IB8, IP2, IP4	IB8, IP3	None	212	242	25 kg	100 kg	A	40
Sulfur	9	NA1350	III	6.1	IB8, IP3	IB8, IP3	153	213	240	100 kg	200 kg	A	40	
Sulfur	4.1	UN1350	III	4.1	IB8, IP3, T1, TP1	IB8, IP3	154	213	240	25 kg	100 kg	A	19, 74	
Sulfur and chlorate, loose mix- tures of.	Forbidden	Forbidden	UN1350	III	4.1	IB8, IP3, T1, TP1	None	None	240	No limit	No limit	A	19, 74	
Sulfur chlorides	8	UN1828	I	8	5, A3, B10, B77, N34, T20, TP2, TP12	None	201	243	Forbidden	2.5 L	C	40		
Sulfur dichloride, see Sulfur chlorides.	2.3	UN1079	.....	2.3, 8	3, B14, T50, TP19	None	304	314, 315	Forbidden	25 kg	D	40		
Sulfur dioxide	2.3	UN1079	.....	2.3, 8	3, B14, T50, TP19	None	304	314, 315	Forbidden	25 kg	D	40		

Research and Special Programs Admin., DOT

\$ 172.101

Sulfur dioxide solution, see Sulfurous acid																									
Sulfur hexafluoride	2.2	UN1080										306								150 kg	A				
Sulfur, molten	9	NA2448	III	2.2																					
Sulfur, molten	4.1	UN2448	III	9	30, B3, T1, TP3																Forbidden	C		61	
Sulfur tetrafluoride	2.3	UN2418		4.1	30, B1, T1, TP3																Forbidden	C		74	
Sulfur trioxide, stabilized	8	UN1829	I	2.3, 8	2, A7, B9, B14, B32, B49, B74, B77, N34, T20, TP4, TP12, TP13, TP25, TP26, TP38, TP45																Forbidden	D		40	
				8, 6.1																	Forbidden	A		40	
Sulfuretted hydrogen, see Hydrogen sulfide.																									
Sulfuric acid, fuming with less than 30 percent free sulfur trioxide.	8	UN1831	I	8	A3, A7, B84, N34, T20, TP2, TP12, TP13																				
Sulfuric acid, fuming with 30 percent or more free sulfur trioxide.	8	UN1831	I	8, 6.1	2, A3, A6, A7, B9, B14, B32, B74, B77, B84, N34, T20, TP2, TP12, TP13																				
Sulfuric acid, spent	8	UN1832	II	8	A3, A7, B2, B83, B84, IB2, N34, T8, TP2, TP12																				
Sulfuric acid with more than 51 percent acid.	8	UN1830	II	8	A3, A7, B3, B83, B84, IB2, N34, T8, TP2, TP12																				
Sulfuric acid with not more than 51% acid.	8	UN2796	II	8	A3, A7, B2, B15, IB2, N6, N34, T8, TP2, TP12																				
Sulfuric and hydrofluoric acid mixtures, see Hydrofluoric and sulfuric acid mixtures.																									
Sulfuric anhydride, see Sulfur trioxide, stabilized.																									
Sulfurous acid	8	UN1833	II	8	B3, IB2, T7, TP2																				
Sulfury chloride	8	UN1834	I	8, 6.1	1, A3, B6, B9, B10, B14, B30, B74, B77, N34, T22, TP2, TP12, TP38, TP44																				
					4																				
Sulfury fluoride	2.3	UN2191		2.3																					
Tars, liquid including road asphalt and oils, bitumen and cut backs.	3	UN1999	II	3	149, B13, IB2, T3, TP3, TP29																				

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
D	Tear gas candles .....	6.1	UN1700	III	3	B1, B13, IB3, T1, TP3	150	203	242	60 L	220 L	A	40
	<i>Tear gas cartridges, see Ammu-nition, tear-producing, etc.</i>			II	6.1, 4.1		None	340	None	Forbidden	50 kg	D	40
	Tear gas devices with more than 2 percent tear gas sub-stances, by mass.	6.1	NA1693	I	6.1		None	340	None	Forbidden	Forbidden	D	40
G	<i>Tear gas devices, with not more than 2 percent tear gas sub-stances, by mass, see Aerosols, etc.</i>			II	6.1		None	340	None	Forbidden	Forbidden	D	40
	<i>Tear gas grenades, see Tear gas candles.</i>												
G	Tear gas substances, liquid, n.o.s.	6.1	UN1693	I	6.1		None	201	None	Forbidden	Forbidden	D	40
	Tear gas substances, solid, n.o.s.	6.1	UN1693	II	6.1	IB2	None	202	None	Forbidden	5 L	D	40
G	Tellurium compound, n.o.s.	6.1	UN3284	II	6.1	IB8, IP2, IP4 IB7, IP1, T14, TP2, TP27	None	212	None	Forbidden	25 kg	D	40
	Tellurium hexafluoride	2.3	UN2195	III	6.1	T11, TP2, TP27 IB8, IP3, T7, TP1, TP28	None	211	242	25 kg	50 kg	B	40
G	Terpene hydrocarbons, n.o.s.	3	UN2319	III	3	B1, IB3, T4, TP1, TP29	None	212	242	100 kg	100 kg	B	40
	Terpinolene	3	UN2541	III	3	B1, IB3, T2, TP1	None	302	None	Forbidden	Forbidden	D	40
G	Tetraazido benzene quinone	Forbidden	UN2504	III	6.1	IB3, T4, TP1	150	203	242	60 L	220 L	A	40
	1,1,2,2-Tetrachloroethane	6.1	UN1702	II	6.1	IB2, N36, T7, TP2	None	202	243	60 L	220 L	A	40
G	Tetrachloroethylene	6.1	UN1897	III	6.1	IB3, N36, T4, TP1	153	203	241	60 L	220 L	A	40
	Tetraethyl dithiopyrophosphate	6.1	UN1704	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	D	40

Tetraethyl silicate	3	UN1292	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Tetraethylammonium perchlorate (dry)	Forbidden											.....
Tetraethylenepentamine	8	UN2320	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	A	.....
1,1,1,2-Tetrafluoroethane or Refrigerant gas R 134a.	2.2	UN3159	.....	2.2	T50	306	304	314, 315	75 kg	150 kg	A	.....
Tetrafluoroethylene, stabilized	2.1	UN1081	.....	2.1		306	304	None	Forbidden	150 kg	E	40
Tetrafluoromethane, or Refrigerant gas R 14.	2.2	UN1982	.....	2.2		None	302	None	75 kg	150 kg	A	.....
1,2,3,6-Tetrahydrobenzaldehyde	3	UN2498	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Tetrahydrofuran	3	UN2056	II	3	IB2, T4, TP1	None	202	242	5 L	60 L	B	.....
Tetrahydrofurfurylamine	3	UN2943	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
Tetrahydrophthalic anhydrides with more than 0.05 percent of maleic anhydride.	8	UN2698	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	.....
1,2,3,6-Tetrahydropyridine	3	UN2410	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Tetrahydrothiophene	3	UN2412	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
Tetramethylammonium hydroxide.	8	UN1835	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	A	.....
Tetramethylene diperoxide dicarbamide	Forbidden											.....
Tetramethylsilane	3	UN2749	I	3	T14, TP2	None	201	243	Forbidden	30 L	D	.....
Tetranitro diglycerin	Forbidden											.....
Tetranitroaniline	1.1D	UN0207	II	1.1D		None	62	None	Forbidden	Forbidden	10	.....
Tetranitromethane	5.1	UN1510	I	5.1, 6.1.	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP44	None	227	None	Forbidden	Forbidden	D	40, 66, 106
2,3,4,6-Tetranitrophenol	Forbidden											.....
2,3,4,6-Tetranitrophenyl methyl nitramine	Forbidden											.....
2,3,4,6-Tetranitrophenyl nitramine	Forbidden											.....
Tetranitroresorcinol (dry)	Forbidden											.....
2,3,5,6-Tetranitroso-1,4-dinitrobenzene.	Forbidden											.....
2,3,5,6-Tetranitroso nitrobenzene (dry).	Forbidden											.....
Tetrapropylorthitanate	3	UN2413	III	3	B1, IB3, T4, TP1	150	203	242	60 L	220 L	A	.....
Tetrazene, see Guananyl nitrosaminoquanyltetrazene.	.....											.....
Tetrazine (dry)	Forbidden											.....
Tetrazol-1-acetic acid	1.4C	UN0407	II	1.4C		None	62	None	Forbidden	75 kg	09	.....
1H-Tetrazole	1.1D	UN0504	.....	1.1D		None	62	None	Forbidden	Forbidden	B	1E, 5E
Tetrazolyl azide (dry)	Forbidden											.....
Tetyl, see Trinitrophenylmethylnitramine.	.....											.....
Textile waste, wet	4.2	UN1857	III	4.2		151	213	240	Forbidden	Forbidden	A	.....
Thallium chlorate	5.1	UN2573	II	5.1, 6.1.	IB6, IP2	None	212	242	5 kg	25 kg	A	56, 58, 106

A, I, W

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age		
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other	
(1)	Thallium compounds, n.o.s. ....	6.1	UN1707	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A		
	Thallium nitrate .....	6.1	UN2727	II	6.1, 5.1	IB6, IP2	None	212	242	5 kg	25 kg	A		
	4-Thiopenental .....	6.1	UN2785	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	D	25, 49	
	Thioacetic acid .....	3	UN2436	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B		
	Thiocarbamate pesticide, liquid, flammable, toxic, flash point less than 23 degrees C. ....	3	UN2772	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40	
	Thiocarbamate pesticide, liquid, toxic, flammable, flash point not less than 23 degrees C. ....	6.1	UN3005	I	6.1, 3	T14, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40	
	Thiocarbamate pesticide, liquid, toxic. ....	6.1	UN3006	I	6.1	IB2, T11, TP2, TP13, TP27, TP28	None	202	243	5 L	60 L	B	40	
	Thiocarbamate pesticides, solid, toxic. ....	6.1	UN2771	III	6.1	IB3, T7, TP2, TP28	153	203	242	60 L	220 L	A	40	
	Thiophosgene. ....													
	Thiocarbonylchloride, see Thiophosgene. ....													
	Thioglycol .....	6.1	UN2966	II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	30 L	B	40	
	Thioglycolic acid .....	8	UN1940	II	8	IB3, T7, TP2, TP28	None	211	242	5 kg	50 kg	A	40	
	Thiolic acid .....	6.1	UN2936	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	40	
	Thionyl chloride .....	8	UN1836	I	8	IB8, IP3	153	213	240	100 kg	200 kg	A	40	
	Thiophene .....	3	UN2414	II	3	IB2, T7, TP2, A7, B2, IB2, N34, T7, TP2, IB2, T7, TP2, A7, B6, B10, N34, T10, TP2, TP12, TP13	150	202	243	5 L	60 L	B	40	



+	Thiophosgene .....	6.1	UN2474	II	6.1	2, A7, B9, B14, B32, B74, N33, N34, T20, TP2, TP38, TP45	None	227	244	Forbidden	Forbidden	B	26, 40
	Thiophosphoryl chloride .....	8	UN1837	II	8	A3, A7, B2, B8, B25, IB2, N34, T7, TP2	None	202	242	Forbidden	30 L	C	40
	Thiourea dioxide .....	4.2	UN3341	II	4.2	IB6, IP2	None	212	241	15 kg	50 kg	D	.....
	<i>Tin chloride, fuming, see Stannic chloride, anhydrous.</i>	.....	.....	.....	4.2	.....	None	213	241	25 kg	100 kg	D	.....
	<i>Tin perchloride or Tin tetrachloride, see Stannic chloride, anhydrous.</i>	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....
	Tinctures, medicinal .....	3	UN1293	II	3	IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B	.....
	.....	.....	.....	.....	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	<i>Tinning flux, see Zinc chloride</i>	.....	.....	.....	4.2	IB8, IP3	None	213	241	25 kg	100 kg	A	.....
	Titanium disulphide .....	4.2	UN3174	III	4.2	A19, A20, IB4, N34	None	212	241	15 kg	50 kg	E	.....
	Titanium hydride .....	4.1	UN1871	II	4.1	.....	None	211	242	Forbidden	Forbidden	D	.....
	Titanium powder, dry .....	4.2	UN2546	I	4.2	A19, A20, IB6, IP2, N5, N34	None	212	241	15 kg	50 kg	D	.....
	.....	.....	.....	.....	4.2	.....	None	213	241	25 kg	100 kg	D	.....
	Titanium powder, wetted with not less than 25 percent water (a visible excess of water must be present) (a) mechanically produced, particle size less than 53 microns; (b) chemically produced, particle size less than 840 microns	.....	.....	.....	4.1	A19, A20, IB6, IP2, N34	None	212	240	15 kg	50 kg	E	.....
	Titanium sponge granules or Titanium sponge powders .....	4.1	UN2878	III	4.1	A1, IB8, IP3	None	213	240	25 kg	100 kg	D	.....
	Titanium tetrachloride .....	8	UN1838	II	8, 6.1	2, A3, A6, B7, B9, B14, B32, B74, B77, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	C	40
	.....	.....	.....	.....	8	A7, IB8, IP2, IP4, N34	154	212	240	15 kg	50 kg	A	40
	Titanium trichloride mixtures .....	8	UN2869	III	8	A7, IB8, IP3, N34	154	213	240	25 kg	100 kg	A	40
	Titanium trichloride, pyrophoric or Titanium trichloride mixtures, pyrophoric. TNT mixed with aluminum, see Tritonal.	4.2	UN2441	I	4.2, 8	A7, A8, A19, A20, N34	None	181	244	Forbidden	Forbidden	D	40
	TNT, see Trinitrotoluene, etc .....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
+	Toluene	3	UN1294	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	.....
	Toluene dithiocyanate	6.1	UN2078	II	6.1	IB2, T7, TP2, TP13	None	202	243	5 L	60 L	D	25, 40
+	<i>Toluene sulfonic acid, see Alkyl, or Aryl sulfonic acid etc.</i>	6.1	UN1708	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	.....
	Toluidines liquid	6.1	UN1708	II	6.1	IB8, IP2, IP4, T7, TP2	None	212	242	25 kg	100 kg	A	.....
+	Toluidines solid	6.1	UN1709	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	.....
	2,4-Toluylenediamine or 2,4-Toluenediamine	6.1	UN1709	III	6.1	IB8, IP3, T4, TP1	153	213	240	100 kg	200 kg	A	.....
	Torpedoes, liquid fueled, with inert head.	1.3J	UN0450	II	1.3J	.....	.....	62	None	Forbidden	Forbidden	04	23E
	Torpedoes, liquid fueled, with or without bursting charge.	1.1J	UN0449	II	1.1J	.....	.....	62	None	Forbidden	Forbidden	04	23E
	Torpedoes with bursting charge	1.1E	UN0329	II	1.1E	.....	.....	62	None	Forbidden	Forbidden	03	.....
	Torpedoes with bursting charge	1.1F	UN0330	II	1.1F	.....	.....	62	None	Forbidden	Forbidden	08	.....
G	Torpedoes with bursting charge	1.1D	UN0451	II	1.1D	.....	.....	62	None	Forbidden	Forbidden	03	.....
	Toxic liquid, corrosive, inorganic, n.o.s.	6.1	UN3289	I	6.1, 8	T14, TP2, TP13, TP27	None	201	243	0.5 L	2.5 L	A	.....
G	Toxic liquid, corrosive, inorganic, n.o.s. Inhalation Hazard, Packing Group I, Zone A.	6.1	UN3289	II	6.1, 8	IB2, T11, TP2, TP27	None	202	243	1 L	30 L	A	.....
	Toxic liquid, corrosive, inorganic, n.o.s. Inhalation Hazard, Packing Group I, Zone A.	6.1	UN3289	I	6.1, 8	1, B9, B14, B30, B72, T22, TP2, TP13, TP27, TP38, TP44	None	226	244	Forbidden	Forbidden	B	40
G	Toxic liquid, corrosive, inorganic, n.o.s. Inhalation Hazard, Packing Group I, Zone B.	6.1	UN3289	I	6.1, 8	2, B9, B14, B32, B74, T20, TP2, TP13, TP27, TP38, TP45	None	227	244	Forbidden	Forbidden	B	40
	Toxic liquid, inorganic, n.o.s. ....	6.1	UN3287	I	6.1	T14, TP2, TP13, TP27	None	201	243	1 L	30 L	A	.....
G	Toxic liquid, inorganic, n.o.s. In- halation Hazard, Packing Group I, Zone A.	6.1	UN3287	II	6.1	IB2, T11, TP2, TP27	None	202	243	5 L	60 L	A	.....
	Toxic liquid, inorganic, n.o.s. In- halation Hazard, Packing Group I, Zone A.	6.1	UN3287	III	6.1	IB3, T7, TP1, TP28	153	203	241	60 L	220 L	A	.....
G	Toxic liquid, inorganic, n.o.s. In- halation Hazard, Packing Group I, Zone A.	6.1	UN3287	I	6.1	1, B9, B14, B30, B72, T22, TP2, TP13, TP27, TP38, TP44	None	226	244	Forbidden	Forbidden	B	40

G	Toxic liquid, inorganic, n.o.s. Inhalation hazard, Packing Group I, Zone B.	6.1	UN3287	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP27, TP38, TP45	None	227	244	Forbidden	Forbidden	40
G	Toxic liquids, corrosive, organic, n.o.s.	6.1	UN2927	I	6.1, 8	T14, TP2, TP27	None	201	243	2.5 L	0.5 L	40
G	Toxic liquids, corrosive, organic, n.o.s., inhalation hazard, Packing Group I, Zone A.	6.1	UN2927	II	6.1, 8	IB2, T11, TP2, TP27	None	202	243	30 L	1 L	40
G	Toxic liquids, corrosive, organic, n.o.s., inhalation hazard, Packing Group I, Zone B.	6.1	UN2927	I	6.1, 8	1, B9, B14, B30, B72, T22, TP2, TP13, TP27, TP38, TP44	None	227	244	Forbidden	Forbidden	40
G	Toxic liquids, flammable, organic, n.o.s.	6.1	UN2929	I	6.1, 3	T14, TP2, TP13, TP27	None	201	243	30 L	1 L	40
G	Toxic liquids, flammable, organic, n.o.s., inhalation hazard, Packing Group I, Zone A.	6.1	UN2929	II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	60 L	5 L	40
G	Toxic liquids, flammable, organic, n.o.s., inhalation hazard, Packing Group I, Zone B.	6.1	UN2929	I	6.1, 3	1, B9, B14, B30, B72, T22, TP2, TP13, TP27, TP38, TP44	None	226	244	Forbidden	Forbidden	40
G	Toxic liquids, organic, n.o.s.	6.1	UN2810	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP27, TP38, TP45	None	227	244	Forbidden	Forbidden	40
G	Toxic liquids, organic, n.o.s.	6.1	UN2810	I	6.1	T14, TP2, TP13, TP27	None	201	243	30 L	1 L	40
G	Toxic liquids, organic, n.o.s., Inhalation hazard, Packing Group I, Zone A.	6.1	UN2810	II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	60 L	5 L	40
G	Toxic liquids, organic, n.o.s., Inhalation hazard, Packing Group I, Zone B.	6.1	UN2810	III	6.1	IB3, T7, TP1, TP28	153	203	241	220 L	60 L	40
G	Toxic liquids, organic, n.o.s., Inhalation hazard, Packing Group I, Zone A.	6.1	UN2810	I	6.1	1, B9, B14, B30, B72, T22, TP2, TP13, TP27, TP38, TP44	None	226	244	Forbidden	Forbidden	40
G	Toxic liquids, organic, n.o.s., Inhalation hazard, Packing Group I, Zone B.	6.1	UN2810	I	6.1	2, B9, B14, B32, B74, T20, TP2, TP13, TP27, TP38, TP45	None	227	244	Forbidden	Forbidden	40
G	Toxic liquids, oxidizing, n.o.s.	6.1	UN3122	I	6.1, 5.1	TP38, TP45 A4	None	201	243	2.5 L	Forbidden	.....
G	Toxic liquids, oxidizing, n.o.s., Inhalation hazard, Packing Group I, Zone A.	6.1	UN3122	II	6.1, 5.1	IB2	None	202	243	5 L	1 L	.....
G	Toxic liquids, oxidizing, n.o.s., Inhalation hazard, Packing Group I, Zone A.	6.1	UN3122	I	6.1, 5.1	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None	226	244	Forbidden	Forbidden	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age		
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other	
G	Toxic liquids, oxidizing, n.o.s. In-halation Hazard, Packing Group I, Zone B.	6.1	UN3122	I	6.1, 5.1.	2, B9, B14, B32, T20, TP2, TP13, TP38, TP44	None ...	227	244	244	Forbidden	Forbidden	C	.....
G	Toxic liquids, water-reactive, n.o.s.	6.1	UN3123	I	6.1, 4.3.	A4	None ...	201	243	243	Forbidden	1 L	E	40
G	Toxic liquids, water-reactive, n.o.s. Inhalation hazard, pack-ing group I, Zone A.	6.1	UN3123	II	6.1, 4.3.	IB2	None ...	202	243	243	1 L	5 L	E	40
G	Toxic liquids, water-reactive, n.o.s. Inhalation hazard, pack-ing group I, Zone B.	6.1	UN3123	I	6.1, 4.3.	1, B9, B14, B30, B72, T22, TP2, TP13, TP38, TP44	None ...	226	244	244	Forbidden	Forbidden	E	40
G	Toxic solid, corrosive, inorganic, n.o.s.	6.1	UN3290	I	6.1, 8	2, B9, B14, B32, B74, T20, TP2, TP13, TP38, TP44	None ...	211	242	242	Forbidden	Forbidden	E	40
G	Toxic solid, inorganic, n.o.s.	6.1	UN3288	II	6.1, 8	IB7	None ...	212	242	242	1 kg	25 kg	A	.....
G	Toxic solids, corrosive, organic, n.o.s.	6.1	UN2928	III	6.1, 8	IB6, IP2	None ...	212	242	242	15 kg	50 kg	A	.....
G	Toxic solids, flammable, organic, n.o.s.	6.1	UN2930	II	6.1, 4.1.	IB8, IP2, IP4	None ...	211	242	242	5 kg	100 kg	A	.....
G	Toxic solids, organic, n.o.s.	6.1	UN2811	III	6.1, 4.1.	IB7	None ...	212	242	242	25 kg	100 kg	A	.....
G	Toxic solids, oxidizing, n.o.s.	6.1	UN3086	I	6.1, 5.1.	IB8, IP2, IP3	None ...	213	240	240	100 kg	200 kg	A	.....
G	Toxic solids, self-heating, n.o.s.	6.1	UN3124	II	6.1, 4.2.	IB6, IP2	None ...	212	242	242	1 kg	25 kg	C	.....
G	Toxic solids, self-heating, n.o.s.	6.1	UN3124	I	6.1, 4.2.	A5	None ...	211	242	242	15 kg	50 kg	C	.....
G	Toxic solids, self-heating, n.o.s.	6.1	UN3124	II	6.1, 4.2.	IB6, IP2	None ...	212	242	242	5 kg	15 kg	D	40
G	Toxic solids, self-heating, n.o.s.	6.1	UN3124	II	6.1, 4.2.	IB6, IP2	None ...	212	242	242	15 kg	50 kg	D	40

G	Toxic solids, water-reactive, n.o.s.	6.1	UN3125	I	6.1, 4.3	A5	None	211	242	5 kg	15 kg	D	40
G	Toxins, from living sources, liquid, n.o.s.	6.1	UN3172	II	6.1, 4.3	IB6, IP2	None	212	242	15 kg	50 kg	D	40
G	Toxins, from living sources, solid, n.o.s.	6.1	UN3172	III	6.1	141	None	201	243	1 L	30 L	B	40
D	Toy Caps	1.4S	NA0337	III	6.1	141	None	202	243	5 L	60 L	B	40
	Tracers for ammunition	1.3G	UN0212	III	6.1	141	None	203	241	60 L	220 L	A	40
	Tracers for ammunition	1.4G	UN0306	III	6.1	141	None	211	243	5 kg	50 kg	B	40
	Tractors, see Vehicle, etc			II	6.1	141	None	212	243	25 kg	100 kg	B	
	Tri-(p-nitroxyethyl) ammonium nitrate	Forbidden		III	6.1	141	None	213	241	100 kg	200 kg	A	
	Triallyl borate	6.1	UN2609	III	6.1	IB3	153	203	241	60 L	220 L	A	13
	Triallylamine	3	UN2610	III	3, 8	B1, IB3, T4, TP1	None	203	242	5 L	60 L	A	40
	Triazine pesticides, liquid, flammable, toxic, flash point less than 23 degrees C.	3	UN2764	I	3, 6.1	T14, TP2, TP13, TP27	None	201	243	Forbidden	30 L	B	40
	Triazine pesticides, liquid, toxic	6.1	UN2998	II	6.1	IB2, T11, TP2, TP13, TP27	None	202	243	1 L	60 L	B	40
	Triazine pesticides, liquid, toxic, flammable, flash point not less than 23 degrees C.	6.1	UN2997	III	6.1	IB2, T11, TP2, TP13, TP27	153	203	241	60 L	220 L	A	40
	Triazine pesticides, solid, toxic	6.1	UN2763	II	6.1, 3	IB2, T11, TP2, TP13, TP27	None	202	243	5 L	60 L	B	40
	Tributylamine	6.1	UN2542	III	6.1, 3	IB3, T7, TP2, TP28	153	203	242	60 L	220 L	A	40
	Tributylphosphane	6.1	UN2542	I	6.1	IB7, IP1	None	211	242	5 kg	50 kg	A	40
	Trichloro-s-triazetrone dry, with more than 39 percent available chlorine, see Trichloroacetic acid, dry.	4.2	UN3254	III	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	40
	Trichloroacetic acid	8	UN1839	I	8	IB8, IP3	153	213	240	100 kg	200 kg	A	40
	Trichloroacetic acid, solution	8	UN2564	II	8	IB2, T7, TP2	None	202	243	5 L	60 L	A	
				II	8	A7, IB8, IP2, IP4, N34	154	212	240	15 kg	50 kg	A	
				II	8	A3, A6, A7, B2, IB2, N34, T7, TP2	154	202	242	1 L	30 L	B	

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§ 173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
+	Trichloroacetyl chloride	8	UN2442	II	8, 6.1	A3, A6, A7, IB3, N34, T4, TP1 2, A3, A7, B9, B14, B32, B74, N34, T20, TP2, TP38, TP45	None	227	244	Forbidden	Forbidden	D	40
	Trichlorobenzenes, liquid	6.1	UN2321	III	6.1	IB3, T4, TP1	153	203	241	60 L	220 L	A	.....
	Trichlorobutene	6.1	UN2322	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	25, 40
	1,1,1-Trichloroethane	6.1	UN2831	III	6.1	IB3, N36, T4, TP1	153	203	241	60 L	220 L	A	40
	Trichloroethylene	6.1	UN1710	III	6.1	IB3, N36, T4, TP1	153	203	241	60 L	220 L	A	40
	Trichloroisocyanuric acid, dry	5.1	UN2468	II	5.1	IB8, IP4	152	212	240	5 kg	25 kg	A	13
	Trichloromethyl perchlorate	Forbidden											
	Trichlorosilane	4.3	UN1295	I	4.3, 3, 8	A7, N34, T14, TP2, TP7, TP13	None	201	244	Forbidden	Forbidden	D	21, 28, 40, 49, 100
	Tricresyl phosphate, with more than 3 percent ortho isomer	6.1	UN2574	II	6.1	A3, IB2, N33, N34, T7, TP2	None	202	243	5 L	60 L	A	.....
	Triethyl phosphite	3	UN2323	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	.....
	Triethylamine	3	UN1296	II	3, 8	IB2, T7, TP1	None	202	243	1 L	5 L	B	40
	Triethylenetetramine	8	UN2559	II	8	B2, IB2, T7, TP2	154	202	242	1 L	30 L	B	40
	Trifluoroacetic acid	8	UN2699	I	8	A3, A6, A7, B4, N3, N34, T10, TP2, TP12	None	201	243	0.5 L	2.5 L	B	12, 40
	Trifluoroacetyl chloride	2.3	UN3057	.....	2.3, 8	2, B7, B9, B14, T50, TP21	None	304	314, 315	Forbidden	Forbidden	D	40
	Trifluorochloroethylene, stabilized	2.3	UN1082	.....	2.3	3, B14, T50	None	304	314, 315	Forbidden	Forbidden	D	40
	1,1,1-Trifluoroethane or Refrigerant gas, R143a	2.1	UN2035	.....	2.1	T50	306	304	314, 315	Forbidden	150 kg	B	40
	Trifluoromethane or Refrigerant gas R 23	2.2	UN1984	.....	2.2		306	304	314, 315	Forbidden	150 kg	A	.....
	Trifluoromethane, refrigerated liquid	2.2	UN3136	.....	2.2	T75, TP5	306	None	314, 315	50 kg	500 kg	D	.....
	2-Trifluoromethylaniline	6.1	UN2942	III	6.1	IB3	153	203	241	60 L	220 L	A	.....
	3-Trifluoromethylaniline	6.1	UN2948	II	6.1	IB2, T7, TP2	None	202	243	5 L	60 L	A	40
	Triformoxime trinitrate	Forbidden											
	Trisobutylene	3	UN2324	III	3	B1, IB3, T4, TP1	150	203	242	60 L	220 L	A	.....

Trisopropyl borate	3	UN2616	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	40
Trimethoxysilane	6.1	NA9269	I	6.1, 3	B1, IB3, T2, TP1 2, B9, B14, B32, B74, T20, TP4, TP12, TP13, TP38, TP45	None	203	242	60 L	220 L	40
Trimethyl borate	3	UN2416	II	3	IB2, T7, TP1	150	202	242	5 L	60 L	
Trimethyl phosphite	3	UN2329	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	
1,3,5-Trimethyl-2,4,6-trinitrobenzene.	Forbidden										
Trimethylacetyl chloride	6.1	UN2438	I	6.1, 8, 3	2, A3, A6, A7, B3, B9, B14, B32, B74, N34, T20, TP2, TP13, TP38, TP45	None	227	244	Forbidden	Forbidden	25, 40
Trimethylamine, anhydrous	2.1	UN1063		2.1	T50	306	304	314, 315	Forbidden	150 kg	40
Trimethylamine, aqueous solutions with not more than 50 percent trimethylamine by mass.	3	UN1297	I	3, 8	T11, TP1	None	201	243	0.5 L	2.5 L	40, 41
1,3,5-Trimethylbenzene	3	UN2325	III	3, 8	B1, IB2, T7, TP1	None	202	243	1 L	5 L	40, 41
Trimethylchlorosilane	3	UN1298	II	3, 8	B1, IB3, T7, TP1	None	203	242	5 L	60 L	40, 41
Trimethylcyclohexylamine	8	UN2326	III	8	A3, A7, B77, IB2, N34, T7, TP2, TP13	None	202	243	1 L	5 L	40
Trimethylene dipchlorate.	Forbidden										
Trimethylhexamethylene diisocyanate.	6.1	UN2328	III	6.1	IB3, T4, TP2, TP13	153	203	241	60 L	220 L	
Trimethylhexamethylenediamine	8	UN2327	III	8	IB3, T4, TP1	154	203	241	5 L	60 L	
Trimethyl nitromethane trinitrate.	Forbidden										
Trinitro-meta-cresol	1.1D	UN0216	II	1.1D		None	62	None	Forbidden	Forbidden	5E
2,4,6-Trinitro-1,3-diazobenzene	Forbidden										
2,4,6-Trinitro-1,3,5-triazolo benzene (dry).	Forbidden										
Trinitroacetic acid	Forbidden										
Trinitroacetone	Forbidden										
Trinitroacetone trinitrate	Forbidden										
Trinitroamine cobalt	1.1D	UN0153	II	1.1D		None	62	None	Forbidden	Forbidden	10
Trinitroaniline or Picramide	1.1D	UN0213	II	1.1D		None	62	None	Forbidden	Forbidden	10
Trinitroanisole	1.1D	UN0214	II	1.1D		None	62	None	Forbidden	Forbidden	10
Trinitrobenzene, dry or wetted with less than 30 percent water, by mass.	4.1	UN3367	I	4.1	162, A8, A19, N41, N84	None	211	None	0.5 kg	0.5 kg	36
Trinitrobenzene, wetted, with not less than 10% water by mass.											

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Trinitrobenzene, wetted with not less than 30 percent water, by mass.	4.1	UN1354	I	4.1	23, A2, A8, A19, N41	None	211	None	0.5 kg	0.5 kg	E	28
	Trinitrobenzenesulfonic acid	1.1D	UN0386	II	1.1D		None	62	None	Forbidden	Forbidden	10	5E
	Trinitrobenzoic acid, dry or wetted with less than 30 percent water, by mass.	1.1D	UN0215	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Trinitrobenzoic acid, wetted, with not less than 10% water by mass.	4.1	UN3368	I	4.1	162, A8, A19, N41, N84	None	211	None	0.5 kg	0.5 kg	E	36
	Trinitrobenzoic acid, wetted with not less than 30 percent water, by mass.	4.1	UN1355	I	4.1	23, A2, A8, A19, N41	None	211	None	0.5 kg	0.5 kg	E	28
	Trinitrochlorobenzene or Picryl chloride.	1.1D	UN0155	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Trinitrochlorobenzene (picryl chloride), wetted, with not less than 10% water by mass.	4.1	UN3365	I	4.1	162, A8, A19, N41, N84	None	211	None	0.5 kg	0.5 kg	E	36
	Trinitroethanol	Forbidden											
	Trinitroethylnitrate	Forbidden											
	Trinitrofluorenone	1.1D	UN0387	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Trinitromethane	Forbidden											
	1,3,5-Trinitronaphthalene	Forbidden											
	Trinitronaphthalene	1.1D	UN0217	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Trinitrophenole	1.1D	UN0218	II	1.1D		None	62	None	Forbidden	Forbidden	10	
	Trinitrophenol or Picric acid, dry or wetted with less than 30 percent water, by mass.	1.1D	UN0154	II	1.1D		None	62	None	Forbidden	Forbidden	10	5E
	Trinitrophenol (picric acid), wetted, with not less than 10% water by mass.	4.1	UN3364	I	4.1	162, A8, A19, N41, N84	None	211	None	0.5 kg	0.5 kg	E	36
	Trinitrophenol, wetted with not less than 30 percent water, by mass.	4.1	UN1344	I	4.1	23, A8, A19, N41	None	211	None	1 kg	15 kg	E	28, 36
	2,4,6-Trinitrophenyl guanidine (dry).	Forbidden											
	2,4,6-Trinitrophenyl nitramine	Forbidden											
	2,4,6-Trinitrophenyl trimethylol methyl nitramine trinitrate (dry).	Forbidden											



Tritrophenylmethylnitramine or Tetyl.	1.1D	UN0208	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	.....
Tritroresorcinol or Styphnic acid, dry or wetted with less than 20 percent water, or mixture of alcohol and water, by mass.	1.1D	UN0219	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	5E
Tritroresorcinol, wetted or Styphnic acid, wetted with not less than 20 percent water, or mixture of alcohol and water by mass.	1.1D	UN0394	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	5E
2,4,6-Trinitroso-3-methyl nitraminoanisole.	Forbidden			.....	.....	.....	.....	.....	.....	.....	.....
Tritroterramine cobalt nitrate ...	Forbidden			.....	.....	.....	.....	.....	.....	.....	.....
Tritroloebene and Tritroloebene mixtures or TNT and trinitrobenzene mixtures or TNT and hexanitrostilbene mixtures or Tritroloebene hexanitrostilbene mixtures.	1.1D	UN0388	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	.....
Tritroloebene mixtures containing Tritroloebene and Hexanitrostilbene or TNT mixtures containing trinitrobenzene and hexanitrostilbene.	1.1D	UN0389	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	.....
Tritroloebene or TNT, dry or wetted with less than 30 percent water, by mass.	1.1D	UN0209	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	.....
Tritroloebene (TNT), wetted, with not less than 10% water by mass.	4.1	UN3366	I	4.1 .....	None ...	211	None ...	0.5 kg	0.5 kg	E	36
Tritroloebene, wetted with not less than 30 percent water, by mass.	4.1	UN1356	I	4.1 .....	None ...	211	None ...	0.5 kg	0.5 kg	E	28
Tripropylamine .....	3	UN2260	III	3, 8 .....	150	203	242	5 L	60 L	A	40
Tripropylene .....	3	UN2057	III	3 .....	150	202	242	5 L	60 L	B	.....
Tris-(1-aziridinyl)phosphine oxide, solution.	6.1	UN2501	II	6.1 .....	None ...	202	243	60 L	220 L	A	.....
Tris, bis-bifluoroamino diethoxy propane (TVOPA).	Forbidden		III	6.1 .....	153	203	241	60 L	220 L	A	.....
Tritonal .....	1.1D	UN0390	II	1.1D ..	None ...	62	None ...	Forbidden	Forbidden	10	.....
Tungsten hexafluoride .....	2.3	UN2196	.....	2.3, 8 .....	None ...	338	None ...	Forbidden	Forbidden	D	40
Turpentine .....	3	UN1299	III	3 .....	150	203	242	60 L	220 L	A	.....
Turpentine substitute .....	3	UN1300	I	3 .....	None ...	201	243	1 L	30 L	B	.....

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di- vision	(4) Identifica- tion Num- bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							(8A) Excep- tions	(8B) Non- bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air- craft only	(10A) Loca- tion	(10B) Other
	.....												
	Urea nitrate, <i>dry or wetted with less than 20 percent water, by mass.</i>	3	UN2330	III	3	B1, IB3, T2, TP1	150	202	242	5 L	60 L	B	
	Undecane	3	UN1511	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	
	Urea hydrogen peroxide	5.1		III	5.1, 8	A1, A7, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	13
	Urea nitrate, <i>dry or wetted with less than 20 percent water, by mass.</i>	1.1D	UN0220	II	1.1D	119	None	62	None	Forbidden	Forbidden	10	
	Urea nitrate, <i>wetted, with not less than 10% water, by mass.</i>	4.1	UN3370	I	4.1	162, A8, A19, N41, N83	None	211	None	0.5 kg	0.5 kg	E	36
	Urea nitrate, <i>wetted with not less than 20 percent water, by mass.</i>	4.1	UN1357	I	4.1	23, 39, A8, A19, N41	None	211	None	1 kg	15 kg	E	28, 36
	Urea peroxide, <i>see Urea hydro- gen peroxide.</i>												
	Valeraldehyde	3	UN2058	II	3	IB2, T4, TP1	150	202	242	5 L	60 L	B	
	Valeric acid, <i>see Corrosive liq- uids, n.o.s.</i>												
	Valeryl chloride	8	UN2502	II	8, 3	A3, A6, A7, B2, IB2, N34, T7, TP2	154	202	243	1 L	30 L	C	40
	Vanadium compound, n.o.s.	6.1	UN3285	I	6.1	IB7, IP1, T14, TP2, TP27	None	211	242	5 kg	50 kg	B	
	.....			II	6.1	IB8, IP2, IP4, T11, IP2, TP27	None	212	242	25 kg	100 kg	B	
	.....			III	6.1	IB8, IP3, T7, TP1, TP28	153	213	240	100 kg	200 kg	A	
	Vanadium oxytrichloride	8	UN2443	II	8	A3, A6, A7, B2, B16, IB2, N34, T7, TP2	154	202	242	Forbidden	30 L	C	40
	Vanadium pentoxide, <i>non-fused form.</i>	6.1	UN2862	III	6.1	IB8, IP3	153	213	240	100 kg	200 kg	A	40
	Vanadium tetrachloride	8	UN2444	I	8	A3, A6, A7, B4, N34, T10, TP2	None	201	243	Forbidden	2.5 L	C	40
	Vanadium trichloride	8	UN2475	III	8	IB8, IP3	154	213	240	25 kg	100 kg	A	40
	Vanadyli sulfate	6.1	UN2931	II	6.1	IB8, IP2, IP4	None	212	242	25 kg	100 kg	A	
	Vehicle, flammable gas powered	9	UN3166	.....	9	135, 157	220	220	220	Forbidden	No limit	A	
	Vehicle, flammable liquid pow- ered.	9	UN3166	.....	9	135, 157	220	220	220	No limit	No limit	A	



§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
G	Water-reactive solid, flammable, n.o.s.	4.3	UN3132	III	4.3, 8	IB8, IP4 IB4, N40	151	213	241	25 kg	100 kg	E	85
				I	4.3, 4.1		None	211	242	Forbidden	15 kg	D	
				II	4.3, 4.1	IB4	151	212	242	15 kg	50 kg	E	
				III	4.3, 4.1	IB6	151	213	241	25 kg	100 kg	E	
G	Water-reactive solid, n.o.s.	4.3	UN2813	I	4.3	IB4, N40	None	211	242	Forbidden	15 kg	E	40
				II	4.3	IB7, IP2	151	212	242	15 kg	50 kg	E	40
				III	4.3	IB8, IP4	151	213	241	25 kg	100 kg	E	40
G	Water-reactive, solid, oxidizing, n.o.s.	4.3	UN3133	II	4.3, 5.1		None	214	214	Forbidden	Forbidden	E	40
				III	4.3, 5.1		None	214	214	Forbidden	Forbidden	E	40
G	Water-reactive solid, self-heat-ing, n.o.s.	4.3	UN3135	I	4.3, 4.2	N40	None	211	242	Forbidden	15 kg	E	
				II	4.3, 4.2	IB5, IP2	None	212	242	15 kg	50 kg	E	
				III	4.3, 4.2	IB8, IP4	None	213	241	25 kg	100 kg	E	
G	Water-reactive solid, toxic, n.o.s.	4.3	UN3134	I	4.3, 6.1	A8, IB4, IP1, N40	None	211	242	Forbidden	15 kg	D	
				II	4.3, 6.1	IB5, IP2	151	212	242	15 kg	50 kg	E	85
				III	4.3, 6.1	IB8, IP4	151	213	241	25 kg	100 kg	E	85
	Wheel chair, electric, see Bat-tery powered vehicle or Bat-tery powered equipment.												
	White acid, see Hydrofluoric acid.												
I	White asbestos (chrysotile, ac-tinolite, anthophyllite, tremolite).	9	UN2590	III	9	156, IB8, IP2, IP3	155	216	240	200 kg	200 kg	A	34, 40
	Wood preservatives, liquid	3	UN1306	II	3	149, IB2, T4, TP1, TP8	150	202	242	5 L	60 L	B	
	Xanthates	4.2	UN3342	III	3	B1, IB3, T2, TP1	150	203	242	60 L	220 L	A	40
				III	4.2	IB6, IP2	None	212	241	15 kg	50 kg	D	40
				III	4.2	IB8, IP3	None	213	241	25 kg	100 kg	D	40

A, I, W	UN	Class	Division	Subdivision	Proper shipping name	Quantity	Special provisions	Forbidden	Forbidden	Quantity	Special provisions	Forbidden	Forbidden	Quantity	Special provisions
	4.2	UN1387	III	4.2	Wool waste, wet	151	213	240	Forbidden	60 L	D	40			
	2.2	UN2036		2.2	Xenon	306	302	None	150 kg	A					
	2.2	UN2591		2.2	Xenon, refrigerated liquid (cryogenic liquids)	320	None	None	500 kg	B					
	3	UN1307	III	3	Xylenes	150	202	242	60 L	B					
	6.1	UN2261	II	6.1	Xylenols	None	212	242	220 L	A					
	6.1	UN1711	II	6.1	Xylidines, liquid	None	202	243	60 L	A					
	6.1	UN1711	II	6.1	Xylidines, solid	None	212	242	100 kg	A					
	6.1	UN1701	II	6.1	Xylyl bromide	None	340	None	60 L	D					
	Forbidden				<i>p</i> -Xylyl diazide										
	5.1	UN1512	II	5.1	Zinc ammonium nitrite	None	212	242	25 kg	E					
	6.1	UN1712	II	6.1	Zinc arsenate or Zinc arsenite or Zinc arsenate and zinc arsenite mixtures	None	212	242	100 kg	A					
	4.3	UN1435	III	4.3	Zinc ashes	151	213	241	100 kg	A					
					Zinc bisulfite solution, see Bisulfites, aqueous solutions, n.o.s.										
	5.1	UN2469	III	5.1	Zinc bromate	152	213	240	100 kg	A			56, 58, 106		
	5.1	UN1513	II	5.1	Zinc chlorate	152	212	242	25 kg	A			56, 58, 106		
	8	UN2331	III	8	Zinc chloride, anhydrous	None	213	240	100 kg	A					
	8	UN1840	III	8	Zinc chloride, solution	None	203	241	60 L	A					
	6.1	UN1713	I	6.1	Zinc cyanide	None	211	242	50 kg	A			26		
	9	UN1931	III	None	Zinc dithionite or Zinc hydro-sulfite	155	204	240	200 kg	A			49		
	6.1	UN2855	III	6.1	Zinc ethyl, see Diethylzinc	153	213	240	200 kg	A			26		
					Zinc fluorosilicate										
					Zinc hydrosulfite, see Zinc dithionite										
					Zinc muriate solution, see Zinc chloride, solution										
	5.1	UN1514	II	5.1	Zinc nitrate	152	212	240	25 kg	A			56, 58, 69, 106, 107		
	5.1	UN1515	II	5.1	Zinc permanganate	152	212	242	25 kg	D			13, 75, 106, 85		
	5.1	UN1516	II	5.1	Zinc peroxide	152	212	242	25 kg	A					
	4.3	UN1714	I	4.3, 6.1	Zinc phosphide	None	211	None	15 kg	E					
	4.3	UN1436	I	4.3, 4.2	Zinc powder or Zinc dust	None	211	242	15 kg	A					

§ 172.101 HAZARDOUS MATERIALS TABLE—Continued

(1) Sym-bols	(2) Hazardous materials descrip-tions and proper shipping names	(3) Hazard class or Di-vision	(4) Identifica-tion Num-bers	(5) PG	(6) Label Codes	(7) Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow-age	
							(8A) Excep-tions	(8B) Non-bulk	(8C) Bulk	(9A) Passenger aircraft/rail	(9B) Cargo air-craft only	(10A) Loca-tion	(10B) Other
	Zinc resinates			III	4.3, 4.2.	A19, IB7, IP2	None	212	242	15 kg	50 kg	A	
	Zinc selenate, see Selenates or Selenites.			III	4.3, 4.2.	IB8, IP4	None	213	242	25 kg	100 kg	A	
	Zinc selenite, see Selenates or Selenites.			III	4.1	A1, IB6	151	213	240	25 kg	100 kg	A	
	Zinc silicofluoride, see Zinc fluorosilicate.												
	Zirconium, dry, coiled wire, finished metal sheets, strip (thinner than 254 microns but not thinner than 18 microns).			III	4.1	A1, IB8	151	213	240	25 kg	100 kg	A	
	Zirconium, dry, finished sheets, strip or coiled wire.			III	4.2	A1, A19, IB8	None	213	240	25 kg	100 kg	D	
	Zirconium hydride			II	4.1	A19, A20, IB4, N34	None	212	240	15 kg	50 kg	E	
	Zirconium nitrate			III	5.1	A1, A29, IB8, IP3	152	213	240	25 kg	100 kg	A	
	Zirconium picramate, dry or wetted with less than 20 percent water, by mass.			II	1.3C		None	62	None	Forbidden	Forbidden	10	5E
	Zirconium picramate, wetted with not less than 20 percent water, by mass.			I	4.1	23, N41	None	211	None	1 kg	15 kg	D	28, 36
	Zirconium powder, dry			I	4.2	A19, A20, IB6, IP2, N5, N34	None	211	242	Forbidden	Forbidden	D	
	Zirconium powder, wetted with not less than 25 percent water (a visible excess of water must be present) (a) mechanically produced, particle size less than 53 microns; (b) chemically produced, particle size less than 840 microns.			II	4.2	A19, A20, IB6, IP2, N34	None	212	241	15 kg	50 kg	D	
	Zirconium scrap			III	4.2	IB8, IP3, N34	None	213	240	Forbidden	Forbidden	D	

Zirconium suspended in a liquid	3	UN1308	I 3	None	None	201	243	Forbidden	Forbidden	B
.....	.....	.....	II 3	IB2	None	202	242	5 L	60 L	B
.....	.....	.....	III 3	B1, IB2	150	203	242	60 L	220 L	B
Zirconium tetrachloride	8	UN2503	III 8	IB8, IP3	154	213	240	25 kg	100 kg	A

[Amdt. 172-173, 55 FR 52474, Dec. 21, 1990]  
 EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.101, see the List of CFR Sections Affected in the Finding Aids section of this volume.

EDITORIAL NOTE: At 68 FR 45020, July 31, 2003, §172.101 was amended by revising entries in the Hazardous Materials Table; however, two amendments could not be incorporated because those entries do not exist. For the convenience of the user, the revised text is set forth as follows:

**§ 172.101 Purpose and use of hazardous materials table.**

\* \* \* \* \*

§ 172.101 HAZARDOUS MATERIALS TABLE

Sym-bols	Hazardous materials descrip-tions and proper shipping names	Hazard class or Di- vision	Identifica- tion Num- bers	PG	Label Codes	Special provisions (§172.102)	(8) Packaging (§173.***)			(9) Quantity limitations		(10) Vessel stow- age	
							Excep- tions	Non- bulk	Bulk	Passenger aircraft/rail	Cargo air- craft only	Loca- tion	Other
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8A)	(8B)	(8C)	(9A)	(9B)	(10A)	(10B)
*	*	*	(4)	(5)	(6)	(7)	*		*	Forbidden	*	*	28
Dipicryl dulide, wetted with <i>not less than 10 percent water, by mass.</i>		4.1	UN2852	I	4.1	162, A2, N41, N84	None	211	None	Forbidden	0.5 kg	D	
*	*	*	UN3269	*	3	40, 149	152	225	None	5 kg	5 kg	B	
Polyester resin		3	UN3269	*	3	*	*	*	*	*	*	*	*

§ 172.101

49 CFR Ch. I (10–1–04 Edition)

APPENDIX A TO § 172.101—LIST OF HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES

1. This appendix lists materials and their corresponding reportable quantities (RQ's) that are listed or designated as "hazardous substances" under section 101(14) of the Comprehensive Environmental Response, Compensation, and Liability Act, 42 U.S.C. 9601(14) (CERCLA; 42 U.S.C. 9601 *et seq.*). This listing fulfills the requirement of CERCLA, 42 U.S.C. 9656(a), that all "hazardous substances," as defined in 42 U.S.C. 9601(14), be listed and regulated as hazardous materials under 49 U.S.C. 5101–5127. That definition includes substances listed under sections 311(b)(2)(A) and 307(a) of the Federal Water Pollution Control Act, 33 U.S.C. 1321(b)(2)(A) and 1317(a), section 3001 of the Solid Waste Disposal Act, 42 U.S.C. 6921, and section 112 of the Clean Air Act, 42 U.S.C. 7412. In addition, this list contains materials that the Administrator of the Environmental Protection Agency has determined to be hazardous substances in accordance with section 102 of CERCLA, 42 U.S.C. 9602. It should be noted that 42 U.S.C. 9656(b) provides that common and contract carriers may be held liable under laws other than CERCLA for the release of a hazardous substance as defined in that Act, during transportation that commenced before the effective date of the listing and regulating of that substance as a hazardous material under 49 U.S.C. 5101–5127.
2. This appendix is divided into two TABLES which are entitled "TABLE 1—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES" and "TABLE 2—RADIONUCLIDES." A material listed in this appendix is regulated as a hazardous material and a hazardous substance under this subchapter if it meets the definition of a hazardous substance in §171.8 of this subchapter.
3. The procedure for selecting a proper shipping name for a hazardous substance is set forth in §172.101(c).
4. Column 1 of TABLE 1, entitled "*Hazardous substance*", contains the names of those elements and compounds that are hazardous substances. Following the listing of elements and compounds is a listing of waste streams. These waste streams appear on the list in numerical sequence and are referenced by the appropriate "D", "F", or "K" numbers. Column 2 of TABLE 1, entitled

- "*Reportable quantity (RQ)*", contains the reportable quantity (RQ), in pounds and kilograms, for each hazardous substance listed in Column 1 of TABLE 1.
5. A series of notes is used throughout TABLE 1 and TABLE 2 to provide additional information concerning certain hazardous substances. These notes are explained at the end of each TABLE.
  6. TABLE 2 lists radionuclides that are hazardous substances and their corresponding RQ's. The RQ's in table 2 for radionuclides are expressed in units of curies and terabecquerels, whereas those in table 1 are expressed in units of pounds and kilograms. If a material is listed in both table 1 and table 2, the lower RQ shall apply. Radionuclides are listed in alphabetical order. The RQ's for radionuclides are given in the radiological unit of measure of curie, abbreviated "Ci", followed, in parentheses, by an equivalent unit measured in terabecquerels, abbreviated "TBq".
  7. For mixtures of radionuclides, the following requirements shall be used in determining if a package contains an RQ of a hazardous substance: (i) if the identity and quantity (in curies or terabecquerels) of each radionuclide in a mixture or solution is known, the ratio between the quantity per package (in curies or terabecquerels) and the RQ for the radionuclide must be determined for each radionuclide. A package contains an RQ of a hazardous substance when the sum of the ratios for the radionuclides in the mixture or solution is equal to or greater than one; (ii) if the identity of each radionuclide in a mixture or solution is known but the quantity per package (in curies or terabecquerels) of one or more of the radionuclides is unknown, an RQ of a hazardous substance is present in a package when the total quantity (in curies or terabecquerels) of the mixture or solution is equal to or greater than the lowest RQ of any individual radionuclide in the mixture or solution; and (iii) if the identity of one or more radionuclides in a mixture or solution is unknown (or if the identity of a radionuclide by itself is unknown), an RQ of a hazardous substance is present when the total quantity (in curies or terabecquerels) in a package is equal to or greater than either one curie or the lowest RQ of any known individual radionuclide in the mixture or solution, whichever is lower.

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Acenaphthene .....	100 (45.4)
Acenaphthylene .....	5000 (2270)
Acetaldehyde .....	1000 (454)



TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilo-grams)
Acetaldehyde, chloro- .....	1000 (454)
Acetaldehyde, trichloro- .....	5000 (2270)
Acetamide .....	100 (45.4)
Acetamide, N-(aminothioxomethyl)- .....	1000 (454)
Acetamide, N-(4-ethoxyphenyl)- .....	100 (45.4)
Acetamide, N-fluoren-2-yl- .....	1 (0.454)
Acetamide, 2-fluoro- .....	100 (45.4)
Acetic acid .....	5000 (2270)
Acetic acid (2,4-dichlorophenoxy)- .....	100 (45.4)
Acetic acid, ethyl ester .....	5000 (2270)
Acetic acid, fluoro-, sodium salt .....	10 (4.54)
Acetic acid, lead (2+) salt .....	10 (4.54)
Acetic acid, thallium(I+) salt .....	1000 (454)
Acetic anhydride .....	5000 (2270)
Acetone .....	5000 (2270)
Acetone cyanohydrin .....	10 (4.54)
Acetonitrile .....	5000 (2270)
Acetophenone .....	5000 (2270)
2-Acetylaminofluorene .....	1 (0.454)
Acetyl bromide .....	5000 (2270)
Acetyl chloride .....	5000 (2270)
1-Acetyl-2-thiourea .....	1 (0.454)
Acrolein .....	1(0.454)
Acrylamide .....	5000 (2270)
Acrylic acid .....	5000 (2270)
Acrylonitrile .....	100 (45.4)
Adipic acid .....	5000 (2270)
AldicarbD1 (0.454).	
Aldrin .....	1 (0.454)
Allyl alcohol .....	100 (45.4)
Allyl chloride .....	1000 (454)
Aluminum phosphide .....	100 (45.4)
Aluminum sulfate .....	5000 (2270)
4-Aminobiphenyl .....	1 (0.454)
5-(Aminomethyl)-3-isoxazolol .....	1000 (454)
4-Aminopyridine .....	1000 (454)
Amitrole .....	10 (4.54)
Ammonia .....	100 (45.4)
Ammonium acetate .....	5000 (2270)
Ammonium benzoate .....	5000 (2270)
Ammonium bicarbonate .....	5000 (2270)
Ammonium bichromate .....	10 (4.54)
Ammonium bifluoride .....	100 (45.4)
Ammonium bisulfite .....	5000 (2270)
Ammonium carbamate .....	5000 (2270)
Ammonium carbonate .....	5000 (2270)
Ammonium chloride .....	5000 (2270)
Ammonium chromate .....	10 (4.54)
Ammonium citrate, dibasic .....	5000 (2270)
Ammonium dichromate @ .....	10 (4.54)
Ammonium fluoroborate .....	5000 (2270)
Ammonium fluoride .....	100 (45.4)
Ammonium hydroxide .....	1000 (454)
Ammonium oxalate .....	5000 (2270)
Ammonium picrate .....	10 (4.54)
Ammonium silicofluoride .....	1000 (454)
Ammonium sulfamate .....	5000 (2270)
Ammonium sulfide .....	100 (45.4)
Ammonium sulfite .....	5000 (2270)
Ammonium tartrate .....	5000 (2270)
Ammonium thiocyanate .....	5000 (2270)
Ammonium vanadate .....	1000 (454)
Amyl acetate .....	5000 (2270)
iso-Amyl acetate .....	.....
sec-Amyl acetate .....	.....
tert-Amyl acetate .....	.....
Aniline .....	5000 (2270)
o-Anisidine .....	100 (45.4)
Anthracene .....	5000 (2270)
Antimony c .....	5000 (2270)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Antimony pentachloride .....	1000 (454)
Antimony potassium tartrate .....	100 (45.4)
Antimony tribromide .....	1000 (454)
Antimony trichloride .....	1000 (454)
Antimony trifluoride .....	1000 (454)
Antimony trioxide .....	1000 (454)
Argentate(1-), bis(cyano-C)-, potassium .....	1 (0.454)
Aroclor 1016 .....	1 (0.454)
Aroclor 1221 .....	1 (0.454)
Aroclor 1232 .....	1 (0.454)
Aroclor 1242 .....	1 (0.454)
Aroclor 1248 .....	1 (0.454)
Aroclor 1254 .....	1 (0.454)
Aroclor 1260 .....	1 (0.454)
Arsenic c .....	1 (0.454)
Arsenic acid .....	1 (0.454)
Arsenic acid H3AsO4 .....	1 (0.454)
Arsenic disulfide .....	1 (0.454)
Arsenic oxide As203 .....	1 (0.454)
Arsenic oxide As205 .....	1 (0.454)
Arsenic pentoxide .....	1 (0.454)
Arsenic trichloride .....	1 (0.454)
Arsenic trioxide .....	1 (0.454)
Arsenic trisulfide .....	1 (0.454)
Arsine, diethyl- .....	1 (0.454)
Arsinic acid, dimethyl- .....	1 (0.454)
Arsonous dichloride, phenyl- .....	1 (0.454)
Asbestos cc .....	1 (0.454)
Auramine100 (45.4) .....	
Azaserine .....	1 (0.454)
Aziridine .....	1 (0.454)
Aziridine, 2-methyl- .....	1 (0.454)
Azino[2,3':3,4]pyrrolo(1,2-a)indole-4,7-dione,6-amino-8-[[[(aminocarbonyl)oxy] methyl]-1,1a,2,8,8a, 8b-hexahydro-8a-methoxy-5-methyl-, [1aS-[alpha,8beta,8alpha,8balpha)]- .....	10 (4.54)
Barium cyanide .....	10 (4.54)
Benz[j]aceanthrylene, 1,2-dihydro-3-methyl- .....	10 (4.54)
Benz[c]acridine .....	100 (45.4)
3,4-Benzacridine .....	100 (45.4)
Benzal chloride .....	5000 (2270)
Benzamide, 3,5-dichloro-N-(1,1-dimethyl-2-propynyl) .....	5000 (2270)
Benz[a]anthracene .....	10 (4.54)
1,2-Benzanthracene .....	10 (4.54)
Benz[a]anthracene, 7,12-dimethyl- .....	1 (0.454)
Benzenamine .....	5000 (2270)
Benzenamine, 4,4'-carbonimidoylbis (N,N-dimethyl- .....	100 (45.4)
Benzenamine, 4-chloro- .....	1000 (454)
Benzenamine, 4-chloro-2-methyl-, hydrochloride .....	100 (45.4)
Benzenamine, N,N-dimethyl-4-(phenylazo)- .....	10 (4.54)
Benzenamine, 2-methyl- .....	100 (45.4)
Benzenamine, 4-methyl- .....	100 (45.4)
Benzenamine, 4,4'-methylenebis(2-chloro- .....	10 (4.54)
Benzenamine, 2-methyl-, hydrochloride .....	100 (45.4)
Benzenamine, 2-methyl-5-nitro- .....	100 (45.4)
Benzenamine, 4-nitro- .....	5000 (2270)
Benzene .....	10 (4.54)
Benzene, 1-bromo-4-phenoxy- .....	100 (45.4)
Benzene, chloro- .....	100 (45.4)
Benzene, chloromethyl- .....	100 (45.4)
Benzene, 1,2-dichloro- .....	100 (45.4)
Benzene, 1,3-dichloro- .....	100 (45.4)
Benzene, 1,4-dichloro- .....	100 (45.4)
Benzene, 1,1'-(2,2-dichloroethylidene)bis[4-chloro .....	1 (0.454)
Benzene, dichloromethyl- .....	5000 (2270)
Benzene, 1,3-diisocyanatomethyl .....	100 (45.4)
Benzene, dimethyl- .....	100 (45.4)
Benzene, m-dimethyl- .....	1000 (454)
Benzene, o-dimethyl- .....	1000 (454)
Benzene, p-dimethyl- .....	100 (45.4)
Benzene, hexachloro- .....	10 (4.54)
Benzene, hexahydro- .....	1000 (454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Benzene, hydroxy-	1000 (454)
Benzene, methyl-	1000 (454)
Benzene, 1-methyl-2,4-dinitro-	10 (4.54)
Benzene, 2-methyl-1,3-dinitro-	100 (45.4)
Benzene, 1-methylethyl-	5000 (2270)
Benzene, nitro-	1000 (454)
Benzene, pentachloro-	10 (4.54)
Benzene, pentachloronitro-	100 (45.4)
Benzene, 1,2,4,5-tetrachloro-	5000 (2270)
Benzene, 1,1'-(2,2,2-trichloroethylidene)bis[4-chloro-	1 (0.454)
Benzene, 1,1'-(2,2,2-trichloroethylidene)bis[4-methoxy]-	1 (0.454)
Benzene, (trichloromethyl)	10 (4.54)
Benzene, 1,3,5-trinitro-	10 (4.54)
Benzenoacetic acid, 4-chloro-alpha-(4-chlorophenyl)-alpha-hydroxy-, ethyl ester	10 (4.54)
Benzenobutanoic acid, 4-[bis(2-chloroethyl)amino]-	10 (4.54)
Benzenediamine, ar-methyl-	10 (4.54)
1,2-Benzenedicarboxylic acid, [bis(2-ethylhexyl)] ester	100 (45.4)
1,2-Benzenedicarboxylic acid, dibutyl ester	10 (4.54)
1,2-Benzenedicarboxylic acid, diethyl ester	1000 (454)
1,2-Benzenedicarboxylic acid, dimethyl ester	5000 (2270)
1,2-Benzenedicarboxylic acid, dioctyl ester	5000 (2270)
1,3-Benzenediol	5000 (2270)
1,2-Benzenediol,4-[1-hydroxy-2-(methylamino)ethyl]-	1000 (454)
Benzenoethanamine, alpha,alpha-dimethyl-	5000 (2270)
Benzenesulfonic acid chloride	100 (45.4)
Benzenesulfonyl chloride	100 (45.4)
Benzenethiol	100 (45.4)
Benzidine	1 (0.454)
1,2-Benzisothiazol-3(2H)-one,1,1-dioxide	100 (45.4)
Benzo[a]anthracene	10 (4.54)
1,3-Benzodioxole, 5-(2-propenyl)-	100 (45.4)
1,3-Benzodioxole, 5-(1-propenyl)-	100 (45.4)
1,3-Benzodioxole, 5-propyl-	10 (4.54)
Benzo[b]fluoranthene	1 (0.454)
Benzo[k]fluoranthene	5000 (2270)
Benzo[j,k]fluorene	100 (45.4)
Benzoic acid	5000 (2270)
Benzonitrile	5000 (2270)
Benzo[g,h,i]perylene	5000 (2270)
2H-1-Benzopyran-2-one, 4-hydroxy-3-(3-oxo-1-phenyl-butyl)-, & salts, when present at concentrations greater than 0.3%	100 (45.4)
Benzo[a]pyrene	1 (0.454)
3,4-Benzopyrene	1 (0.454)
p-Benzoquinone	10 (4.54)
Benzo [rst]pentaphene	10 (4.54)
Benzotrichloride	10 (4.54)
Benzoyl chloride	1000 (454)
1,2-Benzphenanthrene	100 (45.4)
Benzyl chloride	100 (45.4)
Beryllium c	10 (4.54)
Beryllium chloride	1 (0.454)
Beryllium dust c	10 (4.54)
Beryllium fluoride	1 (0.454)
Beryllium nitrate	1 (0.454)
alpha - BHC	10 (4.54)
beta - BHC	1 (0.454)
delta - BHC	1 (0.454)
gamma - BHC	1 (0.454)
2,2'Bioxirane	10 (4.54)
Biphenyl	100 (45.4)
(1,1'-Biphenyl)-4,4'-diamine	1 (0.454)
(1,1'-Biphenyl)-4,4'-diamine,3,3'-dichloro-	1 (0.454)
(1,1'-Biphenyl)-4,4'-diamine,3,3'-dimethoxy-	10 (4.54)
(1,1'-Biphenyl)-4,4'-diamine,3,3'-dimethyl-	10 (4.54)
Bis(2-chloroethoxy) methane	1000 (454)
Bis(2-chloroethyl) ether	10 (4.54)
Bis(2-ethylhexyl)phthalate	100 (45.4)
Bromoacetone	1000 (454)
Bromoform	100 (45.4)
4-Bromophenyl phenyl ether	100 (45.4)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Brucine	100 (45.4)
1,3-Butadiene	10 (4.54)
1,3-Butadiene, 1,1,2,3,4,4-hexachloro-	1 (0.454)
1-Butanamine, N-butyl-N-nitroso-	10 (4.54)
1-Butanol	5000 (2270)
2-Butanone	5000 (2270)
2-Butanone, 3,3-dimethyl-1-(methylthio)-,O-[(methylamino)carbonyl] oxime	100 (45.4)
2-Butanone peroxide	10 (4.54)
2-Butenal	100 (45.4)
2-Butene, 1,4-dichloro-	1 (0.454)
2-Butenoic acid, 2-methyl-7[[2,3-dihydroxy-2-(1-methoxyethyl)-3-methyl-1-oxobutoxy]methyl]-2,3,5,7a-tetrahydro-1H-pyrrolizin-1-yl ester, [1S-[1alpha(Z),7(2S*, 3R*), 7alpha]]-	10 (4.54)
Butyl acetate	5000 (2270)
iso-Butyl acetate	
sec-Butyl acetate	
tert-Butyl acetate	
n-Butyl alcohol	5000 (2270)
Butylamine	1000 (454)
iso-Butylamine	
sec-Butylamine	
tert-Butylamine	
Butyl benzyl phthalate	100 (45.4)
n-Butyl phthalate	10 (4.54)
Butyric acid	5000 (2270)
iso-Butyric acid	
Cacodylic acid	1 (0.454)
Cadmium c	10 (4.54)
Cadmium acetate	10 (4.54)
Cadmium bromide	10 (4.54)
Cadmium chloride	10 (4.54)
Calcium arsenate	1 (0.454)
Calcium arsenite	1 (0.454)
Calcium carbide	10 (4.54)
Calcium chromate	10 (4.54)
Calcium cyanamide	1000 (454)
Calcium cyanide	10 (4.54)
Calcium cyanide Ca(CN) <sub>2</sub>	10 (4.54)
Calcium dodecylbenzene sulfonate	1000 (454)
Calcium hypochlorite	10 (4.54)
Camphene, octachloro-	1 (0.454)
Captan	10 (4.54)
Carbamic acid, ethyl ester	100 (45.4)
Carbamic acid, methylnitroso-, ethyl ester	1 (0.454)
Carbamic chloride, dimethyl-	1 (0.454)
Carbamide, thio-	10 (4.54)
Carbamimidoseleonic acid	1000 (454)
Carbamothioic acid, bis (1-methylethyl)-, S-(2,3-dichloro-2-propenyl) ester	100 (45.4)
Carbaryl	100 (45.4)
Carbofuran	10 (4.54)
Carbon bisulfide	100 (45.4)
Carbon disulfide	100 (45.4)
Carbonic acid, dithallium (I+)	100 (45.4)
Carbonic dichloride	10 (4.54)
Carbonic difluoride	1000 (454)
Carbonochloridic acid, methyl ester	1000 (454)
Carbon oxyfluoride	1000 (454)
Carbon tetrachloride	10 (4.54)
Carbonyl sulfide	100 (45.4)
Catechol	100 (45.4)
Chloral	5000(2270)
Chloramben	100 (45.4)
Chlorambucil	10 (4.54)
Chlordane	1 (0.454)
Chlordane, alpha & gamma isomers	1 (0.454)
Chlordane, technical	1 (0.454)
Chlorine	10 (4.54)
Chlornaphazine	100 (45.4)
Chloroacetaldehyde	1000 (454)
Chloroacetic acid	100 (45.4)
2-Chloroacetophenone	100 (45.4)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
p-Chloroaniline	1000 (454)
Chlorobenzene	100 (45.4)
Chlorobenzilate	10 (4.54)
4-Chloro-m-cresol	5000 (2270)
p-Chloro-m-cresol	5000 (2270)
Chlorodibromomethane	100 (45.4)
Chloroethane	100 (45.4)
2-Chloroethyl vinyl ether	1000 (454)
Chloroform	10 (4.54)
Chloromethane	100 (45.4)
Chloromethyl methyl ether	10 (4.54)
beta-Chloronaphthalene	5000 (2270)
2-Chloronaphthalene	5000 (2270)
2-Chlorophenol	100 (45.4)
o-Chlorophenol	100 (45.4)
4-Chlorophenyl phenyl ether	5000 (2270)
1-(o-Chlorophenyl)thiourea	100 (45.4)
Chloroprene	100 (45.4)
3-Chloropropionitrile	1000 (454)
Chlorosulfonic acid	1000 (454)
4-Chloro-o-toluidine, hydrochloride	100 (45.4)
Chlorpyrifos	1 (0.454)
Chromic acetate	1000 (454)
Chromic acid	10 (4.54)
Chromic acid H2CrO4, calcium salt	10 (4.54)
Chromic sulfate	1000 (454)
Chromium c	5000 (2270)
Chromous chloride	1000 (454)
Chrysene	100 (45.4)
Cobaltous bromide	1000 (454)
Cobaltous formate	1000 (454)
Cobaltous sulfamate	1000 (454)
Coke Oven Emissions	1 (0.454)
Copper c	5000 (2270)
Copper chloride @	10 (4.54)
Copper cyanide	10 (4.54)
Copper cyanide CuCN	10 (4.54)
Coumaphos	10 (4.54)
Creosote	1 (0.454)
Cresols (isomers and mixture)	100 (45.4)
m-Cresol	100 (45.4)
o-Cresolo	100 (45.4)
p-Cresol	100 (45.4)
Cresylic acid (isomers and mixture)	100 (45.4)
m-Cresylic acid	100 (45.4)
o-Cresylic acid	100 (45.4)
p-Cresylic acid	100 (45.4)
Crotonaldehyde	100 (45.4)
Cumene	5000 (2270)
Cupric acetate	100 (45.4)
Cupric acetoarsenite	1 (0.454)
Cupric chloride	10 (4.54)
Cupric nitrate	100 (45.4)
Cupric oxalate	100 (45.4)
Cupric sulfate	10 (4.54)
Cupric sulfate ammoniated	100 (45.4)
Cupric tartrate	100 (45.4)
Cyanides (soluble salts and complexes) not otherwise specified	10 (4.54)
Cyanogen	100 (45.4)
Cyanogen bromide	1000 (454)
Cyanogen bromide (CN)Br	1000 (454)
Cyanogen chloride	10 (4.54)
Cyanogen chloride (CN)Cl	10 (4.54)
2,5-Cyclohexadiene-1,4-dione	10 (4.54)
Cyclohexane	1000 (454)
Cyclohexane, 1,2,3,4,5,6-hexachloro-, (1alpha,2alpha,3beta,4alpha,5alpha,6beta)-	1 (0.454)
Cyclohexanone	5000 (2270)
2-Cyclohexyl-4,6-dinitrophenol	100 (45.4)
1,3-Cyclopentadiene, 1,2,3,4,5-hexachloro-	10 (4.54)
Cyclophosphamide	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
2,4-D Acid	100 (45.4)
2,4-D Ester	100 (45.4)
Daunomycin	10 (4.54)
DDD	1 (0.454)
4,4'-DDD	1 (0.454)
DDE	1 (0.454)
4,4'-DDE	1 (0.454)
DDT	1 (0.454)
4,4'-DDT	1 (0.454)
Diallate	100 (45.4)
Diamine	1 (0.454)
Diazinon	1 (0.454)
Diazomethane	100 (45.4)
Dibenz[a,h]anthracene	1 (0.454)
1,2,5,6-Dibenzanthracene	1 (0.454)
Dibenzo[a,h]anthracene	1 (0.454)
Dibenzofuran	100 (45.4)
Dibenz[a,i]pyrene	10 (4.54)
1,2-Dibromo-3-chloropropane	1 (0.454)
Dibutyl phthalate	10 (4.54)
Di-n-butyl phthalate	10 (4.54)
Dicamba	1000 (454)
Dichlobenil	100 (45.4)
Dichlone	1 (0.454)
Dichlorobenzene	100 (45.4)
1,2-Dichlorobenzene	100 (45.4)
1,3-Dichlorobenzene	100 (45.4)
1,4-Dichlorobenzene	100 (45.4)
m-Dichlorobenzene	100 (45.4)
o-Dichlorobenzene	100 (45.4)
p-Dichlorobenzene	100 (45.4)
3,3'-Dichlorobenzidine	1 (0.454)
Dichlorobromomethane	5000 (2270)
1,4-Dichloro-2-butene	1 (0.454)
Dichlorodifluoromethane	5000 (2270)
1,1-Dichloroethane	1000 (454)
1,2-Dichloroethane	100 (45.4)
1,1-Dichloroethylene	100 (45.4)
1,2-Dichloroethylene	1000 (454)
Dichloroethyl ether	10 (4.54)
Dichloroisopropyl—ether	1000 (454)
Dichloromethane @	1000 (454)
Dichloromethoxy ethane	1000 (454)
Dicholormethyl ether	10 (4.54)
2,4-Dichlorophenol	100 (45.4)
2,6-Dichlorophenol	100 (45.4)
Dichlorophenylarsine	1 (0.454)
Dichloropropane	1000 (454)
1,1-Dichloropropane	.....
1,3-Dichloropropane	.....
1,2-Dichloropropane	1000 (454)
Dichloropropane - Dichloropropene (mixture)	100 (45.4)
Dichloropropene	100 (45.4)
2,3-Dichloropropene	.....
1,3-Dichloropropene	100 (45.4)
2,2-Dichloropropionic acid	5000 (2270)
Dichlorvos	10 (4.54)
Dicofol	10 (4.54)
Dieldrin	1 (0.454)
1,2:3,4-Diepoxybutane	10 (4.54)
Diethanolamine	100 (45.4)
Diethylamine	1000 (454)
N,N-diethylaniline	1000 (454)
Diethylarsine	1 (0.454)
1,4-Diethylenedioxiide	100 (45.4)
Diethylhexyl phthalate	100 (45.4)
N,N'-Diethylhydrazine	10 (4.54)
O,O-Diethyl S-methyl dithiophosphate	5000 (2270)
Diethyl-p-nitrophenyl phosphate	100 (45.4)
Diethyl phthalate	1000(454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
O,O-Diethyl O-pyrazinyl phosphorothioate	100 (45.4)
Diethylstilbestrol	1 (0.454)
Diethyl sulfate	10 (4.54)
Dihydrosafrole	10 (4.54)
Diisopropyl fluorophosphate	100 (45.4)
1,4,5,8-Dimethanonaphthalene	
1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-, (1alpha,4alpha,4beta,5beta,8beta,8beta)-	1 (0.454)
1,4,5,8-Dimethanonaphthalene,1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-(1alpha,4alpha,4beta,5alpha,8alpha,8beta)-	1 (0.454)
2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1alpha,2beta,2beta,3alpha,6alpha,6alpha,7beta,7alpha)-	1 (0.454)
2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1alpha,2beta,2alpha,3beta,6beta,6alpha,7beta,7alpha)-	1 (0.454)
Dimethoate	10 (4.54)
3,3'-Dimethoxybenzidine	10 (4.54)
Dimethylamine	1000 (454)
p-Dimethylaminoazobenzene	10 (4.54)
N,N-dimethylaniline	100 (45.4)
7,12-Dimethylbenz[a]anthracene	1 (0.454)
3,3'-Dimethylbenzidine	10 (4.54)
alpha, alpha-Dimethylbenzylhydroperoxide	10 (4.54)
Dimethylcarbonyl chloride	1 (0.454)
Dimethylformamide	100 (45.4)
1,1-Dimethylhydrazine	10 (4.54)
1,2-Dimethylhydrazine	1 (0.454)
Dimethylhydrazine, unsymmetrical @	10 (4.54)
alpha, alpha-Dimethylphenethylamine	5000 (2270)
12,4-Dimethylphenol	100 (45.4)
Dimethyl phthalate	5000 (2270)
Dimethyl sulfate	100 (45.4)
Dinitrobenzene (mixed)	100 (45.4)
m-Dinitrobenzene	
o-Dinitrobenzene	
p-Dinitrobenzene	
4,6-Dinitro-o-cresol and salts	10 (4.54)
Dinitrogen tetroxide @	10 (4.54)
Dinitrophenol	10 (4.54)
2,5-Dinitrophenol	
2,4-Dinitrophenol	10 (4.54)
Dinitrotoluene	10 (4.54)
3,4-Dinitrotoluene	
2,4-Dinitrotoluene	10 (4.54)
2,6-Dinitrotoluene	100 (45.4)
Dinoseb	1000 (454)
Di-n-octyl phthalate	5000 (2270)
1,4-Dioxane	100 (45.4)
1,2-Diphenylhydrazine	10 (4.54)
Diphosphoramide, octamethyl-	100 (45.4)
Diphosphoric acid, tetraethyl ester	10 (4.54)
Dipropylamine	5000 (2270)
Di-n-propylnitrosamine	10 (4.54)
Diquat	1000 (454)
Disulfoton	1 (0.454)
Dithiobiuret	100 (45.4)
Diuron	100 (45.4)
Dodecylbenzenesulfonic acid	1000 (454)
2,4-D, salts and esters	100 (45.4)
Endosulfan	1 (0.454)
alpha-Endosulfan	1 (0.454)
beta-Endosulfan	1 (0.454)
Endosulfan sulfate	1 (0.454)
Endothall	1000 (454)
Endrin	1 (0.454)
Endrin, & metabolites	1 (0.454)
Endrin aldehyde	1 (0.454)
Epichlorohydrin	100 (45.4)
Epinephrine	1000 (454)
1,2-Epoxybutane	100 (45.4)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Ethanal	1000 (454)
Ethanamine, N-ethyl-N-nitroso-	1 (0.454)
Ethane, 1,2-dibromo-	1 (0.454)
Ethane, 1,1-dichloro-	1000 (454)
Ethane, 1,2-dichloro-	100 (45.4)
Ethane, hexachloro-	100 (45.4)
Ethane, 1,1'-[methylenebis(oxy)]bis(2-chloro-	1000 (454)
Ethane, 1,1'-oxybis-	100 (45.4)
Ethane, 1,1'-oxybis(2-chloro-	10 (4.54)
Ethane, pentachloro-	10 (4.54)
Ethane, 1,1,1,2-tetrachloro-	100 (45.4)
Ethane, 1,1,2,2-tetrachloro-	100 (45.4)
Ethane, 1,1,2-trichloro-	100 (45.4)
Ethane, 1,1,1-trichloro-	1000 (454)
1,2-Ethanediamine, N,N-dimethyl-N'-2-pyridinyl-N'-(2-thienyl-methyl)-	5000 (2270)
Ethanedinitrile	100 (45.4)
Ethanenitrile	5000 (2270)
Ethanethioamide	10 (4.54)
Ethanimidothioic acid, N-[[[(methylamino)carbonyl] oxy]-, methyl ester	100 (45.4)
Ethanol, 2-ethoxy-	1000 (454)
Ethanol, 2,2'-(nitrosoimino)bis-	1 (0.454)
Ethanone, 1-phenyl-	5000 (2270)
Ethanoyl chloride	5000 (2270)
Ethene, chloro-	1 (0.454)
Ethene, 2-chloroethoxy-	1000 (454)
Ethene, 1,1-dichloro-	100 (45.4)
Ethene, 1,2-dichloro- (E)	1000 (454)
Ethene, tetrachloro-	100 (45.4)
Ethene, trichloro-	100 (45.4)
Ethion	10 (4.54)
Ethyl acetate	5000 (2270)
Ethyl acrylate	1000 (454)
Ethylbenzene	1000 (454)
Ethyl carbamate (Urethan)	100 (45.4)
Ethyl chloride @	100 (45.4)
Ethyl cyanide	10 (4.54)
Ethylene dibromide	1 (0.454)
Ethylene dichloride	100 (45.4)
Ethylene glycol	5000 (2270)
Ethylene glycol monoethyl ether	1000 (454)
Ethylene oxide	10 (4.54)
Ethylenebisdithiocarbamic acid	5000 (2270)
Ethylenebisdithiocarbamic acid, salts and esters	5000 (2270)
Ethylenediamine	5000 (2270)
Ethylenediamine tetraacetic acid (EDTA)	5000 (2270)
Ethylenethiourea	10 (4.54)
Ethylenimine	1 (0.454)
Ethyl ether	100 (45.4)
Ethylidene dichloride	1000 (454)
Ethyl methacrylate	1000 (454)
Ethyl methanesulfonate	1 (0.454)
Ethyl methyl ketone @	5000 (2270)
Famphurdimethylester	1000 (454)
Ferric ammonium citrate	1000 (454)
Ferric ammonium oxalate	1000 (454)
Ferric chloride	1000 (454)
Ferric fluoride	100 (45.4)
Ferric nitrate	1000 (454)
Ferric sulfate	1000 (454)
Ferrous ammonium sulfate	1000 (454)
Ferrous chloride	100 (45.4)
Ferrous sulfate	1000 (454)
Fluoranthene	100 (45.4)
Fluorene	5000 (2270)
Fluorine	10 (4.54)
Fluoroacetamide	100 (45.4)
Fluoroacetic acid, sodium salt	10 (4.54)
Formaldehyde	100 (45.4)
Formic acid	5000 (2270)
Fulminic acid, mercury(2+)/salt	10 (4.54)



TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Fumaric acid	5000 (2270)
Furan	100 (45.4)
Furan, tetrahydro-	1000 (454)
2-Furancarboxaldehyde	5000 (2270)
2,5-Furandione	5000 (2270)
Furfural	5000 (2270)
Furfuran	100 (45.4)
Glucopyranose, 2-deoxy-2-(3-methyl-3-nitrosoureido)-	1 (0.454)
D-Glucose, 2-deoxy-2-[[methylnitrosoamino]-carbonyl]amino]-	1 (0.454)
Glycidylaldehyde	10 (4.54)
Guanidine, N-methyl-N'-nitro-N-nitroso-	10 (4.54)
Guthion	1 (0.454)
Heptachlor	1 (0.454)
Heptachlor epoxide	1 (0.454)
Hexachlorobenzene	10 (4.54)
Hexachlorobutadiene	1 (0.454)
Hexachlorocyclohexane (gamma isomer)	1 (0.454)
Hexachlorocyclopentadiene	10 (4.54)
Hexachloroethane	100 (45.4)
1,2,3,4,10-10-Hexachloro-1,4,4a,5,8,8a-hexahydro-1,4:5,8-endo,exo-dimethanonaphthalene	1 (0.454)
Hexachlorophene	100 (45.4)
Hexachloropropene	1000 (454)
Hexaethyl tetraphosphate	100 (45.4)
Hexamethylene-1,6-diisocyanate	100 (45.4)
Hexamethylphosphoramide	1 (0.454)
Hexane	5000 (2270)
Hydrazine	1 (0.454)
Hydrazine, 1,2-diethyl-	10 (4.54)
Hydrazine, 1,1-dimethyl-	10 (4.54)
Hydrazine, 1,2-dimethyl-	1 (0.454)
Hydrazine, 1,2-diphenyl-	10 (4.54)
Hydrazine, methyl-	10 (4.54)
Hydrazinecarbothioamide	100 (45.4)
Hydrochloric acid	5000 (2270)
Hydrocyanic acid	10 (4.54)
Hydrofluoric acid	100 (45.4)
Hydrogen chloride	5000 (2270)
Hydrogen cyanide	10 (4.54)
Hydrogen fluoride	100 (45.4)
Hydrogen phosphide	100 (45.4)
Hydrogen sulfide	100 (45.4)
Hydrogen sulfide H2S	100 (45.4)
Hydroperoxide, 1-methyl-1-phenylethyl-	10 (4.54)
Hydroquinone	100 (45.4)
2-Imidazolidinethione	10 (4.54)
Indeno(1,2,3-cd)pyrene	100 (45.4)
1,3-Isobenzofurandione	5000 (2270)
Isobutyl alcohol	5000 (2270)
Isodrin	1 (0.454)
Isophorone	5000 (2270)
Isoprene	100 (45.4)
Isopropanolamine dodecylbenzene sulfonate	1000 (454)
Isosafrole	100 (45.4)
3(2H)-Isoxazolone, 5-(aminomethyl)-	1000 (454)
Keponedecachloroc-tahydro-	1 (0.454)
Lasiocarpine	10 (4.54)
Lead c	10 (4.54)
Lead acetate	10 (4.54)
Lead arsenate	1 (0.454)
Lead, bis(acetato-O)tetrahydroxytri	10 (4.54)
Lead chloride	10 (4.54)
Lead fluoborate	10 (4.54)
Lead fluoride	10 (4.54)
Lead iodide	10 (4.54)
Lead nitrate	10 (4.54)
Lead phosphate	10 (4.54)
Lead stearate	10 (4.54)
Lead subacetate	10 (4.54)
Lead sulfate	10 (4.54)
Lead sulfide	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Lead thiocyanate	10 (4.54)
Lindane	1 (0.454)
Lithium chromate	10 (4.54)
Malathion	100 (45.4)
Maleic acid	5000 (2270)
Maleic anhydride	5000 (2270)
Maleic hydrazide	5000 (2270)
Malononitrile	1000 (454)
MDI	5000 (2270)
Melphalan	1 (0.454)
Mercaptodimethur	10 (4.54)
Mercuric cyanide	1 (0.454)
Mercuric nitrate	10 (4.54)
Mercuric sulfate	10 (4.54)
Mercuric thiocyanate	10 (4.54)
Mercurous nitrate	10 (4.54)
Mercury	1 (0.454)
Mercury, (acetato-O)phenyl-	100 (45.4)
Mercury fulminate	10 (4.54)
Methacrylonitrile	1000 (454)
Methanamine, N-methyl-	1000 (454)
Methanamine, N-methyl-N-nitroso	10 (4.54)
Methane, bromo-	1000 (454)
Methane, chloro-	100 (45.4)
Methane, chloromethoxy-	10 (4.54)
Methane, dibromo-	1000 (454)
Methane, dichloro-	1000 (454)
Methane, dichlorodifluoro-	5000 (2270)
Methane, iodo-	100 (45.4)
Methane, isocyanato-	10 (4.54)
Methane, oxybis(chloro-	10 (4.54)
Methane, tetrachloro-	10 (4.54)
Methane, tetranitro-	10 (4.54)
Methane, tribromo-	100 (45.4)
Methane, trichloro-	10 (4.54)
Methane, trichlorofluoro-	5000 (2270)
Methanesulfonyl chloride, trichloro-	100 (45.4)
Methanesulfonic acid, ethyl ester	1 (0.454)
Methanethiol	100 (45.4)
6,9-Methano-2,4,3-benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide	1 (0.454)
Methanoic acid	5000 (2270)
4,7-Methano-1H-indene, 1,4,5,6,7,8,8-heptachloro-a,4,7,7a-tetrahydro-	1 (0.454)
4,7-Methano-1H-indene, 1,4,5,6,7,8,8-octachloro-2,3,3a,4,7,7a-hexahydro-	1 (0.454)
Methanol	5000 (2270)
Methapyrilene	5000 (2270)
1,3,4-Metheno-2H-cyclobutal[cd]-pentalen-2-one, 1,1a,3,3a,4,5,5,5a,5b,6-decachlorooctahydro-	1 (0.454)
Methomyl	100 (45.4)
Methoxychlor	1 (0.454)
Methyl alcohol	5000 (2270)
Methylamine @	100 (45.4)
Methyl bromide	1000 (454)
1-Methylbutadiene	100 (45.4)
Methyl chloride	100 (45.4)
Methyl chlorocarbonate	1000 (454)
Methyl chloroform	1000 (454)
Methyl chloroformate	1000 (454)
Methylchloromethyl ether @	1 (0.454)
3-Methylcholanthrene	10 (4.54)
4,4'-Methylenebis(2-chloroaniline)	10 (4.54)
Methylene bromide	1000 (454)
Methylene chloride	1000 (454)
4,4'-Methylenedianiline	10 (4.54)
Methylene diphenyl diisocyanate	5000 (2270)
Methylene oxide	100 (45.4)
Methyl ethyl ketone (MEK)	5000 (2270)
Methyl ethyl ketone peroxide	10 (4.54)
Methyl hydrazine	10 (4.54)
Methyl iodide	100 (45.4)
Methyl isobutyl ketone	5000 (2270)
Methyl isocyanate	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
2-Methylacetonitrile	10 (4.54)
Methyl mercaptan	100 (45.4)
Methyl methacrylate	1000 (454)
Methyl parathion	100 (45.4)
4-Methyl-2-pentanone	5000 (2270)
Methyl tert-butyl ether	1000 (454)
Methylthiouracil	10 (4.54)
Mevinphos	10 (4.54)
Mexacarbate	1000 (454)
Mitomycin C	10 (4.54)
MNNG	10 (4.54)
Monoethylamine	100 (45.4)
Monomethylamine	100 (45.4)
Muscimol	1000 (454)
Naled	10 (4.54)
5,12-Naphthacenedione, 8-acetyl-10-[3-amino-2,3,6-trideoxy-alpha-L-lyxo-hexopyranosyl]oxy]-7,8,9,10-tetrahydro-6,8,11-trihydroxy-1-methoxy-, (8S-cis)-	10 (4.54)
Naphthalenamine, N,N-bis(2-chloroethyl)-	100 (45.4)
Naphthalene	100 (45.4)
Naphthalene, 2-chloro-	5000 (2270)
1,4-Naphthalenedione	5000 (2270)
2,7-Naphthalenedisulfonic acid, 3,3'-[[3,3'-dimethyl-(1,1'-biphenyl)-4,4'-diyl]-bis(azo)]bis(5-amino-4-hydroxy)-tetrasodium salt	10 (4.54)
Naphthenic acid	100 (45.4)
1,4-Naphthoquinone	5000 (2270)
alpha-Naphthylamine	100 (45.4)
beta-Naphthylamine	1 (0.454)
1-Naphthylamine	100 (45.4)
2-Naphthylamine	1 (0.454)
alpha-Naphthylthiourea	100 (45.4)
Nickel c	100 (45.4)
Nickel ammonium sulfate	100 (45.4)
Nickel carbonyl	10 (4.54)
Nickel carbonyl Ni(CO)4,(T-4)-	10 (4.54)
Nickel chloride	100 (45.4)
Nickel cyanide	10 (4.54)
Nickel cyanide Ni(CN)2	10 (4.54)
Nickel hydroxide	10 (4.54)
Nickel nitrate	100 (45.4)
Nickel sulfate	100 (45.4)
Nicotine and salts	100 (45.4)
Nitric acid	1000 (454)
Nitric acid, thallium(1+) salt	100 (45.4)
Nitric oxide	10 (4.54)
p-Nitroaniline	5000 (2270)
Nitrobenzene	1000 (454)
4-nitrobiphenyl	10 (4.54)
Nitrogen dioxide	10 (4.54)
Nitrogen oxide NO	10 (4.54)
Nitrogen oxide NO2	10 (4.54)
Nitroglycerine	10 (4.54)
Nitrophenol (mixed)	100 (45.4)
m-	
o-	
p-	
o-Nitrophenol	100 (45.4)
p-Nitrophenol	100 (45.4)
2-Nitrophenol	100 (45.4)
4-Nitrophenol	100 (45.4)
2-Nitropropane	10 (4.54)
N-Nitrosodi-n-butylamine	10 (4.54)
N-Nitrosodiethanolamine	1 (0.454)
N-Nitrosodiethylamine	1 (0.454)
N-Nitrosodimethylamine	10 (4.54)
N-Nitrosodiphenylamine	100 (45.4)
N-Nitroso-N-ethylurea	1 (0.454)
N-Nitroso-N-methylurea	1 (0.454)
N-Nitroso-N-methylurethane	1 (0.454)
N-Nitrosomethylvinylamine	10 (4.54)
n-Nitrosomorpholine	1 (0.454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilo-grams)
N-Nitrosopiperidine .....	10 (4.54)
N-Nitrosopyrrolidine .....	1 (0.454)
Nitrotoluene .....	1000 (454)
m-Nitrotoluene .....	.....
o-Nitrotoluene .....	.....
p-Nitrotoluene .....	.....
5-Nitro-o-toluidine .....	100 (45.4)
Octamethylpyrophosphoramide .....	100 (45.4)
Osmium oxide OsO4 (T-4) .....	1000 (454)
Osmium tetroxide .....	1000 (454)
7-Oxabicyclo[2.2.1]heptane-2,3-dicarboxylic acid .....	1000 (454)
1,2-Oxathiolane, 2,2-dioxide .....	10 (4.54)
2H-1,3,2-Oxazaphosphorin-2-amine, N,N-bis(2-chloroethyl)tetrahydro-, 2-oxide .....	10 (4.54)
Oxirane .....	10 (4.54)
Oxiranecarboxyaldehyde .....	10 (4.54)
Oxirane, (chloromethyl)- .....	100 (45.4)
Paraformaldehyde .....	1000 (454)
Paraldehyde .....	1000 (454)
Parathion .....	10 (4.54)
Pentachlorobenzene .....	10 (4.54)
Pentachloroethane .....	10 (4.54)
Pentachloronitrobenzene (PCNB) .....	100 (45.4)
Pentachlorophenol .....	10 (4.54)
1,3-Pentadiene .....	100 (45.4)
Perchloroethylene .....	100 (45.4)
Perchloromethyl mercaptan @ .....	100 (45.4)
Phenacetin .....	100 (45.4)
Phenanthrene .....	5000 (2270)
Phenol .....	1000 (454)
Phenol, 2-chloro- .....	100 (45.4)
Phenol, 4-chloro-3-methyl- .....	5000 (2270)
Phenol, 2-cyclohexyl-4,6-dinitro- .....	100 (45.4)
Phenol, 2,4-dichloro- .....	100 (45.4)
Phenol, 2,6-dichloro- .....	100 (45.4)
Phenol, 4,4'-(1,2-diethyl-1,2-ethenediyl)bis-, (E) .....	1 (0.454)
Phenol, 2,4-dimethyl- .....	100 (45.4)
Phenol, 2,4-dinitro- .....	10 (4.54)
Phenol, methyl- .....	100 (45.4)
Phenol, 2-methyl-4,6-dinitro- .....	10 (4.54)
Phenol, 2,2'-methylenebis[3,4,6-trichloro- .....	100 (45.4)
Phenol, 2-(1-methylpropyl)-4,6-dinitro .....	1000 (454)
Phenol, 4-nitro- .....	100 (45.4)
Phenol, pentachloro- .....	10 (4.54)
Phenol, 2,3,4,6-tetrachloro- .....	10 (4.54)
Phenol, 2,4,5-trichloro- .....	10 (4.54)
Phenol, 2,4,6-trichloro- .....	10 (4.54)
Phenol, 2,4,6-trinitro-, ammonium salt .....	10 (4.54)
L-Phenylalanine, 4-[bis(2-chloroethyl)amino] .....	1 (0.454)
p-Phenylenediamine .....	5000 (2270)
1,10-(1,2-Phenylene)pyrene .....	100 (45.4)
Phenyl mercaptan @ .....	100 (45.4)
Phenylmercuric acetate .....	100 (45.4)
Phenylthiourea .....	100 (45.4)
Phorate .....	10 (4.54)
Phosgene .....	10 (4.54)
Phosphine .....	100 (45.4)
Phosphoric acid .....	5000 (2270)
Phosphoric acid, diethyl 4-nitrophenyl ester .....	100 (45.4)
Phosphoric acid, lead(2+) salt (2:3) .....	10 (4.54)
Phosphorodithioic acid, O,O-diethyl S-[2-(ethylthio)ethyl]ester .....	1 (0.454)
Phosphorodithioic acid, O,O-diethyl S-(ethylthio), methyl ester .....	10 (4.54)
Phosphorodithioic acid, O,O-diethyl S-methyl ester .....	5000 (2270)
Phosphorodithioic acid, O,O-dimethyl S-[2 (methylamino)-2-oxoethyl] ester .....	10 (4.54)
Phosphorofluoric acid, bis(1-methylethyl) ester .....	100 (45.4)
Phosphorothioic acid, O,O-diethyl O-(4-nitrophenyl) ester .....	10 (4.54)
Phosphorothioic acid, O,O-diethyl O-pyrazinyl ester .....	100 (45.4)
Phosphorothioic acid, O,O-dimethyl O-(4-nitrophenyl) ester .....	100 (45.4)
Phosphorothioic acid, O,[4-[(dimethylamino)sulfonyl] phenyl] O,O-dimethyl ester .....	1000 (454)
Phosphorus .....	1 (0.454)
Phosphorus oxychloride .....	1000 (454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Phosphorus pentasulfide	100 (45.4)
Phosphorus sulfide	100 (45.4)
Phosphorus trichloride	1000 (454)
Phthalic anhydride	5000 (2270)
2-Picoline	5000 (2270)
Piperidine, 1-nitroso-	10 (4.54)
Plumbane, tetraethyl-	10 (4.54)
POLYCHLORINATED BIPHENYLS (PCBs)	1 (0.454)
Potassium arsenate	1 (0.454)
Potassium arsenite	1 (0.454)
Potassium bichromate	10 (4.54)
Potassium chromate	10 (4.54)
Potassium cyanide	10 (4.54)
Potassium cyanide K(CN)	10 (4.54)
Potassium hydroxide	1000 (454)
Potassium permanganate	100 (45.4)
Potassium silver cyanide	1 (0.454)
Pronamide	5000 (2270)
Propanal, 2-methyl-2-(methylthio)-,O-[(methylamino)carbonyl]oxime	1 (0.454)
1-Propanamine	5000 (2270)
1-Propanamine, N-nitroso-N-propyl-	10 (4.54)
1-Propanamine, N-propyl-	5000 (2270)
Propane, 1,2-dibromo-3-chloro-	1 (0.454)
Propane, 1,2-dichloro-	1000 (454)
Propane, 2-nitro-	10 (4.54)
Propane, 2,2'-oxybis [2-chloro-	1000 (454)
1,3-Propane sultone	10 (4.54)
Propanedinitrile	1000 (454)
Propanenitrile	10 (4.54)
Propanenitrile, 3-chloro-	1000 (454)
Propanenitrile, 2-hydroxy-2-methyl-	10 (4.54)
1,2,3-Propanetriol, trinitrate-	10 (4.54)
1-Propanol, 2,3-dibromo-, phosphate (3:1)	10 (4.54)
1-Propanol, 2-methyl-	5000 (2270)
2-Propanone	5000 (2270)
2-Propanone, 1-bromo-	1000 (454)
Propargite	10 (4.54)
Propargyl alcohol	1000 (454)
2-Propenal	1 (0.454)
2-Propenamide	5000 (2270)
1-Propene, 1,3-dichloro-	100 (45.4)
1-Propene, 1,1,2,3,3,3-hexachloro-	1000 (454)
2-Propenenitrile	100 (45.4)
2-Propenenitrile, 2-methyl-	1000 (454)
2-Propenoic acid	5000 (2270)
2-Propenoic acid, ethyl ester	1000 (454)
2-Propenoic acid, 2-methyl-, ethyl ester	1000 (454)
2-Propenoic acid, 2-methyl-, methyl ester	1000 (454)
2-Propen-1-ol	100 (45.4)
beta-Propioaldehyde	1000 (454)
Propionic acid	5000 (2270)
Propionic acid, 2-(2,4,5-trichlorophenoxy)-	100 (45.4)
Propionic anhydride	5000 (2270)
Propoxur (baygon)	100 (45.4)
n-Propylamine	5000 (2270)
Propylene dichloride	1000 (454)
Propylene oxide	100 (45.4)
1,2-Propylenimine	1 (0.454)
2-Propyn-1-ol	1000 (454)
Pyrene	5000 (2270)
Pyrethrins	1 (0.454)
3,6-Pyridazinedione, 1,2-dihydro-	5000 (2270)
4-Pyridinamine	1000 (454)
Pyridine	1000 (454)
Pyridine, 2-methyl-	5000 (2270)
Pyridine, 3-(1-methyl-2-pyrrolidinyl)-, (S)	100 (45.4)
2,4-(1H,3H)-Pyrimidinedione, 5-[bis(2-chloroethyl)amino]-	10 (4.54)
4(1H)-Pyrimidinone, 2,3-dihydro-6-methyl-2-thioxo-	10 (4.54)
Pyrrolidine, 1-nitroso-	1 (0.454)
Quinoline	5000 (2270)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
<b>RADIONUCLIDES</b>	
Reserpine	See table 2
Resorcinol	5000 (2270)
Saccharin and salts	100 (45.4)
Safrole	100 (45.4)
Selenious acid	10 (4.54)
Selenious acid, dithallium(1+) salt	1000 (454)
Selenium c	100 (45.4)
Selenium dioxide	10 (4.54)
Selenium oxide	10 (4.54)
Selenium sulfide	10 (4.54)
Selenium sulfide SeS2	10 (4.54)
Selenourea	1000 (454)
L-Serine, diazoacetate (ester)	1 (0.454)
Silver c	1000 (454)
Silver cyanide	1 (0.454)
Silver cyanide Ag(CN)	1 (0.454)
Silver nitrate	1 (0.454)
Silvex(2,4,5-TP)	100 (45.4)
Sodium	10 (4.54)
Sodium arsenate	1 (0.454)
Sodium arsenite	1 (0.454)
Sodium azide	1000 (454)
Sodium bichromate	10 (4.54)
Sodium bifluoride	100 (45.4)
Sodium bisulfite	5000 (2270)
Sodium chromate	10 (4.54)
Sodium cyanide	10 (4.54)
Sodium cyanide Na(CN)	10 (4.54)
Sodium dodecylbenzene sulfonate	1000 (454)
Sodium fluoride	1000 (454)
Sodium hydrosulfide	5000 (2270)
Sodium hydroxide	1000 (454)
Sodium hypochlorite	100 (45.4)
Sodium methylate	1000 (454)
Sodium nitrite	100 (45.4)
Sodium phosphate, dibasic	5000 (2270)
Sodium phosphate, tribasic	5000 (2270)
Sodium selenite	100 (45.4)
Streptozotocin	1 (0.454)
Strontium chromate	10 (4.54)
Strychnidin-10-one	10 (4.54)
Strychnidin-10-one, 2,3-dimethoxy-	100 (45.4)
Strychnine and salts	10 (4.54)
Styrene	1000 (454)
Styrene oxide	100 (45.4)
Sulfur chloride @	1000 (454)
Sulfur monochloride	1000 (454)
Sulfur phosphide	100 (45.4)
Sulfuric acid	1000 (454)
Sulfuric acid, dimethyl ester	100 (45.4)
Sulfuric acid, dithallium(1+) salt	100 (45.4)
2,4,5-T	1000 (454)
2,4,5-T acid	1000 (454)
2,4,5-T amines	5000 (2270)
2,4,5-T esters	1000 (454)
2,4,5-T salts	1000 (454)
TDE	1 (0.454)
1,2,4,5-Tetrachlorobenzene	5000 (2270)
2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD)	1 (0.454)
1,1,1,2-Tetrachloroethane	100 (45.4)
1,1,2,2-Tetrachloroethane	100 (45.4)
Tetrachloroethane @	100 (45.4)
Tetrachloroethene	100 (45.4)
Tetrachloroethylene	100 (45.4)
2,3,4,6-Tetrachlorophenol	10 (4.54)
Tetraethyl lead	10 (4.54)
Tetraethyl pyrophosphate	10 (4.54)
Tetraethylthiopyrophosphate	100 (45.4)
Tetrahydrofuran	1000 (454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Tetranitromethane	10 (4.54)
Tetraphosphoric acid, hexaethyl ester	100 (45.4)
Thallic oxide	100 (45.4)
Thallium c	1000 (454)
Thallium(I) acetate	100 (45.4)
Thallium(I) carbonate	100 (45.4)
Thallium(I) chloride	100 (45.4)
Thallium chloride TlCl	100 (45.4)
Thallium(I) nitrate	100 (45.4)
Thallium oxide T1203	100 (45.4)
Thallium selenite	1000 (454)
Thallium(I) sulfate	100 (45.4)
Thioacetamide	10 (4.54)
Thiodiphosphoric acid, tetraethyl ester	100 (45.4)
Thiofanox	100 (45.4)
Thioimidodicarbonic diamide [(H <sub>2</sub> N)C(S)] <sub>2</sub> NH	100 (45.4)
Thiomethanol	100 (45.4)
Thioperoxydicarbonic diamide [(H <sub>2</sub> N)C(S)] <sub>2</sub> S <sub>2</sub> , tetramethyl-	10 (4.54)
Thiophenol	100 (45.4)
Thiosemicarbazide	100 (45.4)
Thiourea	10 (4.54)
Thiourea, (2-chlorophenyl)-	100 (45.4)
Thiourea, 1-naphthalenyl-	100 (45.4)
Thiourea, phenyl-	100 (45.4)
Thiram	10 (4.54)
Titanium tetrachloride	1000 (454)
Toluene	1000 (454)
Toluenediamine	10 (4.54)
Toluene diisocyanate	100 (45.4)
o-Toluidine	100 (45.4)
p-Toluidine	100 (45.4)
o-Toluidine hydrochloride	100 (45.4)
Toxaphene	1 (0.454)
2,4,5-TP acid	100 (45.4)
2,4,5-TP acid esters	100 (45.4)
1H-1,2,4-Triazol-3-amine	10 (4.54)
Trichlorfon	100 (45.4)
1,2,4-Trichlorobenzene	100 (45.4)
1,1,1-Trichloroethane	1000 (454)
1,1,2-Trichloroethane	100 (45.4)
Trichloroethene	100 (45.4)
Trichloroethylene	100 (45.4)
Trichloromethanesulfonyl chloride	100 (45.4)
Trichloromonofluoromethane	5000 (2270)
Trichlorophenol	10 (4.54)
2,3,4-Trichlorophenol	
2,3,5-Trichlorophenol	
2,3,6-Trichlorophenol	
2,4,5-Trichlorophenol	
2,4,6-Trichlorophenol	
3,4,5-Trichlorophenol	
2,4,5-Trichlorophenol	10 (4.54)
2,4,6-Trichlorophenol	10 (4.54)
Triethanolamine dodecylbenzene sulfonate	1000 (454)
Triethylamine	5000 (2270)
Trifluralin	10 (4.54)
Trimethylamine	100 (45.4)
2,2,4-Trimethylpentane	1000 (454)
1,3,5-Trinitrobenzene	10 (4.54)
1,3,5-Trioxane, 2,4,6-trimethyl-	1000 (454)
Tris(2,3-dibromopropyl) phosphate	10 (4.54)
Trypan blue	10 (4.54)
Uracil mustard	10 (4.54)
Uranyl acetate	100 (45.4)
Uranyl nitrate	100 (45.4)
Urea, N-ethyl-N-nitroso-	1 (0.454)
Urea, N-methyl-N-nitroso-	1 (0.454)
Vanadic acid, ammonium salt	1000 (454)
Vanadium oxide V <sub>2</sub> O <sub>5</sub>	1000 (454)
Vanadium pentoxide	1000 (454)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
Vanadyl sulfate .....	1000 (454)
Vinyl acetate .....	5000 (2270)
Vinyl acetate monomer .....	5000 (2270)
Vinylamine, N-methyl-N-nitroso- .....	10 (4.54)
Vinyl bromide .....	100 (45.4)
Vinyl chloride .....	1 (0.454)
Vinylidene chloride .....	100 (45.4)
Warfarin, & salts, when present at concentrations greater than 0.3% .....	100 (45.4)
Xylene .....	100 (45.4)
m-Xylene .....	1000 (454)
o-Xylene .....	1000 (454)
p-Xylene .....	100 (45.4)
Xylene (mixed) .....	100 (45.4)
Xylenes (isomers and mixture) .....	100 (45.4)
Xylenol .....	1000 (454)
Yohimban-16-carboxylic acid, 11,17-dimethoxy-18-[(3,4,5-trimethoxybenzoyl) oxy]-, methyl ester (3beta,16beta,17alpha,18beta,20alpha)- .....	5000 (2270)
Zinc c .....	1000 (454)
Zinc acetate .....	1000 (454)
Zinc ammonium chloride .....	1000 (454)
Zinc borate .....	1000 (454)
Zinc bromide .....	1000 (454)
Zinc carbonate .....	1000 (454)
Zinc chloride .....	1000 (454)
Zinc cyanide .....	10 (4.54)
Zinc cyanide Zn(CN) <sub>2</sub> .....	10 (4.54)
Zinc fluoride .....	1000 (454)
Zinc formate .....	1000 (454)
Zinc hydrosulfite .....	1000 (454)
Zinc nitrate .....	1000 (454)
Zinc phenolsulfonate .....	5000 (2270)
Zinc phosphide .....	100 (45.4)
Zinc phosphide Zn <sub>3</sub> P <sub>2</sub> , when present at concentrations greater than 10% .....	100 (45.4)
Zinc silicofluoride .....	5000 (2270)
Zinc sulfate .....	1000 (454)
Zirconium nitrate .....	5000 (2270)
Zirconium potassium fluoride .....	1000 (454)
Zirconium sulfate .....	5000 (2270)
Zirconium tetrachloride .....	5000 (2270)
D001 Unlisted Hazardous Wastes Characteristic of Ignitability .....	100 (45.4)
D002 Unlisted Hazardous Wastes Characteristic of Corrosivity .....	100 (45.4)
D003 Unlisted Hazardous Wastes Characteristic of Reactivity .....	100 (45.4)
D004-D043 Unlisted Hazardous Wastes Characteristic of Toxicity .....	
D004 Arsenic .....	1 (0.454)
D005 Barium .....	1000 (454)
D006 Cadmium .....	10 (4.54)
D007 Chromium .....	10 (4.54)
D008 Lead .....	10 (4.54)
D009 Mercury .....	1 (0.454)
D010 Selenium .....	10 (4.54)
D011 Silver .....	1 (0.454)
D012 Endrin .....	1 (0.454)
D013 Lindane .....	1 (0.454)
D014 Methoxychlor .....	1 (0.454)
D015 Toxaphene .....	1 (0.454)
D016 2,4-D .....	100 (45.4)
D017 2,4,5-TP .....	100 (45.4)
D018 Benzene .....	10 (4.54)
D019 Carbon tetrachloride .....	10 (4.54)
D020 Chlordane .....	1 (0.454)
D021 Chlorobenzene .....	100 (45.4)
D022 Chloroform .....	10 (4.54)
D023 o-Cresol .....	100 (45.4)
D024 m-Cresol .....	100 (45.4)
D025 p-Cresol .....	100 (45.4)
D026 Cresol .....	100 (45.4)
D027 1,4-Dichlorobenzene .....	100 (45.4)
D028 1,2-Dichloroethane .....	100 (45.4)
D029 1,1-Dichloroethylene .....	100 (45.4)
D030 2,4-Dinitrotoluene .....	10 (4.54)



TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilo-grams)
D031 Heptachlor (and hydroxide) .....	1 (0.454)
D032 Hexachlorobenzene .....	10 (4.54)
D033 Hexachlorobutadiene .....	1 (0.454)
D034 Hexachloroethane .....	100 (45.4)
D035 Methyl ethyl ketone .....	5000 (2270)
D036 Nitrobenzene .....	1000 (454)
D037 Pentachlorophenol .....	10 (4.54)
D038 Pyridine .....	1000 (454)
D039 Tetrachloroethylene .....	100 (45.4)
D040 Trichloroethylene .....	100 (45.4)
D041 2,4,5-Trichlorophenol .....	10 (4.54)
D042 2,4,6-Trichlorophenol .....	10 (4.54)
D043 Vinyl chloride .....	1 (0.454)
F001 .....	
The following spent halogenated solvents used in degreasing; all spent solvent mixtures/blends used in degreasing containing, before use, a total of ten percent or more (by volume) of one or more of the below listed halogenated solvents or those solvents listed in F002, F004 and F005; and still bottoms from the recovery of these spent solvents and spent solvent mixtures .....	10 (4.54)
(a) Tetrachloroethylene .....	100 (45.4)
(b) Trichloroethylene .....	100 (45.4)
(c) Methylene chloride .....	1000 (454)
(d) 1,1,1-Trichloroethane .....	1000 (454)
(e) Carbon tetrachloride .....	10 (4.54)
(f) Chlorinated fluorocarbons .....	5000 (2270)
F002 .....	
The following spent halogenated solvents; all spent solvent mixtures/blends containing, before use, a total of ten percent or more (by volume) of one or more of the below listed halogenated solvents or those listed in F001, F004, F005; and still bottoms from the recovery of these spent solvents and spent solvent mixtures. ....	10 (4.54)
(a) Tetrachloroethylene .....	100 (45.4)
(b) Methylene chloride .....	1000 (454)
(c) Trichloroethylene .....	100 (45.4)
(d) 1,1,1-Trichloroethane .....	1000 (454)
(e) Chlorobenzene .....	100 (45.4)
(f) 1,1,2-Trichloro-1,2,2-trifluoroethane .....	5000 (2270)
(g) o-Dichlorobenzene .....	100 (45.4)
(h) Trichlorofluoromethane .....	5000 (2270)
(i) 1,1,2 Trichloroethane .....	100 (45.4)
F003 .....	
The following spent non-halogenated solvents and solvents: .....	100 (45.4)
(a) Xylene .....	1000 (454)
(b) Acetone .....	5000 (2270)
(c) Ethyl acetate .....	5000 (2270)
(d) Ethylbenzene .....	1000 (454)
(e) Ethyl ether .....	100 (45.4)
(f) Methyl isobutyl ketone .....	5000 (2270)
(g) n-Butyl alcohol .....	5000 (2270)
(h) Cyclohexanone .....	5000 (2270)
(i) Methanol .....	5000 (2270)
F004 .....	100 (45.4)
The following spent non-halogenated solvents and the still bottoms from the recovery of these solvents:	
(a) Cresols/Cresylic acid .....	1000 (454)
(b) Nitrobenzene .....	100 (45.4)
F005 .....	
The following spent non-halogenated solvents and the still bottoms from the recovery of these solvents: .....	100 (45.4)
(a) Toluene .....	1000 (454)
(b) Methyl ethyl ketone .....	5000 (2270)
(c) Carbon disulfide .....	100 (45.4)
(d) Isobutanol .....	5000 (2270)
(e) Pyridine .....	1000 (454)
F006 .....	
Wastewater treatment sludges from electroplating operations except from the following processes: (1) sulfuric acid anodizing of aluminum, (2) tin plating on carbon steel, (3) zinc plating (segregated basis) on carbonsteel, (4) aluminum or zinc-aluminum plating on carbon steel, (5) cleaning/stripping associated with tin, zinc and aluminum plating on carbon steel, and (6) chemical etching and milling of aluminum .....	10 (4.54)
F007 .....	
Spent cyanide plating bath solutions from electroplating operations .....	10 (4.54)
F008 .....	
Plating bath residues from the bottom of plating baths from electroplating operations where cyanides are used in the process .....	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
F009 Spent stripping and cleaning bath solutions from electroplating operations where cyanides are used in the process	10 (4.54)
F010 Quenching bath residues from oil baths from metal heat treating operations where cyanides are used in the process	10 (4.54)
F011 Spent cyanide solutions from salt bath pot cleaning from metal heat treating operations (except for precious metals heat treating spent cyanide solutions from salt bath pot cleaning)	10 (4.54)
F012 Quenching wastewater treatment sludges from metal heat treating operations where cyanides are used in the process	10 (4.54)
F019 Wastewater treatment sludges from the chemical conversion coating of aluminum—except from zirconium phosphating in aluminum can washing when such phosphating is an exclusive conversion coating process	10 (4.54)
F020 Wastes (except wastewater and spent carbon from hydrogen chloride purification) from the production or manufacturing use (as a reactant, chemical intermediate, or component in a formulating process) of tri- or tetrachlorophenol, or of intermediates used to produce their pesticide derivatives. (This listing does not include wastes from the production of hexachlorophene from highly purified 2,4,5-trichlorophenol.)	1 (0.454)
F021 Wastes (except wastewater and spent carbon from hydrogen chloride purification) from the production or manufacturing use (as a reactant, chemical intermediate, or component in a formulating process) of pentachlorophenol, or of intermediates used to produce its derivatives.	1 (0.454)
F022 Wastes (except wastewater and spent carbon from hydrogen chloride purification) from the manufacturing use (as a reactant, chemical intermediate, or component in a formulating process) of tetra-, penta-, or hexachlorobenzenes under alkaline conditions.	1 (0.454)
F023 Wastes (except wastewater and spent carbon from hydrogen chloride purification) from the production of materials on equipment previously used for the production or manufacturing use (as a reactant, chemical intermediate, or component in a formulating process) of tri- and tetrachlorophenols. (This listing does not include wastes from equipment used only for the production or use of hexachlorophene from highly purified 2,4,5-trichlorophenol.)	1 (0.454)
F024 Wastes, including but not limited to distillation residues, heavy ends, tars, and reactor cleanout wastes, from the production of chlorinated aliphatic hydrocarbons, having carbon content from one to five, utilizing free radical catalyzed processes. (This listing does not include light ends, spent filters and filter aids, spent desiccants(sic), wastewater, wastewater treatment sludges, spent catalysts, and wastes listed in 40 CFR 261.32.)	1 (0.454)
F025 Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution	1 (0.454)
F026 Wastes (except wastewater and spent carbon from hydrogen chloride purification) from the production of materials on equipment previously used for the manufacturing use (as a reactant, chemical intermediate, or component in a formulating process) of tetra-, penta-, or hexachlorobenzene under alkaline conditions.	1 (0.454)
F027 Discarded unused formulations containing tri-, tetra-, or pentachlorophenol or discarded unused formulations containing compounds derived from these chlorophenols. (This listing does not include formulations containing hexachlorophene synthesized from prepurified 2,4,5-trichlorophenol as the sole component.)	1 (0.454)
F028 Residues resulting from the incineration or thermal treatment of soil contaminated with EPA Hazardous Waste Nos. F020, F021, F022, F023, F026, and F027.	1 (0.454)
F032	1 (0.454)
F034	1 (0.454)
F035	1 (0.454)
F037	1 (0.454)
F038	1 (0.454)
F039	1 (0.454)
Multi source leachate	1 (0.454)
K001 Bottom sediment sludge from the treatment of wastewaters from wood preserving processes that use creosote and/or pentachlorophenol	1 (0.454)
K002 Wastewater treatment sludge from the production of chrome yellow and orange pigments	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
K003 Wastewater treatment sludge from the production of molybdate orange pigments	10 (4.54)
K004 Wastewater treatment sludge from the production of zinc yellow pigments	10 (4.54)
K005 Wastewater treatment sludge from the production of chrome green pigments	10 (4.54)
K006 Wastewater treatment sludge from the production of chrome oxide green pigments (anhydrous and hydrated)	10 (4.54)
K007 Wastewater treatment sludge from the production of iron blue pigments	10 (4.54)
K008 Oven residue from the production of chrome oxide green pigments	10 (4.54)
K009 Distillation bottoms from the production of acetaldehyde from ethylene	10 (4.54)
K010 Distillation side cuts from the production of acetaldehyde from ethylene	10 (4.54)
K011 Bottom stream from the wastewater stripper in the production of acrylonitrile	10 (4.54)
K013 Bottom stream from the acetonitrile column in the production of acrylonitrile	10 (4.54)
K014 Bottoms from the acetonitrile purification column in the production of acrylonitrile	5000 (2270)
K015 Still bottoms from the distillation of benzyl chloride	10 (4.54)
K016 Heavy ends or distillation residues from the production of carbon tetrachloride	1 (0.454)
K017 Heavy ends (still bottoms) from the purification column in the production of epichlorohydrin	10 (4.54)
K018 Heavy ends from the fractionation column in ethyl chloride production	1 (0.454)
K019 Heavy ends from the distillation of ethylene dichloride in ethylene dichloride production	1 (0.454)
K020 Heavy ends from the distillation of vinyl chloride in vinyl chloride monomer production	1 (0.454)
K021 Aqueous spent antimony catalyst waste from fluoromethanes production	10 (4.54)
K022 Distillation bottom tars from the production of phenol/acetone from cumene	1 (0.454)
K023 Distillation light ends from the production of phthalic anhydride from naphthalene	5000 (2270)
K024 Distillation bottoms from the production of phthalic anhydride from naphthalene	5000 (2270)
K025 Distillation bottoms from the production of nitrobenzene by the nitration of benzene	10 (4.54)
K026 Stripping still tails from the production of methyl ethyl pyridines	1000 (454)
K027 Centrifuge and distillation residues from toluene diisocyanate production	10 (4.54)
K028 Spent catalyst from the hydrochlorinator reactor in the production of 1,1,1-trichloroethane	1 (0.454)
K029 Waste from the product steam stripper in the production of 1,1,1-trichloroethane	1 (0.454)
K030 Column bottoms or heavy ends from the combined production of trichloroethylene and perchloroethylene	1 (0.454)
K031 By-product salts generated in the production of MSMA and cacodylic acid	1 (0.454)
K032 Wastewater treatment sludge from the production of chlordane	10 (4.54)
K033 Wastewater and scrub water from the chlorination of cyclopentadiene in the production of chlordane	10 (4.54)
K034 Filter solids from the filtration of hexachlorocyclopentadiene in the production of chlordane	10 (4.54)
K035 Wastewater treatment sludges generated in the production of creosote	1 (0.454)
K036 Still bottoms from toluene reclamation distillation in the production of disulfoton	1 (0.454)
K037 Wastewater treatment sludges from the production of disulfoton	1 (0.454)
K038 Wastewater from the washing and stripping of phorate production	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
K039 Filter cake from the filtration of diethylphosphorodithioic acid in the production of phorate	10 (4.54)
K040 Wastewater treatment sludge from the production of phorate	10 (4.54)
K041 Wastewater treatment sludge from the production of toxaphene	1 (0.454)
K042 Heavy ends or distillation residues from the distillation of tetrachlorobenzene in the production of 2,4,5-T	10 (4.54)
K043 2,6-dichlorophenol waste from the production of 2,4-D	10 (4.54)
K044 Wastewater treatment sludges from the manufacturing and processing of explosives	10 (4.54)
K045 Spent carbon from the treatment of wastewater containing explosives	10 (4.54)
K046 Wastewater treatment sludges from the manufacturing, formulation and loading of lead-based initiating compounds	10 (4.54)
K047 Pink/red water from TNT operations	10 (4.54)
K048 Dissolved air flotation (DAF) float from the petroleum refining industry	10 (4.54)
K049 Slop oil emulsion solids from the petroleum refining industry	10 (4.54)
K050 Heat exchanger bundle cleaning sludge from the petroleum refining industry	10 (4.54)
K051 API separator sludge from the petroleum refining industry	10 (4.54)
K052 Tank bottoms (leaded) from the petroleum refining industry	10 (4.54)
K060 Ammonia still lime sludge from coking operations	1 (0.454)
K061 Emission control dust/sludge from the primary production of steel in electric furnaces	10 (4.54)
K062 Spent pickle liquor generated by steel finishing operations of facilities within the iron and steel industry	10 (4.54)
K064 Acid plant blowdown slurry/sludge resulting from thickening of blowdown slurry from primary copper production.	10 (4.54)
K065 Surface impoundment solids contained in and dredged from surface impoundments at primary lead smelting facilities.	10 (4.54)
K066 Sludge from treatment of process wastewater and /or acid plant blowdown from primary zinc production.	10 (4.54)
K069 Emission control dust/sludge from secondary lead smelting	10 (4.54)
K071 Brine purification muds from the mercury cell process in chlorine production, where separately prepurified brine is not used	1 (0.454)
K073 Chlorinated hydrocarbon waste from the purification step of the diaphragm cell process using graphite anodes in chlorine production.	10 (4.54)
K083 Distillation bottoms from aniline extraction	100 (45.4)
K084 Wastewater treatment sludges generated during the production of veterinary pharmaceuticals from arsenic or organo-arsenic compounds	1 (0.454)
K085 Distillation or fractionation column bottoms from the production of chlorobenzenes	10 (4.54)
K086 Solvent washes and sludges, caustic washes and sludges, or water washes and sludges from cleaning tubs and equipment used in the formulation of ink from pigments, driers, soaps, and stabilizers containing chromium and lead	10 (4.54)
K087 Decanter tank tar sludge from coking operations	100 (45.4)
K088 Spent potliners from primary aluminum reduction.	10 (4.54)
K090 Emission control dust or sludge from ferrochromiumsilicon production.	10 (4.54)
K091 Emission control dust or sludge from ferrochromium production.	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
K093 Distillation light ends from the production of phthalic anhydride from ortho-xylene	5000 (2270)
K094 Distillation bottoms from the production of phthalic anhydride from ortho-xylene	5000 (2270)
K095 Distillation bottoms from the production of 1,1,1-trichloroethane	100 (45.4)
K096 Heavy ends from the heavy ends column from the production of 1,1,1-trichloroethane	100 (45.4)
K097 Vacuum stripper discharge from the chlordane chlorinator in the production of chlordane	1 (0.454)
K098 Untreated process wastewater from the production of toxaphene	1 (0.454)
K099 Untreated wastewater from the production of 2,4-D	10 (4.54)
K100 Waste leaching solution from acid leaching of emission control dust/sludge from secondary lead smelting	10 (4.54)
K101 Distillation tar residues from the distillation of aniline-based compounds in the production of veterinary pharmaceuticals from arsenic or organo-arsenic compounds	1 (0.454)
K102 Residue from the use of activated carbon for decolorization in the production of veterinary pharmaceuticals from arsenic or organo-arsenic compounds	1 (0.454)
K103 Process residues from aniline extraction from the production of aniline	100 (45.4)
K104 Combined wastewater streams generated from nitrobenzene/aniline chlorobenzenes	10 (4.54)
K105 Separated aqueous stream from the reactor product washing step in the production of chlorobenzenes	10 (4.54)
K106 Wastewater treatment sludge from the mercury cell process in chlorine production	1 (0.454)
K107 Column bottoms from product separation from the production of 1,1-dimethylhydrazine (UDMH) from carboxylic acid hydrazines	10 (4.54)
K108 Condensed column overheads from product separation and condensed reactor vent gases from the production of 1,1-dimethylhydrazine (UDMH) from carboxylic acid hydrazides	10 (4.54)
K109 Spent filter cartridges from product purification from the production of 1,1-dimethylhydrazine (UDMH) from carboxylic acid hydrazides	10 (4.54)
K110 Condensed column overheads from intermediate separation from the production of 1,1-dimethylhydrazines (UDMH) from carboxylic acid hydrazides	10 (4.54)
K111 Product washwaters from the production of dinitrotoluene via nitration of toluene	10 (4.54)
K112 Reaction by-product water from the drying column in the production of toluenediamine via hydrogenation of dinitrotoluene	10 (4.54)
K113 Condensed liquid light ends from the purification of toluenediamine in the production of toluenediamine via hydrogenation of dinitrotoluene	10 (4.54)
K114 Vicinals from the purification of toluenediamine in the production of toluenediamine via hydrogenation of dinitrotoluene	10 (4.54)
K115 Heavy ends from the purification of toluenediamine in the production of toluenediamine via hydrogenation of dinitrotoluene	10 (4.54)
K116 Organic condensate from the solvent recovery column in the production of toluene diisocyanate via phosgenation of toluenediamine	10 (4.54)
K117 Wastewater from the reaction vent gas scrubber in the production of ethylene bromide via bromination of ethene	1 (0.454)
K118 Spent absorbent solids from purification of ethylene dibromide in the production of ethylene dibromide	1 (0.454)
K123 Process wastewater (including supernates, filtrates, and washwaters) from the production of ethylenebisdithiocarbamic acid and its salts	10 (4.54)
K124 Reactor vent scrubber water from the production of ethylenebisdithiocarbamic acid and its salts	10 (4.54)

TABLE 1 TO APPENDIX A—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES—Continued

Hazardous substance	Reportable quantity (RQ) pounds (kilograms)
K125 Filtration, evaporation, and centrifugation solids from the production of ethylenebisdithiocarbamic acid and its salts.	10 (4.54)
K126 Baghouse dust and floor sweepings in milling and packaging operations from the production or formulation of ethylenebisdithiocarbamic acid and its salts.	10 (4.54)
K131 Waste water from the reactor and spent sulfuric acid from the acid dryer in the production of methyl bromide	100 (45.4)
K132 Spent absorbent and wastewater solids from the production of methyl bromide	1000 (454)
K136 Still bottoms from the purification of ethylene dibromide in the production of ethylene dibromide via bromination of ethene.	1 (0.454)
K141	1 (0.454)
K142	1 (0.454)
K143	1 (0.454)
K144	1 (0.454)
K145	1 (0.454)
K147	1 (0.454)
K148	1 (0.454)
K149	10 (4.54)
K150	10 (4.54)
K151	10 (4.54)
K156	1 (0.454)
K157	1 (0.454)
K158	1 (0.454)
K169	10 (4.54)
K170	1 (0.454)
K171	1 (0.454)
K172	1 (0.454)
K174	1 (0.454)
K175	1 (0.454)
K176	1 (0.454)
K177	5000 (2270)
K178	1 (0.454)

Footnotes:  
 c The RQ for these hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 micrometers (0.004 inches)  
 cc The RQ for asbestos is limited to friable forms only  
 @ Indicates that the name was added by RSPA because (1) the name is a synonym for a specific hazardous substance and (2) the name appears in the Hazardous Materials Table as a proper shipping name.

LIST OF HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES

TABLE 2 TO APPENDIX A—RADIONUCLIDES

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Actinium-224	89	100 (3.7)
Actinium-225	89	1 (.037)
Actinium-226	89	10 (.37)
Actinium-227	89	0.001 (.00037)
Actinium-228	89	10 (.37)
Aluminum-26	13	10 (.37)
Americium-237	95	1000 (37)
Americium-238	95	100 (3.7)
Americium-239	95	100 (3.7)
Americium-240	95	10 (.37)
Americium-241	95	0.01 (.00037)
Americium-242	95	100 (3.7)
Americium-242m	95	0.01 (.00037)
Americium-243	95	0.01 (.00037)
Americium-244	95	10 (.37)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Americium-244m	95	1000 (37)
Americium-245	95	1000 (37)
Americium-246	95	1000 (37)
Americium-246m	95	1000 (37)
Antimony-115	51	1000 (37)
Antimony-116	51	1000 (37)
Antimony-116m	51	100 (3.7)
Antimony-117	51	1000 (37)
Antimony-118m	51	10 (.37)
Antimony-119	51	1000 (37)
Antimony-120 (16 min)	51	1000 (37)
Antimony-120 (5.76 day)	51	10 (.37)
Antimony-122	51	10 (.37)
Antimony-124	51	10 (.37)
Antimony-124m	51	1000 (37)
Antimony-125	51	10 (.37)
Antimony-126	51	10 (.37)
Antimony-126m	51	1000 (37)

Research and Special Programs Admin., DOT

§ 172.101

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Antimony-127	51	10 (.37)
Antimony-128 (10.4 min)	51	1000 (.37)
Antimony-128 (9.01 hr)	51	10 (.37)
Antimony-129	51	100 (3.7)
Antimony-130	51	100 (3.7)
Antimony-131	51	1000 (3.7)
Argon-39	18	1000 (3.7)
Argon-41	18	10 (.37)
Arsenic-69	33	1000 (3.7)
Arsenic-70	33	100 (3.7)
Arsenic-71	33	100 (3.7)
Arsenic-72	33	10 (.37)
Arsenic-73	33	100 (3.7)
Arsenic-74	33	10 (.37)
Arsenic-76	33	100 (3.7)
Arsenic-77	33	1000 (3.7)
Arsenic-78	33	100 (3.7)
Astatine-207	85	100 (3.7)
Astatine-211	85	100 (3.7)
Barium-126	56	1000 (3.7)
Barium-128	56	10 (.37)
Barium-131	56	10 (.37)
Barium-131m	56	1000 (3.7)
Barium-133	56	10 (.37)
Barium-133m	56	100 (3.7)
Barium-135m	56	1000 (3.7)
Barium-139	56	1000 (3.7)
Barium-140	56	10 (.37)
Barium-141	56	1000 (3.7)
Barium-142	56	1000 (3.7)
Berkelium-245	97	100 (3.7)
Berkelium-246	97	10 (.37)
Berkelium-247	97	0.01 (.00037)
Berkelium-249	97	1 (.037)
Berkelium-250	97	100 (3.7)
Beryllium-10	4	1 (.037)
Beryllium-7	4	100 (3.7)
Bismuth-200	83	100 (3.7)
Bismuth-201	83	100 (3.7)
Bismuth-202	83	1000 (3.7)
Bismuth-203	83	10 (.37)
Bismuth-205	83	10 (.37)
Bismuth-206	83	10 (.37)
Bismuth-207	83	10 (.37)
Bismuth-210	83	10 (.37)
Bismuth-210m	83	0.1 (.0037)
Bismuth-212	83	100 (3.7)
Bismuth-213	83	100 (3.7)
Bismuth-214	83	100 (3.7)
Bromine-74	35	100 (3.7)
Bromine-74m	35	100 (3.7)
Bromine-75	35	100 (3.7)
Bromine-76	35	10 (.37)
Bromine-77	35	100 (3.7)
Bromine-80	35	1000 (3.7)
Bromine-80m	35	1000 (3.7)
Bromine-82	35	10 (.37)
Bromine-83	35	1000 (3.7)
Bromine-84	35	100 (3.7)
Cadmium-104	48	1000 (3.7)
Cadmium-107	48	1000 (3.7)
Cadmium-109	48	1 (.037)
Cadmium-113	48	0.1 (.0037)
Cadmium-113m	48	0.1 (.0037)
Cadmium-115	48	100 (3.7)
Cadmium-115m	48	10 (.37)
Cadmium-117	48	100 (3.7)
Cadmium-117m	48	10 (.37)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Calcium-41	20	10 (.37)
Calcium-45	20	10 (.37)
Calcium-47	20	10 (.37)
Californium-244	98	1000 (3.7)
Californium-246	98	10 (.37)
Californium-248	98	0.1 (.0037)
Californium-249	98	0.01 (.00037)
Californium-250	98	0.01 (.00037)
Californium-251	98	0.01 (.00037)
Californium-252	98	0.1 (.0037)
Californium-253	98	10 (.37)
Californium-254	98	0.1 (.0037)
Carbon-11	6	1000 (3.7)
Carbon-14	6	10 (.37)
Cerium-134	58	10 (.37)
Cerium-135	58	10 (.37)
Cerium-137	58	1000 (3.7)
Cerium-137m	58	100 (3.7)
Cerium-139	58	100 (3.7)
Cerium-141	58	10 (.37)
Cerium-143	58	100 (3.7)
Cerium-144	58	1 (.037)
Cesium-125	55	1000 (3.7)
Cesium-127	55	100 (3.7)
Cesium-129	55	100 (3.7)
Cesium-130	55	1000 (3.7)
Cesium-131	55	1000 (3.7)
Cesium-132	55	10 (.37)
Cesium-134	55	1 (.037)
Cesium-134m	55	1000 (3.7)
Cesium-135	55	10 (.37)
Cesium-135m	55	100 (3.7)
Cesium-136	55	10 (.37)
Cesium-137	55	1 (.037)
Cesium-138	55	100 (3.7)
Chlorine-36	17	10 (.37)
Chlorine-38	17	100 (3.7)
Chlorine-39	17	100 (3.7)
Chromium-48	24	100 (3.7)
Chromium-49	24	1000 (3.7)
Chromium-51	24	1000 (3.7)
Cobalt-55	27	10 (.37)
Cobalt-56	27	10 (.37)
Cobalt-57	27	100 (3.7)
Cobalt-58	27	10 (.37)
Cobalt-58m	27	1000 (3.7)
Cobalt-60	27	10 (.37)
Cobalt-60m	27	1000 (3.7)
Cobalt-61	27	1000 (3.7)
Cobalt-62m	27	1000 (3.7)
Copper-60	29	100 (3.7)
Copper-61	29	100 (3.7)
Copper-64	29	1000 (3.7)
Copper-67	29	100 (3.7)
Curium-238	96	1000 (3.7)
Curium-240	96	1 (.037)
Curium-241	96	10 (.37)
Curium-242	96	1 (.037)
Curium-243	96	0.01 (.00037)
Curium-244	96	0.01 (.00037)
Curium-245	96	0.01 (.00037)
Curium-246	96	0.01 (.00037)
Curium-247	96	0.01 (.00037)
Curium-248	96	0.001 (.000037)
Curium-249	96	1000 (3.7)
Dysprosium-155	66	100 (3.7)
Dysprosium-157	66	100 (3.7)
Dysprosium-159	66	100 (3.7)

§ 172.101

49 CFR Ch. I (10-1-04 Edition)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)— Atomic Num- ber	(3)—Reportable Quantity (RQ) Ci (TBq)
Dysprosium-165	66	1000 (37)
Dysprosium-166	66	10 (.37)
Einsteinium-250	99	10 (.37)
Einsteinium-251	99	1000 (37)
Einsteinium-253	99	10 (.37)
Einsteinium-254	99	0.1 (.0037)
Einsteinium-254m	99	1 (.037)
Erbium-161	68	100 (3.7)
Erbium-165	68	1000 (37)
Erbium-169	68	100 (3.7)
Erbium-171	68	100 (3.7)
Erbium-172	68	10 (.37)
Europium-145	63	10 (.37)
Europium-146	63	10 (.37)
Europium-147	63	10 (.37)
Europium-148	63	10 (.37)
Europium-149	63	100 (3.7)
Europium-150 (12.6 hr)	63	1000 (37)
Europium-150 (34.2 yr)	63	10 (.37)
Europium-152	63	10 (.37)
Europium-152m	63	100 (3.7)
Europium-154	63	10 (.37)
Europium-155	63	10 (.37)
Europium-156	63	10 (.37)
Europium-157	63	10 (.37)
Europium-158	63	1000 (37)
Fermium-252	100	10 (.37)
Fermium-253	100	10 (.37)
Fermium-254	100	100 (3.7)
Fermium-255	100	100 (3.7)
Fermium-257	100	1 (.037)
Fluorine-18	9	1000 (37)
Francium-222	87	100 (3.7)
Francium-223	87	100 (3.7)
Gadolinium-145	64	100 (3.7)
Gadolinium-146	64	10 (.37)
Gadolinium-147	64	10 (.37)
Gadolinium-148	64	0.001 (.000037)
Gadolinium-149	64	100 (3.7)
Gadolinium-151	64	100 (3.7)
Gadolinium-152	64	0.001 (.000037)
Gadolinium-153	64	10 (.37)
Gadolinium-159	64	1000 (37)
Gallium-65	31	1000 (37)
Gallium-66	31	10 (.37)
Gallium-67	31	100 (3.7)
Gallium-68	31	1000 (37)
Gallium-70	31	1000 (37)
Gallium-72	31	10 (.37)
Gallium-73	31	100 (3.7)
Germanium-66	32	100 (3.7)
Germanium-67	32	1000 (37)
Germanium-68	32	10 (.37)
Germanium-69	32	10 (.37)
Germanium-71	32	1000 (37)
Germanium-75	32	1000 (37)
Germanium-77	32	10 (.37)
Germanium-78	32	1000 (37)
Gold-193	79	100 (3.7)
Gold-194	79	10 (.37)
Gold-195	79	100 (3.7)
Gold-198	79	100 (3.7)
Gold-198m	79	10 (.37)
Gold-199	79	100 (3.7)
Gold-200	79	1000 (37)
Gold-200m	79	10 (.37)
Gold-201	79	1000 (37)
Hafnium-170	72	100 (3.7)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)— Atomic Num- ber	(3)—Reportable Quantity (RQ) Ci (TBq)
Hafnium-172	72	1 (.037)
Hafnium-173	72	100 (3.7)
Hafnium-175	72	100 (3.7)
Hafnium-177m	72	1000 (37)
Hafnium-178m	72	0.1 (.0037)
Hafnium-179m	72	100 (3.7)
Hafnium-180m	72	100 (3.7)
Hafnium-181	72	10 (.37)
Hafnium-182	72	0.1 (.0037)
Hafnium-182m	72	100 (3.7)
Hafnium-183	72	100 (3.7)
Hafnium-184	72	100 (3.7)
Holmium-155	67	1000 (37)
Holmium-157	67	1000 (37)
Holmium-159	67	1000 (37)
Holmium-161	67	1000 (37)
Holmium-162	67	1000 (37)
Holmium-162m	67	1000 (37)
Holmium-164	67	1000 (37)
Holmium-164m	67	1000 (37)
Holmium-166	67	100 (3.7)
Holmium-166m	67	1 (.037)
Holmium-167	67	100 (3.7)
Hydrogen-3	1	100 (3.7)
Indium-109	49	100 (3.7)
Indium-110 (4.9 hr)	49	10 (.37)
Indium-110 (69.1 min)	49	100 (3.7)
Indium-111	49	100 (3.7)
Indium-112	49	1000 (37)
Indium-113m	49	1000 (37)
Indium-114m	49	10 (.37)
Indium-115	49	0.1 (.0037)
Indium-115m	49	100 (3.7)
Indium-116m	49	100 (3.7)
Indium-117	49	1000 (37)
Indium-117m	49	100 (3.7)
Indium-119m	49	1000 (37)
Iodine-120	53	10 (.37)
Iodine-120m	53	100 (3.7)
Iodine-121	53	100 (3.7)
Iodine-123	53	10 (.37)
Iodine-124	53	0.1 (.0037)
Iodine-125	53	0.01 (.00037)
Iodine-126	53	0.01 (.00037)
Iodine-128	53	1000 (37)
Iodine-129	53	0.001 (.000037)
Iodine-130	53	1 (.037)
Iodine-131	53	0.01 (.00037)
Iodine-132	53	10 (.37)
Iodine-132m	53	10 (.37)
Iodine-133	53	0.1 (.0037)
Iodine-134	53	100 (3.7)
Iodine-135	53	10 (.37)
Iridium-182	77	1000 (37)
Iridium-184	77	100 (3.7)
Iridium-185	77	100 (3.7)
Iridium-186	77	10 (.37)
Iridium-187	77	100 (3.7)
Iridium-188	77	10 (.37)
Iridium-189	77	100 (3.7)
Iridium-190	77	10 (.37)
Iridium-190m	77	1000 (37)
Iridium-192	77	10 (.37)
Iridium-192m	77	100 (3.7)
Iridium-194	77	100 (3.7)
Iridium-194m	77	10 (.37)
Iridium-195	77	1000 (37)
Iridium-195m	77	100 (3.7)



Research and Special Programs Admin., DOT

§ 172.101

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Iron-52	26	100 (3.7)
Iron-55	26	100 (3.7)
Iron-59	26	10 (.37)
Iron-60	26	0.1 (.0037)
Krypton-74	36	10 (.37)
Krypton-76	36	10 (.37)
Krypton-77	36	10 (.37)
Krypton-79	36	100 (3.7)
Krypton-81	36	1000 (37)
Krypton-83m	36	1000 (37)
Krypton-85	36	1000 (37)
Krypton-85m	36	100 (3.7)
Krypton-87	36	10 (.37)
Krypton-88	36	10 (.37)
Lanthanum-131	57	1000 (37)
Lanthanum-132	57	100 (3.7)
Lanthanum-135	57	1000 (37)
Lanthanum-137	57	10 (.37)
Lanthanum-138	57	1 (.037)
Lanthanum-140	57	10 (.37)
Lanthanum-141	57	1000 (37)
Lanthanum-142	57	100 (3.7)
Lanthanum-143	57	1000 (37)
Lead-195m	82	1000 (37)
Lead-198	82	100 (3.7)
Lead-199	82	100 (3.7)
Lead-200	82	100 (3.7)
Lead-201	82	100 (3.7)
Lead-202	82	1 (.037)
Lead-202m	82	10 (.37)
Lead-203	82	100 (3.7)
Lead-205	82	100 (3.7)
Lead-209	82	1000 (37)
Lead-210	82	0.01 (.00037)
Lead-211	82	100 (3.7)
Lead-212	82	10 (.37)
Lead-214	82	100 (3.7)
Lutetium-169	71	10 (.37)
Lutetium-170	71	10 (.37)
Lutetium-171	71	10 (.37)
Lutetium-172	71	10 (.37)
Lutetium-173	71	100 (3.7)
Lutetium-174	71	10 (.37)
Lutetium-174m	71	10 (.37)
Lutetium-176	71	1 (.037)
Lutetium-176m	71	1000 (37)
Lutetium-177	71	100 (3.7)
Lutetium-177m	71	10 (.37)
Lutetium-178	71	1000 (37)
Lutetium-178m	71	1000 (37)
Lutetium-179	71	1000 (37)
Magnesium-28	12	10 (.37)
Manganese-51	25	1000 (37)
Manganese-52	25	10 (.37)
Manganese-52m	25	1000 (37)
Manganese-53	25	1000 (37)
Manganese-54	25	10 (.37)
Manganese-56	25	100 (3.7)
Mendelevium-257	101	100 (3.7)
Mendelevium-258	101	1 (.037)
Mercury-193	80	100 (3.7)
Mercury-193m	80	10 (.37)
Mercury-194	80	0.1 (.0037)
Mercury-195	80	100 (3.7)
Mercury-195m	80	100 (3.7)
Mercury-197	80	1000 (37)
Mercury-197m	80	1000 (37)
Mercury-199m	80	1000 (37)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Mercury-203	80	10 (.37)
Molybdenum-101	42	1000 (37)
Molybdenum-90	42	100 (3.7)
Molybdenum-93	42	100 (3.7)
Molybdenum-93m	42	10 (.37)
Molybdenum-99	42	100 (3.7)
Neodymium-136	60	1000 (37)
Neodymium-138	60	1000 (37)
Neodymium-139	60	1000 (37)
Neodymium-139m	60	100 (3.7)
Neodymium-141	60	1000 (37)
Neodymium-147	60	10 (.37)
Neodymium-149	60	100 (3.7)
Neodymium-151	60	1000 (37)
Neptunium-232	93	1000 (37)
Neptunium-233	93	1000 (37)
Neptunium-234	93	10 (.37)
Neptunium-235	93	1000 (37)
Neptunium-236 (1.2 E 5 yr)	93	0.1 (.0037)
Neptunium-236 (22.5 hr)	93	100 (3.7)
Neptunium-237	93	0.01 (.00037)
Neptunium-238	93	10 (.37)
Neptunium-239	93	100 (3.7)
Neptunium-240	93	100 (3.7)
Nickel-56	28	10 (.37)
Nickel-57	28	10 (.37)
Nickel-59	28	100 (3.7)
Nickel-63	28	100 (3.7)
Nickel-65	28	100 (3.7)
Nickel-66	28	10 (.37)
Niobium-88	41	100 (3.7)
Niobium-89 (122 min)	41	100 (3.7)
Niobium-89 (66 min)	41	100 (3.7)
Niobium-90	41	10 (.37)
Niobium-93m	41	100 (3.7)
Niobium-94	41	10 (.37)
Niobium-95	41	10 (.37)
Niobium-95m	41	100 (3.7)
Niobium-96	41	10 (.37)
Niobium-97	41	100 (3.7)
Niobium-98	41	1000 (37)
Osmium-180	76	1000 (37)
Osmium-181	76	100 (3.7)
Osmium-182	76	100 (3.7)
Osmium-185	76	10 (.37)
Osmium-189m	76	1000 (37)
Osmium-191	76	100 (3.7)
Osmium-191m	76	1000 (37)
Osmium-193	76	100 (3.7)
Osmium-194	76	1 (.037)
Palladium-100	46	100 (3.7)
Palladium-101	46	100 (3.7)
Palladium-103	46	100 (3.7)
Palladium-107	46	100 (3.7)
Palladium-109	46	1000 (37)
Phosphorus-32	15	0.1 (.0037)
Phosphorus-33	15	1 (.037)
Platinum-186	78	100 (3.7)
Platinum-188	78	100 (3.7)
Platinum-189	78	100 (3.7)
Platinum-191	78	100 (3.7)
Platinum-193	78	1000 (37)
Platinum-193m	78	100 (3.7)
Platinum-195m	78	100 (3.7)
Platinum-197	78	1000 (37)
Platinum-197m	78	1000 (37)
Platinum-199	78	1000 (37)
Platinum-200	78	100 (3.7)

§ 172.101

49 CFR Ch. I (10–1–04 Edition)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)— Atomic Num- ber	(3)—Reportable Quantity (RQ) Ci (TBq)
Plutonium-234	94	1000 (37)
Plutonium-235	94	1000 (37)
Plutonium-236	94	0.1 (.0037)
Plutonium-237	94	1000 (37)
Plutonium-238	94	0.01 (.00037)
Plutonium-239	94	0.01 (.00037)
Plutonium-240	94	0.01 (.00037)
Plutonium-241	94	1 (.037)
Plutonium-242	94	0.01 (.00037)
Plutonium-243	94	1000 (37)
Plutonium-244	94	0.01 (.00037)
Plutonium-245	94	100 (3.7)
Polonium-203	84	100 (3.7)
Polonium-205	84	100 (3.7)
Polonium-207	84	10 (.37)
Polonium-210	84	0.01 (.00037)
Potassium-40	19	1 (.037)
Potassium-42	19	100 (3.7)
Potassium-43	19	10 (.37)
Potassium-44	19	100 (3.7)
Potassium-45	19	1000 (37)
Praseodymium-136	59	1000 (37)
Praseodymium-137	59	1000 (37)
Praseodymium-138m	59	100 (3.7)
Praseodymium-139	59	1000 (37)
Praseodymium-142	59	100 (3.7)
Praseodymium-142m	59	1000 (37)
Praseodymium-143	59	10 (.37)
Praseodymium-144	59	1000 (37)
Praseodymium-145	59	1000 (37)
Praseodymium-147	59	1000 (37)
Promethium-141	61	1000 (37)
Promethium-143	61	100 (3.7)
Promethium-144	61	10 (.37)
Promethium-145	61	100 (3.7)
Promethium-146	61	10 (.37)
Promethium-147	61	10 (.37)
Promethium-148	61	10 (.37)
Promethium-148m	61	10 (.37)
Promethium-149	61	100 (3.7)
Promethium-150	61	100 (3.7)
Promethium-151	61	100 (3.7)
Protactinium-227	91	100 (3.7)
Protactinium-228	91	10 (.37)
Protactinium-230	91	10 (.37)
Protactinium-231	91	0.01 (.00037)
Protactinium-232	91	10 (.37)
Protactinium-233	91	100 (3.7)
Protactinium-234	91	10 (.37)
RADIONUCLIDES \$†		1 (.037)
Radium-223	88	1 (.037)
Radium-224	88	10 (.37)
Radium-225	88	1 (.037)
Radium-226 **	88	0.1 (.0037)
Radium-227	88	1000 (37)
Radium-228	88	0.1 (.0037)
Radon-220	86	0.1 (.0037)
Radon-222	86	0.1 (.0037)
Rhenium-177	75	1000 (37)
Rhenium-178	75	1000 (37)
Rhenium-181	75	100 (3.7)
Rhenium-182 (12.7 hr)	75	10 (.37)
Rhenium-182 (64.0 hr)	75	10 (.37)
Rhenium-184	75	10 (.37)
Rhenium-184m	75	10 (.37)
Rhenium-186	75	100 (3.7)
Rhenium-186m	75	10 (.37)
Rhenium-187	75	1000 (37)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)— Atomic Num- ber	(3)—Reportable Quantity (RQ) Ci (TBq)
Rhenium-188	75	1000 (37)
Rhenium-188m	75	1000 (37)
Rhenium-189	75	1000 (37)
Rhodium-100	45	10 (.37)
Rhodium-101	45	10 (.37)
Rhodium-101m	45	100 (3.7)
Rhodium-102	45	10 (.37)
Rhodium-102m	45	10 (.37)
Rhodium-103m	45	1000 (37)
Rhodium-105	45	100 (3.7)
Rhodium-106m	45	10 (.37)
Rhodium-107	45	1000 (37)
Rhodium-99	45	10 (.37)
Rhodium-99m	45	100 (3.7)
Rubidium-79	37	1000 (37)
Rubidium-81	37	100 (3.7)
Rubidium-81m	37	1000 (37)
Rubidium-82m	37	10 (.37)
Rubidium-83	37	10 (.37)
Rubidium-84	37	10 (.37)
Rubidium-86	37	10 (.37)
Rubidium-87	37	10 (.37)
Rubidium-88	37	1000 (37)
Rubidium-89	37	1000 (37)
Ruthenium-103	44	10 (.37)
Ruthenium-105	44	100 (3.7)
Ruthenium-106	44	1 (.037)
Ruthenium-94	44	1000 (37)
Ruthenium-97	44	100 (3.7)
Samarium-141	62	1000 (37)
Samarium-141m	62	1000 (37)
Samarium-142	62	1000 (37)
Samarium-145	62	100 (3.7)
Samarium-146	62	0.01 (.00037)
Samarium-147	62	0.01 (.00037)
Samarium-151	62	10 (.37)
Samarium-153	62	100 (3.7)
Samarium-155	62	1000 (37)
Samarium-156	62	100 (3.7)
Scandium-43	21	1000 (37)
Scandium-44	21	100 (3.7)
Scandium-44m	21	10 (.37)
Scandium-46	21	10 (.37)
Scandium-47	21	100 (3.7)
Scandium-48	21	10 (.37)
Scandium-49	21	1000 (37)
Selenium-70	34	1000 (37)
Selenium-73	34	10 (.37)
Selenium-73m	34	100 (3.7)
Selenium-75	34	10 (.37)
Selenium-79	34	10 (.37)
Selenium-81	34	1000 (37)
Selenium-81m	34	1000 (37)
Selenium-83	34	1000 (37)
Silicon-31	14	1000 (37)
Silicon-32	14	1 (.037)
Silver-102	47	100 (3.7)
Silver-103	47	1000 (37)
Silver-104	47	1000 (37)
Silver-104m	47	1000 (37)
Silver-105	47	10 (.37)
Silver-106	47	1000 (37)
Silver-106m	47	10 (.37)
Silver-108m	47	10 (.37)
Silver-110m	47	10 (.37)
Silver-111	47	10 (.37)
Silver-112	47	100 (3.7)
Silver-115	47	1000 (37)

Research and Special Programs Admin., DOT

§ 172.101

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Sodium-22	11	10 (.37)
Sodium-24	11	10 (.37)
Strontium-80	38	100 (3.7)
Strontium-81	38	1000 (37)
Strontium-83	38	100 (3.7)
Strontium-85	38	10 (.37)
Strontium-85m	38	1000 (37)
Strontium-87m	38	100 (3.7)
Strontium-89	38	10 (.37)
Strontium-90	38	0.1 (.0037)
Strontium-91	38	10 (.37)
Strontium-92	38	100 (3.7)
Sulfur-35	16	1 (.037)
Tantalum-172	73	100 (3.7)
Tantalum-173	73	100 (3.7)
Tantalum-174	73	100 (3.7)
Tantalum-175	73	100 (3.7)
Tantalum-176	73	10 (.37)
Tantalum-177	73	1000 (37)
Tantalum-178	73	1000 (37)
Tantalum-179	73	1000 (37)
Tantalum-180	73	100 (3.7)
Tantalum-180m	73	1000 (37)
Tantalum-182	73	10 (.37)
Tantalum-182m	73	1000 (37)
Tantalum-183	73	100 (3.7)
Tantalum-184	73	10 (.37)
Tantalum-185	73	1000 (37)
Tantalum-186	73	1000 (37)
Technetium-101	43	1000 (37)
Technetium-104	43	1000 (37)
Technetium-93	43	100 (3.7)
Technetium-93m	43	1000 (37)
Technetium-94	43	10 (.37)
Technetium-94m	43	100 (3.7)
Technetium-96	43	10 (.37)
Technetium-96m	43	1000 (37)
Technetium-97	43	100 (3.7)
Technetium-97m	43	100 (3.7)
Technetium-98	43	10 (.37)
Technetium-99	43	10 (.37)
Technetium-99m	43	100 (3.7)
Tellurium-116	52	1000 (37)
Tellurium-121	52	10 (.37)
Tellurium-121m	52	10 (.37)
Tellurium-123	52	10 (.37)
Tellurium-123m	52	10 (.37)
Tellurium-125m	52	10 (.37)
Tellurium-127	52	1000 (37)
Tellurium-127m	52	10 (.37)
Tellurium-129	52	1000 (37)
Tellurium-129m	52	10 (.37)
Tellurium-131	52	1000 (37)
Tellurium-131m	52	10 (.37)
Tellurium-132	52	10 (.37)
Tellurium-133	52	1000 (37)
Tellurium-133m	52	1000 (37)
Tellurium-134	52	1000 (37)
Terbium-147	65	100 (3.7)
Terbium-149	65	100 (3.7)
Terbium-150	65	100 (3.7)
Terbium-151	65	10 (.37)
Terbium-153	65	100 (3.7)
Terbium-154	65	10 (.37)
Terbium-155	65	100 (3.7)
Terbium-156	65	10 (.37)
Terbium-156m (24.4 hr)	65	1000 (37)
Terbium-156m (5.0 hr)	65	1000 (37)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Terbium-157	65	100 (3.7)
Terbium-158	65	10 (.37)
Terbium-160	65	10 (.37)
Terbium-161	65	100 (3.7)
Thallium-194	81	1000 (37)
Thallium-194m	81	100 (3.7)
Thallium-195	81	100 (3.7)
Thallium-197	81	100 (3.7)
Thallium-198	81	10 (.37)
Thallium-198m	81	100 (3.7)
Thallium-199	81	100 (3.7)
Thallium-200	81	10 (.37)
Thallium-201	81	1000 (37)
Thallium-202	81	10 (.37)
Thallium-204	81	10 (.37)
Thorium (Irradiated)	90	***
Thorium (Natural)	90	**
Thorium-226	90	100 (3.7)
Thorium-227	90	1 (.037)
Thorium-228	90	0.01 (.00037)
Thorium-229	90	0.001 (.000037)
Thorium-230	90	0.01 (.00037)
Thorium-231	90	100 (3.7)
Thorium-232 **	90	0.001 (.000037)
Thorium-234	90	100 (3.7)
Thulium-162	69	1000 (37)
Thulium-166	69	10 (.37)
Thulium-167	69	100 (3.7)
Thulium-170	69	10 (.37)
Thulium-171	69	100 (3.7)
Thulium-172	69	100 (3.7)
Thulium-173	69	100 (3.7)
Thulium-175	69	1000 (37)
Tin-110	50	100 (3.7)
Tin-111	50	1000 (37)
Tin-113	50	10 (.37)
Tin-117m	50	100 (3.7)
Tin-119m	50	10 (.37)
Tin-121	50	1000 (37)
Tin-121m	50	10 (.37)
Tin-123	50	10 (.37)
Tin-123m	50	1000 (37)
Tin-125	50	10 (.37)
Tin-126	50	1 (.037)
Tin-127	50	100 (3.7)
Tin-128	50	1000 (37)
Titanium-44	22	1 (.037)
Titanium-45	22	1000 (37)
Tungsten-176	74	1000 (37)
Tungsten-177	74	100 (3.7)
Tungsten-178	74	100 (3.7)
Tungsten-179	74	1000 (37)
Tungsten-181	74	100 (3.7)
Tungsten-185	74	10 (.37)
Tungsten-187	74	100 (3.7)
Tungsten-188	74	10 (.37)
Uranium (Depleted)	92	***
Uranium (Irradiated)	92	***
Uranium (Natural)	92	**
Uranium Enriched 20% or greater	92	***
Uranium Enriched less than 20%	92	***
Uranium-230	92	1 (.037)
Uranium-231	92	1000 (37)
Uranium-232	92	0.01 (.00037)
Uranium-233	92	0.1 (.0037)
Uranium-234 **	92	0.1 (.0037)

TABLE 2 TO APPENDIX A—RADIONUCLIDES—  
Continued

(1)—Radionuclide	(2)—Atomic Number	(3)—Reportable Quantity (RQ) Ci (TBq)
Uranium-235 **	92	0.1 (.0037)
Uranium-236	92	0.1 (.0037)
Uranium-237	92	100 (3.7)
Uranium-238 **	92	0.1 (.0037)
Uranium-239	92	1000 (37)
Uranium-240	92	1000 (37)
Vanadium-47	23	1000 (37)
Vanadium-48	23	10 (.37)
Vanadium-49	23	1000 (37)
Xenon-120	54	100 (3.7)
Xenon-121	54	10 (.37)
Xenon-122	54	100 (3.7)
Xenon-123	54	10 (.37)
Xenon-125	54	100 (3.7)
Xenon-127	54	100 (3.7)
Xenon-129m	54	1000 (37)
Xenon-131m	54	1000 (37)
Xenon-133	54	1000 (37)
Xenon-133m	54	1000 (37)
Xenon-135	54	100 (3.7)
Xenon-135m	54	10 (.37)
Xenon-138	54	10 (.37)
Ytterbium-162	70	1000 (37)
Ytterbium-166	70	10 (.37)
Ytterbium-167	70	1000 (37)
Ytterbium-169	70	10 (.37)
Ytterbium-175	70	100 (3.7)
Ytterbium-177	70	1000 (37)
Ytterbium-178	70	1000 (37)
Yttrium-86	39	10 (.37)
Yttrium-86m	39	1000 (37)
Yttrium-87	39	10 (.37)
Yttrium-88	39	10 (.37)
Yttrium-90	39	10 (.37)
Yttrium-90m	39	100 (3.7)
Yttrium-91	39	10 (.37)
Yttrium-91m	39	1000 (37)
Yttrium-92	39	100 (3.7)
Yttrium-93	39	100 (3.7)
Yttrium-94	39	1000 (37)
Yttrium-95	39	1000 (37)
Zinc-62	30	100 (3.7)
Zinc-63	30	1000 (37)
Zinc-65	30	10 (.37)
Zinc-69	30	1000 (37)
Zinc-69m	30	100 (3.7)
Zinc-71m	30	100 (3.7)
Zinc-72	30	100 (3.7)
Zirconium-86	40	100 (3.7)
Zirconium-88	40	10 (.37)
Zirconium-89	40	100 (3.7)
Zirconium-93	40	1 (.037)
Zirconium-95	40	10 (.37)
Zirconium-97	40	10 (.37)

§ The RQs for all radionuclides apply to chemical compounds containing the radionuclides and elemental forms regardless of the diameter of pieces of solid material.

† The RQ of one curie applies to all radionuclides not otherwise listed. Whenever the RQs in TABLE 1—HAZARDOUS SUBSTANCES OTHER THAN RADIONUCLIDES and this table conflict, the lowest RQ shall apply. For example, uranyl acetate and uranyl nitrate have RQs shown in TABLE 1 of 100 pounds, equivalent to about one-tenth the RQ level for uranium-238 in this table.

\*\* The method to determine the RQs for mixtures or solutions of radionuclides can be found in paragraph 7 of the note preceding TABLE 1 of this appendix. RQs for the following four common radionuclide mixtures are provided: radium-226 in secular equilibrium with its daughters (0.053 curie); natural uranium (0.1 curie); natural uranium in secular equilibrium with its daughters (0.052 curie); and natural thorium in secular equilibrium with its daughters (0.011 curie).

\*\*\* Indicates that the name was added by RSPA because it appears in the list of radionuclides in 49 CFR 173.435. The reportable quantity (RQ), if not specifically listed elsewhere in this appendix, shall be determined in accordance with the procedures in paragraph 7 of this appendix.

[Amdt. 172–122, 55 FR 46798, Nov. 7, 1990]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting appendix A to § 172.101, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

APPENDIX B TO § 172.101—LIST OF MARINE POLLUTANTS

1. See § 171.4 of this subchapter for applicability to marine pollutants. This appendix lists potential marine pollutants as defined in § 171.8 of this subchapter.

2. Marine pollutants listed in this appendix are not necessarily listed by name in the § 172.101 Table. If a marine pollutant not listed by name or by synonym in the § 172.101 Table meets the definition of any hazard Class 1 through 8, then you must determine the class and division of the material in accordance with § 173.2a of this subchapter. You must also select the most appropriate hazardous material description and proper shipping name. If a marine pollutant not listed by name or by synonym in the § 172.101 Table does not meet the definition of any Class 1 through 8, then you must offer it for transportation under the most appropriate of the following two Class 9 entries: “Environmentally hazardous substances, liquid, n.o.s.” UN3082, or “Environmentally hazardous substances, solid, n.o.s.” UN3077.

3. This appendix contains two columns. The first column, entitled “S.M.P.” (for severe marine pollutants), identifies whether a material is a severe marine pollutant. If the letters “PP” appear in this column for a material, the material is a severe marine pollutant, otherwise it is not. The second column, entitled “Marine Pollutant”, lists the marine pollutants.

4. If a material is not listed in this appendix and meets the criteria for a marine pollutant as provided in Chapter 2.10 of the IMDG Code, “Guidelines for the Identification of Harmful Substances in Packaged Form” (incorporated by reference; see § 171.7 of this subchapter), the material may be transported as a marine pollutant in accordance with the applicable requirements of this subchapter.

5. If a material listed in this appendix does not meet the criteria for a marine pollutant as provided in Chapter 2.10 of the IMDG Code, “Guidelines for the Identification of

Harmful Substances in Packaged Form” (incorporated by reference; see §171.7 of this subchapter), it may be excepted from the requirements of this subchapter as a marine pollutant if that exception is approved by the Associate Administrator.

LIST OF MARINE POLLUTANTS

S.M.P. (1)	Marine pollutant (2)
	Acetone cyanohydrin, stabilized
	Acetylene tetrabromide
	Acetylene tetrachloride
	Acraldehyde, inhibited
	Acrolein, inhibited
	Acrolein, stabilized
	Acrylic aldehyde, inhibited
	Alcohol C-12 - C-16 poly(1-6) ethoxylate
	Alcohol C-13 - C-15 poly(1-6) ethoxylate
	Alcohol C-6 - C-17 (secondary)poly(3-6) ethoxylate
	Aldicarb
PP	Aldrin
	Alkyl (c12-c14) dimethylamine
	Alkyl (c7-c9) nitrates
	Alkybenzenesulphonates, branched and straight chain (excluding C11–C13 straight chain or branched chain homologues)
	Allyl bromide
	ortho-Aminoanisole
	Aminocarb
	Ammonium dinitro-o-cresolate
	n-Amylbenzene
PP	Azinphos-ethyl
PP	Azinphos-methyl
	Barium cyanide
	Bendiocarb
	Benomyl
	Benquinox
	Benzyl chlorocarbonate
	Benzyl chloroformate
PP	Binapacryl
PP	N,N-Bis (2-hydroxyethyl) oleamide (LOA)
PP	Brodifacoum
	Bromine cyanide
	Bromoacetone
	Bromoallylene
	Bromobenzene
	ortho-Bromobenzyl cyanide
	Bromocyane
	Bromoform
PP	Bromophos-ethyl
	3-Bromopropene
	Bromoxnyl
	Butanedione
	2-Butenal, stabilized
	Butyl benzyl phthalate
	N-tert-butyl-N-cyclopropyl-6-methylthio-1,3,5-triazine-2,4-diamine
	2,4-Di-tert-butylphenol
	2,6-Di-tert-butylphenol
	para-tertiary-butyltoluene
PP	Cadmium compounds
	Cadmium sulphide
	Calcium arsenate
	Calcium arsenate and calcium arsenite, mixtures, solid
	Calcium cyanide
PP	Camphchlor
	Carbaryl
	Carbendazim
	Carbofuran
	Carbon tetrabromide
	Carbon tetrachloride

LIST OF MARINE POLLUTANTS—Continued

S.M.P. (1)	Marine pollutant (2)
PP	Carbophenothion
	Cartap hydrochloride
PP	Chlordane
	Chlorfenvinphos
PP	Chlorinated paraffins (C-10 - C-13)
PP	Chlorinated paraffins (C14–C17), with more than 1% shorter chain length
	Chlorine
	Chlorine cyanide, inhibited
	Chlormephos
	Chloroacetone, stabilized
	1-Chloro-2,3-Epoxypropane
	2-Chloro-6-nitrotoluene
	4-Chloro-2-nitrotoluene
	Chloro-ortho-nitrotoluene
	2-Chloro-5-trifluoromethylnitrobenzene
	para-Chlorobenzyl chloride, liquid or solid
	Chlorodinitrobenzenes, liquid or solid
	1-Chloroheptane
	1-Chlorohexane
	Chloronitroanilines
	Chloronitrotoluenes, liquid
	Chloronitrotoluenes, solid
	1-Chlorooctane
PP	Chlorophenolates, liquid
PP	Chlorophenolates, solid
	Chlorophenyltrichlorosilane
	alpha-Chloropropylene
	Chlorotoluenes (meta-;para-)
PP	Chlorpyrifos
PP	Chlorthiophos
	Cocculus
	Coconitrile
	Copper acetoarsenite
	Copper arsenite
	Copper chloride
PP	Copper chloride solution
PP	Copper cyanide
PP	Copper metal powder
PP	Copper sulphate, anhydrous, hydrates
	Coumachlor
PP	Coumaphos
PP	Cresyl diphenyl phosphate
	Crotonaldehyde, stabilized
	Crotonic aldehyde, stabilized
	Croxyphos
	Cupric arsenite
PP	Cupric chloride
PP	Cupric cyanide
PP	Cupric sulfate
	Cupriethylenediamine solution
PP	Cuprous chloride
	Cyanide mixtures
	Cyanide solutions
	Cyanides, inorganic, n.o.s.
	Cyanogen bromide
	Cyanogen chloride, inhibited
	Cyanogen chloride, stabilized
	Cyanophos
PP	1,5,9-Cyclododecatriene
PP	Cyhexatin
PP	Cymenes (o-;m-;p-)
PP	Cypermethrin
	Decyl acrylate
PP	DDT
	Decycloxytetrahydrothiophene dioxide
	DEF
	Desmedipham
	Di-allate
	Di-n-Butyl phthalate
PP	Dialifos

§ 172.101

49 CFR Ch. I (10–1–04 Edition)

LIST OF MARINE POLLUTANTS—Continued

LIST OF MARINE POLLUTANTS—Continued

S.M.P. (1)	Marine pollutant (2)
PP	4,4'-Diaminodiphenylmethane
	Diazinon
PP	1,3-Dibromobenzene
PP	Dichlofenthion
	Dichloroanilines
	1,3-Dichlorobenzene
	1,2-Dichlorobenzene
	1,4-Dichlorobenzene
	Dichlorobenzene (meta-; para-)
	2,2-Dichlorodiethyl ether
	Dichlorodimethyl ether, symmetrical
	Di-(2-chloroethyl) ether
	1,1-Dichloroethylene, inhibited
	1,6-Dichlorohexane
	Dichlorophenyltrichlorosilane
PP	Dichlorvos
PP	Diclofop-methyl
	Dicrotophos
PP	Dieldrin
	Diisopropylbenzenes
	Diisopropylnaphthalenes, mixed isomers
PP	Dimethoate
PP	N,N-Dimethyldodecylamine
	Dimethylhydrazine, symmetrical
	Dimethylhydrazine, unsymmetrical
	Dinitro-o-cresol, <i>solid</i>
	Dinitro-o-cresol, <i>solution</i>
	Dinitrochlorobenzenes, liquid or solid
	Dinitrophenol, <i>dry or wetted with less than 15 per cent water, by mass</i>
	Dinitrophenol solutions
	Dinitrophenol, <i>wetted with not less than 15 per cent water, by mass</i>
	Dinitrophenolates <i>alkali metals, dry or wetted with less than 15 per cent water, by mass</i>
	Dinitrophenolates, <i>wetted with not less than 15 per cent water, by mass</i>
	Dinobuton
	Dinoseb
	Dinoseb acetate
	Dioxacarb
	Dioxathion
	Dipentene
	Diphacinone
	Diphenyl
	Diphenyl oxide and biphenyl phenyl ether mixtures
PP	Diphenylamine chloroarsine
PP	Diphenylchloroarsine, solid or liquid
	Disulfoton
	1,4-Di-tert-butylbenzene
	DNOC
	DNOC (pesticide)
PP	Dodecyl diphenyl oxide disulphonate
	Dodecyl hydroxypropyl sulfide
	1-Dodecylamine
PP	Dodecylphenol
	Drazoxolon
	Edifenphos
PP	Endosulfan
PP	Endrin
	Epibromohydrin
	Epichlorohydrin
PP	EPN
PP	Esfenvalerate
PP	Ethion
	Ethoprophos
	Ethyl fluid
	Ethyl mercaptan
	2-Ethylhexyl nitrate
	5-Ethyl-2-picoline
	Ethyl propenoate, inhibited

S.M.P. (1)	Marine pollutant (2)
	2-Ethyl-3-propylacrolein
	Ethyl tetraphosphate
	Ethylchloroarsine
	Ethylene dibromide and methyl bromide mixtures, liquid
	2-Ethylhexaldehyde
	Fenamiphos
PP	Fenbutatin oxide
PP	Fenchlorazole-ethyl
PP	Fenitrothion
PP	Fenoxapro-ethyl
PP	Fenoxaprop-P-ethyl
PP	Fenpropathrin
	Fensulfthion
	Fenthion
PP	Fentin acetate
PP	Fentin hydroxide
PP	Ferric arsenate
	Ferric arsenite
	Ferrous arsenate
	Fonofos
	Formetanate
PP	Furathiocarb (ISO)
PP	gamma-BHC
	Gasoline, leaded
PP	Heptachlor
	Heptenophos
	n-Heptaldehyde
	n-Heptylbenzene
	normal-Heptyl chloride
	Hexachlorobutadiene
PP	1,3-Hexachlorobutadiene
	Hexaethyl tetraphosphate <i>liquid</i>
	Hexaethyl tetraphosphate, <i>solid</i>
	normal-Hexyl chloride
	n-Hexylbenzene
	Hydrocyanic acid, anhydrous, stabilized, containing less than 3% water
	Hydrocyanic acid, anhydrous, stabilized, containing less than 3% water and absorbed in a porous inert material
	Hydrocyanic acid, aqueous solutions <i>not more than 20% hydrocyanic acid</i>
	Hydrogen cyanide solution in alcohol, <i>with not more than 45% hydrogen cyanide</i>
	Hydrogen cyanide, stabilized <i>with less than 3% water</i>
	Hydrogen cyanide, stabilized <i>with less than 3% water and absorbed in a porous inert material</i>
	Hydroxydimethylbenzenes, liquid or solid
	Ioxynil
	Isoamyl mercaptan
	Isobenzan
	Isobutyl butyrate
	Isobutylbenzene
	Isodecyl acrylate
	Isodecyl diphenyl phosphate
	Isofenphos
	Isooctyl nitrate
	Isoproc carb
	Isopropenylbenzene
	Isotetramethylbenzene
PP	Isoxathion
	Lead acetate
	Lead arsenates
	Lead arsenites
	Lead compounds, soluble, n.o.s.
	Lead cyanide
	Lead nitrate
	Lead perchlorate, solid or solution
	Lead tetraethyl

Research and Special Programs Admin., DOT

§ 172.101

LIST OF MARINE POLLUTANTS—Continued		LIST OF MARINE POLLUTANTS—Continued	
S.M.P. (1)	Marine pollutant (2)	S.M.P. (1)	Marine pollutant (2)
PP	Lead tetramethyl		Methanethiol
	Lindane		Methodathion
	Linuron		Methomyl
	London Purple		ortho-Methoxyaniline
	Magnesium arsenate		Methyl bromide and ethylene dibromide mixtures, liq- uid
	Malathion		Methyl mercaptan
	Mancozeb (ISO)		3-Methylacroleine, stabilized
	Maneb		Methylchlorobenzenes
	Maneb preparations with not less than 60% maneb		Methylnitrophenols
	Maneb preparation, stabilized against self-heating		3-Methylpyridine
	Maneb stabilized or Maneb preparations, stabilized against self-heating		Methyltrithion
	Manganese ethylene-1,2-bis dithiocarbamate		Methylvinylbenzenes, inhibited
	Manganese ethylene-1,2-bis-dithiocarbamate, sta- bilized against self-heating	PP	Mevinphos
	Mecarbam		Mexacarbate
	Mephostolan		Mirex
	Mercaptodimethur		Monocrotophos
PP	Mercuric acetate		Motor fuel anti-knock mixtures
PP	Mercuric ammonium chloride		Motor fuel anti-knock mixtures or compounds
PP	Mercuric arsenate		Nabam
PP	Mercuric benzoate	PP	Naled
PP	Mercuric bisulphate	PP	Nickel carbonyl
PP	Mercuric bromide	PP	Nickel cyanide
PP	Mercuric chloride	PP	Nickel tetracarbonyl
PP	Mercuric cyanide		3-Nitro-4-chlorobenzotrifluoride
PP	Mercuric gluconate		Nitrobenzene
	Mercuric iodide		Nitrobenzotrifluorides, liquid or solid
PP	Mercuric nitrate		Nonylphenol
PP	Mercuric oleate		normal-Octaldehyde
PP	Mercuric oxide	PP	Oleylamine
PP	Mercuric oxycyanide, desensitized	PP	Organotin compounds, liquid, n.o.s.
PP	Mercuric potassium cyanide	PP	Organotin compounds (pesticides)
PP	Mercuric Sulphate	PP	Organotin compounds, solid, n.o.s.
PP	Mercuric thiocyanate	PP	Organotin pesticides, liquid, flammable, toxic, n.o.s., flash point less than 23deg C
PP	Mercuriol	PP	Organotin pesticides, liquid, toxic, flammable, n.o.s.
PP	Mercurous acetate	PP	Organotin pesticides, liquid, toxic, n.o.s.
PP	Mercurous bisulphate	PP	Organotin pesticides, solid, toxic, n.o.s.
PP	Mercurous bromide		Orthoarsenic acid
PP	Mercurous chloride	PP	Osmium tetroxide
PP	Mercurous nitrate		Oxamyl
PP	Mercurous salicylate		Oxydisulfoton
PP	Mercurous sulphate		Paraoxon
PP	Mercury acetates	PP	Parathion
PP	Mercury ammonium chloride	PP	Parathion-methyl
PP	Mercury based pesticide, liquid, flammable, toxic	PP	PCBs.
PP	Mercury based pesticides, liquid, toxic, flammable	PP	Pentachloroethane
PP	Mercury based pesticides, liquid, toxic		Pentachlorophenol
PP	Mercury based pesticides, solid, toxic		Pentalin
PP	Mercury benzoate		Pentanethiols
PP	Mercury bichloride		n-Pentylbenzene
PP	Mercury bisulphates		Perchloroethylene
PP	Mercury bromides		Perchloromethylmercaptan
PP	Mercury compounds, liquid, n.o.s.		Petrol, leaded
PP	Mercury compounds, solid, n.o.s.	PP	Phenarsazine chloride
PP	Mercury cyanide	PP	d-Phenothrin
PP	Mercury gluconate	PP	Phenthoate
PP	Mercury (I) (mercurous) compounds (pesticides)		1-Phenylbutane
PP	Mercury (II) (mercuric) compounds (pesticides)		2-Phenylbutane
	Mercury iodide		Phenylcyclohexane
PP	Mercury nucleate	PP	Phenylmercuric acetate
PP	Mercury oleate	PP	Phenylmercuric compounds, n.o.s.
PP	Mercury oxide	PP	Phenylmercuric hydroxide
PP	Mercury oxycyanide, desensitized	PP	Phenylmercuric nitrate
PP	Mercury potassium cyanide		2-Phenylpropene
PP	Mercury potassium iodide	PP	Phorate
PP	Mercury salicylate	PP	Phosalone
PP	Mercury sulfates		Phosmet
PP	Mercury thiocyanate	PP	Phosphamidon
	Metam-sodium	PP	Phosphorus, white, molten
	Methamidophos	PP	Phosphorus, white or yellow dry or under water or in solution

§ 172.102

49 CFR Ch. I (10–1–04 Edition)

LIST OF MARINE POLLUTANTS—Continued

S.M.P. (1)	Marine pollutant (2)
PP	Phosphorus white, or yellow, molten
PP	Phosphorus, yellow, molten
	Pindone (and salts of)
	Pirimicarb
PP	Pirimiphos-ethyl
PP	Polychlorinated biphenyls
PP	Polyhalogenated biphenyls, liquid or Terphenyls liq- uid
PP	Polyhalogenated biphenyls, solid or Terphenyls, solid
PP	Potassium cuprocyanide
	Potassium cyanide, solid
	Potassium cyanide, solution
PP	Potassium cyanocuprate (I)
PP	Potassium cyanomercurate
PP	Potassium mercuric iodide
	Promecarb
	Propachlor
	Propaphos
	Propenal, inhibited
	Propoxur
	Prothoate
	Prussic acid, anhydrous, stabilized
	Prussic acid, anhydrous, stabilized, absorbed in a porous inert material
PP	Pyrazophos
	Quinalphos
PP	Quizalofop
PP	Quizalofop-p-ethyl
	Rotenone
	Salithion
PP	Silafluofen
	Silver arsenite
	Silver cyanide
	Silver orthoarsenite
PP	Sodium copper cyanide, solid
PP	Sodium copper cyanide solution
PP	Sodium cuprocyanide, solid
PP	Sodium cuprocyanide, solution
PP	Sodium cyanide, solid
	Sodium cyanide, solution
	Sodium dinitro-o-cresolate, dry or wetted with less than 15 per cent water, by mass
	Sodium dinitro-ortho-cresolate, wetted with not less than 15 per cent water, by mass
PP	Sodium pentachlorophenate
	Strychnine or Strychnine salts
	Sulfotep
PP	Sulprophos
	Tallow nitrile
	Temephos
	TEPP
PP	Terbufos
	Tetrabromoethane
	Tetrabromomethane
	1,1,2,2-Tetrachloroethane
	Tetrachloroethylene
	Tetrachloromethane
	Tetrachlorophenol
	Tetraethyl dithiopyrophosphate
PP	Tetraethyl lead, liquid
	Tetramethrin
	Tetramethyllead
	Thallium chlorate
	Thallium compounds, n.o.s.
	Thallium compounds (pesticides)
	Thallium nitrate
	Thallium sulfate
	Thallos chlorate
	Thiocarbonyl tetrachloride
	Triaryl phosphates, isopropylated

LIST OF MARINE POLLUTANTS—Continued

S.M.P. (1)	Marine pollutant (2)
PP	Triaryl phosphates, n.o.s.
	Triazophos
	Tribromomethane
PP	Tributyltin compounds
	Trichlorfon
PP	1,2,3—Trichlorobenzene
	Trichlorobenzenes, liquid
	Trichlorobutene
	Trichlorobutylene
	Trichloromethane sulphuryl chloride
	Trichloromethyl sulphochloride
	Trichloronat
	Tricresyl phosphate (less than 1% ortho-isomer)
PP	Tricresyl phosphate, not less than 1% ortho-isomer but not more than 3% orthoisomer
PP	Tricresyl phosphate with more than 3 per cent ortho isomer
	Triethylbenzene
	Triisopropylated phenyl phosphates
	Trimethylene dichloride
PP	Triphenylphosphate
	Triphenyl phosphate/tert-butylated triphenyl phosphates mixtures containing 5% to 10% triphenyl phosphates
PP	Triphenyl phosphate/tert-butylated triphenyl phosphates mixtures containing 10% to 48% triphenyl phosphates
PP	Triphenyltin compounds
	Tritolyl phosphate (less than 1% ortho-isomer)
PP	Tritolyl phosphate (not less than 1% ortho-isomer)
	Trixylenyl phosphate
	Vinylidene chloride, stabilized
	Warfarin (and salts of)
PP	White phosphorus, dry
PP	White phosphorus, wet
	White spirit, low (15-20%) aromatic
PP	Yellow phosphorus, dry
PP	Yellow phosphorus, wet
	Zinc bromide
	Zinc cyanide

[Amdt. 172–127, 57 FR 52935, Nov. 5, 1992]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting appendix B to §172.101, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

§ 172.102 Special provisions.

(a) *General.* When column 7 of the §172.101 table refers to a special provision for a hazardous material, the meaning and requirements of that provision are as set forth in this section. When a special provision specifies packaging or packaging requirements—

(1) The special provision is in addition to the standard requirements for all packagings prescribed in §173.24 of this subchapter and any other applicable packaging requirements in subparts A and B of part 173 of this subchapter; and



(2) To the extent a special provision imposes limitations or additional requirements on the packaging provisions set forth in column 8 of the §172.101 table, packagings must conform to the requirements of the special provision.

(b) *Description of codes for special provisions.* Special provisions contain packaging provisions, prohibitions, exceptions from requirements for particular quantities or forms of materials and requirements or prohibitions applicable to specific modes of transportation, as follows:

(1) A code consisting only of numbers (for example, "11") is multi-modal in application and may apply to bulk and non-bulk packagings.

(2) A code containing the letter "A" refers to a special provision which applies only to transportation by aircraft.

(3) A code containing the letter "B" refers to a special provision which applies only to bulk packaging requirements. Unless otherwise provided in this subchapter, these special provisions do not apply to IM portable tanks.

(4) A code containing the letter "H" refers to a special provision which applies only to transportation by highway.

(5) A code containing the letter "N" refers to a special provision which applies only to non-bulk packaging requirements.

(6) A code containing the letter "R" refers to a special provision which applies only to transportation by rail.

(7) A code containing the letter "T" refers to a special provision which applies only to transportation in IM portable tanks.

(8) A code containing the letter "W" refers to a special provision which applies only to transportation by water.

(c) *Tables of special provisions.* The following tables list, and set forth the requirements of, the special provisions referred to in column 7 of the §172.101 table.

(1) *Numeric provisions.* These provisions are multi-modal and apply to bulk and non-bulk packagings:

*Code/Special Provisions*

1 This material is poisonous by inhalation (see §171.8 of this subchapter) in Hazard

Zone A (see §173.116(a) or §173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

2 This material is poisonous by inhalation (see §171.8 of this subchapter) in Hazard Zone B (see §173.116(a) or §173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

3 This material is poisonous by inhalation (see §171.8 of this subchapter) in Hazard Zone C (see §173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

4 This material is poisonous by inhalation (see §171.8 of this subchapter) in Hazard Zone D (see §173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

5 If this material meets the definition for a material poisonous by inhalation (see §171.8 of this subchapter), a shipping name must be selected which identifies the inhalation hazard, in Division 2.3 or Division 6.1, as appropriate.

6 This material is poisonous-by-inhalation and must be described as an inhalation hazard under the provisions of this subchapter.

8 A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid *or* solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

9 Packaging for certain PCBs for disposal and storage is prescribed by EPA in 40 CFR 761.60 and 761.65.

11 The hazardous material must be packaged as either a liquid or a solid, as appropriate, depending on its physical form at 55 °C (131 °F) at atmospheric pressure.

12 In concentrations greater than 40 percent, this material has strong oxidizing properties and is capable of starting fires in contact with combustible materials. If appropriate, a package containing this material must conform to the additional labeling requirements of §172.402 of this subchapter.

13 The words "Inhalation Hazard" shall be entered on each shipping paper in association with the shipping description, shall be marked on each non-bulk package in association with the proper shipping name and identification number, and shall be marked on two opposing sides of each bulk package. Size of marking on bulk package must conform to §172.302(b) of this subchapter. The requirements of §§172.203(m) and 172.505 of this subchapter do not apply.

14 Motor fuel antiknock mixtures are:  
a. Mixtures of one or more organic lead mixtures (such as tetraethyl lead,

- triethylmethyl lead, diethyldimethyl lead, ethyltrimethyl lead, and tetramethyl lead) with one or more halogen compounds (such as ethylene dibromide and ethylene dichloride), hydrocarbon solvents or other equally efficient stabilizers; or
- b. tetraethyl lead.
- 15 This entry applies to “Chemical kits” and “First aid kits” containing one or more compatible items of hazardous materials in boxes, cases, etc. that are used for medical, analytical, diagnostic or testing purposes. For transportation by aircraft, materials forbidden for transportation by passenger aircraft or cargo aircraft may not be included in the kits. Chemical kits and first aid kits are excepted from the specification packaging requirements of this subchapter when packaged in combination packagings. Chemical kits and first aid kits are also excepted from the labeling and placarding requirements of this subchapter, except when offered for transportation or transported by air. Chemical and first aid kits may be transported in accordance with the consumer commodity and ORM exceptions in §173.156, provided they meet all required conditions. Kits that are carried on board transport vehicles for first aid or operating purposes are not subject to the requirements of this subchapter.
- 16 This description applies to smokeless powder and other solid propellants that are used as powder for small arms and have been classed as Division 1.3 and 4.1 in accordance with §173.56 of this subchapter.
- 18 This description is authorized only for fire extinguishers listed in §173.309(b) of this subchapter meeting the following conditions:
- Each fire extinguisher may only have extinguishing contents that are nonflammable, non-poisonous, non-corrosive and commercially free from corroding components.
  - Each fire extinguisher must be charged with a nonflammable, non-poisonous, dry gas that has a dew-point at or below minus 46.7 °C (minus 52 °F) at 101 kPa (1 atmosphere) and is free of corroding components, to not more than the service pressure of the cylinder.
  - A fire extinguisher may not contain more than 30% carbon dioxide by volume or any other corrosive extinguishing agent.
  - Each fire extinguisher must be protected externally by suitable corrosion-resisting coating.
- 19 For domestic transportation only, the identification number “UN1075” may be used in place of the identification number specified in column (4) of the §172.101 table. The identification number used must be consistent on package markings, shipping papers and emergency response information.
- 21 This material must be stabilized by appropriate means (e.g., addition of chemical inhibitor, purging to remove oxygen) to prevent dangerous polymerization (see §173.21(f) of this subchapter).
- 22 If the hazardous material is in dispersion in organic liquid, the organic liquid must have a flash point above 50 °C (122 °F).
- 23 This material may be transported under the provisions of Division 4.1 only if it is so packed that the percentage of diluent will not fall below that stated in the shipping description at any time during transport. Quantities of not more than 500 g per package with not less than 10 percent water by mass may also be classed in Division 4.1, provided a negative test result is obtained when tested in accordance with test series 6(c) of the UN Manual of Tests and Criteria (IBR, see §171.7 of this subchapter).
- 24 Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.
- 26 This entry does not include ammonium permanganate, the transport of which is prohibited except when approved by the Associate Administrator.
- 28 The dihydrated sodium salt of dichloroisocyanuric acid is not subject to the requirements of this subchapter.
- 29 Lithium cells and batteries and equipment containing or packed with lithium cells and batteries which do not comply with the provisions of §173.185 of this subchapter may be transported only if they are approved by the Associate Administrator.
- 30 Sulfur is not subject to the requirements of this subchapter if transported in a non-bulk packaging or if formed to a specific shape (for example, prills, granules, pellets, pastilles, or flakes). A bulk packaging containing sulfur is not subject to the placarding requirements of subpart F of this part, if it is marked with the appropriate identification number as required by subpart D of this part. Molten sulfur must be marked as required by §172.325 of this subchapter.
- 31 Materials which have undergone sufficient heat treatment to render them non-hazardous are not subject to the requirements of this subchapter.
- 32 Polymeric beads and molding compounds may be made from polystyrene, poly(methyl methacrylate) or other polymeric material.
- 33 Ammonium nitrites and mixtures of an inorganic nitrite with an ammonium salt are prohibited.

- 34 The commercial grade of calcium nitrate fertilizer, when consisting mainly of a double salt (calcium nitrate and ammonium nitrate) containing not more than 10 percent ammonium nitrate and at least 12 percent water of crystallization, is not subject to the requirements of this subchapter.
- 35 Antimony sulphides and oxides which do not contain more than 0.5 percent of arsenic calculated on the total mass do not meet the definition of Division 6.1.
- 36 The maximum net quantity per package is 5 L (1 gallon) or 5 kg (11 pounds).
- 37 Unless it can be demonstrated by testing that the sensitivity of the substance in its frozen state is no greater than in its liquid state, the substance must remain liquid during normal transport conditions. It must not freeze at temperatures above  $-15^{\circ}\text{C}$  ( $5^{\circ}\text{F}$ ).
- 38 If this material shows a violent effect in laboratory tests involving heating under confinement, the labeling requirements of Special Provision 53 apply, and the material must be packaged in accordance with packing method OP6 in § 173.225 of this subchapter. If the SADT of the technically pure substance is higher than  $75^{\circ}\text{C}$ , the technically pure substance and formulations derived from it are not self-reactive materials and, if not meeting any other hazard class, are not subject to the requirements of this subchapter.
- 39 This substance may be carried under provisions other than those of Class 1 only if it is so packed that the percentage of water will not fall below that stated at any time during transport. When phlegmatized with water and inorganic inert material, the content of urea nitrate must not exceed 75 percent by mass and the mixture should not be capable of being detonated by test 1(a)(i) or test 1(a)(ii) in the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter).
- 40 Polyester resin kits consist of two components: a base material (Class 3, Packing Group II or III) and an activator (organic peroxide), each separately packed in an inner packaging. The organic peroxide must be type D, E, or F, not requiring temperature control, and be limited to a quantity of 125 mL (4.22 ounces) per inner packaging if liquid, and 500 g (1 pound) if solid. The components may be placed in the same outer packaging provided they will not interact dangerously in the event of leakage. Packing group will be II or III, according to the criteria for Class 3, applied to the base material.
- 43 The membrane filters, including paper separators and coating or backing materials, that are present in transport, must not be able to propagate a detonation as tested by one of the tests described in the UN Manual of Tests and Criteria, Part I, Test series 1(a) (IBR, see § 171.7 of this subchapter). On the basis of the results of suitable burning rate tests, and taking into account the standard tests in the UN Manual of Tests and Criteria, Part III, subsection 33.2.1 (IBR, see § 171.7 of this subchapter), nitrocellulose membrane filters in the form in which they are to be transported that do not meet the criteria for a Division 4.1 material are not subject to the requirements of this subchapter. Packagings must be so constructed that explosion is not possible by reason of increased internal pressure. Nitrocellulose membrane filters covered by this entry, each with a mass not exceeding 0.5 g, are not subject to the requirements of this subchapter when contained individually in an article or a sealed packet.
- 44 The formulation must be prepared so that it remains homogenous and does not separate during transport. Formulations with low nitrocellulose contents and neither showing dangerous properties when tested for their ability to detonate, deflagrate or explode when heated under defined confinement by the appropriate test methods and criteria in the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter), nor classed as a Division 4.1 (flammable solid) when tested in accordance with the procedures specified in § 173.124 of this subchapter (chips, if necessary, crushed and sieved to a particle size of less than 1.25 mm), are not subject to the requirements of this subchapter.
- 45 Temperature should be maintained between  $18^{\circ}\text{C}$  ( $64.4^{\circ}\text{F}$ ) and  $40^{\circ}\text{C}$  ( $104^{\circ}\text{F}$ ). Tanks containing solidified methacrylic acid must not be reheated during transport.
- 46 This material must be packed in accordance with packing method OP6 (see § 173.225 of this subchapter). During transport, it must be protected from direct sunshine and stored (or kept) in a cool and well-ventilated place, away from all sources of heat.
- 47 Mixtures of solids which are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to this subchapter provided there is no free liquid in the packet.
- 48 Mixtures of solids which are not subject to this subchapter and toxic liquids may be transported under this entry without first

- applying the classification criteria of Division 6.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. This entry may not be used for solids containing a Packing Group I liquid.
- 49 Mixtures of solids which are not subject to this subchapter and corrosive liquids may be transported under this entry without first applying the classification criteria of Class 8, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level.
- 50 Cases, cartridge, empty with primer which are made of metallic or plastic casings and meeting the classification criteria of Division 1.4 are not regulated for domestic transportation.
- 51 This description applies to items previously described as “Toy propellant devices, Class C” and includes reloadable kits. Model rocket motors containing 30 grams or less propellant are classed as Division 1.4S and items containing more than 30 grams of propellant but not more than 62.5 grams of propellant are classed as Division 1.4C.
- 52 This entry may only be used for substances that do not exhibit explosive properties of Class 1 (explosive) when tested in accordance with Test Series 1 and 2 of Class 1 (explosive) in the UN Manual of Tests and Criteria, Part I (incorporated by reference; see § 171.7 of this subchapter).
- 53 Packages of these materials must bear the subsidiary risk label, “EXPLOSIVE”, unless otherwise provided in this subchapter or through an approval issued by the Associate Administrator, or the competent authority of the country of origin. A copy of the approval shall accompany the shipping papers.
- 54 Maneb or maneb preparations not meeting the definition of Division 4.3 or any other hazard class are not subject to the requirements of this subchapter when transported by motor vehicle, rail car, or aircraft.
- 55 This device must be approved in accordance with § 173.56 of this subchapter by the Associate Administrator.
- 56 A means to interrupt and prevent detonation of the detonator from initiating the detonating cord must be installed between each electric detonator and the detonating cord ends of the jet perforating guns before the charged jet perforating guns are offered for transportation.
- 57 Maneb or Maneb preparations stabilized against self-heating need not be classified in Division 4.2 when it can be demonstrated by testing that a volume of 1 m<sup>3</sup> of substance does not self-ignite and that the temperature at the center of the sample does not exceed 200 °C, when the sample is maintained at a temperature of not less than 75 °C ± 2 °C for a period of 24 hours, in accordance with procedures set forth for testing self-heating materials in the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter).
- 58 Aqueous solutions of Division 5.1 inorganic solid nitrate substances are considered as not meeting the criteria of Division 5.1 if the concentration of the substances in solution at the minimum temperature encountered in transport is not greater than 80% of the saturation limit.
- 59 Ferrocium, stabilized against corrosion, with a minimum iron content of 10 percent is not subject to the requirements of this subchapter.
- 60 After September 30, 1997, an oxygen generator, chemical, that is shipped with its means of initiation attached must incorporate at least two positive means of preventing unintentional actuation of the generator, and be classed and approved by the Associate Administrator. The procedures for approval of a chemical oxygen generator that contains an explosive means of initiation (e.g., a primer or electric match) are specified in § 173.56 of this subchapter. Each person who offers a chemical oxygen generator for transportation after September 30, 1997, shall: (1) ensure that it is offered in conformance with the conditions of the approval; (2) maintain a copy of the approval at each facility where the chemical oxygen generator is packaged; and (3) mark the approval number on the outside of the package.
- 61 A chemical oxygen generator is spent if its means of ignition and all or a part of its chemical contents have been expended.
- 64 The group of alkali metals includes lithium, sodium, potassium, rubidium, and caesium.
- 65 The group of alkaline earth metals includes magnesium, calcium, strontium, and barium.
- 66 Formulations of these substances containing not less than 30 percent non-volatile, non-flammable phlegmatizer are not subject to this subchapter.
- 70 Black powder that has been classed in accordance with the requirements of § 173.56 of this subchapter may be reclassified and offered for domestic transportation as a Division 4.1 material if it is offered for transportation and transported in accordance with the limitations and packaging requirements of § 173.170 of this subchapter.
- 74 During transport, this material must be protected from direct sunshine and stored

- or kept in a cool and well-ventilated place, away from all sources of heat.
- 77 For domestic transportation, a Division 5.1 subsidiary risk label is required only if a carbon dioxide and oxygen mixture contains more than 23.5% oxygen.
- 78 This entry may not be used to describe compressed air which contains more than 23.5 percent oxygen. An oxidizer label is not required for any oxygen concentration of 23.5 percent or less.
- 79 This entry may not be used for mixtures that meet the definition for oxidizing gas.
- 81 Polychlorinated biphenyl items, as defined in 40 CFR 761.3, for which specification packagings are impractical, may be packaged in non-specification packagings meeting the general packaging requirements of subparts A and B of part 173 of this subchapter. Alternatively, the item itself may be used as a packaging if it meets the general packaging requirements of subparts A and B of part 173 of this subchapter.
- 101 The name of the particular substance or article must be specified.
- 102 The ends of the detonating cord must be tied fast so that the explosive cannot escape. The articles may be transported as in Division 1.4 Compatibility Group D (1.4D) if all of the conditions specified in §173.63(a) of this subchapter are met.
- 103 Detonators which will not mass detonate and undergo only limited propagation in the shipping package may be assigned to 1.4B classification code. Mass detonate means that more than 90 percent of the devices tested in a package explode practically simultaneously. Limited propagation means that if one detonator near the center of a shipping package is exploded, the aggregate weight of explosives, excluding ignition and delay charges, in this and all additional detonators in the outside packaging that explode may not exceed 25 grams.
- 105 The word "Agents" may be used instead of "Explosives" when approved by the Associate Administrator.
- 106 The recognized name of the particular explosive may be specified in addition to the type.
- 107 The classification of the substance is expected to vary especially with the particle size and packaging but the border lines have not been experimentally determined; appropriate classifications should be verified following the test procedures in §§173.57 and 173.58 of this subchapter.
- 108 Fireworks must be so constructed and packaged that loose pyrotechnic composition will not be present in packages during transportation.
- 109 Rocket motors must be nonpropulsive in transportation unless approved in accordance with §173.56 of this subchapter. A rocket motor to be considered "nonpropulsive" must be capable of unrestrained burning and must not appreciably move in any direction when ignited by any means.
- 110 Fire extinguishers transported under UN1044 may include installed actuating cartridges (cartridges, power device of Division 1.4C or 1.4S), without changing the classification of Division 2.2, provided the aggregate quantity of deflagrating (propellant) explosives does not exceed 3.2 grams per extinguishing unit.
- 111 Explosive substances of Division 1.1 Compatibility Group A (1.1A) are forbidden for transportation if dry or not desensitized, unless incorporated in a device.
- 113 The sample must be given a tentative approval by an agency or laboratory in accordance with §173.56 of this subchapter.
- 114 Jet perforating guns, charged, oil well, without detonator may be reclassified to Division 1.4 Compatibility Group D (1.4D) if the following conditions are met:
- The total weight of the explosive contents of the shaped charges assembled in the guns does not exceed 90.5 kg (200 pounds) per vehicle; and
  - The guns are packaged in accordance with Packing Method US 1 as specified in §173.62 of this subchapter.
- 115 Boosters with detonator, detonator assemblies and boosters with detonators in which the total explosive charge per unit does not exceed 25 g, and which will not mass detonate and undergo only limited propagation in the shipping package may be assigned to 1.4B classification code. Mass detonate means more than 90 percent of the devices tested in a package explode practically simultaneously. Limited propagation means that if one booster near the center of the package is exploded, the aggregate weight of explosives, excluding ignition and delay charges, in this and all additional boosters in the outside packaging that explode may not exceed 25 g.
- 116 Fuzes, detonating may be classed in Division 1.4 if the fuzes do not contain more than 25 g of explosive per fuze and are made and packaged so that they will not cause functioning of other fuzes, explosives or other explosive devices if one of the fuzes detonates in a shipping packaging or in adjacent packages.
- 117 If shipment of the explosive substance is to take place at a time that freezing weather is anticipated, the water contained in the explosive substance must be mixed with denatured alcohol so that freezing will not occur.
- 118 This substance may not be transported under the provisions of Division 4.1 unless specifically authorized by the Associate Administrator.
- 119 This substance, when in quantities of not more than 11.5 kg (25.3 pounds), with not less than 10 percent water, by mass,

- also may be classed as Division 4.1, provided a negative test result is obtained when tested in accordance with test series 6(c) of the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter).
- 120 The phlegmatized substance must be significantly less sensitive than dry PETN.
- 121 This substance, when containing less alcohol, water or phlegmatizer than specified, may not be transported unless approved by the Associate Administrator.
- 123 Any explosives, blasting, type C containing chlorates must be segregated from explosives containing ammonium nitrate or other ammonium salts.
- 125 Lactose or glucose or similar materials may be used as a phlegmatizer provided that the substance contains not less than 90%, by mass, of phlegmatizer. These mixtures may be classified in Division 4.1 when tested in accordance with test series 6(c) of the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter) and approved by the Associate Administrator. Testing must be conducted on at least three packages as prepared for transport. Mixtures containing at least 98%, by mass, of phlegmatizer are not subject to the requirements of this subchapter. Packages containing mixtures with not less than 90% by mass, of phlegmatizer need not bear a POISON subsidiary risk label.
- 127 Mixtures containing oxidizing and organic materials transported under this entry may not meet the definition and criteria of a Class 1 material. (See § 173.50 of this subchapter.)
- 128 Regardless of the provisions of § 172.101(c)(12), aluminum smelting by-products and aluminum remelting by-products described under this entry, meeting the definition of Class 8, Packing Group II and III may be classed as a Division 4.3 material and transported under this entry. The presence of a Class 8 hazard must be communicated as required by this Part for subsidiary hazards.
- 129 These materials may not be classified and transported unless authorized by the Associate Administrator on the basis of results from Series 2 Test and a Series 6(c) Test from the UN Manual of Tests and Criteria (IBR, see § 171.7 of this subchapter) on packages as prepared for transport. The packing group assignment and packaging must be approved by the Associate Administrator for Hazardous Materials Safety on the basis of the criteria in § 173.21 of this subchapter and the package type used for the Series 6(c) test.
- 130 For other than a dry battery specifically covered by another entry in the § 172.101 Table, “Batteries, dry” are not subject to the requirements of this subchapter when they are securely packaged and offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals) and protects against short circuits.
- 131 This material may not be offered for transportation unless approved by the Associate Administrator.
- 132 This entry may only be used for uniform, ammonium nitrate-base fertilizer mixtures, containing nitrogen, phosphate or potash, meeting the following criteria: (1) Contains not more than 70% ammonium nitrate; and (2) Contains not more than 0.4% total combustible, organic material calculated as carbon or with not more than 45% ammonium nitrate and unrestricted combustible material. Fertilizers within these composition limits are only subject to the requirements of this subchapter when transported by aircraft or vessel, and are not subject to the requirements of this subchapter if shown by a trough test, as specified in the UN Manual of Tests and Criteria, Part III, Sub-section 38.2 (IBR, see § 171.7 of this subchapter), not to be liable to self-sustaining decomposition.
- 134 This entry only applies to vehicles, machinery and equipment which are powered by wet batteries, sodium batteries, or lithium batteries and which are transported with these batteries installed. Examples of such items are electrically-powered cars, lawn mowers, wheelchairs and other mobility aids. A self-propelled vehicle which also contain an internal combustion engine must be consigned under the entry “Vehicle, flammable gas powered” or “Vehicle, flammable liquid powered”, as appropriate.
- 135 The entries “Vehicle, flammable gas powered” or “Vehicle, flammable liquid powered”, as appropriate, must be used when internal combustion engines are installed in a vehicle.
- 136 This entry only applies to machinery and apparatus containing hazardous materials as in integral element of the machinery or apparatus. It may not be used to describe machinery or apparatus for which a proper shipping name exists in the § 172.101 Table. Except when approved by the Associate Administrator, machinery or apparatus may only contain hazardous materials for which exceptions are referenced in Column (8) of the § 172.101 Table and are provided in part 173, subpart D, of this subchapter. Hazardous materials shipped under this entry are excepted from the labeling requirements of this subchapter unless offered for transportation or transported by aircraft and are not subject to the placarding requirements of part 172, subpart F, of this subchapter. Orientation markings as described in § 172.312 (a)(2) are required when liquid hazardous materials may escape due to incorrect orientation. The machinery or apparatus, if unpackaged, or the packaging in which it is contained shall be marked “Dangerous

- goods in machinery” or “Dangerous goods in apparatus”, as appropriate, with the identification number UN3363. For transportation by aircraft, machinery or apparatus may not contain any material forbidden for transportation by passenger or cargo aircraft. The Associate Administrator may except from the requirements of this subchapter, equipment, machinery and apparatus provided:
- a. It is shown that it does not pose a significant risk in transportation;
  - b. The quantities of hazardous materials do not exceed those specified in §173.4 of this subchapter; and
  - c. The equipment, machinery or apparatus conforms with §173.222 of this subchapter.
- 137 Cotton, dry, is not subject to the requirements of this subchapter when it is baled in accordance with ISO 8115, “Cotton Bales—Dimensions and Density” (IBR, see §171.7 of this subchapter) to a density of at least 360 kg/m<sup>3</sup> (22.4lb/ft<sup>3</sup>) and it is transported in a freight container or closed transport vehicle.
- 138 Lead compounds which, when mixed in a ratio of 1:1000 with 0.07M (Molar concentration) hydrochloric acid and stirred for one hour at a temperature of 23 °C ±2 °C, exhibit a solubility of 5% or less are considered insoluble.
- 139 Use of the “special arrangement” proper shipping names for international shipments must be made under an IAEA Certificate of Competent Authority issued by the Associate Administrator in accordance with the requirements in §173.471, §173.472, or §173.473 of this subchapter. Use of these proper shipping names for domestic shipments may be made only under a DOT exemption, as defined in, and in accordance with the requirements of subpart B of part 107 of this subchapter.
- 140 This material is regulated only when it meets the defining criteria for a hazardous substance or a marine pollutant. In addition, the column 5 reference is modified to read “III” on those occasions when this material is offered for transportation or transported by highway or rail.
- 141 A toxin obtained from a plant, animal, or bacterial source containing an infectious substance, or a toxin contained in an infectious substance, must be classed as Division 6.2, described as an infectious substance, and assigned to UN 2814 or UN 2900, as appropriate.
- 142 These hazardous materials may not be classified and transported unless authorized by the Associate Administrator. The Associate Administrator will base the authorization on results from Series 2 tests and a Series 6(c) test from the UN Manual of Tests and Criteria (IBR, see §171.7 of this subchapter) on packages as prepared for transport in accordance with the requirements of this subchapter.
- 143 These articles may contain:
- a. Division 2.2 compressed gases, including oxygen;
  - b. Signal devices (Class 1) which may include smoke and illumination signal flares. Signal devices must be packed in plastic or fiberboard inner packagings;
  - c. Electric storage batteries;
  - d. First aid kits; or
  - e. Strike anywhere matches.
- 144 If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 180.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see §171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.
- 145 This entry applies to formulations that neither detonate in the cavitated state nor deflagrate in laboratory testing, show no effect when heated under confinement, exhibit no explosive power, and are thermally stable (self-accelerating decomposition temperature (SADT) at 60 °C (140 °F) or higher for a 50 kg (110.2 lbs.) package). Formulations not meeting these criteria must be transported under the provisions applicable to the appropriate entry in the Organic Peroxide Table in §173.225 of this subchapter.
- 146 This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in §171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
- 147 This entry applies to non-sensitized emulsions, suspensions and gels consisting primarily of a mixture of ammonium nitrate and a fuel intended to produce a Type E blasting explosive only after further processing. The mixture typically has the following composition: 60–85% ammonium nitrate; 5–30% water; 2–8% fuel; 0.5–4% emulsifier or thickening agent; 0–10% soluble flame suppressants; and trace additives. Other inorganic nitrate salts may replace part of the ammonium nitrate. These substances may not be classified and transported unless approved by the Associate Administrator.
- 148 When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of

- this subchapter for inner packagings may be increased to 5 L (1.3 gallons).
- 150 This description may be used only for uniform mixtures of fertilizers containing ammonium nitrate as the main ingredient within the following composition limits:
- a. Not less than 90% ammonium nitrate with not more than 0.2% total combustible, organic material calculated as carbon, and with added matter, if any, that is inorganic and inert when in contact with ammonium nitrate; or
  - b. Less than 90% but more than 70% ammonium nitrate with other inorganic materials, or more than 80% but less than 90% ammonium nitrate mixed with calcium carbonate and/or dolomite, and not more than 0.4% total combustible, organic material calculated as carbon; or
  - c. Ammonium nitrate-based fertilizers containing mixtures of ammonium nitrate and ammonium sulphate with more than 45% but less than 70% ammonium nitrate, and not more than 0.4% total combustible, organic material calculated as carbon such that the sum of the percentage of compositions of ammonium nitrate and ammonium sulphate exceeds 70%.
- 151 If this material meets the definition of a flammable liquid in §173.120 of this subchapter, a FLAMMABLE LIQUID label is also required and the basic description on the shipping paper must indicate the Class 3 subsidiary hazard.
- 153 The following applies to aerosols:
- a. Division 2.1 applies when the aerosol is flammable according to §173.306(i) of this subchapter.
  - b. Division 2.2 applies when the contents of the aerosol do not meet the criteria for Division 2.1, or Division 2.3.
  - c. Division 2.3 gases may not be used in an aerosol dispenser.
  - d. When the contents are classified as Division 6.1 or Class 8, the aerosol must have a subsidiary risk of Division 6.1 or Class 8.
  - e. Aerosols with contents meeting the criteria for PG I and PG II for Division 6.1 or Class 8 are forbidden for transportation.
  - f. Aerosols must meet the definition of aerosols in §171.8 of this subchapter.
- 155 Fish meal or fish scrap may not be transported if the temperature at the time of loading either exceeds 35 °C (95 °F), or exceeds 5 °C (41 °F) above the ambient temperature, whichever is higher.
- 156 Asbestos that is immersed or fixed in a natural or artificial binder material, such as cement, plastic, asphalt, resins or mineral ore, or contained in manufactured products is not subject to the requirements of this subchapter.
- 157 This entry includes hybrid electric vehicles powered by both an internal combustion engine and wet, sodium or lithium batteries, transported with one or more batteries installed. Vehicles containing an internal combustion engine must be described as “Vehicle, flammable gas powered,” UN3166, or “Vehicle, flammable liquid powered,” UN3166, as appropriate.
- 159 This material must be protected from direct sunshine and kept in a cool, well-ventilated place away from sources of heat.
- 160 This entry applies to articles that are used as life-saving vehicle air bag inflators, air bag modules or seat-belt pretensioners containing Class 1 (explosive) materials or materials of other hazard classes. Air bag inflators and modules must be tested in accordance with Test series 6(c) of Part I of the UN Manual of Tests and Criteria (incorporated by reference; see §171.7 of this subchapter), with no explosion of the device, no fragmentation of device casing or pressure vessel, and no projection hazard or thermal effect that would significantly hinder fire-fighting or other emergency response efforts in the immediate vicinity. If the air bag inflator unit satisfactorily passes the series 6(c) test, it is not necessary to repeat the test on the air bag module.
- 161 For domestic transport, air bag inflators, air bag modules or seat belt pretensioners that meet the criteria for a Division 1.4G explosive must be transported using the description, “Articles, pyrotechnic for technical purposes,” UN0431.
- 162 This material may be transported under the provisions of Division 4.1 only if it is packed so that at no time during transport will the percentage of diluent fall below the percentage that is stated in the shipping description.
- (2) “A” codes. These provisions apply only to transportation by aircraft:
- Code/Special Provisions*
- A1 Single packagings are not permitted on passenger aircraft.
- A2 Single packagings are not permitted on aircraft.
- A3 For combination packagings, if glass inner packagings (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packagings.
- A4 Liquids having an inhalation toxicity of Packing Group I are not permitted on aircraft.
- A5 Solids having an inhalation toxicity of Packing Group I are not permitted on passenger aircraft and may not exceed a maximum net quantity per package of 15 kg (33 pounds) on cargo aircraft.
- A6 For combination packagings, if plastic inner packagings are used, they must be packed in tightly closed metal receptacles before packing in outer packagings.



- A7 Steel packagings must be corrosion-resistant or have protection against corrosion.
- A8 For combination packagings, if glass inner packagings (including ampoules) are used, they must be packed with cushioning material in tightly closed metal receptacles before packing in outer packagings.
- A9 For combination packagings, if plastic bags are used, they must be packed in tightly closed metal receptacles before packing in outer packagings.
- A10 When aluminum or aluminum alloy construction materials are used, they must be resistant to corrosion.
- A11 For combination packagings, when metal inner packagings are permitted, only specification cylinders constructed of metals which are compatible with the hazardous material may be used.
- A13 Bulk packagings are not authorized for transportation by aircraft.
- A19 Combination packagings consisting of outer fiber drums or plywood drums, with inner plastic packagings, are not authorized for transportation by aircraft.
- A20 Plastic bags as inner receptacles of combination packagings are not authorized for transportation by aircraft.
- A29 Combination packagings consisting of outer expanded plastic boxes with inner plastic bags are not authorized for transportation by aircraft.
- A30 Ammonium permanganate is not authorized for transportation on aircraft.
- A34 Aerosols containing a corrosive liquid in Packing Group II charged with a gas are not permitted for transportation by aircraft.
- A35 This includes any material which is not covered by any of the other classes but which has an anesthetic, narcotic, noxious or other similar properties such that, in the event of spillage or leakage on an aircraft, extreme annoyance or discomfort could be caused to crew members so as to prevent the correct performance of assigned duties.
- A37 This entry applies only to a material meeting the definition in §171.8 of this subchapter for self-defense spray.
- A51 When transported by cargo-only aircraft, an oxygen generator must conform to the provisions of an approval issued under Special Provision 60 and be contained in a packaging prepared and originally offered for transportation by the approval holder.
- A52 A cylinder containing Oxygen, compressed, may not be loaded into a passenger-carrying aircraft or into an inaccessible cargo location on a cargo-only aircraft unless it is placed in an overpack or outer packaging that conforms to the performance criteria of Air Transport Association (ATA) Specification No. 300 (IBR, see §171.7 of this subchapter) for Category I shipping containers.
- A53 Refrigerating machines and refrigerating machine components are not subject to the requirements of this subchapter when containing less than 12 kg (26.4 pounds) of a non-flammable gas or when containing 12 L (3 gallons) or less of ammonia solution (UN2672) (see §173.307 of this subchapter).
- A54 Lithium batteries or lithium batteries contained or packed with equipment that exceed the maximum gross weight allowed by Column (9B) of the §172.101 Table may only be transported on cargo aircraft if approved by the Associate Administrator.
- A55 Prototype lithium batteries and cells that are packed with not more than 24 cells or 12 batteries per packaging that have not completed the test requirements in Sub-section 38.3 of the UN Manual of Tests and Criteria (incorporated by reference; see §171.7 of this subchapter) may be transported by cargo aircraft if approved by the Associate Administrator and provided the following requirements are met:
- a. The cells and batteries must be transported in rigid outer packagings that conform to the requirements of Part 178 of this subchapter at the Packing Group I performance level; and
  - b. Each cell and battery must be protected against short circuiting, must be surrounded by cushioning material that is non-combustible and non-conductive, and must be individually packed in an inner packaging that is placed inside an outer specification packaging.
- A56 Radioactive material with a subsidiary hazard of Division 4.2, Packing Group I, must be transported in Type B packages when offered for transportation by aircraft. Radioactive material with a subsidiary hazard of Division 2.1 is forbidden from transport on passenger aircraft.
- A81 The quantity limits in columns (9A) and (9B) do not apply to body fluids known to contain or suspected of containing an infectious substance when transported in primary receptacles not exceeding 1,000 mL (34 ounces) and in outer packagings not exceeding 4 L (1 gallon) and packaged in accordance with §173.196 of this subchapter.
- A82 The quantity limits in columns (9A) and (9B) do not apply to human or animal body parts, whole organs or whole bodies known to contain or suspected of containing an infectious substance.
- (3) “*B*” codes. These provisions apply only to bulk packagings, other than IBCs:
- Code/Special Provisions*
- B1 If the material has a flash point at or above 38 °C (100 °F) and below 93 °C (200 °F),

then the bulk packaging requirements of §173.241 of this subchapter are applicable. If the material has a flash point of less than 38 °C (100 °F), then the bulk packaging requirements of §173.242 of this subchapter are applicable.

- B2 MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
- B3 MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks and DOT 57 portable tanks are not authorized.
- B4 MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
- B5 Only ammonium nitrate solutions with 35 percent or less water that will remain completely in solution under all conditions of transport at a maximum lading temperature of 116 °C (240 °F) are authorized for transport in the following bulk packagings: MC 307, MC 312, DOT 407 and DOT 412 cargo tanks with at least 172 kPa (25 psig) design pressure. The packaging shall be designed for a working temperature of at least 121 °C (250 °F). Only Specifications MC 304, MC 307 or DOT 407 cargo tank motor vehicles are authorized for transportation by vessel.
- B6 Packagings shall be made of steel.
- B7 Safety relief devices are not authorized on multi-unit tank car tanks. Openings for safety relief devices on multi-unit tank car tanks shall be plugged or blank flanged.
- B8 Packagings shall be made of nickel, stainless steel, or steel with nickel, stainless steel, lead or other suitable corrosion resistant metallic lining.
- B9 Bottom outlets are not authorized.
- B10 MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks, and DOT 57 portable tanks are not authorized.
- B11 Tank car tanks must have a test pressure of at least 2,068.5 kPa (300 psig). Cargo and portable tanks must have a design pressure of at least 1,207 kPa (175 psig).
- B13 A nonspecification cargo tank motor vehicle authorized in §173.247 of this subchapter must be at least equivalent in design and in construction to a DOT 406 cargo tank or MC 306 cargo tank (if constructed before August 31, 1995), except as follows:
- Packagings equivalent to MC 306 cargo tanks are excepted from the certification, venting, and emergency flow requirements of the MC 306 specification.
  - Packagings equivalent to DOT 406 cargo tanks are excepted from §§178.345–7(d)(5), circumferential reinforcements; 178.345–10, pressure relief; 178.345–11, outlets; 178.345–14, marking, and 178.345–15, certification.
  - Packagings are excepted from the design stress limits at elevated temperatures, as described in Section VIII of the ASME Code (IBR, see §171.7 of this subchapter).

However, the design stress limits may not exceed 25 percent of the stress for 0 temper at the maximum design temperature of the cargo tank, as specified in the Aluminum Association's "Aluminum Standards and Data" (IBR, see §171.7 of this subchapter).

- B14 Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 °C (60 °F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.
- B15 Packagings must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance.
- B16 The lading must be completely covered with nitrogen, inert gas or other inert materials.
- B18 Open steel hoppers or bins are authorized.
- B23 Tanks must be made of steel that is rubber lined or unlined. Unlined tanks must be passivated before being placed in service. If unlined tanks are washed out with water, they must be repassivated prior to return to service. Lading in unlined tanks must be inhibited so that the corrosive effect on steel is not greater than that of hydrofluoric acid of 65 percent concentration.
- B25 Packagings must be made from monel or nickel or monel-lined or nickel-lined steel.
- B26 Tanks must be insulated. Insulation must be at least 100 mm (3.9 inches) except that the insulation thickness may be reduced to 51 mm (2 inches) over the exterior heater coils. Interior heating coils are not authorized. The packaging may not be loaded with a material outside of the packaging's design temperature range. In addition, the material also must be covered with an inert gas or the container must be filled with water to the tank's capacity. After unloading, the residual material also must be covered with an inert gas or the container must be filled with water to the tank's capacity.
- B27 Tanks must have a service pressure of 1,034 kPa (150 psig). Tank car tanks must have a test pressure rating of 1,379 kPa (200 psig). Lading must be blanketed at all times with a dry inert gas at a pressure not to exceed 103 kPa (15 psig).
- B28 Packagings must be made of stainless steel.
- B30 MC 312, MC 330, MC 331 and DOT 412 cargo tanks and DOT 51 portable tanks must be made of stainless steel, except that steel other than stainless steel may be used in accordance with the provisions

of §173.24b(b) of this subchapter. Thickness of stainless steel for tank shell and heads for cargo tanks and portable tanks must be the greater of 7.62 mm (0.300 inch) or the thickness required for a tank with a design pressure at least equal to 1.5 times the vapor pressure of the lading at 46 °C (115 °F). In addition, MC 312 and DOT 412 cargo tank motor vehicles must:

- a. Be ASME Code (U) stamped for 100% radiography of all pressure-retaining welds;
- b. Have accident damage protection which conforms with §178.345-8 of this subchapter;
- c. Have a MAWP or design pressure of at least 87 psig; and
- d. Have a bolted manway cover.

B32 MC 312, MC 330, MC 331, DOT 412 cargo tanks and DOT 51 portable tanks must be made of stainless steel, except that steel other than stainless steel may be used in accordance with the provisions of §173.24b(b) of this subchapter. Thickness of stainless steel for tank shell and heads for cargo tanks and portable tanks must be the greater of 6.35 mm (0.250 inch) or the thickness required for a tank with a design pressure at least equal to 1.3 times the vapor pressure of the lading at 46 °C (115 °F). In addition, MC 312 and DOT 412 cargo tank motor vehicles must:

- a. Be ASME Code (U) stamped for 100% radiography of all pressure-retaining welds;
- b. Have accident damage protection which conforms with §178.345-8 of this subchapter;
- c. Have a MAWP or design pressure of at least 87 psig; and
- d. Have a bolted manway cover.

B33 MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I.

TABLE I—MAXIMUM AMBIENT TEMPERATURE—  
GASOLINE

ASTM D439 volatility class	Maximum lading and ambient temperature (see note 1)
A ..... (RVP≤9.0 psia)	131 °F
B ..... (RVP≤10.0 psia)	124 °F
C ..... (RVP≤11.5 psia)	116 °F
D ..... (RVP≤13.5 psia)	107 °F
E .....	100 °F

TABLE I—MAXIMUM AMBIENT TEMPERATURE—  
GASOLINE—Continued

ASTM D439 volatility class	Maximum lading and ambient temperature (see note 1)
(RVP≤15.0 psia)	

Note 1: Based on maximum lading pressure of 1 psig at top of cargo tank.

B35 Tank cars containing hydrogen cyanide may be alternatively marked "Hydrocyanic acid, liquefied" if otherwise conforming to marking requirements in subpart D of this part. Tank cars marked "HYDROCYANIC ACID" prior to October 1, 1991 do not need to be remarked.

B37 The amount of nitric oxide charged into any tank car tank may not exceed 1,379 kPa (200 psig) at 21 °C (70 °F).

B42 Tank cars must have a test pressure of 34.47 Bar (500 psig) or greater and conform to Class 105J. Each tank car must have a reclosing pressure relief device having a start-to-discharge pressure of 10.34 Bar (150 psig). The tank car specification may be marked to indicate a test pressure of 13.79 Bar (200 psig).

B44 All parts of valves and safety relief devices in contact with lading must be of a material which will not cause formation of acetylides.

B45 Each tank must have a reclosing combination pressure relief device equipped with stainless steel or platinum rupture discs approved by the AAR Tank Car Committee.

B46 The detachable protective housing for the loading and unloading valves of multi-unit tank car tanks must withstand tank test pressure and must be approved by the Associate Administrator.

B47 Each tank may have a reclosing pressure relief device having a start-to-discharge pressure setting of 310 kPa (45 psig).

B48 Portable tanks in sodium metal service may be visually inspected at least once every 5 years instead of being retested hydrostatically. Date of the visual inspection must be stenciled on the tank near the other required markings.

B49 Tanks equipped with interior heater coils are not authorized. Single unit tank car tanks must have a reclosing pressure relief device having a start-to-discharge pressure set at no more than 1551 kPa (225 psig).

B50 Each valve outlet of a multi-unit tank car tank must be sealed by a threaded solid plug or a threaded cap with inert luting or gasket material. Valves must be of stainless steel and the caps, plugs, and valve seats must be of a material that will not deteriorate as a result of contact with the lading.

B52 Notwithstanding the provisions of §173.24b of this subchapter, non-reclosing

**§ 172.102**

- pressure relief devices are authorized on DOT 57 portable tanks.
- B53 Packagings must be made of either aluminum or steel.
- B54 Open-top, sift-proof rail cars are also authorized.
- B55 Water-tight, sift-proof, closed-top, metal-covered hopper cars, equipped with a venting arrangement (including flame arrestors) approved by the Associate Administrator are also authorized.
- B56 Water-tight, sift-proof, closed-top, metal-covered hopper cars are also authorized if the particle size of the hazardous material is not less than 149 microns.
- B57 Class 115A tank car tanks used to transport chloroprene must be equipped with a non-reclosing pressure relief device of a diameter not less than 305 mm (12 inches) with a maximum rupture disc pressure of 310 kPa (45 psig).
- B59 Water-tight, sift-proof, closed-top, metal-covered hopper cars are also authorized provided that the lading is covered with a nitrogen blanket.
- B60 DOT Specification 106A500X multi-unit tank car tanks that are not equipped with a pressure relief device of any type are authorized. For the transportation of phosgene, the outage must be sufficient to prevent tanks from becoming liquid full at 55 °C (130 °F).
- B61 Written procedures covering details of tank car appurtenances, dome fittings, safety devices, and marking, loading, handling, inspection, and testing practices must be approved by the Associate Administrator before any single unit tank car tank is offered for transportation.
- B64 Each single unit tank car tank built after December 31, 1990 must be equipped with a tank head puncture resistance system that conforms to §179.16 of this subchapter.
- B65 Tank cars must have a test pressure of 34.47 Bar (500 psig) or greater and conform to Class 105A. Each tank car must have a pressure relief device having a start-to-discharge pressure of 15.51 Bar (225 psig). The tank car specification may be marked to indicate a test pressure of 20.68 Bar (300 psig).
- B66 Each tank must be equipped with gas tight valve protection caps. Outage must be sufficient to prevent tanks from becoming liquid full at 55 °C (130 °F). Specification 110A500W tanks must be stainless steel.
- B67 All valves and fittings must be protected by a securely attached cover made of metal not subject to deterioration by the lading, and all valve openings, except safety valve, must be fitted with screw plugs or caps to prevent leakage in the event of valve failure.
- B68 Sodium must be in a molten condition when loaded and allowed to solidify before

**49 CFR Ch. I (10–1–04 Edition)**

- shipment. Outage must be at least 5 percent at 98 °C (208 °F). Bulk packagings must have exterior heating coils fusion welded to the tank shell which have been properly stress relieved. The only tank car tanks authorized are Class DOT 105 tank cars having a test pressure of 2,069 kPa (300 psig) or greater.
- B69 Dry sodium cyanide or potassium cyanide may be shipped in sift-proof weather-resistant metal covered hopper cars, covered motor vehicles, portable tanks or non-specification bins. Siftproof, water-resistant, fiberboard IBCs are permitted when transported in closed freight containers or transport vehicles. Bins must be approved by the Associate Administrator.
- B70 If DOT 103ANW tank car tank is used: All cast metal in contact with the lading must have 96.7 percent nickel content; and the lading must be anhydrous and free from any impurities.
- B71 Tank cars must have a test pressure of 20.68 Bar (300 psig) or greater and conform to Class 105, 112, 114 or 120.
- B72 Tank cars must have a test pressure of 34.47 Bar (500 psig) or greater and conform to Class 105J, 106, or 110.
- B74 Tank cars must have a test pressure of 20.68 Bar (300 psig) or greater and conform to Class 105S, 106, 110, 112J, 114J or 120S.
- B76 Tank cars must have a test pressure of 20.68 Bar (300 psig) or greater and conform to Class 105S, 112J, 114J or 120S. Each tank car must have a reclosing pressure relief device having a start-to-discharge pressure of 10.34 Bar (150 psig). The tank car specification may be marked to indicate a test pressure of 13.79 Bar (200 psig).
- B77 Other packaging are authorized when approved by the Associate Administrator.
- B78 Tank cars must have a test pressure of 4.14 Bar (60 psig) or greater and conform to Class 103, 104, 105, 109, 111, 112, 114 or 120. Heater pipes must be of welded construction designed for a test pressure of 500 psig. A 25 mm (1 inch) woven lining of asbestos or other approved material must be placed between the bolster slabbing and the bottom of the tank. If a tank car tank is equipped with a non-reclosing pressure relief device, the rupture disc must be perforated with a 3.2 mm (0.13 inch) diameter hole. If a tank car tank is equipped with a reclosing pressure relief valve, the tank must also be equipped with a vacuum relief valve.
- B80 Each cargo tank must have a minimum design pressure of 276 kPa (40 psig).
- B81 Venting and pressure relief devices for tank car tanks and cargo tanks must be approved by the Associate Administrator.
- B82 Cargo tanks and portable tanks are not authorized.
- B83 Bottom outlets are prohibited on tank car tanks transporting sulfuric acid in concentrations over 65.25 percent.

B84 Packagings must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance for sulfuric acid or spent sulfuric acid in concentration up to 65.25 percent.

B85 Cargo tanks must be marked with the name of the lading in accordance with the requirements of §172.302(b).

B90 Steel tanks conforming or equivalent to ASME specifications which contain solid or semisolid residual motor fuel anti-knock mixture (including rust, scale, or other contaminants) may be shipped by rail freight or highway. The tank must have been designed and constructed to be capable of withstanding full vacuum. All openings must be closed with gasketed blank flanges or vapor tight threaded closures.

B115 Rail cars, highway trailers, roll-on/roll-off bins, or other non-specification bulk packagings are authorized. Packagings must be sift-proof, prevent liquid water from reaching the hazardous material, and be provided with sufficient venting to preclude dangerous accumulation of flammable, corrosive, or toxic gaseous

emissions such as methane, hydrogen, and ammonia. The material must be loaded dry.

(4) *Table 1, Table 2, and Table 3—IB Codes, Organic Peroxide IBC Code, and IP Special IBC Packing Provisions.* These provisions apply only to transportation in IBCs. When no IBC code is assigned in the §172.101 Table for a specific proper shipping name, an IBC may be authorized when approved by the Associate Administrator. When only certain types of IBCs are authorized in Table 2 (IBC Code IB52), alternative types of IBCs may be authorized when approved by the Associate Administrator. The letter “Z” shown in the marking code for composite IBCs must be replaced with a capital code letter designation found in §178.702(a)(2) of this subchapter to specify the material used for the outer packaging. Tables 1, 2, and 3 follow:

TABLE 1—IB CODES (IBC CODES)

IBC Code	Authorized IBCs
IB1 .....	<i>Authorized IBCs:</i> Metal (31A, 31B and 31N). <i>Additional Requirement:</i> Only liquids with a vapor pressure less than or equal to 110 kPa at 50 °C (1.1 bar at 122 °F), or 130 kPa at 55 °C (1.3 bar at 131 °F) are authorized.
IB2 .....	<i>Authorized IBCs:</i> Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). <i>Additional Requirement:</i> Only liquids with a vapor pressure less than or equal to 110 kPa at 50 °C (1.1 bar at 122 °F), or 130kPa at 55 °C (1.3 bar at 131 °F) are authorized.
IB3 .....	<i>Authorized IBCs:</i> Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). <i>Additional Requirement:</i> Only liquids with a vapor pressure less than or equal to 110 kPa at 50 °C (1.1 bar at 122 °F), or 130 kPa at 55 °C (1.3 bar at 131 °F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 3 for UN2672).
IB4 .....	<i>Authorized IBCs:</i> Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N).
IB5 .....	<i>Authorized IBCs:</i> Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 21HZ1 and 31HZ1).
IB6 .....	<i>Authorized IBCs:</i> Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2). <i>Additional Requirement:</i> Composite IBCs 11HZ2 and 21HZ2 may not be used when the hazardous materials being transported may become liquid during transport.
IB7 .....	<i>Authorized IBCs:</i> Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Wooden (11C, 11D and 11F). <i>Additional Requirement:</i> Liners of wooden IBCs must be sift-proof.
IB8 .....	<i>Authorized IBCs:</i> Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).
IB99 .....	IBCs are only authorized if approved by the Associate Administrator.

TABLE 2—ORGANIC PEROXIDE IBC CODE (IB52)

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
3109 .....	ORGANIC PEROXIDE, TYPE F, LIQUID tert-Butyl hydroperoxide, not more than 72% with water. tert-Butyl peroxyacetate, not more than 32% in diluent type A.	31A 31A 31HA1	1250 1250 1000		

TABLE 2—ORGANIC PEROXIDE IBC CODE (IB52)—Continued

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
	tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 32% in diluent type A.	31A	1250		
		31HA1	1000		
	Cumyl hydroperoxide, not more than 90% in diluent type A.	31HA1	1250		
	Dibenzoyl peroxide, not more than 42% as a stable dispersion.	31H1	1000		
	Dicumyl peroxide, less than or equal to 100%.	31A	1250		
		31HA1	1000		
	Di-tert-butyl peroxide, not more than 52% on diluent type B.	31A	1250		
		31HA1	1000		
	1,1-Di-(tert-butylperoxy) cyclohexane, not more than 42% in diluent type A.	31H1	1000		
	Dilauroyl peroxide, not more than 42%, stable dispersion, in water.	31HA1	1000		
	Isopropyl cumyl hydroperoxide, not more than 72% in diluent type A.	31HA1	1250		
	p-Menthyl hydroperoxide, not more than 72% in diluent type A.	31HA1	1250		
	Peroxyacetic acid, stabilized, not more than 17%.	31H1	1500		
		31HA1	1500		
		31A	1500		
	Peroxyacetic acid, with not more than 26% hydrogen peroxide.	31A	1500		
		31HA1	1500		
	Peroxyacetic acid, type F, stabilized .....	31A	1500		
		31HA1	1500		
3110 .....	Dicumyl peroxide, less than or equal to 100%.	31A	2000		
		31H1			
		31HA1			
3119 .....	ORGANIC PEROXIDE, TYPE F, LIQUID, TEMPERATURE CONTROLLED				
	tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent type B.	31HA1	1000	+30 °C	+35 °C
		31A	1250	+30 °C	+35 °C
	tert-Butyl peroxyneodecanoate, not more than 32% in diluent type A.	31A	1250	0 °C	+10 °C
	tert-Butyl peroxyneodecanoate, not more than 42% stable dispersion, in water.	31A	1250	−5 °C	+5 °C
	tert-Butyl peroxy-pivalate, not more than 27% in diluent type B.	31HA1	1000	+10 °C	+15 °C
		31A	1250	+10 °C	+15 °C
	Cumyl peroxyneodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	−15 °C	−5 °C
	Di-(4-tert-butylcyclohexyl) peroxydicarbonate, not more than 42%, stable dispersion, in water.	31HA1	1000	+30 °C	+35 °C
	Dicetyl peroxydicarbonate, not more than 42%, stable dispersion, in water.	31HA1	1000	+30 °C	+35 °C
	Di-(2-ethylhexyl) peroxydicarbonate, not more than 52%, stable dispersion, in water.	31A	1250	−20 °C	−10 °C
	Dimyristyl peroxydicarbonate, not more than 42%, stable dispersion, in water.	31HA1	1000	+15 °C	+20 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 38% in diluent type A.	31HA1	1000	+10 °C	+15 °C
		31A	1250	+10 °C	+15 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 52%, stable dispersion, in water.	31A	1250	+10 °C	+15 °C
	1,1,3,3-Tetramethylbutyl peroxyneodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	−5 °C	+5 °C

TABLE 3—IP CODES

- IP1 IBCs must be packed in closed freight containers or a closed transport vehicle.
- IP2 When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.
- IP3 Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

TABLE 3—IP CODES—Continued

---

IP4	Flexible, fiberboard or wooden IBCs must be sift-proof and water-resistant or be fitted with a sift-proof and water-resistant liner.
IP5	IBCs must have a device to allow venting. The inlet to the venting device must be located in the vapor space of the IBC under maximum filling conditions.
IP6	Non-specification bulk bins are authorized.
IP7	For UN identification numbers 1327, 1363, 1364, 1365, 1386, 1841, 2211, 2217, 2793 and 3314, IBCs are not required to meet the IBC performance tests specified in part 178, subpart N of this subchapter.
IP8	Ammonia solutions may be transported in rigid or composite plastic IBCs (31H1, 31H2 and 31HZ1) that have successfully passed, without leakage or permanent deformation, the hydrostatic test specified in § 178.814 of this subchapter at a test pressure that is not less than 1.5 times the vapor pressure of the contents at 55 °C (131 °F).

---

(5) “N” codes. These provisions apply only to non-bulk packagings:

*Code/Special Provisions*

- |     |   |  |
|-----|---|--|
| N3  | Glass inner packagings are permitted in combination or composite packagings only if the hazardous material is free from hydrofluoric acid.  | subchapter if the material is packaged in strong, tight non-bulk packaging meeting the requirements of subparts A and B of part 173 of this subchapter.  |
| N4  | For combination or composite packagings, glass inner packagings, other than ampoules, are not permitted.  | N12 Plastic packagings are not authorized.   |
| N5  | Glass materials of construction are not authorized for any part of a packaging which is normally in contact with the hazardous material.  | N20 A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle.   |
| N6  | Battery fluid packaged with electric storage batteries, wet or dry, must conform to the packaging provisions of § 173.159 (g) or (h) of this subchapter.  | N25 Steel single packagings are not authorized.  |
| N7  | The hazard class or division number of the material must be marked on the package in accordance with § 172.302 of this subchapter. However, the hazard label corresponding to the hazard class or division may be substituted for the marking.  | N32 Aluminum materials of construction are not authorized for single packagings.   |
| N8  | Nitroglycerin solution in alcohol may be transported under this entry only when the solution is packed in metal cans of not more than 1 L capacity each, overpacked in a wooden box containing not more than 5 L. Metal cans must be completely surrounded with absorbent cushioning material. Wooden boxes must be completely lined with a suitable material impervious to water and nitroglycerin.  | N33 Aluminum drums are not authorized.   |
| N10 | Lighters and their inner packagings, which have been approved by the Associate Administrator (see § 173.21(i) of this subchapter), must be packaged in one of the following outer packagings at the Packing Group II level: 4C1 or 4C2 wooden boxes; 4D plywood boxes; 4F reconstituted wood boxes; 4G fiberboard boxes; or 4H1 or 4H2 plastic boxes. The approval number (e.g., T-* * *) must be marked on each outer package and on the shipping paper. | N34 Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.   |
| N11 | This material is excepted for the specification packaging requirements of this  | N36 Aluminum or aluminum alloy construction materials are permitted only for halogenated hydrocarbons that will not react with aluminum.   |
|     |   | N37 This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the § 172.101 table. |
|     |   | N40 This material is not authorized in the following packagings:   |
|     |   | a. A combination packaging consisting of a 4G fiberboard box with inner receptacles of glass or earthenware;   |
|     |   | b. A single packaging of a 4C2 sift-proof, natural wood box; or  |
|     |   | c. A composite packaging 6PG2 (glass, porcelain or stoneware receptacles within a fiberboard box).   |
|     |   | N41 Metal construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.  |
|     |   | N42 1A1 drums made of carbon steel with thickness of body and heads of not less than 1.3 mm (0.050 inch) and with a corrosion-resistant phenolic lining are authorized for stabilized benzyl chloride if tested  |

- and certified to the Packing Group I performance level at a specific gravity of not less than 1.8.
- N43 Metal drums are permitted as single packagings only if constructed of nickel or monel.
- N45 Copper cartridges are authorized as inner packagings if the hazardous material is not in dispersion.
- N65 Outage must be sufficient to prevent cylinders or spheres from becoming liquid full at 55 °C (130 °F). The vacant space (outage) may be charged with a nonflammable nonliquefied compressed gas if the pressure in the cylinder or sphere at 55 °C (130 °F) does not exceed 125 percent of the marked service pressure.
- N72 Packagings must be examined by the Bureau of Explosives and approved by the Associate Administrator.
- N73 Packagings consisting of outer wooden or fiberboard boxes with inner glass, metal or other strong containers; metal or fiber drums; kegs or barrels; or strong metal cans are authorized and need not conform to the requirements of part 178 of this subchapter.
- N74 Packages consisting of tightly closed inner containers of glass, earthenware, metal or polyethylene, capacity not over 0.5 kg (1.1 pounds) securely cushioned and packed in outer wooden barrels or wooden or fiberboard boxes, not over 15 kg (33 pounds) net weight, are authorized and need not conform to the requirements of part 178 of this subchapter.
- N75 Packages consisting of tightly closed inner packagings of glass, earthenware or metal, securely cushioned and packed in outer wooden barrels or wooden or fiberboard boxes, capacity not over 2.5 kg (5.5 pounds) net weight, are authorized and need not conform to the requirements of part 178 of this subchapter.
- N76 For materials of not more than 25 percent active ingredient by weight, packages consisting of inner metal packagings not greater than 250 mL (8 ounces) capacity each, packed in strong outer packagings together with sufficient absorbent material to completely absorb the liquid contents are authorized and need not conform to the requirements of part 178 of this subchapter.
- N77 For materials of not more than two percent active ingredients by weight, packagings need not conform to the requirements of part 178 of this subchapter, if liquid contents are absorbed in an inert material.
- N78 Packages consisting of inner glass, earthenware, or polyethylene or other non-fragile plastic bottles or jars not over 0.5 kg (1.1 pounds) capacity each, or metal cans not over five pounds capacity each, packed in outer wooden boxes, barrels or kegs, or fiberboard boxes are authorized and need not conform to the requirements of part 178 of this subchapter. Net weight of contents in fiberboard boxes may not exceed 29 kg (64 pounds). Net weight of contents in wooden boxes, barrels or kegs may not exceed 45 kg (99 pounds).
- N79 Packages consisting of tightly closed metal inner packagings not over 0.5 kg (1.1 pounds) capacity each, packed in outer wooden or fiberboard boxes, or wooden barrels, are authorized and need not conform to the requirements of part 178 of this subchapter. Net weight of contents may not exceed 15 kg (33 pounds).
- N80 Packages consisting of one inner metal can, not over 2.5 kg (5.5 pounds) capacity, packed in an outer wooden or fiberboard box, or a wooden barrel, are authorized and need not conform to the requirements of part 178 of this subchapter.
- N82 See §173.306 of this subchapter for classification criteria for flammable aerosols.
- N83 This material may not be transported in quantities of more than 11.5 kg (25.4 lbs) per package.
- N84 The maximum quantity per package is 500 g (1.1 lbs.).
- N85 Packagings certified at the Packing Group I performance level may not be used.
- (6) “*R*” codes. These provisions apply only to transportation by rail. [Reserved]
- (7) “*T*” codes. (i) These provisions apply to the transportation of hazardous materials in UN and IM Specification portable tanks. Portable tank instructions specify the requirements applicable to a portable tank when used for the transportation of a specific hazardous material. These requirements must be met in addition to the design and construction specifications in part 178 of this subchapter. Portable tank instructions T1 through T22 specify the applicable minimum test pressure, the minimum shell thickness (in reference steel), bottom opening requirements and pressure relief requirements. In T23, the organic peroxides and self-reactive substances which are authorized to be transported in portable tanks are listed along with the applicable control and emergency temperatures. Liquefied compressed gases are assigned to portable tank instruction T50. T50 provides the maximum allowable working pressures, bottom opening requirements, pressure relief requirements and degree of filling requirements for liquefied compressed



gases permitted for transport in portable tanks. Refrigerated liquefied gases which are authorized to be transported in portable tanks are specified in tank instruction T75.

(ii) The following table specifies the portable tank requirements applicable to T Codes T1 through T22. Column 1 specifies the T Code. Column 2 specifies the minimum test pressure, in bar (1 bar = 14.5 psig), at which the periodic hydrostatic testing required by §180.605 of this subchapter must be conducted. Column 3 specifies the section ref-

erence for minimum shell thickness or, alternatively, the minimum shell thickness value. Column 4 specifies the applicability of §178.275(g)(3) of this subchapter for the pressure relief devices. When the word "Normal" is indicated, §178.275(g)(3) of this subchapter does not apply. Column 5 references the applicable requirements for bottom openings in part 178 of this subchapter or references "Prohibited" which means bottom openings are prohibited. The table follows:

TABLE OF PORTABLE TANK T CODER T1–T22

[Portable tank code T1–T22 apply to liquid and solid hazardous materials of Classes 3 through 9 which are transported in portable tanks.]

Portable tank instruction (1)	Minimum test pressure (bar) (2)	Minimum shell thickness (in mm-reference steel) (See § 178.274(d)) (3)	Pressure-relief requirements (See § 178.275(g)) (4)	Bottom opening requirements (See § 178.275(d)) (5)
T1 .....	1.5	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(2).
T2 .....	1.5	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(3).
T3 .....	2.65	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(2).
T4 .....	2.65	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(3).
T5 .....	2.65	§ 178.274(d)(2)	§ 178.275(g)(3) .....	Prohibited.
T6 .....	4	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(2).
T7 .....	4	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(3).
T8 .....	4	§ 178.274(d)(2)	Normal .....	Prohibited.
T9 .....	4	6 mm	Normal .....	Prohibited.
T10 .....	4	6 mm	§ 178.275(g)(3) .....	Prohibited.
T11 .....	6	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(3).
T12 .....	6	§ 178.274(d)(2)	§ 178.275(g)(3) .....	§ 178.275(d)(3).
T13 .....	6	6 mm	Normal .....	Prohibited.
T14 .....	6	6 mm	§ 178.275(g)(3) .....	Prohibited.
T15 .....	10	§ 178.274(d)(2)	Normal .....	§ 178.275(d)(3).
T16 .....	10	§ 178.274(d)(2)	§ 178.275(g)(3) .....	§ 178.275(d)(3).
T17 .....	10	6 mm	Normal .....	§ 178.275(d)(3).
T18 .....	10	6 mm	§ 178.275(g)(3) .....	§ 178.275(d)(3).
T19 .....	10	6 mm	§ 178.275(g)(3) .....	Prohibited.
T20 .....	10	8 mm	§ 178.275(g)(3) .....	Prohibited.
T21 .....	10	10 mm	Normal .....	Prohibited.
T22 .....	10	10 mm	§ 178.275(g)(3) .....	Prohibited.

(iii) The following table specifies the portable tank requirements applicable to T23 for self-reactive substances of Division 4.1 and organic peroxides of

Division 5.2 which are authorized to be transported in portable tanks:

**PORTABLE TANK CODE T23**  
[Portable tank code T23 applies to self-reactive substances of Division 4.1 and organic peroxides of Division 5.2.]

UN No.	Hazardous material	Minimum test pressure (bar)	Minimum shell thickness (mm-reference steel) See . . . .	Bottom opening requirements See . . . .	Pressure-relief requirements See . . . .	Filling limits	Control temperature	Emergency temperature
3109	Organic peroxide, Type F, liquid	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	tert-Butyl hydroperoxide, not more than 72% with water. *Provided that steps have been taken to achieve the safety equivalence of 65% tert-Butyl hydroperoxide and 35% water	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Cumyl hydro-peroxide, not more than 90% in diluent type A	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Dicumyl peroxide, less than or equal to 100% in diluent Type B	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Di-tert-butyl peroxide, not more than 32% in diluent type A	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Isopropyl cumyl hydro-peroxide, not more than 72% in diluent type A	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	p-Menthyl hydro-peroxide, not more than 72% in diluent type A	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Pinanyl hydro-peroxide, not more than 50% in diluent type A	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
	Organic peroxide, Type F, solid	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		

		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin. +30 °C	As approved by Assoc. Admin. +35 °C
	Di-cumyl peroxide less than r equal to 100% with inert solids	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin. +30 °C	As approved by Assoc. Admin. +35 °C
3119	Maximum quantity per portable tank 2,000 kg Organic peroxide, Type F, liquid, temperature controlled tert-Butyl peroxyacetate, not more than 32% in diluent Type B tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent type B tert-Butyl peroxyvalate, not more than 27% in diluent Type B tert-Butyl peroxy-3,5,5-trimethyl-hexanoate, not more than 32% in diluent type B Di-(3,5,5-trimethyl-hexanoyl) peroxide, not more than 38% in diluent type A Peroxyacetic acid, distilled, stabilized, not more than 41%	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin. +30 °C	As approved by Assoc. Admin. +35 °C
3120	Organic peroxide Type F, solid, temperature controlled	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin. +30 °C	As approved by Assoc. Admin. +35 °C
3229	Self-reactive liquid Type F	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
3230	Self-reactive solid Type F	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		

**PORTABLE TANK CODE T23—Continued**

[Portable tank code T23 applies to self-reactive substances of Division 4.1 and organic peroxides of Division 5.2.]

UN No.	Hazardous material	Minimum test pressure (bar)	Minimum shell thickness (mm-reference steel) See . . . .	Bottom opening requirements See . . . .	Pressure-relief requirements See . . . .	Filling limits	Control temperature	Emergency temperature
3239	Self-reactive liquid Type F, temperature controlled	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin.	As approved by Assoc. Admin.
3240	Self-reactive solid Type F, temperature controlled	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	As approved by Assoc. Admin.	As approved by Assoc. Admin.

(iv) The following portable tank instruction applies to portable tanks used for the transportation of liquefied compressed gases. The T50 table provides the UN identification number and proper shipping name for each liquefied compressed gas authorized to be transported in a T50 portable tank. The table provides maximum allowable working pressures, bottom opening requirements, pressure relief device requirements and degree of filling requirements for each liquefied compressed gases permitted for transportation in a T50 portable tank. In the minimum test pressure column, "small"

means a portable tank with a diameter of 1.5 meters or less when measured at the widest part of the shell, "sunshield" means a portable tank with a shield covering at least the upper third of the shell, "bare" means no sunshield or insulation is provided, and "insulated" means a complete cladding of sufficient thickness of insulating material necessary to provide a minimum conductance of not more than 0.67 w/m<sup>2</sup>/k. In the pressure relief requirements column, the word "Normal" denotes that a frangible disc as specified in § 178.276(e)(3) of this subchapter is not required. The T50 table follows:

PORTABLE TANK CODE T50

[Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
1005	Ammonia, anhydrous	29.0 25.7 22.0 19.7	Allowed	§ 178.276(e)(3)	0.53
1009	Bromotrifluoromethane or Refrigerant gas R 13B1.	38.0 34.0 30.0 27.5	Allowed	Normal	1.13
1010	Butadienes, stabilized	7.5 7.0 7.0 7.0	Allowed	Normal	0.55
1011	Butane	7.0 7.0 7.0 7.0	Allowed	Normal	0.51
1012	Butylene	8.0 7.0 7.0 7.0	Allowed	Normal	0.53
1017	Chlorine	19.0 17.0 15.0 13.5	Not Allowed	§ 178.276(e)(3)	1.25
1018	Chlorodifluoromethane or Refrigerant gas R 22.	26.0 24.0 21.0 19.0	Allowed	Normal	1.03
1020	Chloropentafluoroethane or Refrigerant gas R 115.	23.0 20.0 18.0 16.0	Allowed	Normal	1.06
1021	1-Chloro-1,2,2,2-tetrafluoroethane or Refrigerant gas R 124.	10.3 9.8 7.9 7.0	Allowed	Normal	1.2

PORTABLE TANK CODE T50—Continued

[Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
1027	Cyclopropane	18.0 16.0 14.5 13.0	Allowed	Normal	0.53
1028	Dichlorodifluoromethane or Refrigerant gas R 12.	16.0 15.0 13.0 11.5	Allowed	Normal	1.15
1029	Dichlorofluoromethane or Refrigerant gas R 21.	7.0 7.0 7.0 7.0	Allowed	Normal	1.23
1030	1,1-Difluoroethane or Refrigerant gas R 152a.	16.0 14.0 12.4 11.0	Allowed	Normal	0.79
1032	Dimethylamine, anhydrous	7.0 7.0 7.0 7.0	Allowed	Normal	0.59
1033	Dimethyl ether	15.5 13.8 12.0 10.6	Allowed	Normal	0.58
1036	Ethylamine	7.0 7.0 7.0 7.0	Allowed	Normal	0.61
1037	Ethyl chloride	7.0 7.0 7.0 7.0	Allowed	Normal	0.8
1040	Ethylene oxide with nitrogen up to a total pressure of 1MPa (10 bar) at 50 °C.	Only authorized in 10 bar insulated portable tanks.	Not allowed	§ 178.276(e)(3)	0.78
1041	Ethylene oxide and carbon dioxide mixture with more than 9% but not more than 87% ethylene oxide.	See MAWP definition in § 178.276(a).	Allowed	Normal	See § 173.32(f)
1055	Isobutylene	8.1 7.0 7.0 7.0	Allowed	Normal	0.52
1060	Methyl acetylene and propadiene mixture, stabilized.	28.0 24.5 22.0 20.0	Allowed	Normal	0.43
1061	Methylamine, anhydrous	10.8 9.6 7.8 7.0	Allowed	Normal	0.58

PORTABLE TANK CODE T50—Continued  
 [Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
1062	Methyl bromide	7.0 7.0 7.0 7.0	Not allowed	§ 178.276(e)(3)	1.51
1063	Methyl chloride or Refrigerant gas R 40.	14.5 12.7 11.3 10.0	Allowed	Normal	0.81
1064	Methyl mercaptan	7.0 7.0 7.0 7.0	Not allowed	§ 178.276(e)(3)	0.78
1067	Dinitrogen tetroxide	7.0 7.0 7.0 7.0	Not allowed	§ 178.276(e)(3)	1.3
1075	Petroleum gas, liquefied	See MAWP definition in § 178.276(a).	Allowed	Normal	See § 173.32(f)
1077	Propylene	28.0 24.5 22.0 20.0	Allowed	Normal	0.43
1078	Refrigerant gas, n.o.s.	See MAWP definition in § 178.276(a).	Allowed	Normal	See § 173.32(f)
1079	Sulphur dioxide	11.6 10.3 8.5 7.6	Not allowed	§ 178.276(e)(3)	1.23
1082	Trifluorochloroethylene, stabilized or Refrigerant gas R 1113.	17.0 15.0 13.1 11.6	Not allowed	§ 178.276(e)(3)	1.13
1083	Trimethylamine, anhydrous	7.0 7.0 7.0 7.0	Allowed	Normal	0.56
1085	Vinyl bromide, stabilized	7.0 7.0 7.0 7.0	Allowed	Normal	1.37
1086	Vinyl chloride, stabilized	10.6 9.3 8.0 7.0	Allowed	Normal	0.81
1087	Vinyl methyl ether, stabilized	7.0 7.0 7.0 7.0	Allowed	Normal	0.67
1581	Chloropicrin and methyl bromide mixture.	7.0 7.0 7.0 7.0	Not Allowed	§ 178.276(e)(3)	1.51

PORTABLE TANK CODE T50—Continued

[Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
1582 .....	Chloropicrin and methyl chloride mixture.	19.2 ..... 16.9 ..... 15.1 ..... 13.1 .....	Not allowed .....	§ 178.276(e)(3) ....	0.81
1858 .....	Hexafluoropropylene compressed or Refrigerant gas R 1216.	19.2 ..... 16.9 ..... 15.1 ..... 13.1 .....	Allowed .....	Normal .....	1.11
1912 .....	Methyl chloride and methylene chloride mixture.	15.2, 13.0, 11.6, 10.1.	Allowed .....	Normal .....	0.81
NA 1954 ...	Insecticide gases, <i>flammable</i> , n.o.s..	See MAWP definition in § 178.276(a).	Allowed .....	Normal .....	§ 173.32(f)
1958 .....	1,2-Dichloro-1,1,2,2-tetrafluoroethane or Refrigerant gas R 114.	7.0 ..... 7.0 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	1.3
1965 .....	Hydrocarbon gas, mixture liquefied, n.o.s..	See MAWP definition in 178.276(a).	Allowed .....	Normal .....	See § 173.32(f)
1969 .....	Isobutane .....	8.5 ..... 7.5 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	0.49
1973 .....	Chlorodifluoromethane and chloropentafluoroethane mixture with fixed boiling point, with approximately 49% chlorodifluoromethane or Refrigerant gas R502.	28.3 ..... 25.3 ..... 22.8 ..... 20.3 .....	Allowed .....	Normal .....	1.05
1974 .....	Chlorodifluorobromomethane or Refrigerant gas R 12B1.	7.4 ..... 7.0 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	1.61
1976 .....	Octafluorocyclobutane or Refrigerant gas RC 318.	8.8 ..... 7.8 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	1.34
1978 .....	Propane .....	22.5 ..... 20.4 ..... 18.0 ..... 16.5 .....	Allowed .....	Normal .....	0.42
1983 .....	1-Chloro-2,2,2-trifluoroethane or Refrigerant gas R 133a.	7.0 ..... 7.0 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	1.18
2035 .....	1,1,1-Trifluoroethane compressed or Refrigerant gas R 143a.	31.0 ..... 27.5 ..... 24.2 ..... 21.8 .....	Allowed .....	Normal .....	0.76
2424 .....	Octafluoropropane or Refrigerant gas R 218.	23.1 ..... 20.8 ..... 18.6 ..... 16.6 .....	Allowed .....	Normal .....	1.07



PORTABLE TANK CODE T50—Continued

[Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
2517 .....	1-Chloro-1,1-difluoroethane or Refrigerant gas R 142b.	8.9 ..... 7.8 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	0.99
2602 .....	Dichlorodifluoromethane and difluoroethane azeotropic mixture with approximately 74% dichlorodifluoromethane or Refrigerant gas R 500.	20.0 ..... 18.0 ..... 16.0 ..... 14.5 .....	Allowed .....	Normal .....	1.01
3057 .....	Trifluoroacetyl chloride .....	14.6 ..... 12.9 ..... 11.3 ..... 9.9 .....	Not allowed .....	§ 178.276(e)(3) ...	1.17
3070 .....	Ethylene oxide and dichlorodifluoromethane mixture with not more than 12.5% ethylene oxide.	14.0 ..... 12.0 ..... 11.0 ..... 9.0 .....	Allowed .....	§ 178.276(e)(3) ...	1.09
3153 .....	Perfluoro (methyl vinyl ether) ..	14.3 ..... 13.4 ..... 11.2 ..... 10.2 .....	Allowed .....	Normal .....	1.14
3159 .....	1,1,1,2-Tetrafluoroethane or Refrigerant gas R 134a.	17.7 ..... 15.7 ..... 13.8 ..... 12.1 .....	Allowed .....	Normal .....	1.04
3161 .....	Liquefied gas, flammable, n.o.s..	See MAWP definition in § 178.276(a).	Allowed .....	Normal .....	§ 173.32(f)
3163 .....	Liquefied gas, n.o.s. ....	See MAWP definition in § 178.276(a).	Allowed .....	Normal .....	§ 173.32(f)
3220 .....	Pentafluoroethane or Refrigerant gas R 125.	34.4 ..... 30.8 ..... 27.5 ..... 24.5 .....	Allowed .....	Normal .....	0.95
3252 .....	Difluoromethane or Refrigerant gas R 32.	43.0 ..... 39.0 ..... 34.4 ..... 30.5 .....	Allowed .....	Normal .....	0.78
3296 .....	Heptafluoropropane or Refrigerant gas R 227.	16.0 ..... 14.0 ..... 12.5 ..... 11.0 .....	Allowed .....	Normal .....	1.2
3297 .....	Ethylene oxide and chlorotetrafluoroethane mixture, with not more than 8.8% ethylene oxide.	8.1 ..... 7.0 ..... 7.0 ..... 7.0 .....	Allowed .....	Normal .....	1.16
3298 .....	Ethylene oxide and pentafluoroethane mixture, with not more than 7.9% ethylene oxide.	25.9 ..... 23.4 ..... 20.9 ..... 18.6 .....	Allowed .....	Normal .....	1.02

PORTABLE TANK CODE T50—Continued

[Portable tank code T50 applies to liquefied compressed gases.]

UN No.	Non-refrigerated liquefied compressed gases	Max. allowable working pressure (bar) small; bare; sunshield; insulated	Openings below liquid level	Pressure relief requirements (see § 178.27(e))	Maximum filling density (kg/l)
3299 .....	Ethylene oxide and tetrafluoroethane mixture, with not more than 5.6% ethylene oxide.	16.7 ..... 14.7 ..... 12.9 ..... 11.2 .....	Allowed .....	Normal .....	1.03
3318 .....	Ammonia solution, relative density less than 0.880 at 15 °C in water, with more than 50% ammonia.	See MAWP definition in 178.276(a).	Allowed .....	§ 178.276(e)(3) ...	§ 173.32(f)
3337 .....	Refrigerant gas R 404A .....	31.6 ..... 28.3 ..... 25.3 ..... 22.5 .....	Allowed .....	Normal .....	0.84
3338 .....	Refrigerant gas R 407A .....	31.3 ..... 28.1 ..... 25.1 ..... 22.4 .....	Allowed .....	Normal .....	0.95
3339 .....	Refrigerant gas R 407B .....	33.0 ..... 29.6 ..... 26.5 ..... 23.6 .....	Allowed .....	Normal .....	0.95
3340 .....	Refrigerant gas R 407C .....	29.9 ..... 26.8 ..... 23.9 ..... 21.3 .....	Allowed .....	Normal .....	0.95

(v) When portable tank instruction T75 is referenced in Column (7) of the §172.101 Table, the applicable refrigerated liquefied gases are authorized to be transported in portable tanks in accordance with the requirements of §178.277 of this subchapter.

(vi) *UN and IM portable tank codes/special provisions.* When a specific portable tank instruction is specified by a T Code in Column (7) of the §172.101 Table for a specific hazardous material, a Specification portable tank conforming to an alternative tank instruction may be used if:

(A) the alternative portable tank has a higher or equivalent test pressure (for example, 4 bar when 2.65 bar is specified);

(B) the alternative portable tank has greater or equivalent wall thickness (for example, 10 mm when 6 mm is specified);

(C) the alternative portable tank has a pressure relief device as specified in the T Code. If a frangible disc is required in series with the reclosing pres-

sure relief device for the specified portable tank, the alternative portable tank must be fitted with a frangible disc in series with the reclosing pressure relief device; and

(D) With regard to bottom openings—

(1) When two effective means are specified, the alternative portable tank is fitted with bottom openings having two or three effective means of closure or no bottom openings; or

(2) When three effective means are specified, the portable tank has no bottom openings or three effective means of closure; or

(3) When no bottom openings are authorized, the alternative portable tank must not have bottom openings.

(vii) When a hazardous material is not assigned a portable tank T Code or TP 9 is referenced in Column (7) of the §172.101 Table, the hazardous material may only be transported in a portable tank if approved by the Associate Administrator.

(viii) Portable tank special provisions are assigned to certain hazardous

materials to specify requirements that are in addition to those provided by the portable tank instructions or the requirements in part 178 of this subchapter. Portable tank special provisions are designated with the abbreviation TP (tank provision) and are assigned to specific hazardous materials in Column (7) of the §172.101 Table. The following is a list of the portable tank special provisions:

*Code/Special Provisions*

TP1 The maximum degree of filling must not exceed the degree of filling determined by the following:

$$\left( \text{Degree of filling} = \frac{97}{1 + \alpha(t_r - t_f)} \right).$$

Where:

$t_r$  is the maximum mean bulk temperature during transport, and  $t_f$  is the temperature in degrees celsius of the liquid during filling.

TP2 a. The maximum degree of filling must not exceed the degree of filling determined by the following:

$$\left( \text{Degree of filling} = \frac{95}{1 + \alpha(t_r - t_f)} \right).$$

Where:

$t_r$  is the maximum mean bulk temperature during transport,

$t_f$  is the temperature in degrees celsius of the liquid during filling, and

$\alpha$  is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling ( $t_f$ ) and the maximum mean bulk temperature during transportation ( $t_r$ ) both in degrees celsius.

b. For liquids transported under ambient conditions  $\alpha$  may be calculated using the formula:

$$\alpha = \frac{d_{15} - d_{50}}{35 d_{50}}$$

Where:

$d_{15}$  and  $d_{50}$  are the densities (in units of mass per unit volume) of the liquid at 15 °C (59 °F) and 50 °C (122 °F), respectively.

TP3 For materials transported under elevated temperatures, the maximum degree of filling is determined by the following:

$$\left( \text{Degree of filling} = 95 \frac{d_t}{d_f} \right).$$

Where:

$d_t$  is the density of the material at the maximum mean bulk temperature during transport; and

$d_f$  is the density of the material at the temperature in degrees celsius of the material during filling; and

TP4 The maximum degree of filling for portable tanks must not exceed 90%.

TP5 For a portable tank used for the transport of flammable refrigerated liquefied gases or refrigerated liquefied oxygen, the maximum rate at which the portable tank may be filled must not exceed the liquid flow capacity of the primary pressure relief system rated at a pressure not exceeding 120 percent of the portable tank's design pressure. For portable tanks used for the transport of refrigerated liquefied helium and refrigerated liquefied atmospheric gas (except oxygen), the maximum rate at which the tank is filled must not exceed the liquid flow capacity of the pressure relief device rated at 130 percent of the portable tank's design pressure. Except for a portable tank containing refrigerated liquefied helium, a portable tank shall have an outage of at least two percent below the inlet of the pressure relief device or pressure control valve, under conditions of incipient opening, with the portable tank in a level attitude. No outage is required for helium.

TP6 To prevent the tank from bursting in an event, including fire engulfment (the conditions prescribed in CGA pamphlet S-1.2 (IBR, see §171.7 of this subchapter) may be used to consider the fire engulfment condition), it must be equipped with pressure relief devices that are adequate in relation to the capacity of the tank and the nature of the hazardous material transported.

TP7 The vapor space must be purged of air by nitrogen or other means.

TP8 A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 °C (32 °F).

TP9 A hazardous material assigned to special provision TP9 in Column (7) of the §172.101 Table may only be transported in a portable tank if approved by the Associate Administrator.

TP10 The portable tank must be fitted with a lead lining at least 5 mm (0.2 inches) thick. The lead lining must be tested annually to ensure that it is intact and functional. Another suitable lining material may be used if approved by the Associate Administrator.

TP12 This material is considered highly corrosive to steel.

TP13 Self-contained breathing apparatus must be provided when this hazardous material is transported by sea.

TP16 The portable tank must be protected against over and under pressurization which may be experienced during transportation. The means of protection must be approved by the approval agency designated to approve the portable tank in accordance with the procedures in part 107, subpart E, of this subchapter. The pressure relief device must be preceded by a frangible disk in accordance with the requirements in §178.275(g)(3) of this subchapter to prevent crystallization of the product in the pressure relief device.

TP17 Only inorganic non-combustible materials may be used for thermal insulation of the tank.

TP18 The temperature of this material must be maintained between 18 °C (64.4 °F) and 40 °C (104 °F) while in transportation. Portable tanks containing solidified methacrylic acid must not be reheated during transportation.

TP19 The calculated wall thickness must be increased by 3 mm at the time of construction. Wall thickness must be verified ultrasonically at intervals midway between periodic hydraulic tests (every 2.5 years). The portable tank must not be used if the wall thickness is less than that prescribed by the applicable T code in Column (7) of the Table for this material.

TP20 This hazardous material must only be transported in insulated tanks under a nitrogen blanket.

TP21 The wall thickness must not be less than 8 mm. Portable tanks must be hydraulically tested and internally inspected at intervals not exceeding 2.5 years.

TP22 Lubricants for portable tank fittings (for example, gaskets, shut-off valves, flanges) must be oxygen compatible.

TP24 The portable tank may be fitted with a device to prevent the build up of excess pressure due to the slow decomposition of the hazardous material being transported. The device must be in the vapor space when the tank is filled under maximum filling conditions. This device must also prevent an unacceptable amount of leakage of liquid in the case of overturning.

TP25 Sulphur trioxide 99.95% pure and above may be transported in tanks without an inhibitor provided that it is maintained at a temperature equal to or above 32.5 °C (90.5 °F).

TP26 The heating device must be exterior to the shell. For UN 3176, this requirement only applies when the hazardous material reacts dangerously with water.

TP27 A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in §178.275 of this sub-

chapter, where the test pressure is 1.5 times the MAWP.

TP28 A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in §178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

TP29 A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in §178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

TP30 This hazardous material may only be transported in insulated tanks.

TP31 This hazardous material may only be transported in tanks in the solid state.

TP37 IM portable tanks are only authorized for the shipment of hydrogen peroxide solutions in water containing 72% or less hydrogen peroxide by weight. Pressure relief devices shall be designed to prevent the entry of foreign matter, the leakage of liquid and the development of any dangerous excess pressure. In addition, the portable tank must be designed so that internal surfaces may be effectively cleaned and passivated. Each tank must be equipped with pressure relief devices conforming to the following requirements:

Concentration of hydrogen peroxide solution	Total <sup>1</sup>
52% or less .....	11
Over 52%, but not greater than 60% .....	22
Over 60%, but not greater than 72% .....	32

<sup>1</sup>Total venting capacity in standard cubic feet per hour (S.C.F.H.) per pound of hydrogen peroxide solution.

TP38 Each portable tank must be insulated with an insulating material so that the overall thermal conductance at 15.5 °C (60 °F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials may not promote corrosion to steel when wet.

TP44 Each portable tank must be made of stainless steel, except that steel other than stainless steel may be used in accordance with the provisions of §173.24b(b) of this subchapter. Thickness of stainless steel for tank shell and heads must be the greater of 7.62 mm (0.300 inch) or the thickness required for a portable tank with a design pressure at least equal to 1.5 times the vapor pressure of the hazardous material at 46 °C (115 °F).

TP45 Each portable tank must be made of stainless steel, except that steel other than stainless steel may be used in accordance

with the provisions of 173.24b(b) of this subchapter. Thickness of stainless steel for portable tank shells and heads must be the greater of 6.35 mm (0.250 inch) or the thickness required for a portable tank with a design pressure at least equal to 1.3 times the vapor pressure of the hazardous material at 46 °C (115 °F).

TP46 Portable tanks in sodium metal service are not required to be hydrostatically retested.

(8) “W” codes. These provisions apply only to transportation by water:

*Code/Special Provisions*

W7 Vessel stowage category for uranyl nitrate hexahydrate solution is “D” as defined in §172.101(k)(4).

W8 Vessel stowage category for pyrophoric thorium metal or pyrophoric uranium metal is “D” as defined in §172.101(k)(4).

W9 When offered for transportation by water, the following Specification packagings are not authorized unless approved by the Associate Administrator: woven plastic bags, plastic film bags, textile bags, paper bags, IBCs and bulk packagings.

W41 When offered for transportation by water, this material must be packaged in bales and be securely and tightly bound with rope, wire or similar means.

[Amdt. 172-123, 55 FR 52582, Dec. 21, 1990]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.102, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

### Subpart C—Shipping Papers

#### § 172.200 Applicability.

(a) *Description of hazardous materials required.* Except as otherwise provided in this subpart, each person who offers a hazardous material for transportation shall describe the hazardous material on the shipping paper in the manner required by this subpart.

(b) This subpart does not apply to any material, other than a hazardous substance, hazardous waste or marine pollutant, that is—

(1) Identified by the letter “A” in column 1 of the §172.101 table, except when the material is offered or intended for transportation by air; or

(2) Identified by the letter “W” in column 1 of the §172.101 table, except when the material is offered or intended for transportation by water; or

(3) An ORM-D, except when the material is offered or intended for transportation by air.

[Amdt. 172-29A, 41 FR 40677, Sept. 20, 1976, as amended by Amdt. 172-58, 45 FR 34697, May 22, 1980; Amdt. 172-74, 47 FR 43065, Sept. 30, 1982; Amdt. 172-112, 53 FR 17160, May 13, 1988; Amdt. 172-127, 57 FR 52938, Nov. 5, 1992]

#### § 172.201 Preparation and retention of shipping papers.

(a) *Contents.* When a description of hazardous material is required to be included on a shipping paper, that description must conform to the following requirements:

(1) When a hazardous material and a material not subject to the requirements of this subchapter are described on the same shipping paper, the hazardous material description entries required by §172.202 and those additional entries that may be required by §172.203:

(i) Must be entered first, or

(ii) Must be entered in a color that clearly contrasts with any description on the shipping paper of a material not subject to the requirements of this subchapter, except that a description on a reproduction of a shipping paper may be highlighted, rather than printed, in a contrasting color (the provisions of this paragraph apply only to the basic description required by §172.202(a)(1), (2), (3), and (4)), or

(iii) Must be identified by the entry of an “X” placed before the proper shipping name in a column captioned “HM.” (The “X” may be replaced by “RQ,” if appropriate.)

(2) The required shipping description on a shipping paper and all copies thereof used for transportation purposes, must be legible and printed (manually or mechanically) in English.

(3) Unless it is specifically authorized or required in this subchapter, the required shipping description may not contain any code or abbreviation.

(4) A shipping paper may contain additional information concerning the material provided the information is not inconsistent with the required description. Unless otherwise permitted or required by this subpart, additional information must be placed after the basic description required by §172.202(a).

(b) [Reserved]

(c) *Continuation page.* A shipping paper may consist of more than one page, if each page is consecutively numbered and the first page bears a notation specifying the total number of pages included in the shipping paper. For example, “Page 1 of 4 pages.”

(d) *Emergency response telephone number.* Except as provided in §172.604(c), a shipping paper must contain an emergency response telephone number, as prescribed in subpart G of this part.

(e) Each person who provides a shipping paper must retain a copy of the shipping paper required by §172.200(a), or an electronic image thereof, that is accessible at or through its principal place of business and must make the shipping paper available, upon request, to an authorized official of a Federal, State, or local government agency at reasonable times and locations. For a hazardous waste, the shipping paper copy must be retained for three years after the material is accepted by the initial carrier. For all other hazardous materials, the shipping paper copy must be retained for 375 days after the material is accepted by the initial carrier. Each shipping paper copy must include the date of acceptance by the initial carrier, except that, for rail, vessel, or air shipments, the date on the shipment waybill, airbill, or bill of lading may be used in place of the date of acceptance by the initial carrier. A motor carrier (as defined in §390.5 of subchapter B of chapter III of subtitle B) using a shipping paper without change for multiple shipments of one or more hazardous materials having the same shipping name and identification number may retain a single copy of the shipping paper, instead of a copy for each shipment made, if the carrier also retains a record of each shipment made, to include shipping name, identification number, quantity transported, and date of shipment.

[Amdt. 172–29A, 41 FR 40677, Sept. 20, 1976]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting § 172.201, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

**§ 172.202 Description of hazardous material on shipping papers.**

(a) The shipping description of a hazardous material on the shipping paper must include:

(1) The proper shipping name prescribed for the material in column 2 of the §172.101 table;

(2) The hazard class or division number prescribed for the material, as shown in Column (3) of the §172.101 Table. Except for combustible liquids, the subsidiary hazard class(es) or subsidiary division number(s) must be entered in parentheses immediately following the primary hazard class or division number.

In addition—

(i) The words “Class” or “Division” may be included preceding the primary and subsidiary hazard class or division numbers.

(ii) The hazard class need not be included for the entry “Combustible liquid, n.o.s.”.

(iii) For domestic shipments, primary and subsidiary hazard class or division names may be entered following the numerical hazard class or division or following the basic description. For example, “Oxygen, compressed, 2.2 (non-flammable, non-poisonous compressed gas), 5.1 (oxidizer), UN1072,” or “Oxygen, compressed, 2.2, 5.1, UN1072, (non-flammable, non-poisonous compressed gas) (oxidizer)”;

(3) The identification number prescribed for the material as shown in column 4 of the §172.101 table;

(4) The packing group in Roman numerals, as designated for the hazardous material in Column 5 of the §172.101 Table. Class 1 (explosives) materials, self-reactive substances, organic peroxides and entries that are not assigned a packing group are excepted from this requirement. The packing group may be preceded by the letters “PG” (for example, “PG II”); and

(5) The total quantity of hazardous materials covered by the description must be indicated (by mass or volume, or by activity for Class 7 materials) and must include an indication of the applicable unit of measurement. For example, “200 kgs.” or “50 L.” The following provisions also apply:

(i) For Class 1 materials, the quantity must be the net explosive mass.

(ii) For hazardous materials in salvage packaging, an estimate of the total quantity is acceptable.

(iii) The following are excepted from the requirements of paragraph (a)(5) of this section:

(A) Bulk packages, provided some indication of the total quantity is shown, for example, "1 cargo tank" or "2 IBCs."

(B) Cylinders, provided some indication of the total quantity is shown, for example, "10 cylinders".

(C) Packages containing only residue.

(6) The number and type of packages must be indicated. The type of packages must be indicated by description of the package (for example, "12 drums"). Indication of the packaging specification number ("1H1") may be included in the description of the package (for example, "12 1H1 drums" or "12 drums (UN 1A1).") Abbreviations may be used for indicating packaging types (for example, "cyl." for "cylinder") provided the abbreviations are commonly accepted and recognizable.

(b) Except as provided in this subpart, the basic description specified in paragraphs (a)(1), (2), (3) and (4) of this section must be shown in sequence with no additional information interspersed. For example, "Cyclobutyl chloroformate, 6.1, (8,3), UN2744, PG II". Alternatively, the basic description may be shown with the identification (ID) number listed first. For example, "UN2744, Cyclobutyl chloroformate, 6.1, (8, 3), PG II."

(c) The total quantity of the material covered by one description must appear before or after, or both before and after, the description required and authorized by this subpart. The type of packaging and destination marks may be entered in any appropriate manner before or after the basic description. Abbreviations may be used to express units of measurement and types of packagings.

(d) Technical and chemical group names may be entered in parentheses between the proper shipping name and hazard class or following the basic description. An appropriate modifier, such as "contains" or "containing," and/or the percentage of the technical constituent may also be used. For example: "Flammable liquids, n.o.s. (con-

tains Xylene and Benzene), 3, UN 1993, II".

(e) Except for those materials in the UN Recommendations, the ICAO Technical Instructions, or the IMDG Code (IBR, see §171.7 of this subchapter), a material that is not a hazardous material according to this subchapter may not be offered for transportation or transported when its description on a shipping paper includes a hazard class or an identification number specified in the §172.101 Table.

[Amdt. 172-101, 45 FR 74665, Nov. 10, 1980, as amended by Amdt. 172-103, 51 FR 5970, Feb. 18, 1986; Amdt. 172-123, 55 FR 52589, Dec. 21, 1990; 56 FR 66252, Dec. 20, 1991; Amdt. 172-127, 57 FR 52938, Nov. 5, 1992; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993; 66 FR 33425, June 21, 2001; 68 FR 45030, July 31, 2003; 68 FR 75741, Dec. 31, 2003; 69 FR 34611, June 22, 2004; 69 FR 54046, Sept. 7, 2004]

#### § 172.203 Additional description requirements.

(a) *Exemptions.* Each shipping paper issued in connection with a shipment made under an exemption must bear the notation "DOT-E" followed by the exemption number assigned and so located that the notation is clearly associated with the description to which the exemption applies.

(b) *Limited quantities.* The description for a material offered for transportation as "limited quantity," as authorized by this subchapter, must include the words "Limited Quantity" or "Ltd Qty" following the basic description.

(c) *Hazardous substances.* (1) Except for Class 7 (radioactive) materials described in accordance with paragraph (d) of this section, if the proper shipping name for a material that is a hazardous substance does not identify the hazardous substance by name, the name of the hazardous substance must be entered in parentheses in association with the basic description. If the material contains two or more hazardous substances, at least two hazardous substances, including the two with the lowest reportable quantities (RQs), must be identified. For a hazardous waste, the waste code (e.g., D001), if appropriate, may be used to identify the hazardous substance.

(2) The letters "RQ" shall be entered on the shipping paper either before or after, the basic description required by

## § 172.203

## 49 CFR Ch. I (10–1–04 Edition)

§ 172.202 for each hazardous substance (see definition in § 171.8 of this subchapter). For example: “RQ, Allyl alcohol, 6.1, UN 1098, I”; or “Environmentally hazardous substance, solid, n.o.s., 9, UN 3077, III, RQ (Adipic acid)”.

(d) *Radioactive material.* The description for a shipment of a Class 7 (radioactive) material must include the following additional entries as appropriate:

(1) The name of each radionuclide in the Class 7 (radioactive) material that is listed in § 173.435 of this subchapter. For mixtures of radionuclides, the radionuclides that must be shown must be determined in accordance with § 173.433(g) of this subchapter. Abbreviations, *e.g.*, “<sup>99</sup>Mo,” are authorized.

(2) A description of the physical and chemical form of the material, if the material is not in special form (generic chemical description is acceptable for chemical form).

(3) The activity contained in each package of the shipment in terms of the appropriate SI units (*e.g.*, Becquerels (Bq), Terabecquerels (TBq), etc.). The activity may also be stated in appropriate customary units (Curies (Ci), milliCuries (mCi), microCuries (uCi), etc.) in parentheses following the SI units. Abbreviations are authorized. Except for plutonium-239 and plutonium-241, the weight in grams or kilograms of fissile radionuclides may be inserted instead of activity units. For plutonium-239 and plutonium-241, the weight in grams of fissile radionuclides may be inserted in addition to the activity units.

(4) The category of label applied to each package in the shipment. For example: “RADIOACTIVE WHITE-I.”

(5) The transport index assigned to each package in the shipment bearing RADIOACTIVE YELLOW-II or RADIOACTIVE YELLOW-III labels.

(6) For a package containing fissile Class 7 (radioactive) material:

(i) The words “Fissile Excepted” if the package is excepted pursuant to § 173.453 of this subchapter; or otherwise

(ii) The criticality safety index for that package.

(7) For a package approved by the U.S. Department of Energy (DOE) or U.S. Nuclear Regulatory Commission

(NRC), a notation of the package identification marking as prescribed in the applicable DOE or NRC approval (see § 173.471 of the subchapter).

(8) For an export shipment or a shipment in a foreign made package, a notation of the package identification marking as prescribed in the applicable International Atomic Energy Agency (IAEA) Certificate of Competent Authority which has been issued for the package (see § 173.473 of the subchapter).

(9) For a shipment required by this subchapter to be consigned as exclusive use:

(i) An indication that the shipment is consigned as exclusive use; or

(ii) If all the descriptions on the shipping paper are consigned as exclusive use, then the statement “Exclusive Use Shipment” may be entered only once on the shipping paper in a clearly visible location.

(10) For the shipment of a package containing a highway route controlled quantity of Class 7 (radioactive) materials (see § 173.403 of this subchapter) the words “Highway route controlled quantity” or “HRCQ” must be entered in association with the basic description.

(e) *Empty packagings.* (1) The description on the shipping paper for a packaging containing the residue of a hazardous material may include the words “RESIDUE: Last Contained \* \* \*” in association with the basic description of the hazardous material last contained in the packaging.

(2) The description on the shipping paper for a tank car containing the residue of a hazardous material must include the phrase, “RESIDUE: LAST CONTAINED \* \* \*” before the basic description.

(f) *Transportation by air.* When a package containing a hazardous material is offered for transportation by air and this subchapter prohibits its transportation aboard passenger-carrying aircraft, the words “Cargo aircraft only” must be entered after the basic description.

(g) *Transportation by rail.* (1) A shipping paper prepared by a rail carrier for a rail car, freight container, transport vehicle or portable tank that contains hazardous materials must include



the reporting mark and number when displayed on the rail car, freight container, transport vehicle or portable tank.

(2) The shipping paper for each DOT-113 tank car containing a Division 2.1 material or its residue must contain an appropriate notation, such as "DOT 113", and the statement "Do not hump or cut off car while in motion."

(3) When shipments of elevated temperature materials are transported under the exception permitted in §173.247(h)(3) of this subchapter, the shipping paper must contain an appropriate notation, such as "Maximum operating speed 15 mph."

(h) *Transportation by highway.* Following the basic description for a hazardous material in a Specification MC 330 or MC 331 cargo tank, there must be entered for—

(1) *Anhydrous ammonia.* (i) The words "0.2 PERCENT WATER" to indicate the suitability for shipping anhydrous ammonia in a cargo tank made of quenched and tempered steel as authorized by §173.315(a), Note 14 of this subchapter, or

(ii) The words "NOT FOR Q and T TANKS" when the anhydrous ammonia does not contain 0.2 percent or more water by weight.

(2) *Liquefied petroleum gas.* (i) The word "NONCORROSIVE" or "NONCOR" to indicate the suitability for shipping "Noncorrosive" liquefied petroleum gas in a cargo tank made of quenched and tempered steel as authorized by §173.315(a), Note 15 of this subchapter, or

(ii) The words "NOT FOR Q and T TANKS" for grades of liquefied petroleum gas other than "Noncorrosive".

(i) *Transportation by water.* Each shipment by water must have the following additional shipping paper entries:

(1) The name of the shipper.

(2) Minimum flash point if 61 °C or below (in °C closed cup (c.c.) in association with the basic description.

(j) [Reserved]

(k) *Technical names for "n.o.s." and other generic descriptions.* Unless otherwise excepted, if a material is described on a shipping paper by one of the proper shipping names identified by the letter "G" in column (1) of the §172.101 Table, the technical name of

the hazardous material must be entered in parentheses in association with the basic description. For example "Corrosive liquid, n.o.s., (Octanoyl chloride), 8, UN 1760, II", or "Corrosive liquid, n.o.s., 8, UN 1760, II (contains Octanoyl chloride)". The word "contains" may be used in association with the technical name, if appropriate. For organic peroxides which may qualify for more than one generic listing depending on concentration, the technical name must include the actual concentration being shipped or the concentration range for the appropriate generic listing. For example, "Organic peroxide type B, solid, 5.2, UN 3102 (dibenzoyl peroxide, 52-100%)" or "Organic peroxide type E, solid, 5.2, UN 3108 (dibenzoyl peroxide, paste, <52%)". Shipping descriptions for toxic materials that meet the criteria of Division 6.1, PG I or II (as specified in §173.132(a) of this subchapter) or Division 2.3 (as specified in §173.115(c) of this subchapter) and are identified by the letter "G" in column (1) of the §172.101 Table, must have the technical name of the toxic constituent entered in parentheses in association with the basic description.

(1) If a hazardous material is a mixture or solution of two or more hazardous materials, the technical names of at least two components most predominately contributing to the hazards of the mixture or solution must be entered on the shipping paper as required by paragraph (k) of this section. For example, "Flammable liquid, corrosive, n.o.s., 3, UN 2924, II (contains Methanol, Potassium hydroxide)".

(2) The provisions of this paragraph do not apply—

(i) To a material that is a hazardous waste and described using the proper shipping name "Hazardous waste, liquid or solid, n.o.s.", classed as a miscellaneous Class 9, provided the EPA hazardous waste number is included on the shipping paper in association with the basic description, or provided the material is described in accordance with the provisions of §172.203(c) of this part.

(ii) To a material for which the hazard class is to be determined by testing under the criteria in §172.101(c)(11).

(iii) If the n.o.s. description for the material (other than a mixture of hazardous materials of different classes meeting the definitions of more than one hazard class) contains the name of the chemical element or group which is primarily responsible for the material being included in the hazard class indicated.

(iv) If the n.o.s. description for the material (which is a mixture of hazardous materials of different classes meeting the definition of more than one hazard class) contains the name of the chemical element or group responsible for the material meeting the definition of one of these classes. In such cases, only the technical name of the component that is not appropriately identified in the n.o.s. description shall be entered in parentheses.

(1) *Marine pollutants.* (1) If the proper shipping name for a material which is a marine pollutant does not identify by name the component which makes the material a marine pollutant, the name of that component must appear in parentheses in association with the basic description. Where two or more components which make a material a marine pollutant are present, the names of at least two of the components most predominantly contributing to the marine pollutant designation must appear in parentheses in association with the basic description.

(2) The words “Marine Pollutant” shall be entered in association with the basic description for a material which is a marine pollutant.

(3) Except for transportation by vessel, marine pollutants subject to the provisions of 49 CFR 130.11 are excepted from the requirements of paragraph (1) of this section if a phrase indicating the material is an oil is placed in association with the basic description.

(m) *Poisonous materials.* Notwithstanding the hazard class to which a material is assigned—

(1) If a liquid or solid material in a package meets the definition of a Division 6.1, Packing Group I or II, according to this subchapter, and the fact that it is a poison is not disclosed in the shipping name or class entry, the word “Poison” or “Toxic” shall be entered on the shipping paper in association with the shipping description.

(2) For materials which are poisonous by inhalation (see §171.8 of this subchapter), the words “Poison-Inhalation Hazard” or “Toxic-Inhalation Hazard” and the words “Zone A”, “Zone B”, “Zone C”, or “Zone D”, for gases or “Zone A” or “Zone B” for liquids, as appropriate, shall be entered on the shipping paper immediately following the shipping description. The word “Poison” or “Toxic” need not be repeated if it otherwise appears in the shipping description.

(n) *Elevated temperature materials.* If a liquid material in a package meets the definition of an elevated temperature material in §171.8 of this subchapter, and the fact that it is an elevated temperature material is not disclosed in the proper shipping name (for example, when the words “Molten” or “Elevated temperature” are part of the proper shipping name), the word “HOT” must immediately precede the proper shipping name of the material on the shipping paper.

(o) *Organic peroxides and self-reactive materials.* The description on a shipping paper for a Division 4.1 (self-reactive) material or a Division 5.2 (organic peroxide) material must include the following additional information, as appropriate:

(1) If notification or competent authority approval is required, the shipping paper must contain a statement of approval of the classification and conditions of transport.

(2) For Division 4.1 (self-reactive) and Division 5.2 (organic peroxide) materials that require temperature control during transport, the control and emergency temperature must be included on the shipping paper.

(3) The word “SAMPLE” must be included in association with the basic description when a sample of a Division 4.1 (self-reactive) material (see §173.224(c)(3) of this subchapter) or Division 5.2 (organic peroxide) material (see §173.225(c)(2) of this subchapter) is offered for transportation or transported.

[Amdt. 172-29A, 41 FR 40677, Sept. 20, 1976]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.203, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

**§ 172.204 Shipper's certification.**

(a) *General.* Except as provided in paragraphs (b) and (c) of this section, each person who offers a hazardous material for transportation shall certify that the material is offered for transportation in accordance with this subchapter by printing (manually or mechanically) on the shipping paper containing the required shipping description the certification contained in paragraph (a)(1) of this section or the certification (declaration) containing the language contained in paragraph (a)(2) of this section.

(1) "This is to certify that the above-named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation."

NOTE: In line one of the certification the words "herein-named" may be substituted for the words "above-named".

(2) "I hereby declare that the contents of this consignment are fully and accurately described above by the proper shipping name, and are classified, packaged, marked and labelled/placarded, and are in all respects in proper condition for transport according to applicable international and national governmental regulations."

(b) *Exceptions.* (1) Except for a hazardous waste, no certification is required for a hazardous material offered for transportation by motor vehicle and transported:

(i) In a cargo tank supplied by the carrier, or

(ii) By the shipper as a private carrier except for a hazardous material that is to be reshipped or transferred from one carrier to another.

(2) No certification is required for the return of an empty tank car which previously contained a hazardous material and which has not been cleaned or purged.

(c) *Transportation by air—(1) General.* Certification containing the following language may be used in place of the certification required by paragraph (a) of this section:

I hereby certify that the contents of this consignment are fully and accurately described above by proper shipping name and

are classified, packaged, marked and labeled, and in proper condition for carriage by air according to applicable national governmental regulations.

NOTE TO PARAGRAPH (c)(1): In the certification, the word "packed" may be used instead of the word "packaged" until October 1, 2010.

(2) *Certificate in duplicate.* Each person who offers a hazardous material to an aircraft operator for transportation by air shall provide two copies of the certification required in this section. (See §175.30 of this subchapter.)

(3) *Passenger and cargo aircraft.* Each person who offers for transportation by air a hazardous material authorized for air transportation shall add to the certification required in this section the following statement:

This shipment is within the limitations prescribed for passenger aircraft/cargo aircraft only (delete nonapplicable).

(4) *Radioactive material.* Each person who offers any radioactive material for transportation aboard a passenger-carrying aircraft shall sign (mechanically or manually) a printed certificate stating that the shipment contains radioactive material intended for use in, or incident to, research, or medical diagnosis or treatment.

(d) *Signature.* The certifications required by paragraph (a) or (c) of this section:

(1) Must be legibly signed by a principal, officer, partner, or employee of the shipper or his agent; and

(2) May be legibly signed manually, by typewriter, or by other mechanical means.

[Amdt. 172-29A, 41 FR 40677, Sept. 20, 1976]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.204, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

**§ 172.205 Hazardous waste manifest.**

(a) No person may offer, transport, transfer, or deliver a hazardous waste (waste) unless an EPA Form 8700-22 and 8700-22A (when necessary) hazardous waste manifest (manifest) is prepared in accordance with 40 CFR 262.20 and is signed, carried, and given as required of that person by this section.

§ 172.205

49 CFR Ch. I (10–1–04 Edition)

(b) The shipper (generator) shall prepare the manifest in accordance with 40 CFR part 262.

(c) The original copy of the manifest must be dated by, and bear the handwritten signature of, the person representing:

(1) The shipper (generator) of the waste at the time it is offered for transportation, and

(2) The initial carrier accepting the waste for transportation.

(d) A copy of the manifest must be dated by, and bear the handwritten signature of the person representing:

(1) Each subsequent carrier accepting the waste for transportation, at the time of acceptance, and

(2) The designated facility receiving the waste, upon receipt.

(e) A copy of the manifest bearing all required dates and signatures must be:

(1) Given to a person representing each carrier accepting the waste for transportation,

(2) Carried during transportation in the same manner as required by this subchapter for shipping papers,

(3) Given to a person representing the designated facility receiving the waste,

(4) Returned to the shipper (generator) by the carrier that transported the waste from the United States to a foreign destination with a notation of the date of departure from the United States, and

(5) Retained by the shipper (generator) and by the initial and each subsequent carrier for three years from the date the waste was accepted by the initial carrier. Each retained copy must bear all required signatures and dates up to and including those entered by the next person who received the waste.

(f) *Transportation by rail.* Notwithstanding the requirements of paragraphs (d) and (e) of this section, the following requirements apply:

(1) When accepting hazardous waste from a non-rail transporter, the initial rail transporter must:

(i) Sign and date the manifest acknowledging acceptance of the hazardous waste;

(ii) Return a signed copy of the manifest to the non-rail transporter;

(iii) Forward at least three copies of the manifest to:

(A) The next non-rail transporter, if any;

(B) The designated facility, if the shipment is delivered to that facility by rail; or

(C) The last rail transporter designated to handle the waste in the United States; and

(iv) Retain one copy of the manifest and rail shipping paper in accordance with 40 CFR 263.22.

(2) Rail transporters must ensure that a shipping paper containing all the information required on the manifest (excluding the EPA identification numbers, generator certification and signatures) and, for exports, an EPA Acknowledgment of Consent accompanies the hazardous waste at all times. Intermediate rail transporters are not required to sign either the manifest or shipping paper.

(3) When delivering hazardous waste to the designated facility, a rail transporter must:

(i) Obtain the date of delivery and handwritten signature of the owner or operator of the designated facility on the manifest or the shipping paper (if the manifest has not been received by the facility); and

(ii) Retain a copy of the manifest or signed shipping paper in accordance with 40 CFR 263.22.

(4) When delivering hazardous waste to a non-rail transporter, a rail transporter must:

(i) Obtain the date of delivery and the handwritten signature of the next non-rail transporter on the manifest; and

(ii) Retain a copy of the manifest in accordance with 40 CFR 263.22.

(5) Before accepting hazardous waste from a rail transporter, a non-rail transporter must sign and date the manifest and provide a copy to the rail transporter.

(g) The person delivering a hazardous waste to an initial rail carrier shall send a copy of the manifest, dated and signed by a representative of the rail carrier, to the person representing the designated facility.

(h) A hazardous waste manifest required by 40 CFR part 262, containing all of the information required by this

subpart, may be used as the shipping paper required by this subpart.

[Amdt. 172-58, 45 FR 34698, May 22, 1980, as amended by Amdt. 172-90, 49 FR 10510, Mar. 20, 1984; 49 FR 11184, Mar. 26, 1984; Amdt. 172-248, 61 FR 28675, June 5, 1996]

### Subpart D—Marking

#### § 172.300 Applicability.

(a) Each person who offers a hazardous material for transportation shall mark each package, freight container, and transport vehicle containing the hazardous material in the manner required by this subpart.

(b) When assigned the function by this subpart, each carrier that transports a hazardous material shall mark each package, freight container, and transport vehicle containing the hazardous material in the manner required by this subpart.

[Amdt. 172-101, 45 FR 74666, Nov. 10, 1980]

#### § 172.301 General marking requirements for non-bulk packagings.

(a) *Proper shipping name and identification number.* (1) Except as otherwise provided by this subchapter, each person who offers a hazardous material for transportation in a non-bulk packaging must mark the package with the proper shipping name and identification number (preceded by “UN” or “NA,” as appropriate) for the material as shown in the §172.101 Table. Identification numbers are not required on packagings that contain only ORM-D materials or limited quantities, as defined in §171.8 of this subchapter, except for limited quantities marked in accordance with the marking requirements in §172.315.

(2) The proper shipping name for a hazardous waste (as defined in §171.8 of this subchapter) is not required to include the word “waste” if the package bears the EPA marking prescribed by 40 CFR 262.32.

(3) *Large quantities of a single hazardous material in non-bulk packages.* A transport vehicle or freight container containing only a single hazardous material in non-bulk packages must be marked, on each side and each end as specified in the §172.332 or §172.336, with the identification number speci-

fied for the hazardous material in the §172.101 Table, subject to the following provisions and limitations:

(i) Each package is marked with the same proper shipping name and identification number;

(ii) The aggregate gross weight of the hazardous material is 4,000 kg (8,820 pounds) or more;

(iii) All of the hazardous material is loaded at one loading facility;

(iv) The transport vehicle or freight container contains no other material, hazardous or otherwise; and

(v) The identification number marking requirement of this paragraph (a)(3) does not apply to Class 1, Class 7, or to non-bulk packagings for which identification numbers are not required.

(b) *Technical names.* In addition to the marking required by paragraph (a) of this section, each non-bulk packaging containing hazardous materials subject to the provisions of §172.203(k) of this part shall be marked with the technical name in parentheses in association with the proper shipping name in accordance with the requirements and exceptions specified for display of technical descriptions on shipping papers in §172.203(k) of this part.

(c) *Exemption packagings.* The outside of each package authorized by an exemption shall be plainly and durably marked “DOT-E” followed by the exemption number assigned.

(d) *Consignee’s or consignor’s name and address.* Each person who offers for transportation a hazardous material in a non-bulk package shall mark that package with the name and address of the consignor or consignee except when the package is—

(1) Transported by highway only and will not be transferred from one motor carrier to another; or

(2) Part of a carload lot, truckload lot or freight container load, and the entire contents of the rail car, truck or freight container are shipped from one consignor to one consignee.

(e) *Previously marked packagings.* A package which has been previously marked as required for the material it contains and on which the marking remains legible, need not be remarked.

## § 172.302

(For empty packagings, see §173.29 of this subchapter.)

[Amdt. 172-123, 55 FR 52590, Dec. 21, 1990, as amended by Amdt. 172-151, 62 FR 1227, Jan. 8, 1997; 62 FR 39404, July 22, 1997; 63 FR 16075, Apr. 1, 1998; 66 FR 45182, Aug. 28, 2001; 68 FR 45030, July 31, 2003]

### § 172.302 General marking requirements for bulk packagings.

(a) *Identification numbers.* Except as otherwise provided in this subpart, no person may offer for transportation or transport a hazardous material in a bulk packaging unless the packaging is marked as required by §172.332 with the identification number specified for the material in the §172.101 table—

(1) On each side and each end, if the packaging has a capacity of 3,785 L (1,000 gallons) or more;

(2) On two opposing sides, if the packaging has a capacity of less than 3,785 L (1,000 gallons); or

(3) For cylinders permanently installed on a tube trailer motor vehicle, on each side and each end of the motor vehicle.

(b) *Size of markings.* Except as otherwise provided, markings required by this subpart on bulk packagings must—

(1) Have a width of at least 6.0 mm (0.24 inch) and a height of at least 100 mm (3.9 inches) for rail cars;

(2) Have a width of at least 4.0 mm (0.16 inch) and a height of at least 25 mm (one inch) for portable tanks with capacities of less than 3,785 L (1,000 gallons) and IBCs; and

(3) Have a width of at least 6.0 mm (0.24 inch) and a height of at least 50 mm (2.0 inches) for cargo tanks and other bulk packagings.

(c) *Exemption packagings.* The outside of each bulk package used under the terms of an exemption shall be plainly and durably marked “DOT-E” followed by the exemption number assigned.

(d) Each bulk packaging marked with a proper shipping name, common name or identification number as required by this subpart must remain marked when it is emptied unless it is—

(1) Sufficiently cleaned of residue and purged of vapors to remove any potential hazard; or

(2) Refilled, with a material requiring different markings or no markings, to

## 49 CFR Ch. I (10-1-04 Edition)

such an extent that any residue remaining in the packaging is no longer hazardous.

(e) Additional requirements for marking portable tanks, cargo tanks, tank cars, multi-unit tank car tanks, and other bulk packagings are prescribed in §§172.326, 172.328, 172.330, and 172.331, respectively, of this subpart.

(f) A bulk packaging marked prior to October 1, 1991, in conformance to the regulations of this subchapter in effect on September 30, 1991, need not be remarked if the key words of the proper shipping name are identical to those currently specified in the §172.101 table. For example, a tank car marked “ANHYDROUS AMMONIA” need not be remarked “ANHYDROUS AMMONIA, LIQUEFIED”.

(g) A rail car, freight container, truck body or trailer in which the lading has been fumigated with any hazardous material, or is undergoing fumigation, must be marked as specified in §173.9 of this subchapter.

[Amdt. 172-123, 55 FR 52591, Dec. 21, 1990, as amended at 56 FR 66254, Dec. 20, 1991; Amdt. 172-150, 61 FR 50624, Sept. 26, 1996; Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 62 FR 39398, July 22, 1997; 66 FR 45379, Aug. 28, 2001]

### § 172.303 Prohibited marking.

(a) No person may offer for transportation or transport a package which is marked with the proper shipping name or identification number of a hazardous material unless the package contains the identified hazardous material or its residue.

(b) This section does not apply to—

(1) Transportation of a package in a transport vehicle or freight container if the package is not visible during transportation and is loaded by the shipper and unloaded by the shipper or consignee.

(2) Markings on a package which are securely covered in transportation.

(3) The marking of a shipping name on a package when the name describes a material not regulated under this subchapter.

[Amdt. 172-123, 55 FR 52591, Dec. 21, 1990, as amended at 56 FR 66254, Dec. 20, 1991]

### § 172.304 Marking requirements.

(a) The marking required in this subpart—

(1) Must be durable, in English and printed on or affixed to the surface of a package or on a label, tag, or sign.

(2) Must be displayed on a background of sharply contrasting color;

(3) Must be unobscured by labels or attachments; and

(4) Must be located away from any other marking (such as advertising) that could substantially reduce its effectiveness.

(b) [Reserved]

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-29B, 41 FR 57067, Dec. 30, 1976]

**§ 172.306 [Reserved]**

**§ 172.308 Authorized abbreviations.**

(a) Abbreviations may not be used in a proper shipping name marking except as authorized in this section.

(b) The abbreviation “ORM” may be used in place of the words “Other Regulated Material.”

(c) Abbreviations which appear as authorized descriptions in column 2 of the § 172.101 table (e.g., “TNT” and “PCB”) are authorized.

[Amdt. 172-123, 55 FR 52591, Dec. 21, 1990, as amended by Amdt. 172-145, 60 FR 49110, Sept. 21, 1995]

**§ 172.310 Class 7 (radioactive) materials.**

In addition to any other markings required by this subpart, each package containing Class 7 (radioactive) materials must be marked as follows:

(a) Each package with a gross mass greater than 50 kg (110 lb) must have its gross mass including the unit of measurement (which may be abbreviated) marked on the outside of the package.

(b) Each industrial, Type A, Type B(U), or Type B(M) package must be legibly and durably marked on the outside of the packaging, in letters at least 13 mm (0.5 in) high, with the words “TYPE IP-1,” “TYPE IP-2,” “TYPE IP-3,” “TYPE A,” “TYPE B(U)” or “TYPE B(M),” as appropriate. A package which does not conform to Type IP-1, Type IP-2, Type IP-3, Type A, Type B(U) or Type B(M) requirements may not be so marked.

(c) Each package which conforms to an IP-1, IP-2, IP-3 or a Type A package

design must be legibly and durably marked on the outside of the packaging with the international vehicle registration code of the country of origin of the design. The international vehicle registration code for packages designed by a United States company or agency is the symbol “USA.”

(d) Each package which conforms to a Type B(U) or Type B(M) package design must have the outside of the outermost receptacle, which is resistant to the effects of fire and water, plainly marked by embossing, stamping or other means resistant to the effects of fire and water with a radiation symbol that conforms to the requirements of Appendix B of this part.

(e) Each Type B(U), Type B(M) or fissile material package destined for export shipment must also be marked “USA” in conjunction with the specification marking, or other package certificate identification. (See §§ 173.471, 173.472, and 173.473 of this subchapter.)


[Docket No. RSPA-99-6283 (HM-230), 69 FR 3668, Jan. 26, 2004]

**§ 172.312 Liquid hazardous materials in non-bulk packagings.**

(a) Except as provided in this section, each non-bulk combination package having inner packagings containing liquid hazardous materials must be:

(1) Packed with closures upward, and

(2) Legibly marked, with package orientation markings that conform pictorially to the illustration shown in this paragraph, on two opposite vertical sides of the package with the arrows pointing in the correct upright direction. Depicting a rectangular border around the arrows is optional.



Package orientation

(b) Arrows for purposes other than indicating proper package orientation may not be displayed on a package containing a liquid hazardous material.

(c) The requirements of paragraph (a) of this section do not apply to—

(1) A non-bulk package with inner packagings which are cylinders.

(2) Except when offered or intended for transportation by aircraft, packages containing flammable liquids in inner packagings of 1 L or less prepared in accordance with §173.150 (b) or (c) of this subchapter.

(3) When offered or intended for transportation by aircraft, packages containing flammable liquids in inner packagings of 120 mL (4 fluid oz.) or less prepared in accordance with §173.150 (b) or (c) of this subchapter when packed with sufficient absorption material between the inner and outer packagings to completely absorb the liquid contents.

(4) Liquids contained in manufactured articles (e.g., alcohol or mercury in thermometers) which are leak-tight in all orientations.

(5) A non-bulk package with hermetically-sealed inner packagings.

(6) Packages containing liquid infectious substances in primary receptacles not exceeding 50 ml (1.7 oz.).

[Amdt. 172-123, 55 FR 52591, Dec. 21, 1990, as amended at 56 FR 66254, Dec. 20, 1991; 57 FR 45458, Oct. 1, 1992; 64 FR 51918, Sept. 27, 1999; 66 FR 45379, Aug. 28, 2001; 68 FR 45030, July 31, 2003]

**§ 172.313 Poisonous hazardous materials.**

In addition to any other markings required by this subpart:

(a) A material poisonous by inhalation (see §171.8 of this subchapter) shall be marked “Inhalation Hazard” in association with the required labels or placards, as appropriate, and shipping name when required. The marking must be on two opposing sides of a bulk packaging. (See §172.302(b) of this subpart for size of markings on bulk packages.) When the words “Inhalation Hazard” appear on the label, as prescribed in §§172.416 and 172.429, or placard, as prescribed in §§172.540 and 172.555, the “Inhalation Hazard” marking is not required on the package.

(b) Each non-bulk plastic outer packaging used as a single or composite packaging for materials meeting the definition of Division 6.1 (in §173.132 of this subchapter) shall be permanently marked, by embossment or other durable means, with the word “POISON” in letters at least 6.3 mm (0.25 inch) in height. Additional text or symbols related to hazard warning may be included in the marking. The marking shall be located within 150 mm (6 inches) of the closure of the packaging.

(c) A transport vehicle or freight container containing a material poisonous by inhalation in non-bulk packages shall be marked, on each side and each end as specified in §172.332 or §172.336, with the identification number specified for the hazardous material in the §172.101 table, subject to the following provisions and limitations:

(1) The material is in Hazard Zone A or B;

(2) The transport vehicle or freight container is loaded at one facility with 1,000 kg (2,205 pounds) or more aggregate gross weight of the material in non-bulk packages marked with the same proper shipping name and identification number; and



(3) If the transport vehicle or freight container contains more than one material meeting the provisions of this paragraph (c), it shall be marked with the identification number for one material, determined as follows:

(i) For different materials in the same hazard zone, with the identification number of the material having the greatest aggregate gross weight; and

(ii) For different materials in both Hazard Zones A and B, with the identification number for the Hazard Zone A material.

(d) For a packaging containing a Division 6.1 PG III material, "PG III" may be marked adjacent to the POISON label. (See § 172.405(c).)

[Amdt. 172-123, 55 FR 52592, Dec. 21, 1990, as amended at 57 FR 46624, Oct. 9, 1992; Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 62 FR 39398, 39405, July 22, 1997; 63 FR 16075, Apr. 1, 1998; 64 FR 10776, Mar. 5, 1999]

#### § 172.315 Packages containing limited quantities.

Except as otherwise provided in this subchapter, a package containing a limited quantity of hazardous materials is not required to be marked with the proper shipping name provided it is marked with the identification (ID) number, preceded by the letters "UN" or "NA," as applicable, for the entry as shown in the § 172.101 Table, and placed within a square-on-point border in accordance with the following:

(a) The ID number marking must be durable, legible and of such a size relative to the package as to be readily visible. The width of line forming the square-on-point must be at least 2 mm and the height of the ID number must be at least 6 mm. The marking must be applied on at least one side or one end of the outer packaging.

(b) When two or more hazardous materials with different ID numbers are contained in the package, the packaging must be marked with either individual square-on-points bearing a single ID number, or a single square-on-point large enough to include each applicable ID number.

[68 FR 45030, July 31, 2003]

#### § 172.316 Packagings containing materials classed as ORM-D.

(a) Each non-bulk packaging containing a material classed as ORM-D must be marked on at least one side or end with the ORM-D designation immediately following or below the proper shipping name of the material. The ORM designation must be placed within a rectangle that is approximately 6.3 mm (0.25 inches) larger on each side than the designation. The designation for ORM-D must be:

(1) ORM-D-AIR for an ORM-D that is prepared for air shipment and packaged in accordance with the provisions of § 173.27 of this subchapter.

(2) ORM-D for an ORM-D other than as described in paragraph (a)(1) of this section.

(b) When the ORM-D marking including the proper shipping name can not be affixed on the package surface, it may be on an attached tag.

(c) The marking ORM-D is the certification by the person offering the packaging for transportation that the material is properly described, classed, packaged, marked and labeled (when appropriate) and in proper condition for transportation according to the applicable regulations of this subchapter. This form of certification does not preclude the requirement for a certificate on a shipping paper when required by subpart C of this part.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-123, 55 FR 52592, Dec. 21, 1990; 56 FR 66254, Dec. 20, 1991]

#### § 172.320 Explosive hazardous materials.

(a) Except as otherwise provided in paragraphs (b), (c), (d) and (e) of this section, each package containing a Class 1 material must be marked with the EX-number for each substance, article or device contained therein.

(b) Except for fireworks approved in accordance with § 173.56(j) of this subchapter, a package of Class 1 materials may be marked, in lieu of the EX-number required by paragraph (a) of this section, with a national stock number issued by the Department of Defense or identifying information, such as a product code required by regulations for commercial explosives specified in 27 CFR part 55, if the national stock

§ 172.321

number or identifying information can be specifically associated with the EX-number assigned.

(c) When more than five different Class 1 materials are packed in the same package, the package may be marked with only five of the EX-numbers, national stock numbers, product codes, or combination thereof.

(d) The requirements of this section do not apply if the EX-number, product code or national stock number of each explosive item described under a proper shipping description is shown in association with the shipping description required by §172.202(a) of this part. Product codes and national stock numbers must be traceable to the specific EX-number assigned by the Associate Administrator.

(e) The requirements of this section do not apply to the following Class 1 materials:

(1) Those being shipped to a testing agency in accordance with §173.56(d) of this subchapter;

(2) Those being shipped in accordance with §173.56(e) of this subchapter, for the purposes of developmental testing;

(3) Those which meet the requirements of §173.56(h) of this subchapter and therefore are not subject to the approval process of §173.56 of this subchapter;

(4) Until October 1, 1993, those which are shipped under §171.19 of this subchapter; and

(5) Those that are transported in accordance with §173.56(c)(2) of this subchapter and, therefore, are covered by a national security classification currently in effect.

[Amdt. 172-123, 56 FR 66254, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67487, Dec. 29, 1994; 66 FR 45379, Aug. 28, 2001]

§ 172.321 Air eligibility mark.

(a) *General.* Except as otherwise specified in this subchapter, each person who offers for transportation by aircraft a hazardous material in a non-bulk package must mark the package as required by this section to indicate that it meets the applicable requirements for air transport. The marking is a certification that the person offering the package for transportation has determined that it meets the air transport requirements of this subchapter;

such as, the package is authorized and properly marked and labeled, its contents are properly classed and within quantity limits for air transport, and it conforms to all relevant packaging provisions such as those pertaining to closures, compatibility, pressure differential, and use of absorbent materials.

(b) *Location and design.* The marking must—

(1) Be placed adjacent to the markings prescribed in §172.301(a);

(2) Be durable, legible and of a size relative to the package so as to be readily visible;

(3) Include an aircraft within a circle and may include the words “Air Eligible” in conjunction with the mark, such as:



Air Eligible

(c) *Exceptions from the air eligibility mark.* The air eligibility mark is not required for—

(1) Packages that are transported in accordance with the small quantity exceptions in §173.4 of this subchapter;

(2) Packages that contain solid carbon dioxide (dry ice) and no other materials subject to the requirements of this subchapter;

(3) Except when overpacked, hazardous materials contained in articles that are not required to be packaged according to the requirements of this subchapter.

(4) Cylinders, except for those which are required to be overpacked or placed in an outer packaging, in which case the overpack or outer packaging must be marked with the air eligibility marking; and

(5) Packages or articles which are excepted from the marking requirements of this subchapter (for example, non-spillable batteries, vehicles).

(d) *Prohibited display.* The air eligibility marking may not appear on a package containing a hazardous material which does not meet the requirements of this subchapter for air transport.

(e) *Transition Date.* Compliance with the requirements of this section is not mandatory until October 1, 2006.

[68 FR 45031, July 31, 2003, as amended at 68 FR 57632, Oct. 6, 2003; 69 FR 20833, Apr. 19, 2004]

**§ 172.322 Marine pollutants.**

(a) For vessel transportation of each non-bulk packaging that contains a marine pollutant—

(1) If the proper shipping name for a material which is a marine pollutant does not identify by name the component which makes the material a marine pollutant, the name of that component must be marked on the package in parentheses in association with the marked proper shipping name. Where two or more components which make a material a marine pollutant are present, the names of at least two of the components most predominantly contributing to the marine pollutant designation must appear in parentheses in association with the marked proper shipping name; and

(2) The MARINE POLLUTANT mark shall be placed in association with the hazard warning labels required by subpart E of this part or, in the absence of any labels, in association with the marked proper shipping name.

(b) A bulk packaging that contains a marine pollutant must—

(1) Be marked with the MARINE POLLUTANT mark on at least two opposing sides or two ends other than the bottom if the packaging has a capacity of less than 3,785 L (1,000 gallons). The mark must be visible from the direction it faces. The mark may be displayed in black lettering on a square-on-point configuration having the same outside dimensions as a placard; or

(2) Be marked on each end and each side with the MARINE POLLUTANT mark if the packaging has a capacity of 3,785 L (1,000 gallons) or more. The mark must be visible from the direc-

tion it faces. The mark may be displayed in black lettering on a square-on-point configuration having the same outside dimensions as a placard.

(c) A transport vehicle or freight container that contains a package subject to the marking requirements of paragraph (a) or (b) of this section must be marked with the MARINE POLLUTANT mark. The mark must appear on each side and each end of the transport vehicle or freight container, and must be visible from the direction it faces. This requirement may be met by the marking displayed on a freight container or portable tank loaded on a motor vehicle or rail car. This mark may be displayed in black lettering on a white square-on-point configuration having the same outside dimensions as a placard.

(d) The MARINE POLLUTANT mark is not required—

(1) On a combination package containing a severe marine pollutant (see appendix B to § 172.101), in inner packagings each of which contains:

(i) 0.5 L (17 ounces) or less net capacity for liquids; or

(ii) 500 g (17.6 ounces) or less net capacity for solids.

(2) On a combination packaging containing a marine pollutant, other than a severe marine pollutant, in inner packagings each of which contains:


(i) 5 L (1.3 gallons) or less net capacity for liquids; or

(ii) 5 kg (11 pounds) or less net capacity for solids.

(3) Except for transportation by vessel, on a bulk packaging, freight container or transport vehicle that bears a label or placard specified in subparts E or F of this part.

(e) *MARINE POLLUTANT mark.* The MARINE POLLUTANT mark must conform to the following:

(1) Except for size, the MARINE POLLUTANT mark must appear as follows:



(2) The symbol, letters and border must be black and the background white, or the symbol, letters, border and background must be of contrasting color to the surface to which the mark is affixed. Each side of the mark must be—

(i) At least 100 mm (3.9 inches) for marks applied to:

(A) Non-bulk packagings, except in the case of packagings which, because of their size, can only bear smaller marks; or

(B) Bulk packagings with a capacity of less than 3785 L (1,000 gallons); or

(ii) At least 250 mm (9.8 inches) for marks applied to all other bulk packagings.

[Amdt. 172-127, 57 FR 52938, Nov. 5, 1992, as amended by Amdt. 172-136, 59 FR 38064, July 26, 1994; Amdt. 172-145, 60 FR 49110, Sept. 21, 1995; 66 FR 45379, Aug. 28, 2001]

**§ 172.323 Infectious substances.**

(a) In addition to other requirements of this subpart, after September 30, 2003, a bulk packaging containing a regulated medical waste, as defined in § 173.134(a)(5) of this subchapter, must be marked with a BIOHAZARD mark-

ing conforming to 29 CFR 1910.1030(g)(1)(i)—

(1) On two opposing sides or two ends other than the bottom if the packaging has a capacity of less than 3,785 L (1,000 gallons). The BIOHAZARD marking must measure at least 152.4 mm (6 inches) on each side and must be visible from the direction it faces.

(2) On each end and each side if the packaging has a capacity of 3,785 L (1,000 gallons) or more. The BIOHAZARD marking must measure at least 152.4 mm (6 inches) on each side and must be visible from the direction it faces.

(b) For a bulk packaging contained in or on a transport vehicle or freight container, if the BIOHAZARD marking on the bulk packaging is not visible, the transport vehicle or freight container must be marked as required by paragraph (a) of this section on each side and each end.

(c) The background color for the BIOHAZARD marking required by paragraph (a) of this section must be orange and the symbol and letters must be black. Except for size the BIOHAZARD marking must appear as follows:



(d) The BIOHAZARD marking required by paragraph (a) of this section must be displayed on a background of contrasting color. It may be displayed on a plain white square-on-point configuration having the same outside dimensions as a placard, as specified in § 172.519(c) of this part.

[67 FR 53135, Aug. 14, 2002]

**§ 172.324 Hazardous substances in non-bulk packagings.**

For each non-bulk package that contains a hazardous substance—

(a) Except for packages of radioactive material labeled in accordance with § 172.403, if the proper shipping name of a material that is a hazardous substance does not identify the hazardous substance by name, the name of the hazardous substance must be marked on the package, in parentheses,

**§ 172.325**

**49 CFR Ch. I (10–1–04 Edition)**

in association with the proper shipping name. If the material contains two or more hazardous substances, at least two hazardous substances, including the two with the lowest reportable quantities (RQs), must be identified. For a hazardous waste, the waste code (e.g., D001), if appropriate, may be used to identify the hazardous substance.

(b) The letters “RQ” shall be marked on the package in association with the proper shipping name.

[Amdt. 172–108, 52 FR 4843, Feb. 17, 1987, as amended by Amdt. 172–119, 54 FR 39505, Sept. 26, 1989; Amdt. 172–122, 55 FR 46825, Nov. 7, 1990; Amdt. 172–123, 55 FR 52592, Dec. 21, 1990; Amdt. 172–127, 57 FR 52939, Nov. 5, 1992; Amdt. 172–149, 61 FR 27172, May 30, 1996]

**§ 172.325 Elevated temperature materials.**

(a) Except as provided in paragraph (b) of this section, a bulk packaging containing an elevated temperature material must be marked on two opposing sides with the word “HOT” in

black or white Gothic lettering on a contrasting background. The marking must be displayed on the packaging itself or in black lettering on a plain white square-on-point configuration having the same outside dimensions as a placard. (See §172.302(b) for size of markings on bulk packagings.)

(b) Bulk packagings containing molten aluminum or molten sulfur must be marked “MOLTEN ALUMINUM” or “MOLTEN SULFUR”, respectively, in the same manner as prescribed in paragraph (a) of this section.

(c) If the identification number is displayed on a white-square-on-point display configuration, as prescribed in §172.336(b), the word “HOT” may be displayed in the upper corner of the same white-square-on-point display configuration. The word “HOT” must be in black letters having a height of at least 50 mm (2.0 inches). Except for size, these markings shall be as illustrated for an Elevated temperature material, liquid, n.o.s.:



[Amdt. 172-125, 58 FR 3348, Jan. 8, 1993, as amended by Amdt. 172-139, 59 FR 67487, Dec. 29, 1994]

**§ 172.326 Portable tanks.**

(a) *Shipping name.* No person may offer for transportation or transport a portable tank containing a hazardous material unless it is legibly marked on two opposing sides with the proper shipping name specified for the material in the § 172.101 table.

(b) *Owner's name.* The name of the owner or of the lessee, if applicable, must be displayed on a portable tank that contains a hazardous material.

(c) *Identification numbers.* (1) If the identification number markings required by § 172.302(a) are not visible, a transport vehicle or freight container used to transport a portable tank con-

taining a hazardous material must be marked on each side and each end as required by § 172.332 with the identification number specified for the material in the § 172.101 table.

(2) Each person who offers a portable tank containing a hazardous material to a motor carrier, for transportation in a transport vehicle or freight container, shall provide the motor carrier with the required identification numbers on placards, orange panels, or the white square-on-point configuration, as appropriate, for each side and each end

## § 172.328

of the transport vehicle or freight container from which identification numbers on the portable tank are not visible.

[Amdt. 172-123, 55 FR 52592, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991]

### § 172.328 Cargo tanks.

(a) *Providing and affixing identification numbers.* Unless a cargo tank is already marked with the identification numbers required by this subpart, the identification numbers must be provided or affixed as follows:

(1) A person who offers a hazardous material to a motor carrier for transportation in a cargo tank shall provide the motor carrier the identification numbers on placards or shall affix orange panels containing the required identification numbers, prior to or at the time the material is offered for transportation.

(2) A person who offers a cargo tank containing a hazardous material for transportation shall affix the required identification numbers on panels or placards prior to or at the time the cargo tank is offered for transportation.

(3) For a cargo tank transported on or in a transport vehicle or freight container, if the identification number marking on the cargo tank required by § 172.302(a) would not normally be visible during transportation—

(i) The transport vehicle or freight container must be marked as required by § 172.332 on each side and each end with the identification number specified for the material in the § 172.101 table; and

(ii) When the cargo tank is permanently installed within an enclosed cargo body of the transport vehicle or freight container, the identification number marking required by § 172.302(a) need only be displayed on each side and end of a cargo tank that is visible when the cargo tank is accessed.

(b) *Required markings: Gases.* Except for certain nurse tanks which must be marked as specified in § 173.315(m) of this subchapter, each cargo tank transporting a Class 2 material subject to this subchapter must be marked, in lettering no less than 50 mm (2.0 inches), on each side and each end with—

## 49 CFR Ch. I (10-1-04 Edition)

(1) The proper shipping name specified for the gas in the § 172.101 table; or

(2) An appropriate common name for the material (e.g., “Refrigerant Gas”).

(c) *QT/NQT markings.* Each MC 330 and MC 331 cargo tank must be marked near the specification plate, in letters no less than 50 mm (2.0 inches) in height, with—

(1) “QT”, if the cargo tank is constructed of quenched and tempered steel; or

(2) “NQT”, if the cargo tank is constructed of other than quenched and tempered steel.

(d) After October 3, 2005, each on-vehicle manually-activated remote shutoff device for closure of the internal self-closing stop valve must be identified by marking “Emergency Shutoff” in letters at least 0.75 inches in height, in a color that contrasts with its background, and located in an area immediately adjacent to the means of closure.

[Amdt. 172-123, 55 FR 52592, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 62 FR 39045, July 22, 1997; 68 FR 19277, Apr. 18, 2003]

### § 172.330 Tank cars and multi-unit tank car tanks.

(a) *Shipping name and identification number.* No person may offer for transportation or transport a hazardous material—

(1) In a tank car unless the following conditions are met:

(i) The tank car must be marked on each side and each end as required by § 172.302 with the identification number specified for the material in the § 172.101 table; and

(ii) A tank car containing any of the following materials must be marked on each side with the key words of the proper shipping name specified for the material in the § 172.101 table, or with a common name authorized for the material in this subchapter (e.g., “Refrigerant Gas”):

Acrolein, stabilized  
Ammonia, anhydrous, liquefied  
Ammonia solutions (more than 50% ammonia)  
Bromine or Bromine solutions  
Bromine chloride  
Chloroprene, stabilized  
Dispersant gas or Refrigerant gas (as defined in § 173.115 of this subchapter)



Division 2.1 materials  
 Division 2.2 materials (in Class DOT 107 tank cars only)  
 Division 2.3 materials  
 Formic acid  
 Hydrocyanic acid, aqueous solutions  
 Hydrofluoric acid, solution  
 Hydrogen cyanide, stabilized (less than 3% water)  
 Hydrogen fluoride, anhydrous  
 Hydrogen peroxide, aqueous solutions (greater than 20% hydrogen peroxide)  
 Hydrogen peroxide, stabilized  
 Hydrogen peroxide and peroxyacetic acid mixtures  
 Nitric acid (other than red fuming)  
 Phosphorus, amorphous  
 Phosphorus, white dry *or* Phosphorus, white, under water *or* Phosphorus white, in solution, *or* Phosphorus, yellow dry *or* Phosphorus, yellow, under water *or* Phosphorus, yellow, in solution  
 Phosphorus white, molten  
 Potassium nitrate and sodium nitrate mixtures  
 Potassium permanganate  
 Sulfur trioxide, stabilized  
 Sulfur trioxide, uninhibited

(2) In a multi-unit tank car tank, unless the tank is marked on two opposing sides, in letters and numerals no less than 50 mm (2.0 inches) high—

(i) With the proper shipping name specified for the material in the §172.101 table or with a common name authorized for the material in this subchapter (e.g., “Refrigerant Gas”); and

(ii) With the identification number specified for the material in the §172.101 table, unless marked in accordance with §§172.302(a) and 172.332 of this subpart.

(b) A motor vehicle or rail car used to transport a multi-unit tank car tank containing a hazardous material must be marked on each side and each end, as required by §172.332, with the identification number specified for the material in the §172.101 table.

[Amdt. 172-123, 55 FR 52593, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; 57 FR 45458, Oct. 1, 1992; Amdt. 172-148, 61 FR 28676, June 5, 1996; Amdt. 172-148, 61 FR 50254, Sept. 25, 1996; 66 FR 33425, June 21, 2001]

**§ 172.331 Bulk packagings other than portable tanks, cargo tanks, tank cars and multi-unit tank car tanks.**

(a) Each person who offers a hazardous material to a motor carrier for transportation in a bulk packaging shall provide the motor carrier with

the required identification numbers on placards or plain white square-on-point display configurations, as authorized, or shall affix orange panels containing the required identification numbers to the packaging prior to or at the time the material is offered for transportation, unless the packaging is already marked with the identification number as required by this subchapter.

(b) Each person who offers a bulk packaging containing a hazardous material for transportation shall affix to the packaging the required identification numbers on orange panels, square-on-point configurations or placards, as appropriate, prior to, or at the time the packaging is offered for transportation unless it is already marked with identification numbers as required by this subchapter.

(c) For a bulk packaging contained in or on a transport vehicle or freight container, if the identification number marking on the bulk packaging (e.g., an IBC) required by §172.302(a) is not visible, the transport vehicle or freight container must be marked as required by §172.332 on each side and each end with the identification number specified for the material in the §172.101 table.

[Amdt. 172-123, 55 FR 52593, Dec. 21, 1994, as amended by Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 62 FR 39398, July 22, 1997]

**§ 172.332 Identification number markings.**

(a) *General.* When required by §172.301, §172.302, §172.313, §172.326, §172.328, §172.330, or §172.331, identification number markings must be displayed on orange panels or placards as specified in this section, or on white square-on-point configurations as prescribed in §172.336(b).

(b) *Orange panels.* Display of an identification number on an orange panel shall be in conformance with the following:

(1) The orange panel must be 160 mm (6.3 inches) high by 400 mm (15.7 inches) wide with a 15 mm (0.6 inches) black outer border. The identification number shall be displayed in 100 mm (3.9 inches) black Helvetica Medium numerals on the orange panel. Measurements may vary from those specified plus or minus 5 mm (0.2 inches).

§ 172.334

49 CFR Ch. I (10-1-04 Edition)

(2) The orange panel may be made of any durable material prescribed for placards in §172.519, and shall be of the orange color specified for labels or placards in appendix A to this part.

(3) The name and hazard class of a material may be shown in the upper left border of the orange panel in letters not more than 18 points (0.25 in.) high.

(4) Except for size and color, the orange panel and identification numbers shall be as illustrated for Liquefied petroleum gas:



(c) *Placards.* Display of an identification number on a hazard warning placard shall be in conformance with the following:

(1) The identification number shall be displayed across the center area of the placard in 88 mm (3.5 inches) black Alpine Gothic or Alternate Gothic No. 3 numerals on a white background 100 mm (3.9 inches) high and approximately 215 mm (8.5 inches) wide and may be outlined with a solid or dotted line border.

(2) The top of the 100 mm (3.9 inches) high white background shall be approximately 40 mm (1.6 inches) above the placard horizontal center line.

(3) An identification number may be displayed only on a placard corresponding to the primary hazard class of the hazardous material.

(4) For a COMBUSTIBLE placard used to display an identification number, the entire background below the white background for the identification number must be white during transportation by rail and may be white during transportation by highway.

(5) The name of the hazardous material and the hazard class may be shown in letters not more than 18 points high immediately within the upper border of the space on the placard bearing the identification number of the material.

(6) If an identification number is placed over the word(s) on a placard, the word(s) should be substantially covered to maximize the effectiveness of the identification number.

(d) Except for size and color, the display of an identification number on a placard shall be as illustrated for Acetone:



[Amdt. 172-101, 45 FR 74667, Nov. 10, 1980, as amended by Amdt. 172-81, 48 FR 28099, June 20, 1983; Amdt. 172-110, 52 FR 29527, Aug. 10, 1987; Amdt. 172-123, 55 FR 52593, Dec. 21, 1990; 56 FR 66255, Dec. 20, 1991; Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 65 FR 50459, Aug. 18, 2000; 68 FR 57632, Oct. 6, 2003]

§ 172.334 Identification numbers; prohibited display.

(a) No person may display an identification number on a RADIOACTIVE, EXPLOSIVES 1.1, 1.2, 1.3, 1.4, 1.5 or 1.6, DANGEROUS, or subsidiary hazard placard.

(b) No person may display an identification number on a placard, orange panel or white square-on-point display configuration unless—

(1) The identification number is specified for the material in §172.101;

(2) The identification number is displayed on the placard, orange panel or white square-on-point configuration authorized by §172.332 or §172.336(b), as appropriate, and any placard used for display of the identification number corresponds to the hazard class of the material specified in §172.504;

(3) Except as provided under §172.336 (c)(4) or (c)(5), the package, freight container, or transport vehicle on which the number is displayed contains the

hazardous material associated with that identification number in §172.101.

(c) Except as required by §172.332(c)(4) for a combustible liquid, the identification number of a material may be displayed only on the placards required by the tables in §172.504.

(d) Except as provided in §172.336, a placard bearing an identification number may not be used to meet the requirements of subpart F of this part unless it is the correct identification number for all hazardous materials of the same class in the transport vehicle or freight container on which it is displayed.

(e) Except as specified in §172.338, an identification number may not be displayed on an orange panel on a cargo tank unless affixed to the cargo tank by the person offering the hazardous material for transportation in the cargo tank.

(f) If a placard is required by §172.504, an identification number may not be displayed on an orange panel unless it is displayed in proximity to the placard.

(g) No person shall add any color, number, letter, symbol, or word other than as specified in this subchapter, to any identification number marking display which is required or authorized by this subchapter.

[Amdt. 172-101, 45 FR 74667, Nov. 10, 1980, as amended by Amdt. 172-104, 51 FR 23078, June 25, 1986; Amdt. 172-110, 52 FR 29528, Aug. 10, 1987; Amdt. 172-123, 55 FR 52593, Dec. 21, 1990; 56 FR 66255, Dec. 20, 1991; Amdt. 172-127, 59 FR 49133, Sept. 26, 1994]

**§ 172.336 Identification numbers; special provisions.**

(a) When not required or prohibited by this subpart, identification numbers may be displayed on a transport vehicle or a freight container in the manner prescribed by this subpart.

(b) Identification numbers, when required, must be displayed on either orange panels (see §172.332(b)) or on a plain white square-on-point display configuration having the same outside dimensions as a placard. In addition, for materials in hazard classes for which placards are specified and identification number displays are required, but for which identification numbers may not be displayed on the placards

authorized for the material (see §172.334(a)), identification numbers must be displayed on orange panels or on the plain white square-on-point display configuration in association with the required placards. An identification number displayed on a white square-on-point display configuration is not considered to be a placard.

(1) The 100 mm (3.9 inch) by 215 mm (8.5 inches) area containing the identification number shall be located as prescribed by §172.332 (c)(1) and (c)(2) and may be outlined with a solid or dotted line border.

(2) [Reserved]

(c) Identification numbers are not required:

(1) On the ends of a portable tank, cargo tank or tank car having more than one compartment if hazardous materials having different identification numbers are being transported therein. In such a circumstance, the identification numbers on the sides of the tank shall be displayed in the same sequence as the compartments containing the materials they identify.

(2) On a cargo tank containing only gasoline, if the cargo tank is marked "Gasoline" on each side and rear in letters no less than 50 mm (2 inches) high, or is placarded in accordance with §172.542(c).

(3) On a cargo tank containing only fuel oil, if the cargo tank is marked "Fuel Oil" on each side and rear in letters no less than 50 mm (2 inches) high, or is placarded in accordance with §172.544(c).

(4) For each of the different liquid petroleum distillate fuels, including gasoline and gasohol in a compartmented cargo tank or tank car, if the identification number is displayed for the distillate fuel having the lowest flash point.

(5) For each of the different liquid petroleum distillate fuels, including gasoline and gasohol transported in a cargo tank, if the identification number is displayed for the liquid petroleum distillate fuel having the lowest flash point.

**§ 172.338**

(6) On nurse tanks meeting the provisions of §173.315(m) of this subchapter.

[Amdt. 172-101, 45 FR 74667, Nov. 10, 1980, as amended by Amdt. 172-74, 47 FR 40365, Sept. 30, 1982; Amdt. 172-109, 52 FR 13038, Apr. 20, 1987; Amdt. 172-110, 52 FR 29528, Aug. 10, 1987; Amdt. 172-123, 55 FR 52593, Dec. 21, 1990; 56 FR 66255, Dec. 20, 1991; 65 FR 50459, Aug. 18, 2000]

**§ 172.338 Replacement of identification numbers.**

If more than one of the identification number markings on placards, orange panels, or white square-on-point display configurations that are required to be displayed are lost, damaged or destroyed during transportation, the carrier shall replace all the missing or damaged identification numbers as soon as practicable. However, in such a case, the numbers may be entered by hand on the appropriate placard, orange panel or white square-on-point display configuration providing the correct identification numbers are entered legibly using an indelible marking material. When entered by hand, the identification numbers must be located in the white display area specified in §172.332. This section does not preclude required compliance with the placarding requirements of subpart F of this subchapter.

[Amdt. 172-110, 52 FR 29528, Aug. 10, 1987]

**49 CFR Ch. I (10-1-04 Edition)**

**Subpart E—Labeling**

**§ 172.400 General labeling requirements.**

(a) Except as specified in §172.400a, each person who offers for transportation or transports a hazardous material in any of the following packages or containment devices, shall label the package or containment device with labels specified for the material in the §172.101 table and in this subpart:

- (1) A non-bulk package;
  - (2) A bulk packaging, other than a cargo tank, portable tank, or tank car, with a volumetric capacity of less than 18m<sup>3</sup> (640 cubic feet), unless placarded in accordance with subpart F of this part;
  - (3) A portable tank of less than 3785 L (1000 gallons) capacity, unless placarded in accordance with subpart F of this part;
  - (4) A DOT Specification 106 or 110 multi-unit tank car tank, unless placarded in accordance with subpart F of this part; and
  - (5) An overpack, freight container or unit load device, of less than 18 m<sup>3</sup> (640 cubic feet), which contains a package for which labels are required, unless placarded or marked in accordance with §172.512 of this part.
- (b) Labeling is required for a hazardous material which meets one or more hazard class definitions, in accordance with column 6 of the §172.101 table and the following table:

Hazard class or division	Label name	Label design or section reference
1.1 .....	EXPLOSIVES 1.1 .....	172.411
1.2 .....	EXPLOSIVES 1.2 .....	172.411
1.3 .....	EXPLOSIVES 1.3 .....	172.411
1.4 .....	EXPLOSIVES 1.4 .....	172.411
1.5 .....	EXPLOSIVES 1.5 .....	172.411
1.6 .....	EXPLOSIVES 1.6 .....	172.411
2.1 .....	FLAMMABLE GAS .....	172.417
2.2 .....	NONFLAMMABLE GAS .....	172.415
2.3 .....	POISON GAS .....	172.416
3 (flammable liquid) Combustible liquid .....	FLAMMABLE LIQUID (none) .....	172.419
4.1 .....	FLAMMABLE SOLID .....	172.420
4.2 .....	SPONTANEOUSLY COMBUSTIBLE .....	172.422
4.3 .....	DANGEROUS WHEN WET .....	172.423
5.1 .....	OXIDIZER .....	172.426
5.2 .....	ORGANIC PEROXIDE .....	172.427
6.1 (inhalation hazard, Zone A or B) .....	POISON INHALATION HAZARD .....	172.429
6.1 (other than inhalation hazard, Zone A or B) .....	POISON .....	172.430
6.2 .....	INFECTIOUS SUBSTANCE <sup>1</sup> .....	172.432
7 (see § 172.403) .....	RADIOACTIVE WHITE-I .....	172.436
7 .....	RADIOACTIVE YELLOW-II .....	172.438
7 .....	RADIOACTIVE YELLOW-III .....	172.440

Hazard class or division	Label name	Label design or section reference
7 (fissile radioactive material; see § 172.402) .....	FISSILE .....	172.441
7 (empty packages, see § 173.428 of this subchapter) ..	EMPTY .....	172.450
8 .....	CORROSIVE .....	172.442
9 .....	CLASS 9 .....	172.446

<sup>1</sup>The ETIOLOGIC AGENT label specified in regulations of the Department of Health and Human Services at 42 CFR 72.3 may apply to packages of infectious substances.

[Amdt. 172-123, 55 FR 52593, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; Amdt. 172-151, 62 FR 1228, Jan. 8, 1997; 64 FR 10776, Mar. 5, 1999; 64 FR 51918, Sept. 27, 1999; 69 FR 3668, Jan. 26, 2004]

**§ 172.400a Exceptions from labeling.**

(a) Notwithstanding the provisions of § 172.400, a label is not required on—

(1) A cylinder, or a Dewar flask conforming to § 173.320 of this subchapter containing a Division 2.1 or Division 2.2 gas that is—

- (i) Not poisonous;
- (ii) Carried by a private or contract motor carrier;
- (iii) Not overpacked; and
- (iv) Durably and legibly marked in accordance with CGA C-7, appendix A (IBR, see § 171.7 of this subchapter).

(2) A package or unit of military explosives (including ammunition) shipped by or on behalf of the DOD when in—

- (i) Freight containerload, carload or truckload shipments, if loaded and unloaded by the shipper or DOD; or
- (ii) Unitized or palletized break-bulk shipments by cargo vessel under charter to DOD if at least one required label is displayed on each unitized or palletized load.

(3) A package containing a hazardous material other than ammunition that is—

- (i) Loaded and unloaded under the supervision of DOD personnel, and
- (ii) Escorted by DOD personnel in a separate vehicle.

(4) A compressed gas cylinder permanently mounted in or on a transport vehicle.

(5) A freight container, aircraft unit load device or portable tank, which—

- (i) Is placarded in accordance with subpart F of this part, or
- (ii) Conforms to paragraph (a)(3) or (b)(3) of § 172.512.

(6) An overpack or unit load device in or on which labels representative of

each hazardous material in the overpack or unit load device are visible.

(7) A package of low specific activity radioactive material and surface contaminated objects, when transported under § 173.427(a)(6)(vi) of this subchapter.

(b) Certain exceptions to labeling requirements are provided for small quantities and limited quantities in applicable sections in part 173 of this subchapter.

(c) Notwithstanding the provisions of § 172.402(a), a subsidiary hazard label is not required on a package containing a Class 8 (corrosive) material which has a subsidiary hazard of Division 6.1 (poisonous) if the toxicity of the material is based solely on the corrosive destruction of tissue rather than systemic poisoning.

(d) A package containing a material poisonous by inhalation (see § 171.8 of this subchapter) in a closed transport vehicle or freight container may be excepted from the POISON INHALATION HAZARD or POISON GAS label or placard, under the conditions set forth in §§ 171.12 and 171.12a of this subchapter.

[Amdt. 172-123, 55 FR 52594, Dec. 21, 1990, as amended by Amdt. 172-132, 58 FR 50501, Sept. 27, 1993; 172-130, 58 FR 51531, Oct. 1, 1993; Amdt. 172-139, 59 FR 67490, Dec. 29, 1994; Amdt. 172-145, 60 FR 49110, Sept. 21, 1995; 63 FR 52849, Oct. 1, 1998; 64 FR 10776, Mar. 5, 1999; 65 FR 58626, Sept. 29, 2000; 66 FR 44255, Aug. 22, 2001; 68 FR 75742, Dec. 31, 2003]

**§ 172.401 Prohibited labeling.**

(a) Except as otherwise provided in this section, no person may offer for transportation and no carrier may transport a package bearing a label specified in this subpart unless:

§ 172.402

49 CFR Ch. I (10–1–04 Edition)

(1) The package contains a material that is a hazardous material, and

(2) The label represents a hazard of the hazardous material in the package.

(b) No person may offer for transportation and no carrier may transport a package bearing any marking or label which by its color, design, or shape could be confused with or conflict with a label prescribed by this part.

(c) The restrictions in paragraphs (a) and (b) of this section, do not apply to packages labeled in conformance with:

(1) The UN Recommendations (IBR, see § 171.7 of this subchapter);

(2) The IMDG Code (IBR, see § 171.7 of this subchapter);

(3) The ICAO Technical Instructions (IBR, see § 171.7 of this subchapter);

(4) The TDG Regulations (IBR, see § 171.7 of this subchapter).

(d) The provisions of paragraph (a) of this section do not apply to a packaging bearing a label if that packaging is:

(1) Unused or cleaned and purged of all residue;

(2) Transported in a transport vehicle or freight container in such a manner that the packaging is not visible during transportation; and

(3) Loaded by the shipper and unloaded by the shipper or consignee.

[Amdt. 172-9, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-75, 47 FR 44471, Oct. 7, 1982; Amdt. 172-77, 47 FR 54822, Dec. 6, 1982; Amdt. 172-94, 49 FR 38134, Sept. 27, 1984; Amdt. 172-100, 50 FR 41521, Oct. 11, 1985; Amdt. 172-123, 55 FR 52594, Dec. 21, 1990; Amdt. 172-132, 58 FR 50501, Sept. 27, 1993; 66 FR 8647, Feb. 1, 2001; 66 FR 45379, Aug. 28, 2001; 68 FR 75741, 75742, Dec. 31, 2003]

§ 172.402 Additional labeling requirements.

(a) *Subsidiary hazard labels.* Each package containing a hazardous material—

(1) Shall be labeled with primary and subsidiary hazard labels as specified in column 6 of the § 172.101 table (unless excepted in paragraph (a)(2) of this section); and

(2) For other than Class 1 or Class 2 materials (for subsidiary labeling requirements for Class 1 or Class 2 materials see paragraph (e) or paragraphs (f) and (g), respectively, of this section), if not already labeled under paragraph (a)(1) of this section, shall be labeled

with subsidiary hazard labels in accordance with the following table:

SUBSIDIARY HAZARD LABELS

Subsidiary hazard level (packing group)	Subsidiary Hazard (Class or Division)						
	3	4.1	4.2	4.3	5.1	6.1	8
I .....	X	***	***	X	X	X	X
II .....	X	X	X	X	X	X	X
III .....	*	X	X	X	X	X	X

X—Required for all modes.  
 \*—Required for all modes, except for a material with a flash point at or above 38 °C (100 °F) transported by rail or highway.

—Reserved  
 \*\*\*—Impossible as subsidiary hazard.

(b) *Display of hazard class on labels.* The appropriate hazard class or division number must be displayed in the lower corner of a primary hazard label and a subsidiary hazard label. A subsidiary label meeting the specifications of this section which were in effect on September 30, 2001, such as, a label without the hazard class or division number displayed in the lower corner of the label) may continue to be used as a subsidiary label in domestic transportation by rail or highway until October 1, 2005, provided the color tolerances are maintained and are in accordance with the display requirements in this subchapter.

(c) *Cargo Aircraft Only label.* Each person who offers for transportation or transports by aircraft a package containing a hazardous material which is authorized on cargo aircraft only shall label the package with a CARGO AIRCRAFT ONLY label specified in § 172.448 of this subpart.

(d) *Class 7 (Radioactive) Materials.* Except as otherwise provided in this paragraph, each package containing a Class 7 material that also meets the definition of one or more additional hazard classes must be labeled as a Class 7 material as required by § 172.403 and for each additional hazard.

(1) For a package containing a Class 7 material that also meets the definition of one or more additional hazard classes, whether or not the material satisfies § 173.4(a)(1)(iv) of this subchapter, a subsidiary label is not required on the package if the material conforms to the remaining criteria in § 173.4 of this subchapter.

(2) Each package or overpack containing fissile material, other than fissile-excepted material (see § 173.453

of this subchapter) must bear two FISSILE labels, affixed to opposite sides of the package or overpack, which conforms to the figure shown in §172.441; such labels, where applicable, must be affixed adjacent to the labels for radioactive materials.

(e) *Class 1 (explosive) Materials.* In addition to the label specified in column 6 of the §172.101 table, each package of Class 1 material that also meets the definition for:

(1) Division 6.1, Packing Groups I or II, shall be labeled POISON or POISON INHALATION HAZARD, as appropriate.

(2) Class 7, shall be labeled in accordance with §172.403 of this subpart.

(f) *Division 2.2 materials.* In addition to the label specified in column 6 of the §172.101 table, each package of Division 2.2 material that also meets the definition for an oxidizing gas (see §171.8 of this subchapter) must be labeled OXIDIZER.

(g) *Division 2.3 materials.* In addition to the label specified in column 6 of the §172.101 table, each package of Division 2.3 material that also meets the definition for:

(1) Division 2.1, must be labeled Flammable Gas;

(2) Division 5.1, must be labeled Oxidizer; and

(3) Class 8, must be labeled Corrosive.

[Amdt. 172-123, 55 FR 52594, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; Amdt. 172-139, 59 FR 67490, Dec. 29, 1994; Amdt. 172-140, 60 FR 26805, May 18, 1995; Amdt. 172-149, 61 FR 27173, May 30, 1996; 62 FR 39405, July 22, 1997; 66 FR 33425, June 21, 2001; 69 FR 3668, Jan. 26, 2004]

**§ 172.403 Class 7 (radioactive) material.**

(a) Unless excepted from labeling by §§173.421 through 173.427 of this subchapter, each package of radioactive material must be labeled as provided in this section.

(b) The proper label to affix to a package of Class 7 (radioactive) material is based on the radiation level at the surface of the package and the transport index. The proper category of label must be determined in accordance with paragraph (c) of this section. The label to be applied must be the highest category required for any of the two determining conditions for the package. RADIOACTIVE WHITE-I is the lowest category and RADIOACTIVE YELLOW-III is the highest. For example, a package with a transport index of 0.8 and a maximum surface radiation level of 0.6 millisievert (60 millirems) per hour must bear a RADIOACTIVE YELLOW-III label.

(c) Category of label to be applied to Class 7 (radioactive) materials packages:

Transport index	Maximum radiation level at any point on the external surface	Label category <sup>1</sup>
0 <sup>2</sup> .....	Less than or equal to 0.005 mSv/h (0.5 mrem/h).	WHITE-I.
More than 0 but not more than 1 .....	Greater than 0.005 mSv/h (0.5 mrem/h) but less than or equal to 0.5 mSv/h (50 mrem/h).	YELLOW-II.
More than 1 but not more than 10 .....	Greater than 0.5 mSv/h (50 mrem/h) but less than or equal to 2 mSv/h (200 mrem/h).	YELLOW-III.
More than 10 .....	Greater than 2 mSv/h (200 mrem/h) but less than or equal to 10 mSv/h (1,000 mrem/h).	YELLOW-III (Must be shipped under exclusive use provisions; see 173.441(b) of this subchapter).

<sup>1</sup> Any package containing a "highway route controlled quantity" (§ 173.403 of this subchapter) must be labelled as RADIOACTIVE YELLOW-III.

<sup>2</sup> If the measured TI is not greater than 0.05, the value may be considered to be zero.

(d) *EMPTY* label. See §173.428(d) of this subchapter for EMPTY labeling requirements.

(e) *FISSILE* label. For packages required in §172.402 to bear a FISSILE label, each such label must be com-

pleted with the criticality safety index (CSI) assigned in the NRC or DOE package design approval, or in the certificate of approval for special arrangement or the certificate of approval for

the package design issued by the Competent Authority for import and export shipments. For overpacks and freight containers required in §172.402 to bear a FISSILE label, the CSI on the label must be the sum of the CSIs for all of the packages contained in the overpack or freight container.

(f) Each package required by this section to be labeled with a RADIOACTIVE label must have two of these labels, affixed to opposite sides of the package. (See §172.406(e)(3) for freight container label requirements).

(g) The following applicable items of information must be entered in the blank spaces on the RADIOACTIVE label by legible printing (manual or mechanical), using a durable weather resistant means of marking:

(1) *Contents.* Except for LSA-1 material, the names of the radionuclides as taken from the listing of radionuclides in §173.435 of this subchapter (symbols which conform to established radiation protection terminology are authorized, i.e., <sup>99</sup>Mo, <sup>60</sup>Co, etc.). For mixtures of radionuclides, with consideration of space available on the label, the radionuclides that must be shown must be determined in accordance with §173.433(g) of this subchapter. For LSA-I material, the term “LSA-I” may be used in place of the names of the radionuclides.

(2) *Activity.* The activity in the package must be expressed in appropriate SI units (e.g., Becquerels (Bq), Terabecquerels (TBq), etc.). The activity may also be stated in appropriate customary units (Curies (Ci), milliCuries (mCi), microCuries (uCi), etc.) in parentheses following the SI units. Abbreviations are authorized. Except for plutonium-239 and plutonium-241, the weight in grams or kilograms of fissile radionuclides may be inserted instead of activity units. For plutonium-239 and plutonium-241, the weight in grams of fissile radionuclides may be inserted in addition to the activity units.

(3) *Transport index.* (see §173.403 of this subchapter.)

(h) When one or more packages of Class 7 (radioactive) material are placed within an overpack, the overpack must be labeled as prescribed in this section, except as follows:

(1) The “contents” entry on the label may state “mixed” in place of the names of the radionuclides unless each inside package contains the same radionuclide(s).

(2) The “activity” entry on the label must be determined by adding together the number of becquerels of the Class 7 (radioactive) materials packages contained therein.

(3) For an overpack, the transport index (TI) must be determined by adding together the transport indices of the Class 7 (radioactive) materials packages contained therein, except that for a rigid overpack, the transport index (TI) may alternatively be determined by direct measurement as prescribed in §173.403 of this subchapter under the definition for “transport index,” taken by the person initially offering the packages contained within the overpack for shipment.

(4) The category of Class 7 label for the overpack must be determined from the table in §172.403(c) using the TI derived according to paragraph (h)(3) of this section, and the maximum radiation level on the surface of the overpack.

(5) The category of the Class 7 label of the overpack, and not that of any of the packages contained therein, must be used in accordance with Table 1 of §172.504(e) to determine when the transport vehicle must be placarded.

(6) For fissile material, the criticality safety index which must be entered on the overpack FISSILE label is the sum of the criticality safety indices of the individual packages in the overpack, as stated in the certificate of approval for the package design issued by the NRC or the U.S. Competent Authority.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.403, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

**§ 172.404 Labels for mixed and consolidated packaging.**

(a) *Mixed packaging.* When hazardous materials having different hazard classes are packed within the same packaging, or within the same outside container or overpack as described in



§173.25 and authorized by §173.21 of this subchapter, the packaging, outside container or overpack must be labeled as required for each class of hazardous material contained therein.

(b) *Consolidated packaging.* When two or more packages containing compatible hazardous material (see §173.21 of this subchapter) are placed within the same outside container or overpack, the outside container or overpack must be labeled as required for each class of hazardous material contained therein.

**§172.405 Authorized label modifications.**

(a) For Classes 1, 2, 3, 4, 5, 6, and 8, text indicating a hazard (for example FLAMMABLE LIQUID) is not required on a primary or subsidiary label.

(b) For a package containing Oxygen, compressed, or Oxygen, refrigerated liquid, the OXIDIZER label specified in §172.426 of this subpart, modified to display the word "OXYGEN" instead of "OXIDIZER", and the class number "2" instead of "5.1", may be used in place of the NON-FLAMMABLE GAS and OXIDIZER labels. Notwithstanding the provisions of paragraph (a) of this section, the word "OXYGEN" must appear on the label.

(c) For a package containing a Division 6.1, Packing Group III material, the POISON label specified in §172.430 may be modified to display the text "PG III" instead of "POISON" or "TOXIC" below the mid line of the label. Also see §172.313(d).

[Amdt. 172-123, 55 FR 52594, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; 57 FR 45458, Oct. 1, 1992; 64 FR 10776, Mar. 5, 1999; 66 FR 33425, June 21, 2001]

**§172.406 Placement of labels.**

(a) *General.* (1) Except as provided in paragraphs (b) and (e) of this section, each label required by this subpart must—

(i) Be printed on or affixed to a surface (other than the bottom) of the package or containment device containing the hazardous material; and

(ii) Be located on the same surface of the package and near the proper shipping name marking, if the package dimensions are adequate.

(2) Except as provided in paragraph (e) of this section, duplicate labeling is

not required on a package or containment device (such as to satisfy redundant labeling requirements).

(b) *Exceptions.* A label may be printed on or placed on a securely affixed tag, or may be affixed by other suitable means to:

(1) A package that contains no radioactive material and which has dimensions less than those of the required label;

(2) A cylinder; and

(3) A package which has such an irregular surface that a label cannot be satisfactorily affixed.

(c) *Placement of multiple labels.* When primary and subsidiary hazard labels are required, they must be displayed next to each other. Placement conforms to this requirement if labels are within 150 mm (6 inches) of one another.

(d) *Contrast with background.* Each label must be printed on or affixed to a background of contrasting color, or must have a dotted or solid line outer border.

(e) *Duplicate labeling.* Generally, only one of each different required label must be displayed on a package. However, duplicate labels must be displayed on at least two sides or two ends (other than the bottom) of—

(1) Each package or overpack having a volume of 1.8 m<sup>3</sup> (64 cubic feet) or more;

(2) Each non-bulk package containing a radioactive material;

(3) Each DOT 106 or 110 multi-unit tank car tank. Labels must be displayed on each end;

(4) Each portable tank of less than 3,785 L (1000 gallons) capacity; and

(5) Each freight container or aircraft unit load device having a volume of 1.8 m<sup>3</sup> (64 cubic feet) or more, but less than 18 m<sup>3</sup> (640 cubic feet). One of each required label must be displayed on or near the closure.

(f) *Visibility.* A label must be clearly visible and may not be obscured by markings or attachments.

[Amdt. 172-123, 55 FR 52594, Dec. 21, 1990, as amended at 56 FR 66255, Dec. 20, 1991; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993]

**§172.407 Label specifications.**

(a) *Durability.* Each label, whether printed on or affixed to a package,

must be durable and weather resistant. A label on a package must be able to withstand, without deterioration or a substantial change in color, a 30-day exposure to conditions incident to transportation that reasonably could be expected to be encountered by the labeled package.

(b) *Design.* (1) Except for size and color, the printing, inner border, and symbol on each label must be as shown in §§ 172.411 through 172.448 of this subpart, as appropriate.

(2) The dotted line border shown on each label is not part of the label specification, except when used as an alternative for the solid line outer border to meet the requirements of § 172.406(d) of this subpart.

(c) *Size.* (1) Each diamond (square-on-point) label prescribed in this subpart must be at least 100 mm (3.9 inches) on each side with each side having a solid line inner border 5.0 to 6.3 mm (0.2 to 0.25 inches) from the edge.

(2) The CARGO AIRCRAFT ONLY label must be a rectangle measuring at least 110 mm (4.3 inches) in height by 120 mm (4.7 inches) in width. The word “DANGER” must be shown in letters measuring at least 12.7 mm (0.5 inches) in height.

(3) Except as otherwise provided in this subpart, the hazard class number, or division number, as appropriate, must be at least 6.3 mm (0.25 inches) and not greater than 12.7 mm (0.5 inches).

(4) When text indicating a hazard is displayed on a label, the label name must be shown in letters measuring at least 7.6 mm (0.3 inches) in height. For SPONTANEOUSLY COMBUSTIBLE or DANGEROUS WHEN WET labels, the words “Spontaneously” and “When Wet” must be shown in letters measuring at least 5.1 mm (0.2 inches) in height.

(5) The symbol on each label must be proportionate in size to that shown in the appropriate section of this subpart.

(d) *Color.* (1) The background color on each label must be as prescribed in §§ 172.411 through 172.448 of this subpart, as appropriate.

(2) The symbol, text, numbers, and border must be shown in black on a label except that—

(i) White may be used on a label with a one color background of green, red or blue; and

(ii) White must be used for the text and class number for the CORROSIVE label.

(3) Black and any color on a label must be able to withstand, without substantial change, a 72-hour fadeometer test (for a description of equipment designed for this purpose, see ASTM G 23-69 (1975) or ASTM G 26-70).

(4) (i) A color on a label, upon visual examination, must fall within the color tolerances—

(A) Displayed on color charts conforming to the technical specifications for charts set forth in table 1 or 2 in appendix A to this part; or

(B) For labels printed on packaging surfaces, specified in table 3 in appendix A to this part.

(ii) Color charts conforming to appendix A to this part are on display in Office of Hazardous Materials Safety, Office of Hazardous Materials Standards, Room 8422, Nassif Building, 400 Seventh Street, SW., Washington DC 20590-0001.

(5) The specified label color must extend to the edge of the label in the area designated on each label except the CORROSIVE, RADIOACTIVE YELLOW-II AND RADIOACTIVE YELLOW-III labels on which the color must extend only to the inner border.

(e) *Form identification.* A label may contain form identification information, including the name of its maker, provided that information is printed outside the solid line inner border in no larger than 10-point type.

(f) *Exceptions.* Except for materials poisonous by inhalation (See § 171.8 of this subchapter), a label conforming to specifications in the UN Recommendations may be used in place of a corresponding label that conforms to the requirements of this subpart.

(g) *Trefoil symbol.* The trefoil symbol on the RADIOACTIVE WHITE-I, RADIOACTIVE YELLOW-II, and RADIOACTIVE YELLOW-III labels must meet

the appropriate specifications in appendix B of this part.

[Amdt. 172-123, 55 FR 52595, Dec. 21, 1990, as amended at 56 FR 66256, Dec. 20, 1991; Amdt. 172-143, 60 FR 50305, Sept. 28, 1995; 64 FR 10776, Mar. 5, 1999; 66 FR 8647, Feb. 1, 2001; 66 FR 44255, Aug. 22, 2001; 67 FR 61013, Sept. 27, 2002]

**§ 172.411 EXPLOSIVE 1.1, 1.2, 1.3, 1.4, 1.5 and 1.6 labels, and EXPLOSIVE Subsidiary label.**

(a) Except for size and color, the EXPLOSIVE 1.1, EXPLOSIVE 1.2 and EXPLOSIVE 1.3 labels must be as follows:




(b) In addition to complying with § 172.407, the background color on the EXPLOSIVE 1.1, EXPLOSIVE 1.2 and EXPLOSIVE 1.3 labels must be orange. The “\*\*\*” must be replaced with the appropriate division number and compatibility group letter. The compatibility group letter must be the same size as the division number and must be shown as a capitalized Roman letter.

(c) Except for size and color, the EXPLOSIVE 1.4, EXPLOSIVE 1.5 and EXPLOSIVE 1.6 labels must be as follows:


EXPLOSIVE 1.4:



EXPLOSIVE 1.5:



EXPLOSIVE 1.6:



(d) In addition to complying with §172.407, the background color on the EXPLOSIVE 1.4, EXPLOSIVE 1.5 and EXPLOSIVE 1.6 label must be orange. The “\*” must be replaced with the appropriate compatibility group. The compatibility group letter must be shown as a capitalized Roman letter. Division numbers must measure at least 30 mm (1.2 inches) in height and at least 5 mm (0.2 inches) in width.


(e) An EXPLOSIVE subsidiary label is required for materials identified in Column (6) of the HMT as having an explosive subsidiary hazard. The division number or compatibility group letter may be displayed on the subsidiary hazard label. Except for size and color, the EXPLOSIVE subsidiary label must be as follows:

(f) The EXPLOSIVE subsidiary label must comply with §172.407.

[Amdt. 172-123, 56 FR 66256, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67490, Dec. 29, 1994; 66 FR 33425, June 21, 2001; 68 FR 45031, July 31, 2003]

**§ 172.415 NON-FLAMMABLE GAS label.**

(a) Except for size and color, the NON-FLAMMABLE GAS label must be as follows:



(b) In addition to complying with §172.407, the background color on the NON-FLAMMABLE GAS label must be green.

[Amdt. 172-123, 56 66256, Dec. 20, 1991]

**§ 172.416 POISON GAS label.**

(a) Except for size and color, the POISON GAS label must be as follows:




(b) In addition to complying with §172.407, the background on the POISON GAS label and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 14 mm (0.54 inches) above the horizontal center line.

[62 FR 39405, July 22, 1997]

**§ 172.417 FLAMMABLE GAS label.**

(a) Except for size and color, the FLAMMABLE GAS label must be as follows:



(b) In addition to complying with §172.407, the background color on the FLAMMABLE GAS label must be red.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991]

**§ 172.419 FLAMMABLE LIQUID label.**

(a) Except for size and color the FLAMMABLE LIQUID label must be as follows:



(b) In addition to complying with §172.407, the background color on the FLAMMABLE LIQUID label must be red.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991]

**§ 172.420 FLAMMABLE SOLID label.**

(a) Except for size and color, the FLAMMABLE SOLID label must be as follows:



§ 172.422

(b) In addition to complying with § 172.407, the background on the FLAMMABLE SOLID label must be white with vertical red stripes equally spaced on each side of a red stripe placed in the center of the label. The red vertical stripes must be spaced so that, visually, they appear equal in width to the white spaces between them. The symbol (flame) and text (when used) must be overprinted. The text "FLAMMABLE SOLID" may be placed in a white rectangle.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991]

§ 172.422 SPONTANEOUSLY COMBUSTIBLE label.

(a) Except for size and color, the SPONTANEOUSLY COMBUSTIBLE label must be as follows:



(b) In addition to complying with § 172.407, the background color on the lower half of the SPONTANEOUSLY COMBUSTIBLE label must be red and the upper half must be white.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991, as amended at 57 FR 45458, Oct. 1, 1992]

§ 172.423 DANGEROUS WHEN WET label.

(a) Except for size and color, the DANGEROUS WHEN WET label must be as follows:

49 CFR Ch. I (10-1-04 Edition)



(b) In addition to complying with § 172.407, the background color on the DANGEROUS WHEN WET label must be blue.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991]

§ 172.426 OXIDIZER label.

(a) Except for size and color, the OXIDIZER label must be as follows:




(b) In addition to complying with § 172.407, the background color on the OXIDIZER label must be yellow.

[Amdt. 172-123, 56 FR 66257, Dec. 20, 1991]

§ 172.427 ORGANIC PEROXIDE label.

(a) Except for size and color, the ORGANIC PEROXIDE label must be as follows:

FOLLOWS.



(b) In addition to complying with §172.407, the background color on the ORGANIC PEROXIDE label must be yellow.

[Amdt. 172-123, 56 FR 66258, Dec. 20, 1991]

**§ 172.429 POISON INHALATION HAZARD label.**

(a) Except for size and color, the POISON INHALATION HAZARD label must be as follows:



(b) In addition to complying with §172.407, the background on the POISON INHALATION HAZARD label and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 14 mm (0.54 inches) above the horizontal center line.

[62 FR 39406, July 22, 1997]

**§ 172.430 POISON label.**

(a) Except for size and color, the POISON label must be as follows:



(b) In addition to complying with §172.407, the background on the POISON label must be white. The word "TOXIC" may be used in lieu of the word "POISON".

[Amdt. 172-123, 56 FR 66258, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67490, Dec. 29, 1994]

**§ 172.431 [Reserved]**

**§ 172.432 INFECTIOUS SUBSTANCE label.**

(a) Except for size and color, the INFECTIOUS SUBSTANCE label must be as follows:



(b) In addition to complying with § 172.407, the background on the INFECTIOUS SUBSTANCE label must be white.

[Amdt. 172-123, 56 FR 66258, Dec. 20, 1991, as amended at 67 FR 53136, Aug. 14, 2002]

**§ 172.436 RADIOACTIVE WHITE-I label.**

(a) Except for size and color, the RADIOACTIVE WHITE-I label must be as follows:



(b) In addition to complying with § 172.407, the background on the RADIOACTIVE WHITE-I label must be white. The printing and symbol must be



black, except for the "I" which must be red.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

**§ 172.438 RADIOACTIVE YELLOW-II label.**

(a) Except for size and color, the RADIOACTIVE YELLOW-II must be as follows:



(b) In addition to complying with §172.407, the background color on the RADIOACTIVE YELLOW-II label must be yellow in the top half and white in the lower half. The printing and symbol must be black, except for the "II" which must be red.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

**§ 172.440 RADIOACTIVE YELLOW-III label.**

(a) Except for size and color, the RADIOACTIVE YELLOW-III label must be as follows:




(b) In addition to complying with §172.407, the background color on the RADIOACTIVE YELLOW-III label must be yellow in the top half and white in the lower half. The printing and symbol must be black, except for the "III" which must be red.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

**§ 172.441 FISSILE label.**

(a) Except for size and color, the FISSILE label must be as follows:




(b) In addition to complying with §172.407, the background color on the FISSILE label must be white.

[69 FR 3669, Jan. 26, 2004]

**§ 172.442 CORROSIVE label.**

(a) Except for size and color, the CORROSIVE label must be as follows:




(b) In addition to complying with § 172.407, the background on the CORROSIVE label must be white in the top half and black in the lower half.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§ 172.444 [Reserved]

§ 172.446 CLASS 9 label.

(a) Except for size and color, the "CLASS 9" (miscellaneous hazardous materials) label must be as follows:



(b) In addition to complying with § 172.407, the background on the CLASS 9 label must be white with seven black vertical stripes on the top half. The black vertical stripes must be spaced, so that, visually, they appear equal in width to the six white spaces between them. The lower half of the label must be white with the class number "9" underlined and centered at the bottom.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§ 172.448 CARGO AIRCRAFT ONLY label.

(a) Except for size and color, the CARGO AIRCRAFT ONLY label must be as follows:




(b) The CARGO AIRCRAFT ONLY label must be black on an orange background.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§ 172.450 EMPTY label.

(a) Each EMPTY label, except for size, must be as follows:



(1) Each side must be at least 6 inches (152 mm.) with each letter at least 1 inch (25.4 mm.) in height.

(2) The label must be white with black printing.

(b) [Reserved]

Subpart F—Placarding

§ 172.500 Applicability of placarding requirements.

(a) Each person who offers for transportation or transports any hazardous

## § 172.502

material subject to this subchapter shall comply with the applicable placarding requirements of this subpart.

(b) This subpart does not apply to—

- (1) Infectious substances;
- (2) Hazardous materials classed as ORM-D;
- (3) Hazardous materials authorized by this subchapter to be offered for transportation as Limited Quantities when identified as such on shipping papers in accordance with §172.203(b);
- (4) Hazardous materials prepared in accordance with §173.13 of this subchapter;
- (5) Hazardous materials which are packaged as small quantities under the provisions of §173.4 of this subchapter; and
- (6) Combustible liquids in non-bulk packagings.

[Amdt. 172-123, 55 FR 52599, Dec. 21, 1990, as amended by Amdt. 172-149, 61 FR 27173, May 30, 1996]

### § 172.502 Prohibited and permissive placarding.

(a) *Prohibited placarding.* Except as provided in paragraph (b) of this section, no person may affix or display on a packaging, freight container, unit load device, motor vehicle or rail car—

- (1) Any placard described in this subpart unless—
  - (i) The material being offered or transported is a hazardous material;
  - (ii) The placard represents a hazard of the hazardous material being offered or transported; and
  - (iii) Any placarding conforms to the requirements of this subpart.

(2) Any sign, advertisement, slogan (such as “Drive Safely”), or device that, by its color, design, shape or content, could be confused with any placard prescribed in this subpart.

(b) *Exceptions.* (1) The restrictions in paragraph (a) of this section do not apply to a bulk packaging, freight container, unit load device, transport vehicle or rail car which is placarded in conformance with TDG Regulations, the IMDG Code or the UN Recommendations (IBR, see §171.7 of this subchapter).

(2) The restrictions of paragraph (a) of this section do not apply to the display of a BIOHAZARD marking, a

## 49 CFR Ch. I (10-1-04 Edition)

“HOT” marking, or an identification number on a white square-on-point configuration in accordance with §§172.323(c), 172.325(c), or 172.336(b) of this part, respectively.

(3) The restrictions in paragraph (a)(2) of this section do not apply until October 1, 2001 to a safety sign or safety slogan (e.g., “Drive Safely” or “Drive Carefully”), which was permanently marked on a transport vehicle, bulk packaging, or freight container on or before August 21, 1997.

(c) *Permissive placarding.* Placards may be displayed for a hazardous material, even when not required, if the placarding otherwise conforms to the requirements of this subpart.

[Amdt. 172-123, 55 FR 52599, Dec. 21, 1990, as amended at 56 FR 66259, Dec. 20, 1991; Amdt. 172-151, 62 FR 1230, Jan. 8, 1997; 62 FR 39389 and 39407, July 22, 1997; 66 FR 8647, Feb. 1, 2001; 66 FR 33426, June 21, 2001; 67 FR 53137, Aug. 14, 2002; 68 FR 75741, Dec. 31, 2003]

### § 172.503 Identification number display on placards.

For procedures and limitations pertaining to the display of identification numbers on placards, see §172.334.

[Amdt. 172-58, 45 FR 34701, May 22, 1980]

### § 172.504 General placarding requirements.

(a) *General.* Except as otherwise provided in this subchapter, each bulk packaging, freight container, unit load device, transport vehicle or rail car containing any quantity of a hazardous material must be placarded on each side and each end with the type of placards specified in tables 1 and 2 of this section and in accordance with other placarding requirements of this subpart, including the specifications for the placards named in the tables and described in detail in §§172.519 through 172.560.

(b) *DANGEROUS placard.* A freight container, unit load device, transport vehicle, or rail car which contains non-bulk packages with two or more categories of hazardous materials that require different placards specified in table 2 of paragraph (e) of this section may be placarded with a DANGEROUS placard instead of the separate placarding specified for each of the materials in table 2 of paragraph (e) of

this section. However, when 1,000 kg (2,205 pounds) aggregate gross weight or more of one category of material is loaded therein at one loading facility on a freight container, unit load device, transport vehicle, or rail car, the placard specified in table 2 of paragraph (e) of this section for that category must be applied.

(c) *Exception for less than 454 kg (1,001 pounds).* Except for bulk packagings and hazardous materials subject to §172.505, when hazardous materials covered by table 2 of this section are transported by highway or rail, placards are not required on—

(1) A transport vehicle or freight container which contains less than 454 kg (1001 pounds) aggregate gross weight of hazardous materials covered by table 2 of paragraph (e) of this section; or

(2) A rail car loaded with transport vehicles or freight containers, none of which is required to be placarded.

The exceptions provided in paragraph (c) of this section do not prohibit the display of placards in the manner prescribed in this subpart, if not otherwise prohibited (see §172.502), on transport vehicles or freight containers which are not required to be placarded.

(d) *Exception for empty non-bulk packages.* Except for hazardous materials subject to §172.505, a non-bulk packaging that contains only the residue of a hazardous material covered by Table 2 of paragraph (e) of this section need not be included in determining placarding requirements.

(e) *Placarding tables.* Placards are specified for hazardous materials in accordance with the following tables:

TABLE 1

Category of material (Hazard class or division number and additional description, as appropriate)	Placard name	Placard design section reference (§)
1.1 .....	EXPLOSIVES 1.1 .....	172.522
1.2 .....	EXPLOSIVES 1.2 .....	172.522
1.3 .....	EXPLOSIVES 1.3 .....	172.522
2.3 .....	POISON GAS .....	172.540
4.3 .....	DANGEROUS WHEN WET .....	172.548
5.2 (Organic peroxide, Type B, liquid or solid, temperature controlled).	ORGANIC PEROXIDE .....	172.552
6.1 (inhalation hazard, Zone A or B) .....	POISON INHALATION HAZARD .....	172.555
7 (Radioactive Yellow III label only) .....	RADIOACTIVE <sup>1</sup> .....	172.556

<sup>1</sup> RADIOACTIVE placard also required for exclusive use shipments of low specific activity material and surface contaminated objects transported in accordance with § 173.427(a) of this subchapter.

TABLE 2

Category of material (Hazard class or division number and additional description, as appropriate)	Placard name	Placard design section reference (§)
1.4 .....	EXPLOSIVES 1.4 .....	172.523
1.5 .....	EXPLOSIVES 1.5 .....	172.524
1.6 .....	EXPLOSIVES 1.6 .....	172.525
2.1 .....	FLAMMABLE GAS .....	172.532
2.2 .....	NON-FLAMMABLE GAS .....	172.528
3 .....	FLAMMABLE .....	172.542
Combustible liquid .....	COMBUSTIBLE .....	172.544
4.1 .....	FLAMMABLE SOLID .....	172.546
4.2 .....	SPONTANEOUSLY COMBUSTIBLE .....	172.547
5.1 .....	OXIDIZER .....	172.550
5.2 (Other than organic peroxide, Type B, liquid or solid, temperature controlled).	ORGANIC PEROXIDE .....	172.552
6.1 (other than inhalation hazard, Zone A or B) .....	POISON .....	172.554
6.2 .....	(None) .....	.....
8 .....	CORROSIVE .....	172.558
9 .....	Class 9 (see § 172.504(f)(9)) .....	172.560
ORM-D .....	(None) .....	.....

(f) *Additional placarding exceptions.* (1) When more than one division placard is required for Class 1 materials on a transport vehicle, rail car, freight container or unit load device, only the placard representing the lowest division number must be displayed.

(2) A FLAMMABLE placard may be used in place of a COMBUSTIBLE placard on—

(i) A cargo tank or portable tank.

(ii) A compartmented tank car which contains both flammable and combustible liquids.

(3) A NON-FLAMMABLE GAS placard is not required on a transport vehicle which contains non-flammable gas if the transport vehicle also contains flammable gas or oxygen and it is placarded with FLAMMABLE GAS or OXYGEN placards, as required.

(4) OXIDIZER placards are not required for Division 5.1 materials on freight containers, unit load devices, transport vehicles or rail cars which also contain Division 1.1 or 1.2 materials and which are placarded with EXPLOSIVES 1.1 or 1.2 placards, as required.

(5) For transportation by transport vehicle or rail car only, an OXIDIZER placard is not required for Division 5.1 materials on a transport vehicle, rail car or freight container which also contains Division 1.5 explosives and is placarded with EXPLOSIVES 1.5 placards, as required.

(6) The EXPLOSIVE 1.4 placard is not required for those Division 1.4 Compatibility Group S (1.4S) materials that are not required to be labeled 1.4S.

(7) For domestic transportation of oxygen, compressed or oxygen, refrigerated liquid, the OXYGEN placard in §172.530 of this subpart may be used in place of a NON-FLAMMABLE GAS placard.

(8) For domestic transportation, a POISON INHALATION HAZARD placard is not required on a transport vehicle or freight container that is already placarded with the POISON GAS placard.

(9) For domestic transportation, a Class 9 placard is not required. A bulk packaging containing a Class 9 material must be marked with the appropriate identification number displayed on a Class 9 placard, an orange panel or

a white-square-on-point display configuration as required by subpart D of this part.

(10) For Division 6.1, PG III materials, a POISON placard may be modified to display the text “PG III” below the mid line of the placard.

(11) For domestic transportation, a POISON placard is not required on a transport vehicle or freight container required to display a POISON INHALATION HAZARD or POISON GAS placard.

(g) For shipments of Class 1 (explosive materials) by aircraft or vessel, the applicable compatibility group letter must be displayed on the placards, or labels when applicable, required by this section. When more than one compatibility group placard is required for Class 1 materials, only one placard is required to be displayed, as provided in paragraphs (g)(1) through (g)(4) of this section. For the purposes of paragraphs (g)(1) through (g)(4), there is a distinction between the phrases *explosive articles* and *explosive substances*. *Explosive article* means an article containing an explosive substance; examples include a detonator, flare, primer or fuse. *Explosive substance* means a substance contained in a packaging that is not contained in an article; examples include black powder and smokeless powder.

(1) Explosive articles of compatibility groups C, D or E may be placarded displaying compatibility group E.

(2) Explosive articles of compatibility groups C, D, E or N may be placarded displaying compatibility group D.

(3) Explosive substances of compatibility groups C and D may be placarded displaying compatibility group D.

(4) Explosive articles of compatibility groups C, D, E or G, except for fireworks, may be placarded displaying compatibility group E.

[Amdt. 172–123, 55 FR 52600, Dec. 21, 1990]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §172.504, see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

**§ 172.505 Placarding for subsidiary hazards.**

(a) Each transport vehicle, freight container, portable tank, unit load device, or rail car that contains a poisonous material subject to the "Poison Inhalation Hazard" shipping description of § 172.203(m)(2) must be placarded with a POISON INHALATION HAZARD or POISON GAS placard, as appropriate, on each side and each end, in addition to any other placard required for that material in § 172.504. Duplication of the POISON INHALATION HAZARD or POISON GAS placard is not required.

(b) In addition to the RADIOACTIVE placard which may be required by § 172.504(e) of this subpart, each transport vehicle, portable tank or freight container that contains 454 kg (1001 pounds) or more gross weight of fissile or low specific activity uranium hexafluoride shall be placarded with a CORROSIVE placard on each side and each end.

(c) Each transport vehicle, portable tank, freight container or unit load device that contains a material which has a subsidiary hazard of being dangerous when wet, as defined in § 173.124 of this subchapter, shall be placarded with DANGEROUS WHEN WET placards, on each side and each end, in addition to the placards required by § 172.504.

(d) Hazardous materials that possess secondary hazards may exhibit subsidiary placards that correspond to the placards described in this part, even when not required by this part (see also § 172.519(b) (4) of this subpart).

[Amdt. 172-123, 55 FR 52601, Dec. 21, 1990, as amended at 56 FR 66260, Dec. 20, 1991; 57 FR 45460, Oct. 1, 1992; Amdt. 172-127, 59 FR 49133, Sept. 26, 1994; Amdt. 172-151, 62 FR 1231, Jan. 8, 1997; 62 FR 39398, July 22, 1997; 65 FR 58626, Sept. 29, 2000]

**§ 172.506 Providing and affixing placards: Highway.**

(a) Each person offering a motor carrier a hazardous material for transportation by highway shall provide to the motor carrier the required placards for the material being offered prior to or at the same time the material is offered for transportation, unless the carrier's motor vehicle is already plac-

arded for the material as required by this subpart.

(1) No motor carrier may transport a hazardous material in a motor vehicle, unless the placards required for the hazardous material are affixed thereto as required by this subpart.

(2) [Reserved]

(b) [Reserved]

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-29A, 41 FR 40679, Sept. 20, 1976]

**§ 172.507 Special placarding provisions: Highway.**

(a) Each motor vehicle used to transport a package of highway route controlled quantity Class 7 (radioactive) materials (see § 173.403 of this subchapter) must have the required RADIOACTIVE warning placard placed on a square background as described in § 172.527.

(b) A nurse tank, meeting the provisions of § 173.315(m) of this subchapter, is not required to be placarded on an end containing valves, fittings, regulators or gauges when those appurtenances prevent the markings and placard from being properly placed and visible.

[Amdt. 172-103, 51 FR 5971, Feb. 18, 1986, as amended by Amdt. 172-143, 60 FR 50305, Sept. 28, 1995]

**§ 172.508 Placarding and affixing placards: Rail.**

(a) Each person offering a hazardous material for transportation by rail shall affix to the rail car containing the material, the placards specified by this subpart. Placards displayed on motor vehicles, transport containers, or portable tanks may be used to satisfy this requirement, if the placards otherwise conform to the provisions of this subpart.

(b) No rail carrier may accept a rail car containing a hazardous material for transportation unless the placards for the hazardous material are affixed thereto as required by this subpart.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-123, 55 FR 52601, Dec. 21, 1990]

## § 172.510

## 49 CFR Ch. I (10–1–04 Edition)

### § 172.510 Special placarding provisions: Rail.

(a) *White square background.* The following must have the specified placards placed on a white square background, as described in § 172.527:

(1) Division 1.1 and 1.2 (explosive) materials which require EXPLOSIVES 1.1 or EXPLOSIVES 1.2 placards affixed to the rail car;

(2) Materials classed in Division 2.3 Hazard Zone A or 6.1 Packing Group I Hazard Zone A which require POISON GAS or POISON placards affixed to the rail car, including tank cars containing only a residue of the material; and

(3) Class DOT 113 tank cars used to transport a Division 2.1 (flammable gas) material, including tank cars containing only a residue of the material.

(b) *Chemical ammunition.* Each rail car containing Division 1.1 or 1.2 (explosive) ammunition which also meets the definition of a material poisonous by inhalation (see § 171.8 of this subchapter) must be placarded EXPLOSIVES 1.1 or EXPLOSIVES 1.2 and POISON GAS or POISON INHALATION HAZARD.

[Amdt. 172–29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172–103, 51 FR 5971, Feb. 18, 1986; Amdt. 172–110, 52 FR 29528, Aug. 10, 1987; Amdt. 172–111, 52 FR 36671, Sept. 30, 1987; Amdt. 172–123, 55 FR 52601, Dec. 21, 1990; 56 FR 66260, Dec. 20, 1991; 57 FR 45460, Oct. 1, 1992; Amdt. 172–248, 61 FR 28676, June 5, 1996; Amdt. 172–151, 62 FR 1231, Jan. 8, 1997; 62 FR 39398, July 22, 1997]

### § 172.512 Freight containers and aircraft unit load devices.

(a) *Capacity of 640 cubic feet or more.* Each person who offers for transportation, and each person who loads and transports, a hazardous material in a freight container or aircraft unit load device having a capacity of 640 cubic feet or more shall affix to the freight container or aircraft unit load device the placards specified for the material in accordance with § 172.504. However:

(1) The placarding exception provided in § 172.504(c) applies to motor vehicles transporting freight containers and aircraft unit load devices,

(2) The placarding exception provided in § 172.504(c) applies to each freight container and aircraft unit load device being transported for delivery to a con-

signee immediately following an air or water shipment, and,

(3) Placarding is not required on a freight container or aircraft unit load device if it is only transported by air and is identified as containing a hazardous material in the manner provided in part 7, chapter 2, section 2.7, of the ICAO Technical Instructions (IBR, see § 171.7 of this subchapter).

(b) *Capacity less than 18 m<sup>3</sup> (640 cubic feet).* Each person who offers for transportation by air, and each person who loads and transports by air, a hazardous material in a freight container or aircraft unit load device having a capacity of less than 18 m<sup>3</sup> (640 cubic feet) shall affix one placard of the type specified by paragraph (a) of this section unless the freight container or aircraft unit load device:

(1) Is labeled in accordance with subpart E of this part, including § 172.406(e);

(2) Contains radioactive materials requiring the Radioactive Yellow III label and is placarded with one Radioactive placard and is labeled in accordance with subpart E of this part, including § 172.406(e); or,

(3) Is identified as containing a hazardous material in the manner provided in part 7, chapter 2, section 2.7, of the ICAO Technical Instructions. When hazardous materials are offered for transportation, not involving air transportation, in a freight container having a capacity of less than 640 cubic feet the freight container need not be placarded. However, if not placarded, it must be labeled in accordance with subpart E of this part.

(c) Notwithstanding paragraphs (a) and (b) of this section, packages containing hazardous materials, other than ORM-D, offered for transportation by air in freight containers are subject to the inspection requirements of § 175.30 of this chapter.

[Amdt. 172–29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172–29A, 41 FR 40680, Sept. 20, 1976; Amdt. 172–87, 48 FR 53712, Nov. 29, 1983; 48 FR 55469, Dec. 13, 1983; Amdt. 172–103, 51 FR 5971, Feb. 18, 1986; Amdt. 172–111, 52 FR 36671, Sept. 30, 1987; Amdt. 172–123, 55 FR 52601, Dec. 21, 1990; 66 FR 33426, June 21, 2001; 66 FR 45182, Aug. 28, 2001; 68 FR 75741, Dec. 31, 2003; 69 FR 54046, Sept. 7, 2004]



**§ 172.514 Bulk packagings.**

(a) Except as provided in paragraph (c) of this section, each person who offers for transportation a bulk packaging which contains a hazardous material, shall affix the placards specified for the material in §§ 172.504 and 172.505.

(b) Each bulk packaging that is required to be placarded when it contains a hazardous material, must remain placarded when it is emptied, unless it is—

(1) Sufficiently cleaned of residue and purged of vapors to remove any potential hazard; or

(2) Refilled, with a material requiring different placards or no placards, to such an extent that any residue remaining in the packaging is no longer hazardous.

(c) Exceptions. The following packagings may be placarded on only two opposite sides or, alternatively, may be labeled instead of placarded in accordance with subpart E of this part:

(1) A portable tank having a capacity of less than 3,785 L (1000 gallons);

(2) A DOT 106 or 110 multi-unit tank car tank;

(3) A bulk packaging other than a portable tank, cargo tank, or tank car (e.g., a bulk bag or box) with a volumetric capacity of less than 18 m<sup>3</sup> (640 cubic feet); and

(4) An IBC.

[Amdt. 172-136, 59 FR 38064, July 26, 1994; Amdt. 172-148, 61 FR 50255, Sept. 25, 1996, as amended by 66 FR 45379, Aug. 28, 2001]

**§ 172.516 Visibility and display of placards.**

(a) Each placard on a motor vehicle and each placard on a rail car must be clearly visible from the direction it faces, except from the direction of another transport vehicle or rail car to which the motor vehicle or rail car is coupled. This requirement may be met by the placards displayed on the freight containers or portable tanks loaded on a motor vehicle or rail car.

(b) The required placarding of the front of a motor vehicle may be on the front of a truck-tractor instead of or in addition to the placarding on the front of the cargo body to which a truck-tractor is attached.

(c) Each placard on a transport vehicle, bulk packaging, freight container or aircraft unit load device must—

(1) Be securely attached or affixed thereto or placed in a holder thereon. (See appendix C to this part.);

(2) Be located clear of appurtenances and devices such as ladders, pipes, doors, and tarpaulins;

(3) So far as practicable, be located so that dirt or water is not directed to it from the wheels of the transport vehicle;

(4) Be located away from any marking (such as advertising) that could substantially reduce its effectiveness, and in any case at least 3 inches (76.0 mm.) away from such marking;

(5) Have the words or identification number (when authorized) printed on it displayed horizontally, reading from left to right;

(6) Be maintained by the carrier in a condition so that the format, legibility, color, and visibility of the placard will not be substantially reduced due to damage, deterioration, or obscurement by dirt or other matter;

(7) Be affixed to a background of contrasting color, or must have a dotted or solid line outer border which contrasts with the background color.

(d) Recommended specifications for a placard holder are set forth in appendix C of this part. Except for a placard holder similar to that contained in appendix C to this part, the means used to attach a placard may not obscure any part of its surface other than the borders.

(e) A placard or placard holder may be hinged provided the required format, color, and legibility of the placard are maintained.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-101, 45 FR 74668, Nov. 10, 1980; Amdt. 172-123, 55 FR 52601, Dec. 21, 1990; 65 FR 50460, Aug. 18, 2000]

**§ 172.519 General specifications for placards.**

(a) *Strength and durability.* Placards must conform to the following:

(1) A placard may be made of any plastic, metal or other material capable of withstanding, without deterioration or a substantial reduction in effectiveness, a 30-day exposure to open weather conditions.

§ 172.519

49 CFR Ch. I (10–1–04 Edition)

(2) A placard made of tagboard must be at least equal to that designated commercially as white tagboard. Tagboard must have a weight of at least 80 kg (176 pounds) per ream of 610 by 910 mm (24 by 36-inch) sheets, water-proofing materials included. In addition, each placard made of tagboard must be able to pass a 414 kPa (60 p.s.i.) Mullen test.

(3) Reflective or retroreflective materials may be used on a placard if the prescribed colors, strength and durability are maintained.

(b) *Design.* (1) Except as provided in § 172.332 of this part, each placard must be as described in this subpart, and except for size and color, the printing, inner border and symbol must be as shown in §§ 172.521 through 172.560 of this subpart, as appropriate.

(2) The dotted line border shown on each placard is not part of the placard specification. However, a dotted or solid line outer border may be used when needed to indicate the full size of a placard that is part of a larger format or is on a background of a non-contrasting color.

(3) For other than Class 7 or the DANGEROUS placard, text indicating a hazard (for example, “FLAMMABLE”) is not required. Text may be omitted from the OXYGEN placard only if the specific identification number is displayed on the placard.

(4) For a placard corresponding to the primary or subsidiary hazard class of a material, the hazard class or division number must be displayed in the lower corner of the placard. However, a permanently affixed subsidiary placard meeting the specifications of this section which were in effect on October 1, 2001, (such as, a placard without the hazard class or division number displayed in the lower corner of the placard) and which was installed prior to September 30, 2001, may continue to be used as a subsidiary placard in domestic transportation by rail or highway, provided the color tolerances are maintained and are in accordance with the display requirements in this subchapter. Stocks of non-permanently affixed subsidiary placards in compliance with the requirements in effect on September 30, 2001, may continue to be used in domestic transportation by rail

or highway until October 1, 2005, or until current stocks are depleted, whichever occurs first.

(c) *Size.* (1) Each placard prescribed in this subpart must measure at least 273 mm (10.8 inches) on each side and must have a solid line inner border approximately 12.7 mm (0.5 inches) from each edge.

(2) Except as otherwise provided in this subpart, the hazard class or division number, as appropriate, must be shown in numerals measuring at least 41 mm (1.6 inches) in height.

(3) Except as otherwise provided in this subpart, when text indicating a hazard is displayed on a placard, the printing must be in letters measuring at least 41 mm (1.6 inches) in height.

(d) *Color.* (1) The background color, symbol, text, numerals and inner border on a placard must be as specified in §§ 172.521 through 172.560 of this subpart, as appropriate.

(2) Black and any color on a placard must be able to withstand, without substantial change—

(i) A 72-hour fadeometer test (for a description of equipment designed for this purpose, see ASTM G 23-69 or ASTM G 26-70); and

(ii) A 30-day exposure to open weather.

(3) Upon visual examination, a color on a placard must fall within the color tolerances displayed on the appropriate Hazardous Materials Label and Placard Color Tolerance Chart (see § 172.407(d)(4)).

(4) The placard color must extend to the inner border and may extend to the edge of the placard in the area designated on each placard except the color on the CORROSIVE and RADIOACTIVE placards (black and yellow, respectively) must extend only to the inner border.

(e) *Form identification.* A placard may contain form identification information, including the name of its maker, provided that information is printed outside of the solid line inner border in no larger than 10-point type.

(f) *Exceptions.* When hazardous materials are offered for transportation or transported under the provisions of §§ 171.11, 171.12, or 171.12a of this subchapter, a placard conforming to the specifications in the ICAO Technical

Instructions, the IMDG Code, or the TDG Regulations, respectively, may be used in place of a corresponding placard that conforms to the requirements of this subpart, except that a bulk packaging, transport vehicle, or freight container containing a material poisonous by inhalation (see §171.8 of this subchapter) must be placarded in accordance with this subpart (see §§171.12(b)(8), 171.12(e) and 171.12a(b)(5) of this subchapter).

(g) *Trefoil symbol.* The trefoil symbol on the RADIOACTIVE placard must meet the appropriate specification in appendix B of this part.

[Amdt. 172-123, 55 FR 52601, Dec. 21, 1990, as amended at 56 FR 66260, Dec. 20, 1991; 57 FR 45460, Oct. 1, 1992; Amdt. 172-143, 60 FR 50305, Sept. 28, 1995; 65 FR 50460, Aug. 18, 2000; 66 FR 33426, June 21, 2001; 66 FR 44255, Aug. 22, 2001; 67 FR 15743, Apr. 3, 2002]

**§ 172.521 DANGEROUS placard.**

(a) Except for size and color, the DANGEROUS placard must be as follows:



(b) In addition to meeting the requirements of §172.519, and appendix B to this part, the DANGEROUS placard must have a red upper and lower triangle. The placard center area and 1/2-inch (12.7 mm.) border must be white. The inscription must be black with the 1/8-inch (3.2 mm.) border marker in the white area at each end of the inscription red.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-29A, 41 FR 40680, Sept. 20, 1976]

**§ 172.522 EXPLOSIVES 1.1, EXPLOSIVES 1.2 and EXPLOSIVES 1.3 placards.**

(a) Except for size and color, the EXPLOSIVES 1.1, EXPLOSIVES 1.2 and EXPLOSIVES 1.3 placards must be as follows:



(b) In addition to complying with §172.519 of this subpart, the background color on the EXPLOSIVES 1.1, EXPLOSIVES 1.2, and EXPLOSIVES 1.3 placards must be orange. The "\*" shall be replaced with the appropriate division number and, when required, appropriate compatibility group letter. The symbol, text, numerals and inner border must be black.

[Amdt. 172-123, 55 FR 52602, Dec. 21, 1990, as amended at 56 FR 66260, Dec. 20, 1991]

**§ 172.523 EXPLOSIVES 1.4 placard.**

(a) Except for size and color, the EXPLOSIVES 1.4 placard must be as follows:

§ 172.524



(b) In addition to complying with § 172.519 of this subpart, the background color on the EXPLOSIVES 1.4 placard must be orange. The “\*” shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.4, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

[Amdt. 172-123, 55 FR 52602, Dec. 21, 1990, as amended at 56 FR 66261, Dec. 20, 1991]

§ 172.524 **EXPLOSIVES 1.5 placard.**

(a) Except for size and color, the EXPLOSIVES 1.5 placard must be as follows:



(b) In addition to complying with the § 172.519 of this subpart, the background color on EXPLOSIVES 1.5 placard

49 CFR Ch. I (10-1-04 Edition)

must be orange. The “\*” shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.5, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

[Amdt. 172-123, 55 FR 52602, Dec. 21, 1990, as amended at 56 FR 66261, Dec. 20, 1991]

§ 172.525 **EXPLOSIVES 1.6 placard.**

(a) Except for size and color the EXPLOSIVES 1.6 placard must be as follows:




(b) In addition to complying with § 172.519 of this subpart, the background color on the EXPLOSIVES 1.6 placard must be orange. The “\*” shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.6, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

[Amdt. 172-123, 55 FR 52603, Dec. 21, 1990, as amended at 56 FR 66261, Dec. 20, 1991; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993]

§ 172.526 [Reserved]

§ 172.527 **Background requirements for certain placards.**

(a) Except for size and color, the square background required by § 172.510(a) for certain placards on rail cars, and § 172.507 for placards on motor vehicles containing a package of highway route controlled quantity radioactive materials, must be as follows:



(b) In addition to meeting the requirements of §172.519 for minimum durability and strength, the square background must consist of a white square measuring 14¼ inches (362.0 mm.) on each side surrounded by a black border extending to 15¼ inches (387.0 mm.) on each side.

[Amdt. 172-29, 41 FR 15996, Apr. 15, 1976, as amended by Amdt. 172-64, 46 FR 5316, Jan. 19, 1981; Amdt. 172-78, 48 FR 10226, Mar. 10, 1983]

**§ 172.528 NON-FLAMMABLE GAS placard.**

(a) Except for size and color, the NON-FLAMMABLE GAS placard must be as follows:



(b) In addition to complying with §172.519, the background color on the NON-FLAMMABLE GAS placard must be green. The letters in both words must be at least 38 mm (1.5 inches)

high. The symbol, text, class number and inner border must be white.

[Amdt. 172-123, 56 FR 66261, Dec. 20, 1991]

**§ 172.530 OXYGEN placard.**

(a) Except for size and color, the OXYGEN placard must be as follows:



(b) In addition to complying with §172.519 of this subpart, the background color on the OXYGEN placard must be yellow. The symbol, text, class number and inner border must be black.

[Amdt. 172-123, 56 FR 66262, Dec. 20, 1991]

**§ 172.532 FLAMMABLE GAS placard.**

(a) Except for size and color, the FLAMMABLE GAS placard must be as follows:



(b) In addition to complying with §172.519, the background color on the

**§ 172.536**

FLAMMABLE GAS placard must be red. The symbol, text, class number and inner border must be white.

[Amdt. 172-123, 56 FR 66262, Dec. 20, 1991]

**§ 172.536 [Reserved]**

**§ 172.540 POISON GAS placard.**

(a) Except for size and color, the POISON GAS placard must be as follows:



(b) In addition to complying with §172.519, the background on the POISON GAS placard and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 65 mm (2<sup>5</sup>/<sub>8</sub> inches) above the horizontal center line. The text, class number, and inner border must be black.

[62 FR 39408, July 22, 1997]

**§ 172.542 FLAMMABLE placard.**

(a) Except for size and color, the FLAMMABLE placard must be as follows:

**49 CFR Ch. I (10-1-04 Edition)**



(b) In addition to complying with §172.519, the background color on the FLAMMABLE placard must be red. The symbol, text, class number and inner border must be white.

(c) The word "GASOLINE" may be used in place of the word "FLAMMABLE" on a placard that is displayed on a cargo tank or a portable tank being used to transport gasoline by highway. The word "GASOLINE" must be shown in white.

[Amdt. 172-123, 56 FR 66262, Dec. 20, 1991]

**§ 172.544 COMBUSTIBLE placard.**

(a) Except for size and color, the COMBUSTIBLE placard must be as follows:



(b) In addition to complying with §172.519, the background color on the COMBUSTIBLE placard must be red.

The symbol, text, class number and inner border must be white. On a COMBUSTIBLE placard with a white bottom as prescribed by §172.332(c)(4), the class number must be red or black.

(c) The words "FUEL OIL" may be used in place of the word "COMBUSTIBLE" on a placard that is displayed on a cargo tank or portable tank being used to transport by highway fuel oil that is not classed as a flammable liquid. The words "FUEL OIL" must be white.

[Amdt. 172-123, 56 FR 66262, Dec. 20, 1991]

**§ 172.546 FLAMMABLE SOLID placard.**

(a) Except for size and color, the FLAMMABLE SOLID placard must be as follows:



(b) In addition to complying with §172.519, the background on the FLAMMABLE SOLID placard must be white with seven vertical red stripes. The stripes must be equally spaced, with one red stripe placed in the center of the label. Each red stripe and each white space between two red stripes must be 25 mm (1.0 inches) wide. The letters in the word "SOLID" must be at least 38.1 mm (1.5 inches) high. The symbol, text, class number and inner border must be black.

[Amdt. 172-123, 56 FR 66263, Dec. 20, 1991]

**§ 172.547 SPONTANEOUSLY COMBUSTIBLE placard.**

(a) Except for size and color, the SPONTANEOUSLY COMBUSTIBLE placard must be as follows:



(b) In addition to complying with §172.519, the background color on the SPONTANEOUSLY COMBUSTIBLE placard must be red in the lower half and white in upper half. The letters in the word "SPONTANEOUSLY" must be at least 12 mm (0.5 inch) high. The symbol, text, class number and inner border must be black.

[Amdt. 172-123, 56 FR 66263, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67490, Dec. 29, 1994]

**§ 172.548 DANGEROUS WHEN WET placard.**

(a) Except for size and color, the DANGEROUS WHEN WET placard must be as follows:



(b) In addition to complying with §172.519, the background color on the DANGEROUS WHEN WET placard must be blue. The letters in the words

§ 172.550

“WHEN WET” must be at least 25 mm (1.0 inches) high. The symbol, text, class number and inner border must be white.

[Amdt. 172-123, 56 FR 66263, Dec. 20, 1991]

§ 172.550 **OXIDIZER placard.**

(a) Except for size and color, the OXIDIZER placard must be as follows:




(b) In addition to complying with §172.519, the background color on the OXIDIZER placard must be yellow. The symbol, text, division number and inner border must be black.

[Amdt. 172-123, 56 FR 66263, Dec. 20, 1991]

§ 172.552 **ORGANIC PEROXIDE placard.**

(a) Except for size and color, the ORGANIC PEROXIDE placard must be as follows:

49 CFR Ch. I (10-1-04 Edition)



(b) In addition to complying with §172.519, the background color on the ORGANIC PEROXIDE placard must be yellow. The symbol, text, division number and inner border must be black.

[Amdt. 172-123, 56 FR 66263, Dec. 20, 1991]

§ 172.553 [Reserved]

§ 172.554 **POISON placard.**

(a) Except for size and color, the POISON placard must be as follows:



(b) In addition to complying with §172.519, the background on the POISON placard must be white. The symbol, text, class number and inner border must be black. The word “TOXIC”



**Research and Special Programs Admin., DOT**

**§ 172.556**

may be used in lieu of the word "POISON".

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67490, Dec. 29, 1994]

**§ 172.555 POISON INHALATION HAZARD placard.**

(a) Except for size and color, the POISON INHALATION HAZARD placard must be as follows:



(b) In addition to complying with §172.519, the background on the POISON INHALATION HAZARD placard and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 65 mm (2<sup>5</sup>/<sub>8</sub> inches) above the horizontal center line. The text, class number, and inner border must be black.

[62 FR 39409, July 22, 1997]

**§ 172.556 RADIOACTIVE placard.**

(a) Except for size and color, the RADIOACTIVE placard must be as follows:



(b) In addition to complying with §172.519, the background color on the RADIOACTIVE placard must be white in the lower portion with a yellow triangle in the upper portion. The base of the yellow triangle must be 29 mm ± 5 mm (1.1 inches ±0.2 inches) above the placard horizontal center line. The

symbol, text, class number and inner border must be black.

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993; 65 FR 58627, Sept. 29, 2000]

**§ 172.558 CORROSIVE placard.**

(a) Except for size and color, the CORROSIVE placard must be as follows:




(b) In addition to complying with §172.519, the background color on the CORROSIVE placard must be black in the lower portion with a white triangle in the upper portion. The base of the white triangle must be 38 mm ± 5 mm (1.5 inches ± 0.2 inches) above the placard horizontal center line. The text and class number must be white. The symbol and inner border must be black.

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991, as amended at 65 FR 58627, Sept. 29, 2000]

**§ 172.560 CLASS 9 placard.**

(a) Except for size and color the CLASS 9 (miscellaneous hazardous materials) placard must be as follows:



## § 172.600

(b) In addition to conformance with § 172.519, the background on the CLASS 9 placard must be white with seven black vertical stripes on the top half extending from the top of the placard to one inch above the horizontal centerline. The black vertical stripes must be spaced so that, visually, they appear equal in width to the six white spaces between them. The space below the vertical lines must be white with the class number 9 underlined and centered at the bottom.

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991, as amended at 57 FR 45460, Oct. 1, 1992]

### Subpart G—Emergency Response Information

#### § 172.600 Applicability and general requirements.

(a) *Scope.* Except as provided in paragraph (d) of this section, this subpart prescribes requirements for providing and maintaining emergency response information during transportation and at facilities where hazardous materials are loaded for transportation, stored incidental to transportation or otherwise handled during any phase of transportation.

(b) *Applicability.* This subpart applies to persons who offer for transportation, accept for transportation, transfer or otherwise handle hazardous materials during transportation.

(c) *General requirements.* No person to whom this subpart applies may offer for transportation, accept for transportation, transfer, store or otherwise handle during transportation a hazardous material unless:

(1) Emergency response information conforming to this subpart is immediately available for use at all times the hazardous material is present; and

(2) Emergency response information, including the emergency response telephone number, required by this subpart is immediately available to any person who, as a representative of a Federal, State or local government agency, responds to an incident involving a hazardous material, or is conducting an investigation which involves a hazardous material.

(d) *Exceptions.* The requirements of this subpart do not apply to hazardous material which is excepted from the

## 49 CFR Ch. I (10-1-04 Edition)

shipping paper requirements of this subchapter or a material properly classified as an ORM-D.

[Amdt. 172-116, 54 FR 27145, June 27, 1989; 54 FR 28750, July 5, 1989, as amended at 55 FR 33712, Aug. 17, 1990; 172-127, 59 FR 49133, Sept. 26, 1994; Amdt. 172-149, 61 FR 27173, May 30, 1996]

#### § 172.602 Emergency response information.

(a) *Information required.* For purposes of this subpart, the term “emergency response information” means information that can be used in the mitigation of an incident involving hazardous materials and, as a minimum, must contain the following information:

(1) The basic description and technical name of the hazardous material as required by §§ 172.202 and 172.203(k), the ICAO Technical Instructions, the IMDG Code, or the TDG Regulations, as appropriate (IBR, see § 171.7 of this subchapter);

(2) Immediate hazards to health;

(3) Risks of fire or explosion;

(4) Immediate precautions to be taken in the event of an accident or incident;

(5) Immediate methods for handling fires;

(6) Initial methods for handling spills or leaks in the absence of fire; and

(7) Preliminary first aid measures.

(b) *Form of information.* The information required for a hazardous material by paragraph (a) of this section must be:

(1) Printed legibly in English;

(2) Available for use away from the package containing the hazardous material; and

(3) Presented—

(i) On a shipping paper;

(ii) In a document, other than a shipping paper, that includes both the basic description and technical name of the hazardous material as required by §§ 172.202 and 172.203(k), the ICAO Technical Instructions, the IMDG Code, or the TDG Regulations, as appropriate, and the emergency response information required by this subpart (e.g., a material safety data sheet); or

(iii) Related to the information on a shipping paper, a written notification to pilot-in-command, or a dangerous cargo manifest, in a separate document

(e.g., an emergency response guidance document), in a manner that cross-references the description of the hazardous material on the shipping paper with the emergency response information contained in the document. Aboard aircraft, the ICAO "Emergency Response Guidance for Aircraft Incidents Involving Dangerous Goods" and, aboard vessels, the IMO "Emergency Procedures for Ships Carrying Dangerous Goods", or equivalent documents, may be used to satisfy the requirements of this section for a separate document.

(c) *Maintenance of information.* Emergency response information shall be maintained as follows:

(1) *Carriers.* Each carrier who transports a hazardous material shall maintain the information specified in paragraph (a) of this section and § 172.606 of this part in the same manner as prescribed for shipping papers, except that the information must be maintained in the same manner aboard aircraft as the notification of pilot-in-command, and aboard vessels in the same manner as the dangerous cargo manifest. This information must be immediately accessible to train crew personnel, drivers of motor vehicles, flight crew members, and bridge personnel on vessels for use in the event of incidents involving hazardous materials.

(2) *Facility operators.* Each operator of a facility where a hazardous material is received, stored or handled during transportation, shall maintain the information required by paragraph (a) of this section whenever the hazardous material is present. This information must be in a location that is immediately accessible to facility personnel in the event of an incident involving the hazardous material.

[Amdt. 172-116, 54 FR 27146, June 27, 1989; 54 FR 28750, July 5, 1989, as amended by Amdt. 172-116, 55 FR 875, Jan. 10, 1990; Amdt. 172-151, 62 FR 1234, Jan. 8, 1997; 66 FR 45379, Aug. 28, 2001; 68 FR 75741, Dec. 31, 2003]

**§ 172.604 Emergency response telephone number.**

(a) A person who offers a hazardous material for transportation must provide an emergency response telephone number, including the area code or international access code, for use in

the event of an emergency involving the hazardous material. The telephone number must be—

(1) Monitored at all times the hazardous material is in transportation, including storage incidental to transportation;

(2) The number of a person who is either knowledgeable of the hazardous material being shipped and has comprehensive emergency response and incident mitigation information for that material, or has immediate access to a person who possesses such knowledge and information; and

(3) Entered on a shipping paper, as follows:

(i) Immediately following the description of the hazardous material required by subpart C of this part; or

(ii) Entered once on the shipping paper in a clearly visible location. This provision may be used only if the telephone number applies to each hazardous material entered on the shipping paper, and if it is indicated that the telephone number is for emergency response information (for example: "EMERGENCY CONTACT: \* \* \*").

(b) The telephone number required by paragraph (a) of this section must be the number of the person offering the hazardous material for transportation or the number of an agency or organization capable of, and accepting responsibility for, providing the detailed information concerning the hazardous material. A person offering a hazardous material for transportation who lists the telephone number of an agency or organization shall ensure that agency or organization has received current information on the material, as required by paragraph (a)(2) of this section before it is offered for transportation.

(c) The requirements of this section do not apply to—

(1) Hazardous materials that are offered for transportation under the provisions applicable to limited quantities; and

(2) Materials properly described under the following shipping names:

Battery powered equipment  
 Battery powered vehicle  
 Carbon dioxide, solid  
 Castor bean  
 Castor flake

## § 172.606

Castor meal  
Castor pomace  
Consumer commodity  
Dry ice  
Engines, internal combustion  
Fish meal, stabilized  
Fish scrap, stabilized  
Refrigerating machine  
Vehicle, flammable gas powered  
Vehicle, flammable liquid powered  
Wheelchair, electric

[Amdt. 172-116, 54 FR 27145, June 27, 1989, as amended at 55 FR 33713, Aug. 17, 1990; Amdt. 172-127, 59 FR 49133, Sept. 26, 1994; Amdt. 172-149, 61 FR 27173, May 30, 1996; 65 FR 50460, Aug. 18, 2000; 65 FR 58628, Sept. 29, 2000; 66 FR 45182, Aug. 28, 2001]

### § 172.606 Carrier information contact.

(a) Each carrier who transports or accepts for transportation a hazardous material for which a shipping paper is required shall instruct the operator of a motor vehicle, train, aircraft, or vessel to contact the carrier (e.g., by telephone or mobile radio) in the event of an incident involving the hazardous material.

(b) For transportation by highway, if a transport vehicle, (e.g., a semi-trailer or freight container-on-chassis) contains hazardous material for which a shipping paper is required and the vehicle is separated from its motive power and parked at a location other than a facility operated by the consignor or consignee or a facility (e.g., a carrier's terminal or a marine terminal) subject to the provisions of §172.602(c)(2), the carrier shall—

(1) Mark the transport vehicle with the telephone number of the motor carrier on the front exterior near the brake hose and electrical connections or on a label, tag, or sign attached to the vehicle at the brake hose or electrical connection; or

(2) Have the shipping paper and emergency response information readily available on the transport vehicle.

(c) The requirements specified in paragraph (b) of this section do not apply to an unattended motor vehicle separated from its motive power when the motor vehicle is marked on an orange panel, a placard, or a plain white square-on-point configuration with the identification number of each hazardous material loaded therein, and the

## 49 CFR Ch. I (10-1-04 Edition)

marking or placard is visible on the outside of the motor vehicle.

[Amdt. 172-151, 62 FR 1234, Jan. 8, 1997, as amended at 62 FR 39398 and 39409, July 22, 1997; 63 FR 16076, Apr. 1, 1998]

## Subpart H—Training

SOURCE: Amdt. 172-126, 57 FR 20952, May 15, 1992, unless otherwise noted.

### § 172.700 Purpose and scope.

(a) *Purpose.* This subpart prescribes requirements for training hazmat employees.

(b) *Scope.* Training as used in this subpart means a systematic program that ensures a hazmat employee has familiarity with the general provisions of this subchapter, is able to recognize and identify hazardous materials, has knowledge of specific requirements of this subchapter applicable to functions performed by the employee, and has knowledge of emergency response information, self-protection measures and accident prevention methods and procedures (see §172.704).

(c) *Modal-specific training requirements.* Additional training requirements for the individual modes of transportation are prescribed in parts 174, 175, 176, and 177 of this subchapter.

### § 172.701 Federal-State relationship.

This subpart and the parts referenced in §172.700(c) prescribe minimum training requirements for the transportation of hazardous materials. For motor vehicle drivers, however, a State may impose more stringent training requirements only if those requirements—

(a) Do not conflict with the training requirements in this subpart and in part 177 of this subchapter; and

(b) Apply only to drivers domiciled in that State.

### § 172.702 Applicability and responsibility for training and testing.

(a) A hazmat employer shall ensure that each of its hazmat employees is trained in accordance with the requirements prescribed in this subpart.

(b) Except as provided in §172.704(c)(1), a hazmat employee who performs any function subject to the

requirements of this subchapter may not perform that function unless instructed in the requirements of this subchapter that apply to that function. It is the duty of each hazmat employer to comply with the applicable requirements of this subchapter and to thoroughly instruct each hazmat employee in relation thereto.

(c) Training may be provided by the hazmat employer or other public or private sources.

(d) A hazmat employer shall ensure that each of its hazmat employees is tested by appropriate means on the training subjects covered in §172.704.

[Amdt. 172-126, 57 FR 20952, May 15, 1992; 57 FR 22182, May 27, 1992, as amended by Amdt. 172-149, 61 FR 27173, May 30, 1996]

#### § 172.704 Training requirements.

(a) Hazmat employee training must include the following:

(1) *General awareness/familiarization training.* Each hazmat employee shall be provided general awareness/familiarization training designed to provide familiarity with the requirements of this subchapter, and to enable the employee to recognize and identify hazardous materials consistent with the hazard communication standards of this subchapter.

(2) *Function-specific training.* (i) Each hazmat employee shall be provided function-specific training concerning requirements of this subchapter, or exemptions issued under subchapter A of this chapter, which are specifically applicable to the functions the employee performs.

(ii) As an alternative to function-specific training on the requirements of this subchapter, training relating to the requirements of the ICAO Technical Instructions and the IMDG Code may be provided to the extent such training addresses functions authorized by §§171.11 and 171.12 of this subchapter.

(3) *Safety training.* Each hazmat employee shall receive safety training concerning—

(i) Emergency response information required by subpart G of part 172;

(ii) Measures to protect the employee from the hazards associated with hazardous materials to which they may be exposed in the work place, including

specific measures the hazmat employer has implemented to protect employees from exposure; and

(iii) Methods and procedures for avoiding accidents, such as the proper procedures for handling packages containing hazardous materials.

(4) *Security awareness training.* No later than the date of the first scheduled recurrent training after March 25, 2003, and in no case later than March 24, 2006, each hazmat employee must receive training that provides an awareness of security risks associated with hazardous materials transportation and methods designed to enhance transportation security. This training must also include a component covering how to recognize and respond to possible security threats. After March 25, 2003, new hazmat employees must receive the security awareness training required by this paragraph within 90 days after employment.

(5) *In-depth security training.* By December 22, 2003, each hazmat employee of a person required to have a security plan in accordance with subpart I of this part must be trained concerning the security plan and its implementation. Security training must include company security objectives, specific security procedures, employee responsibilities, actions to take in the event of a security breach, and the organizational security structure.

(b) *OSHA, EPA, and other training.* Training conducted by employers to comply with the hazard communication programs required by the Occupational Safety and Health Administration of the Department of Labor (29 CFR 1910.120 or 1910.1200) or the Environmental Protection Agency (40 CFR 311.1), or training conducted by employers to comply with security training programs required by other Federal or international agencies, may be used to satisfy the training requirements in paragraph (a) of this section to the extent that such training addresses the training components specified in paragraph (a) of this section.

(c) *Initial and recurrent training—(1) Initial training.* A new hazmat employee, or a hazmat employee who changes job functions may perform

## § 172.800

those functions prior to the completion of training provided—

(i) The employee performs those functions under the direct supervision of a properly trained and knowledgeable hazmat employee; and

(ii) The training is completed within 90 days after employment or a change in job function.

(2) *Recurrent training.* A hazmat employee shall receive the training required by this subpart at least once every three years.

(3) *Relevant Training.* Relevant training received from a previous employer or other source may be used to satisfy the requirements of this subpart provided a current record of training is obtained from hazmat employees' previous employer.

(4) *Compliance.* Each hazmat employer is responsible for compliance with the requirements of this subchapter regardless of whether the training required by this subpart has been completed.

(d) *Recordkeeping.* A record of current training, inclusive of the preceding three years, in accordance with this section shall be created and retained by each hazmat employer for as long as that employee is employed by that employer as a hazmat employee and for 90 days thereafter. The record shall include:

- (1) The hazmat employee's name;
- (2) The most recent training completion date of the hazmat employee's training;
- (3) A description, copy, or the location of the training materials used to meet the requirements in paragraph (a) of this section;
- (4) The name and address of the person providing the training; and
- (5) Certification that the hazmat employee has been trained and tested, as required by this subpart.

(e) *Limitation.* A hazmat employee who repairs, modifies, reconditions, or tests packagings as qualified for use in the transportation of hazardous materials, and who does not perform any other function subject to the requirements of this subchapter, is not subject

## 49 CFR Ch. I (10–1–04 Edition)

to the safety training requirement of paragraph (a)(3) of this section.

[Amdt. 172–126, 57 FR 20952, May 15, 1992, as amended by Amdt. 172–126, 58 FR 5851, Jan. 22, 1993; Amdt. 172–145, 60 FR 49110, Sept. 21, 1995; Amdt. 172–149, 61 FR 27173, May 30, 1996; 65 FR 50460, Aug. 18, 2000; 68 FR 14521, Mar. 25, 2003]

### Subpart I—Security Plans

SOURCE: 68 FR 14521, Mar. 25, 2003, unless otherwise noted.

#### § 172.800 Purpose and applicability.

(a) *Purpose.* This subpart prescribes requirements for development and implementation of plans to address security risks related to the transportation of hazardous materials in commerce.

(b) *Applicability.* By September 25, 2003, each person who offers for transportation in commerce or transports in commerce one or more of the following hazardous materials must develop and adhere to a security plan for hazardous materials that conforms to the requirements of this subpart:

(1) A highway route-controlled quantity of a Class 7 (radioactive) material, as defined in §173.403 of this subchapter, in a motor vehicle, rail car, or freight container;

(2) More than 25 kg (55 pounds) of a Division 1.1, 1.2, or 1.3 (explosive) material in a motor vehicle, rail car, or freight container;

(3) More than one L (1.06 qt) per package of a material poisonous by inhalation, as defined in §171.8 of this subchapter, that meets the criteria for Hazard Zone A, as specified in §§173.116(a) or 173.133(a) of this subchapter;

(4) A shipment of a quantity of hazardous materials in a bulk packaging having a capacity equal to or greater than 13,248 L (3,500 gallons) for liquids or gases or more than 13.24 cubic meters (468 cubic feet) for solids;

(5) A shipment in other than a bulk packaging of 2,268 kg (5,000 pounds) gross weight or more of one class of hazardous materials for which placarding of a vehicle, rail car, or freight container is required for that class under the provisions of subpart F of this part;



(6) A select agent or toxin regulated by the Centers for Disease Control and Prevention under 42 CFR part 73; or

(7) A quantity of hazardous material that requires placarding under the provisions of subpart F of this part.

**§ 172.802 Components of a security plan.**

(a) The security plan must include an assessment of possible transportation security risks for shipments of the hazardous materials listed in § 172.800 and appropriate measures to address the assessed risks. Specific measures put into place by the plan may vary commensurate with the level of threat at a particular time. At a minimum, a security plan must include the following elements:

(1) *Personnel security.* Measures to confirm information provided by job applicants hired for positions that involve access to and handling of the hazardous materials covered by the security plan. Such confirmation system must be consistent with applicable Federal and State laws and requirements concerning employment practices and individual privacy.

(2) *Unauthorized access.* Measures to address the assessed risk that unauthorized persons may gain access to the hazardous materials covered by the security plan or transport conveyances being prepared for transportation of the hazardous materials covered by the security plan.

(3) *En route security.* Measures to address the assessed security risks of shipments of hazardous materials covered by the security plan en route from origin to destination, including shipments stored incidental to movement.

(b) The security plan must be in writing and must be retained for as long as it remains in effect. Copies of the security plan, or portions thereof, must be available to the employees who are responsible for implementing it, consistent with personnel security clearance or background investigation re-

strictions and a demonstrated need to know. The security plan must be revised and updated as necessary to reflect changing circumstances. When the security plan is updated or revised, all copies of the plan must be maintained as of the date of the most recent revision.

**§ 172.804 Relationship to other Federal requirements.**

To avoid unnecessary duplication of security requirements, security plans that conform to regulations, standards, protocols, or guidelines issued by other Federal agencies, international organizations, or industry organizations may be used to satisfy the requirements in this subpart, provided such security plans address the requirements specified in this subpart.

APPENDIX A TO PART 172—OFFICE OF HAZARDOUS MATERIALS TRANSPORTATION COLOR TOLERANCE CHARTS AND TABLES

The following are Munsell notations and Commission Internationale de L'Eclairage (CIE) coordinates which describe the Office of Hazardous Materials Transportation Label and Placard Color Tolerance Charts in tables 1 and 2, and the CIE coordinates for the color tolerances specified in table 3. Central colors and tolerances described in table 2 approximate those described in table 1 while allowing for differences in production methods and materials used to manufacture labels and placards surfaced with printing inks. Primarily, the color charts based on table 1 are for label or placard colors applied as opaque coatings such as paint, enamel or plastic, whereas color charts based on table 2 are intended for use with labels and placards surfaced only with inks.

For labels printed directly on packaging surfaces, table 3 may be used, although compliance with either table 1 or table 2 is sufficient. However, if visual reference indicates that the colors of labels printed directly on package surfaces are outside the table 1 or 2 tolerances, a spectrophotometer or other instrumentation may be required to insure compliance with table 3.

TABLE 1—SPECIFICATIONS FOR COLOR TOLERANCE CHARTS FOR USE WITH LABELS AND PLACARDS SURFACED WITH PAINT, LACQUER, ENAMEL, PLASTIC, OTHER OPAQUE COATINGS, OR INK<sup>1</sup>

Color	Munsell notations	CIE data for source C		
		Y	x	y
<b>Red:</b>				
Central color	7.5R 4.0/14	12.00	.5959	.3269
Orange	8.5R 4.0/14	12.00	.6037	.3389
Purple and vivid	6.5R 4.0/14	12.00	.5869	.3184
Grayish	7.5R 4.0/12	12.00	.5603	.3321
Vivid	7.5R 4.0/16	12.00	.6290	.3192
Light	7.5R 4.5/14	15.57	.5775	.3320
Dark	7.5R 3.5/14	09.00	.6226	.3141
<b>Orange:</b>				
Central color	5.OYR 6.0/15	30.05	.5510	.4214
Yellow and Grayish	6.25YR 6.0/15	30.05	.5452	.4329
Red and vivid	3.75YR 6.0/15	30.05	.5552	.4091
Grayish	5.OYR 6.0/13	30.05	.5311	.4154
Vivid	5.OYR 6.0/16	30.05	.5597	.4239
Light	5.OYR 6.5/15	36.20	.5427	.4206
Dark	5.OYR 5.5/15	24.58	.5606	.4218
<b>Yellow:</b>				
Central color	5.OY 8.0/12	59.10	.4562	.4788
Green	6.5Y 8.0/12	59.10	.4498	.4865
Orange and vivid	3.5Y 8.0/12	59.10	.4632	.4669
Grayish	5.OY 8.0/10	59.10	.4376	.4601
Vivid	5.OY 8.0/14	59.10	.4699	.4920
Light	5.OY 8.5/12	68.40	.4508	.4754
Dark	5.OY 7.5/12	50.68	.4620	.4823
<b>Green:</b>				
Central color	7.5G 4.0/9	12.00	.2111	.4121
Bluish	0.5BG 4.0/9	12.00	.1974	.3809
Green-yellow	5.0G 4.0/9	12.00	.2237	.4399
Grayish A	7.5G 4.0/7	12.00	.2350	.3922
Grayish B <sup>2</sup>	7.5G 4.0/6	12.00	.2467	.3822
Vivid	7.5G 4.0/11	12.00	.1848	.4319
Light	7.5G 4.5/9	15.57	.2204	.4060
Dark	7.5G 3.5/9	09.00	.2027	.4163
<b>Blue:</b>				
Central color	2.5PB 3.5/10	09.00	.1691	.1744
Purple	4.5PB 3.5/10	09.00	.1796	.1711
Green and vivid	10.0B 3.5/10	09.00	.1557	.1815
Grayish	2.5PB 3.5/8	09.00	.1888	.1964
Vivid	2.5PB 3.5/12	09.00	.1516	.1547
Light	2.5PB 4.0/10	12.00	.1805	.1888
Dark	2.5PB 3.0/10	06.55	.1576	.1600
<b>Purple:</b>				
Central color	10.0P 4.5/10	15.57	.3307	.2245
Reddish purple	2.5RP 4.5/10	15.57	.3584	.2377
Blue purple	7.5P 4.5/10	15.57	.3068	.2145
Reddish gray	10.0P 4.5/8	15.57	.3280	.2391
Gray <sup>2</sup>	10.0P 4.5/6.5	15.57	.3254	.2519
Vivid	10.0P 4.5/12	15.57	.3333	.2101
Light	10.0P 5.0/10	19.77	.3308	.2328
Dark	10.0P 4.0/10	12.00	.3306	.2162

<sup>1</sup> Maximum chroma is not limited.  
<sup>2</sup> For the colors green and purple, the minimum saturation (chroma) limits for porcelain enamel on metal are lower than for most other surface coatings. Therefore, the minimum chroma limits of these two colors as displayed on the Charts for comparison to porcelain enamel on metal is low, as shown for green (grayish B) and purple (gray).  
 NOTE: CIE=Commission Internationale de L'Eclairage.

TABLE 2—SPECIFICATIONS FOR COLOR TOLERANCE CHARTS FOR USE WITH LABELS AND PLACARDS SURFACED WITH INK

Color/series	Munsell notation	CIE data for source C		
		Y	x	y
<b>Red:</b>				
<b>Central series:</b>				
Central color	6.8R 4.47/12.8	15.34	.5510	.3286
Grayish	7.2R 4.72/12.2	17.37	.5368	.3348
Purple	6.4R 4.49/12.7	15.52	.5442	.3258
Purple and vivid	6.1R 4.33/13.1	14.25	.5529	.3209

TABLE 2—SPECIFICATIONS FOR COLOR TOLERANCE CHARTS FOR USE WITH LABELS AND PLACARDS SURFACED WITH INK—Continued

Color/series	Munsell notation	CIE data for source C		
		Y	x	y
Vivid .....	6.7R 4.29/13.2 .....	13.99	.5617	.3253
Orange .....	7.3R 4.47/12.8 .....	15.34	.5572	.3331
Orange and grayish .....	7.65R 4.70/12.4 .....	17.20	.5438	.3382
Light series:				
Light .....	7.0R 4.72/13.2 .....	17.32	.5511	.3322
Light and orange .....	7.4R 4.96/12.6 .....	19.38	.5365	.3392
Light and purple .....	6.6R 4.79/12.9 .....	17.94	.5397	.3289
Dark series:				
Dark A .....	6.7R 4.19/12.5 .....	13.30	.5566	.3265
Dark B .....	7.0R 4.25/12.35 .....	13.72	.5522	.3294
Dark and purple .....	7.5R 4.23/12.4 .....	13.58	.5577	.3329
Orange:				
Central series:				
Central color .....	5.0YR 6.10/12.15 .....	31.27	.5193	.4117
Yellow and grayish A .....	5.8YR 6.22/11.7 .....	32.69	.5114	.4155
Yellow and grayish B .....	6.1YR 6.26/11.85 .....	33.20	.5109	.4190
Vivid .....	5.1YR 6.07/12.3 .....	30.86	.5226	.4134
Red and vivid A .....	3.9YR 5.87/12.75 .....	28.53	.5318	.4038
Red and vivid B .....	3.6YR 5.91/12.6 .....	29.05	.5291	.4021
Grayish .....	4.9YR 6.10/11.9 .....	31.22	.5170	.4089
Light series:				
Light and vivid A .....	5.8YR 6.78/12.7 .....	39.94	.5120	.4177
Light and yellow .....	6.0YR 6.80/12.8 .....	40.20	.5135	.4198
Light and vivid B .....	4.9YR 6.60/12.9 .....	37.47	.5216	.4126
Dark series:				
Dark and yellow .....	5.8YR 5.98/11.0 .....	29.87	.5052	.4132
Dark A .....	5.1YR 5.80/11.1 .....	27.80	.5127	.4094
Dark B .....	5.0YR 5.80/11.0 .....	27.67	.5109	.4068
Yellow:				
Central series:				
Central color .....	4.3Y 7.87/10.3 .....	56.81	.4445	.4589
Vivid A .....	4.5Y 7.82/10.8 .....	55.92	.4503	.4658
Vivid B .....	3.3Y 7.72/11.35 .....	54.24	.4612	.4624
Vivid and orange .....	3.2Y 7.72/10.8 .....	54.25	.4576	.4572
Grayish A .....	4.1Y 7.95/9.7 .....	58.18	.4380	.4516
Grayish B .....	5.1Y 8.06/9.05 .....	60.12	.4272	.4508
Green-yellow .....	5.2Y 7.97/9.9 .....	58.53	.4356	.4605
Light series:				
Light .....	5.4Y 8.59/10.5 .....	70.19	.4351	.4628
Light and green-yellow .....	5.4Y 8.56/11.2 .....	69.59	.4414	.4692
Light and vivid .....	4.4Y 8.45/11.4 .....	67.42	.4490	.4662
Dark series:				
Dark and green-yellow .....	4.4Y 7.57/9.7 .....	51.82	.4423	.4562
Dark and orange A .....	3.4Y 7.39/10.4 .....	48.86	.4584	.4590
Dark and orange B .....	3.5Y 7.41/10.0 .....	49.20	.4517	.4544
Green:				
Central series:				
Central color .....	9.75G 4.26/7.75 .....	13.80	.2214	.3791
Grayish .....	10G 4.46/7.5 .....	15.25	.2263	.3742
Blue A .....	1.4BG 4.20/7.4 .....	13.36	.2151	.3625
Blue B .....	1.0BG 4.09/7.75 .....	12.60	.2109	.3685
Vivid .....	8.4G 4.09/8.05 .....	12.59	.2183	.3954
Vivid green-yellow .....	7.0G 4.23/8.0 .....	13.54	.2292	.4045
Green-yellow .....	7.85G 4.46/7.7 .....	15.23	.2313	.3914
Light series:				
Light and vivid .....	9.5G 4.45/8.8 .....	15.21	.2141	.3863
Light and blue .....	0.2BG 4.31/8.8 .....	14.12	.2069	.3814
Light and green-yellow .....	8.3G 4.29/9.05 .....	14.01	.2119	.4006
Dark series:				
Dark and green-yellow .....	7.1G 4.08/7.1 .....	12.55	.2354	.3972
Dark and grayish .....	9.5G 4.11/6.9 .....	12.70	.2282	.3764
Dark .....	8.5G 3.97/7.2 .....	11.78	.2269	.3874
Blue:				
Central series:				
Central color .....	3.5PB 3.94/9.7 .....	11.58	.1885	.1911
Green and grayish A .....	2.0PB 4.35/8.7 .....	14.41	.1962	.2099
Green and grayish B .....	1.7PB 4.22/9.0 .....	13.50	.1898	.2053
Vivid .....	2.9PB 3.81/9.7 .....	10.78	.1814	.1852
Purple and vivid A .....	4.7PB 3.53/10.0 .....	9.15	.1817	.1727

TABLE 2—SPECIFICATIONS FOR COLOR TOLERANCE CHARTS FOR USE WITH LABELS AND PLACARDS SURFACED WITH INK—Continued

Color/series	Munsell notation	CIE data for source C		
		Y	x	y
Purple and vivid B .....	5.0PB 3.71/9.9 .....	10.20	.1888	.1788
Grayish .....	3.75PB 4.03/9.1 .....	12.17	.1943	.1961
Light series:				
Light and green A .....	1.7PB 4.32/9.2 .....	14.22	.1904	.2056
Light and green B .....	1.5PB 4.11/9.6 .....	12.72	.1815	.1971
Light and vivid .....	3.2PB 3.95/10.05 .....	11.70	.1831	.1868
Dark series:				
Dark and grayish .....	3.9PB 4.01/8.7 .....	12.04	.1982	.1992
Dark and purple A .....	4.8PB 3.67/9.3 .....	9.95	.1918	.1831
Dark and purple B .....	5.2PB 3.80/9.05 .....	10.76	.1985	.1885
Purple:				
Central series:				
Central color .....	9.5P 4.71/11.3 .....	17.25	.3274	.2165
Red .....	1.0RP 5.31/10.8 .....	22.70	.3404	.2354
Red and vivid A .....	1.4RP 5.00/11.9 .....	19.78	.3500	.2274
Red and vivid B .....	0.2RP 4.39/12.5 .....	14.70	.3365	.2059
Vivid .....	8.0P 4.04/12.0 .....	12.23	.3098	.1916
Blue .....	7.0P 4.39/10.8 .....	14.71	.3007	.2037
Grayish .....	8.8P 5.00/10.3 .....	19.73	.3191	.2251
Light series:				
Light and red A .....	0.85RP 5.56/11.1 .....	25.18	.3387	.2356
Light and red B .....	1.1RP 5.27/12.3 .....	22.27	.3460	.2276
Light and vivid .....	9.2P 4.94/11.95 .....	19.24	.3247	.2163
Dark series:				
Dark and grayish .....	9.6P 4.70/10.9 .....	17.19	.3283	.2204
Dark and vivid .....	8.4P 4.05/11.6 .....	12.35	.3144	.1970
Dark and blue .....	7.5P 4.32/10.5 .....	14.19	.3059	.2078

TABLE 3—SPECIFICATION FOR COLORS FOR USE WITH LABELS PRINTED ON PACKAGINGS SURFACES

CIE data for source C	Red	Orange	Yellow	Green	Blue	Purple
x .....	.424	.460	.417	.228	.200	.377
y .....	.306	.370	.392	.354	.175	.205
x .....	.571	.543	.490	.310	.255	.377
y .....	.306	.400	.442	.354	.250	.284
x .....	.424	.445	.390	.228	.177	.342
y .....	.350	.395	.430	.403	.194	.205
x .....	.571	.504	.440	.310	.230	.342
y .....	.350	.430	.492	.403	.267	.284
Y (high) .....	23.0	41.6	72.6	20.6	15.9	21.2
Y (low) .....	7.7	19.5	29.1	7.4	6.5	8.2

[Amdt. 172–50, 44 FR 9757, Feb. 15, 1979; Amdt. 172–50, 44 FR 10984, Feb. 26, 1979, as amended by Amdt. 172–50, 44 FR 22467, Apr. 16, 1979; 50 FR 45731, Nov. 1, 1985; Amdt. 172–127, 59 FR 49133, Sept. 26, 1994]


APPENDIX B TO PART 172—TREFOIL SYMBOL

SOURCE: 60 FR 50306, Sept. 28, 1995, unless otherwise noted.

1. Except as provided in paragraph 2 of this appendix, the trefoil symbol required for RADIOACTIVE labels and placards and required

to be marked on certain packages of Class 7 materials must conform to the design and size requirements of this appendix.

2. RADIOACTIVE labels and placards that were printed prior to April 1, 1996, in conformance with the requirements of this subchapter in effect on March 30, 1996, may continue to be used.




1=Radius of Circle—  
Minimum dimensions  
4 mm (0.16 inch) for markings and labels  
12.5 mm (0.5 inch) for placards  
2=1½ Radii

3=5 radii for markings and labels  
4½ radii for placards.

[60 FR 50306, Sept. 28, 1995, as amended by  
172-143, 61 FR 20750, May 8, 1996]

APPENDIX C TO PART 172—DIMENSIONAL SPECIFICATIONS FOR RECOMMENDED PLACARD HOLDER

APPENDIX C—DIMENSIONAL SPECIFICATIONS FOR RECOMMENDED PLACARD HOLDER



PART 173—SHIPPERS—GENERAL REQUIREMENTS FOR SHIPMENTS AND PACKAGINGS

Subpart A—General

Sec.  
173.1 Purpose and scope.

173.2 Hazardous materials classes and index to hazard class definitions.  
173.2a Classification of a material having more than one hazard.  
173.3 Packaging and exceptions.  
173.4 Small quantity exceptions.  
173.5 Agricultural operations.  
173.5a Oilfield service vehicles.  
173.6 Materials of trade exceptions.